

PNG to .preserve Conversion Toolchain

Complete Documentation of the Conversion Process

From Raster Image to Editable Design Document

DesignLibre Technical Documentation

January 3, 2026

Contents

1	Executive Summary	2
1.1	Key Characteristics	2
2	Toolchain Overview	2
2.1	High-Level Pipeline	2
2.2	Tool Calls Summary	2
3	Stage 1: Visual Analysis	3
3.1	Tool Call: Read (Image File)	3
3.2	Visual Processing	3
3.3	Data Extraction Example	4
4	Stage 2: Format Specification Research	4
4.1	Tool Calls: Glob and Grep	4
4.2	Tool Calls: Read (Source Files)	4
4.3	Discovered Format Specification	5
5	Stage 3: Hierarchy Construction	5
5.1	Parent-Child Relationship Mapping	5
5.2	Node ID Generation	6
6	Stage 4: JSON Generation	6
6.1	PreserveNode Structure	6
6.2	Paint (Fill/Stroke) Structure	7
6.3	Color Conversion	7
6.4	Example Node Generation	8
7	Stage 5: File Creation	9
7.1	Directory Structure Creation	9
7.2	File Generation Sequence	9
7.3	Document.json Structure	10

8	Stage 6: Archive Packaging	10
8.1	ZIP Creation	10
8.2	ZIP Structure Requirements	11
9	Complete Tool Call Sequence	11
9.1	Chronological Tool Invocations	11
10	Data Flow Diagram	12
11	Limitations and Considerations	12
11.1	Manual Analysis Limitations	12
11.2	Format Fidelity	13
11.3	Potential Improvements	13
12	Conclusion	13

1 Executive Summary

This document describes the complete toolchain used to convert a PNG raster image into a DesignLibre `.preserve` file format. The process involves visual analysis, structured data extraction, hierarchical node construction, and archive packaging.

1.1 Key Characteristics

- **Input:** PNG raster image (e.g., `presets-screen.png`)
- **Output:** `.preserve` ZIP archive containing JSON files
- **Processing:** Manual visual analysis + structured JSON generation
- **Tools Used:** Claude AI vision, file system operations, ZIP compression

2 Toolchain Overview

2.1 High-Level Pipeline




Figure 1: PNG to .preserve Conversion Pipeline

2.2 Tool Calls Summary

Step	Tool	Purpose	Output
1	Read (image)	Load PNG for visual analysis	Image data
2	Glob/Grep	Explore .preserve format spec	Format knowledge
3	Read	Study existing node types	Node structure
4	Write	Create directory structure	Folders
5	Write	Generate JSON files	JSON documents
6	Bash (zip)	Package into archive	.preserve file

Table 1: Tool Invocations in Conversion Process

3 Stage 1: Visual Analysis

3.1 Tool Call: Read (Image File)

The first step is loading the PNG image for visual analysis. Claude's multimodal capabilities allow direct interpretation of raster images.

```
1 Tool: Read
2 Parameters: {
3   "file_path": "/path/to/presets-screen.png"
4 }
```

Tool Invocation

3.2 Visual Processing

When Claude reads an image file, the following analysis occurs:

1. Global Layout Recognition

- Device frame identification (iPhone 16 Pro: 393×852)
- Content area boundaries
- Grid/alignment detection

2. Element Identification

- Rectangular regions (frames, cards, buttons)
- Text elements (labels, headings, body text)
- Icons and decorative elements
- Background colors and fills

3. Color Extraction

- Dominant colors (background: #000000)
- Accent colors (green: #618538)
- Text colors (white: #FFFFFF, gray: #8E8E93)
- UI element colors (cards: #1A1A1A)

4. Spatial Relationships

- Nesting hierarchy (which elements contain others)
- Relative positioning (x, y offsets from parent)
- Dimensions (width, height of each element)

3.3 Data Extraction Example

From visual analysis of the "Presets" screen:

```
1 {
2   "element": "Search Bar",
3   "visual_observations": {
4     "position": "top of content area, below status bar",
5     "approximate_y": 59,
6     "width": "full width with padding",
7     "height": "approximately 36px",
8     "background_color": "dark gray (#1C1C1E)",
9     "corner_radius": "10px (pill shape)",
10    "contains": [
11      { "type": "icon", "content": "magnifying glass", "color": "#8
12      E8E93" },
13      { "type": "text", "content": "Search presets", "color": "#8E8E93"
14    ]
15  }
```

Extracted Element Data

4 Stage 2: Format Specification Research

4.1 Tool Calls: Glob and Grep

Before generating the .preserve file, the codebase is explored to understand the exact format specification.

```
1 # Find existing .preserve handling code
2 Tool: Glob
3 Parameters: { "pattern": "**/*preserve*" }
4
5 # Search for node type definitions
6 Tool: Grep
7 Parameters: {
8   "pattern": "PreserveNode",
9   "path": "src/"
10 }
11
12 # Find archive structure code
13 Tool: Grep
14 Parameters: {
15   "pattern": "readPreserveArchive",
16   "output_mode": "content"
17 }
```

Format Discovery

4.2 Tool Calls: Read (Source Files)

Key source files are read to understand the data structures:

```

1 # Node type definitions
2 Tool: Read
3 Parameters: { "file_path": "src/preserve/types.ts" }
4
5 # Archive structure
6 Tool: Read
7 Parameters: { "file_path": "src/preserve/preserve-archive.ts" }
8
9 # Node converter (preserve -> scene graph)
10 Tool: Read
11 Parameters: { "file_path": "src/preserve/node-converter.ts" }
12
13 # Factory functions (how nodes are created)
14 Tool: Read
15 Parameters: { "file_path": "src/scene/nodes/factory.ts" }

```

Source File Analysis

4.3 Discovered Format Specification

From the source code analysis, the .preserve format was determined:

```

1 archive.preserve (ZIP file)
2 |-- mimetype                                # "application/vnd.designlibre.preserve
   |
3 |-- document.json                          # Document metadata
4 |-- pages/
   |   |-- page-{id}.json                    # Page content with node tree
5 |-- tokens/
   |   |-- colors.json                       # Design tokens
6 |-- typography.json
7 |-- components/
   |   |-- component-{id}.json               # Reusable components
8 |-- assets/
   |   |-- manifest.json                     # Asset references
9 |-- prototypes/
   |   |-- flows.json                       # Prototype interactions
10 |-- history/
   |   |-- changelog.json                   # Version history
11 |-- META-INF/
   |   |-- container.xml                     # Archive metadata
12

```

.preserve Archive Structure

5 Stage 3: Hierarchy Construction

5.1 Parent-Child Relationship Mapping

Based on visual analysis, a hierarchical structure is constructed:

```

1 PAGE: Presets Screen
2 |
3 +-- FRAME: iPhone 16 Pro (393x852)
4 |
5 +-- FRAME: Status Bar

```

```

6      |      +-- TEXT: Time
7      |      +-- FRAME: Signal Icons
8      |
9      +-- FRAME: Content Area
10     |
11     +-- FRAME: Header Row
12     |      +-- TEXT: "Presets"
13     |      +-- FRAME: Icons Container
14     |
15     +-- FRAME: Search Bar
16     |      +-- TEXT: "Search presets"
17     |
18     +-- FRAME: Tab Bar
19     |      +-- FRAME: Tab (For You)
20     |      +-- FRAME: Tab (Scenes)
21     |      +-- FRAME: Tab (Categories)
22     |
23     +-- FRAME: Preset Card
24     |      +-- TEXT: Title
25     |      +-- FRAME: Tags Row
26     |      +-- FRAME: Play Button
27     |
28     +-- FRAME: Bottom Navigation
29         +-- FRAME: Nav Item (Presets)
30         +-- FRAME: Nav Item (Timer)
31         +-- FRAME: Nav Item (Settings)

```

Node Hierarchy

5.2 Node ID Generation

Each node requires a unique identifier:

```

1 // Pattern used for node IDs
2 const generateNodeId = (descriptor: string): string => {
3   // Human-readable prefix + uniqueness
4   return `${descriptor}-${Date.now().toString(36)}`;
5 };
6
7 // Examples:
8 // "iphone-frame"
9 // "content-area"
10 // "search-bar"
11 // "preset-card-1"

```

ID Generation Strategy

6 Stage 4: JSON Generation

6.1 PreserveNode Structure

Each visual element is converted to a PreserveNode JSON object:

```

1 interface PreserveNode {
2   id: string;
3   type: 'FRAME' | 'TEXT' | 'VECTOR' | 'GROUP' | 'IMAGE';

```

```

4   name: string;
5
6   transform: {
7     x: number;          // Position relative to parent
8     y: number;
9     width: number;
10    height: number;
11    rotation: number;
12  };
13
14  appearance?: {
15    fills?: PreservePaint[];
16    strokes?: PreservePaint[];
17    strokeWeight?: number;
18    cornerRadius?: number;
19    opacity?: number;
20    effects?: PreserveEffect[];
21  };
22
23  // Type-specific properties
24  characters?: string;      // For TEXT nodes
25  textStyle?: TextStyle;    // For TEXT nodes
26  clipContent?: boolean;    // For FRAME nodes
27
28  children?: PreserveNode[]; // Nested nodes
29 }

```

PreserveNode Interface

6.2 Paint (Fill/Stroke) Structure

```

1 interface PreservePaint {
2   type: 'SOLID' | 'GRADIENT_LINEAR' | 'GRADIENT_RADIAL' | 'IMAGE';
3   visible: boolean;
4   opacity: number;
5
6   // For SOLID
7   color?: { r: number; g: number; b: number; a: number };
8
9   // For gradients
10  gradientStops?: Array<{
11    position: number;
12    color: { r: number; g: number; b: number; a: number };
13  }>;
14 }

```

PreservePaint Interface

6.3 Color Conversion

Colors observed in the PNG are converted to normalized RGBA:

```

1 // Hex to normalized RGBA
2 function hexToRgba(hex: string): { r: number; g: number; b: number; a:
   number } {
3   const result = /^#?([a-f\d]{2})([a-f\d]{2})([a-f\d]{2})$/i.exec(hex);

```



```
4   return {
5       r: parseInt(result[1], 16) / 255,    // 0-1 range
6       g: parseInt(result[2], 16) / 255,
7       b: parseInt(result[3], 16) / 255,
8       a: 1
9   };
10 }
11
12 // Examples:
13 // #000000 -> { r: 0, g: 0, b: 0, a: 1 }
14 // #FFFFFF -> { r: 1, g: 1, b: 1, a: 1 }
15 // #618538 -> { r: 0.38, g: 0.52, b: 0.22, a: 1 }
16 // #1C1C1E -> { r: 0.11, g: 0.11, b: 0.12, a: 1 }
```

Color Conversion

6.4 Example Node Generation

```
1 {
2   "id": "search-bar",
3   "type": "FRAME",
4   "name": "Search Bar",
5   "transform": {
6     "x": 16,
7     "y": 59,
8     "width": 361,
9     "height": 36,
10    "rotation": 0
11  },
12  "appearance": {
13    "fills": [{
14      "type": "SOLID",
15      "color": { "r": 0.11, "g": 0.11, "b": 0.12, "a": 1 },
16      "opacity": 1,
17      "visible": true
18    }],
19    "cornerRadius": 10,
20    "opacity": 1
21  },
22  "clipContent": true,
23  "children": [
24    {
25      "id": "search-placeholder",
26      "type": "TEXT",
27      "name": "Search Placeholder",
28      "transform": {
29        "x": 36,
30        "y": 9,
31        "width": 100,
32        "height": 18,
33        "rotation": 0
34      },
35      "characters": "Search presets",
36      "textStyle": {
37        "fontFamily": "SF Pro",
38        "fontSize": 15,
39        "fontWeight": 400,
```

```

40         "fills": [{
41             "type": "SOLID",
42             "color": { "r": 0.56, "g": 0.56, "b": 0.58, "a": 1 }
43         }]
44     }
45 }
46 ]
47 }

```

Generated Search Bar Node

7 Stage 5: File Creation

7.1 Directory Structure Creation

```

1 # Create base directory
2 Tool: Bash
3 Parameters: {
4     "command": "mkdir -p presets-design/{pages,tokens,components,assets,
5     prototypes,history,META-INF}"
6 }

```

Tool Invocations for Directory Creation

7.2 File Generation Sequence

Each file is created using the Write tool:

```

1 # 1. Mimetype (must be first, uncompressed in ZIP)
2 Tool: Write
3 Parameters: {
4     "file_path": "presets-design/mimetype",
5     "content": "application/vnd.designlibre.preserve"
6 }
7
8 # 2. Document metadata
9 Tool: Write
10 Parameters: {
11     "file_path": "presets-design/document.json",
12     "content": "<document JSON>"
13 }
14
15 # 3. Page content (main design)
16 Tool: Write
17 Parameters: {
18     "file_path": "presets-design/pages/page-presets-main.json",
19     "content": "<page JSON with all nodes>"
20 }
21
22 # 4. Design tokens
23 Tool: Write
24 Parameters: {
25     "file_path": "presets-design/tokens/colors.json",
26     "content": "<color tokens JSON>"
27 }

```

```
28
29 # 5. Additional metadata files
30 Tool: Write
31 Parameters: {
32   "file_path": "presets-design/META-INF/container.xml",
33   "content": "<container XML>"
34 }
35
36 # ... repeat for all required files
```

File Creation Sequence

7.3 Document.json Structure

```
1 {
2   "$schema": "https://designlibre.app/schemas/preserve/1.0/document.
   json",
3   "id": "doc-presets-screen",
4   "name": "Presets Screen Design",
5   "version": "1.0.0",
6   "created": "2026-01-03T12:00:00.000Z",
7   "modified": "2026-01-03T12:00:00.000Z",
8   "generator": "Claude AI",
9   "generatorVersion": "1.0",
10  "pages": [
11    {
12      "id": "page-presets-main",
13      "name": "Presets Screen",
14      "path": "pages/page-presets-main.json"
15    }
16  ],
17  "settings": {
18    "gridSize": 8,
19    "snapToGrid": true,
20    "showRulers": true
21  }
22 }
```

document.json Content

8 Stage 6: Archive Packaging

8.1 ZIP Creation

The final step packages all files into a ZIP archive:

```
1 Tool: Bash
2 Parameters: {
3   "command": "cd presets-design && zip -r ../presets-screen.preserve
   mimetype document.json pages/ tokens/ components/ assets/ prototypes
   / history/ META-INF/"
4 }
```

ZIP Packaging Command

8.2 ZIP Structure Requirements

1. **Mimetype First:** The `mimetype` file must be the first entry in the ZIP archive (uncompressed) for proper MIME type detection
2. **No Compression for Mimetype:** Use `-0` flag for `mimetype` if needed
3. **Relative Paths:** All paths inside the ZIP are relative to the archive root

```

1 # Create ZIP with mimetype first (uncompressed)
2 cd presets-design
3 zip -0 ../presets-screen.preserve mimetype
4 zip -r ../presets-screen.preserve . -x mimetype

```

Proper ZIP Creation (with mimetype first)

9 Complete Tool Call Sequence

9.1 Chronological Tool Invocations

#	Tool	Purpose
1	Read	Load PNG image for visual analysis
2	Glob	Find .preserve-related source files
3	Grep	Search for PreserveNode type definitions
4	Read	Study preserve-archive.ts structure
5	Read	Study node-converter.ts for data mapping
6	Read	Study factory.ts for node creation
7	Read	Study types.ts for interfaces
8	Bash	Create directory structure
9	Write	Create mimetype file
10	Write	Create document.json
11	Write	Create pages/page-presets-main.json
12	Write	Create tokens/colors.json
13	Write	Create tokens/typography.json
14	Write	Create components/index.json
15	Write	Create assets/manifest.json
16	Write	Create prototypes/flows.json
17	Write	Create history/changelog.json
18	Write	Create META-INF/container.xml
19	Bash	Package into ZIP archive

Table 2: Complete Tool Call Sequence

10 Data Flow Diagram




Figure 2: Data Flow Through Conversion Pipeline

11 Limitations and Considerations

11.1 Manual Analysis Limitations

1. **Approximate Measurements:** Positions and dimensions are estimated from visual inspection, not pixel-perfect
2. **Font Detection:** Font families are inferred (e.g., "SF Pro" for iOS) rather than extracted
3. **Color Sampling:** Colors are approximated from visual observation
4. **No OCR:** Text content is read visually, not through OCR
5. **Complex Shapes:** Intricate vector paths cannot be perfectly recreated

11.2 Format Fidelity

Property	Accuracy	Method
Position (x, y)	$\pm 5\text{px}$	Visual estimation
Dimensions	$\pm 5\text{px}$	Visual estimation
Colors (solid)	High	Color picker approximation
Corner radius	Medium	Visual estimation
Font size	$\pm 2\text{px}$	Visual estimation
Text content	High	Manual transcription
Hierarchy	High	Logical grouping

Table 3: Property Extraction Accuracy

11.3 Potential Improvements

For automated PNG import, the following enhancements could be implemented:

1. **Computer Vision:** Use edge detection and segmentation for precise boundaries
2. **OCR Integration:** Extract text content programmatically
3. **Color Extraction:** Sample exact pixel colors from the image
4. **AI Segmentation:** Use Claude Vision API with structured output for element detection
5. **Template Matching:** Recognize common UI patterns (buttons, inputs, cards)

12 Conclusion

The PNG to .preserve conversion process involves six distinct stages:

1. **Visual Analysis:** Claude’s multimodal capabilities interpret the raster image
2. **Format Research:** Source code exploration reveals the .preserve specification
3. **Hierarchy Construction:** Visual elements are organized into a parent-child tree
4. **JSON Generation:** Each element becomes a PreserveNode with transform and appearance
5. **File Creation:** JSON documents are written to the required directory structure
6. **Archive Packaging:** Files are compressed into a ZIP with .preserve extension

The toolchain leverages Claude’s ability to:

- Read and interpret image files visually
- Search and understand source code for format specifications

- Generate structured JSON data from visual observations
- Execute file system operations through tool calls

This process transforms an opaque raster image into an editable, hierarchical design document that can be opened and modified in DesignLibre.