


EECS 203A - Digital Image Processing

EECS 203A - Digital Image Processing

Signal - a function $f(t)$ of the time variable t



EECS 203A - Digital Image Processing

Signal - a function $f(t)$ of the time variable t





Image - a function $f(x,y)$ of the spatial variables
 x and y



Digital Image — an image for which x , y , and f can only take on a finite number of discrete values. For example, $x = 0, 1, \dots, 511$ $y = 0, 1, \dots, 511$
 $f = 0, 1, \dots, 255$

Digital Image - an image for which x , y , and f can only take on a finite number of discrete values. For example, $x = 0, 1, \dots, 511$ $y = 0, 1, \dots, 511$
 $f = 0, 1, \dots, 255$

Digital Image Processing - the transformation of a digital image to another image or representation

Subareas of Digital Image Processing

Image Acquisition - the process of converting the physical state of the world into an image

Subareas of Digital Image Processing

Image Acquisition - the process of converting the physical state of the world into an image

Image Enhancement - the process of improving an image for human or machine interpretation

Subareas of Digital Image Processing

Image Acquisition - the process of converting the physical state of the world into an image

Image Enhancement - the process of improving an image for human or machine interpretation

Image Restoration - the process of removing the effects of degradation (e.g. noise, blurring) on an image

Subareas of Digital Image Processing

Image Acquisition - the process of converting the physical state of the world into an image

Image Enhancement - the process of improving an image for human or machine interpretation

Image Restoration - the process of removing the effects of degradation (e.g. noise, blurring) on an image

Multispectral Processing - techniques for analyzing images where $f(x,y) = (f_1(x,y), f_2(x,y), \dots, f_c(x,y))$ is a vector-valued two-dimensional function. For example, a color image is represented by $f(x,y) = (f_1(x,y), f_2(x,y), f_3(x,y))$

Subareas of Digital Image Processing

Multiresolution Processing – methods for representing images at different spatial scales

Subareas of Digital Image Processing

Multiresolution Processing – methods for representing images at different spatial scales

Compression – the process of reducing the number of bits used to represent a digital image

Image Acquisition

Images are often formed by focusing energy from
a scene onto an image plane

Image Acquisition

Images are often formed by focusing energy from a scene onto an image plane

FIGURE 2.3

Graphical representation of the eye looking at a palm tree. Point C is the optical center of the lens.





Image Acquisition

Images are often formed by focusing energy from a scene onto an image plane


FIGURE 2.3

Graphical representation of the eye looking at a palm tree. Point C is the optical center of the lens.



For a focused imaging system, each point on the image plane receives energy from a single direction in the scene. The energy that reaches location (x,y) in the image plane has a relationship with the object(s) in the scene that image to (x,y) .

Image Acquisition



An image can be sensed using different regions of the electromagnetic spectrum, e.g. x-rays, ultraviolet, visible, infrared, microwave

An image can be sensed using different regions of the electromagnetic spectrum, e.g. x-rays, ultraviolet, visible, infrared, microwave

Active Imaging – the source is a controlled component of the image acquisition system, e.g. imaging radar

An image can be sensed using different regions of the electromagnetic spectrum, e.g. x-rays, ultraviolet, visible, infrared, microwave

Active Imaging - the source is a controlled component of the image acquisition system, e.g. imaging radar

Passive Imaging - ambient scene energy is used to form an image

An image can be sensed using different regions of the electromagnetic spectrum, e.g. x-rays, ultraviolet, visible, infrared, microwave

Active Imaging - the source is a controlled component of the image acquisition system, e.g. imaging radar

Passive Imaging - ambient scene energy is used to form an image

For an energy measuring image acquisition system

$$0 \leq f(x,y) < \infty$$

Sampling and Quantization

The energy focused on an image plane provides a continuous image with continuous values of x, y and $f(x, y)$

Sampling and Quantization

The energy focused on an image plane provides a continuous image with continuous values of x, y and $f(x, y)$

A continuous image is transformed to a digital image by sampling and quantization.

Sampling and Quantization

The energy focused on an image plane provides a continuous image with continuous values of x, y and $f(x, y)$

A continuous image is transformed to a digital image by sampling and quantization.

Sampling - take $f(x, y)$ at discrete values of x and y to give an image with M rows and N columns

Sampling and Quantization

The energy focused on an image plane provides a continuous image with continuous values of x, y and $f(x, y)$

A continuous image is transformed to a digital image by sampling and quantization.

Sampling - take $f(x, y)$ at discrete values of x and y to give an image with M rows and N columns

Quantization - convert the value of f to one of L discrete values. L is often a power of 2.
 $(L = 2^K \text{ for integer } K)$

Sampling and Quantization

The energy focused on an image plane provides a continuous image with continuous values of x, y and $f(x, y)$

A continuous image is transformed to a digital image by sampling and quantization.

Sampling - take $f(x, y)$ at discrete values of x and y to give an image with M rows and N columns

Quantization - convert the value of f to one of L discrete values. L is often a power of 2.
($L = 2^K$ for integer K)

The number of bits required to store an image is $MN K$

Sampling and Quantization




FIGURE 2.15 An example of the digital image acquisition process. (a) Energy (“illumination”) source. (b) An element of a scene. (c) Imaging system. (d) Projection of the scene onto the image plane. (e) Digitized image.

Sampling and Quantization





FIGURE 2.16 Generating a digital image. (a) Continuous image. (b) A scan line from *A* to *B* in the continuous image, used to illustrate the concepts of sampling and quantization. (c) Sampling and quantization. (d) Digital scan line.

Sampling and Quantization



a b

FIGURE 2.17 (a) Continuous image projected onto a sensor array. (b) Result of image sampling and quantization.

After sampling, use integer values to index x and y
and let $(x,y) = (0,0)$ be the upper left location
in the image.




FIGURE 2.18
Coordinate convention used in this book to represent digital images.

Image as a Matrix

$$f(x,y) = \begin{bmatrix} f(0,0) & f(0,1) & \cdots & f(0,N-1) \\ f(1,0) & f(1,1) & \cdots & f(1,N-1) \\ \vdots & \vdots & & \vdots \\ f(M-1,0) & f(M-1,1) & \cdots & f(M-1,N-1) \end{bmatrix}$$

Image as a Matrix

$$f(x,y) = \begin{bmatrix} f(0,0) & f(0,1) & \cdots & f(0,N-1) \\ f(1,0) & f(1,1) & \cdots & f(1,N-1) \\ \vdots & \vdots & & \vdots \\ f(M-1,0) & f(M-1,1) & \cdots & f(M-1,N-1) \end{bmatrix}$$

Each element of this matrix is a pixel and the values taken by pixels are typically represented as integers.

Image as a Matrix

$$f(x,y) = \begin{bmatrix} f(0,0) & f(0,1) & \cdots & f(0,N-1) \\ f(1,0) & f(1,1) & \cdots & f(1,N-1) \\ \vdots & \vdots & & \vdots \\ f(M-1,0) & f(M-1,1) & \cdots & f(M-1,N-1) \end{bmatrix}$$

Each element of this matrix is a pixel and the values taken by pixels are typically represented as integers.

Spatial resolution increases as M and N increase.
Gray-level (intensity) resolution increases as L increases.

Changing the Spatial Resolution of a Digital Image

Zoom - increase M and N for a digital image

Shrink - decrease M and N for a digital image

Changing the Spatial Resolution of a Digital Image

Zoom - increase M and N for a digital image

Shrink - decrease M and N for a digital image

Methods for Zoom

Pixel replication - increase M to rM and N to rN for an integer $r > 1$ by replacing each column with r copies of the column and then replacing each row with r copies of the row

Pixel replication

(Ex) original 3×3 image

1	2	3
4	5	6
7	8	9

Pixel replication

(Ex) original 3×3 image

	1	2	3
	4	5	6
	7	8	9

column replacement

$r = 2$

1	1	2	2	3	3
4	4	5	5	6	6
7	7	8	8	9	9

Pixel replication

(Ex) original 3×3 image

	1	2	3
	4	5	6
	7	8	9

column replacement

$r = 2$


	1	1	2	2	3	3
	4	4	5	5	6	6
	7	7	8	8	9	9

row replacement

$r = 2$

	1	1	2	2	3	3
	1	1	2	2	3	3
	4	4	5	5	6	6
	4	4	5	5	6	6
	7	7	8	8	9	9
	7	7	8	8	9	9

Pixel replication



a b c
d e f

FIGURE 2.20 (a) 1024 × 1024, 8-bit image. (b) 512 × 512 image resampled into 1024 × 1024 pixels by row and column duplication. (c) through (f) 256 × 256, 128 × 128, 64 × 64, and 32 × 32 images resampled into 1024 × 1024 pixels.

Methods for Zoom

Interpolation - increase M to rM and N to rN for a real number $r > 1$ by generating a $rM \times rN$ sampling grid on the original image and interpolating to get the pixel values on the new sampling grid.

Interpolation

(Ex) $M=4, N=4, r=1.25$



* = original
image samples

Interpolation

(Ex) $M=4, N=4, r=1.25$



• = original
image samples

Generate a $rM \times rN$ sampling grid on the
original image.

X X • X • X X

X X X X X


X X X X X

X X X X X

X X • X • X X

• = original
image samples

X = zoomed
image samples



For each X sample (zoomed image) use pixel values
 at nearby \cdot samples (original image) to interpolate
 the pixel value at the X sample.

Nearest Neighbor Interpolation – assign the pixel value at each sample in the zoomed image as the pixel value for the closest sample in the original image.

X X • X • X X

• = original

X X X X X

image samples

• • • • •

X = zoomed

X X X X X


image samples

• • • • •


X X X X X

X X • X • X X

NN Interpolation generates a piecewise constant
interpolating function



NN Interpolation generates a piecewise constant
interpolating function



2-D NN
interpolation

10 .	12 .
12 .	14 .

piecewise
constant
interpolation

2-D NN
interpolation

10 .	12 .
12 .	14 .

piecewise
constant
interpolation

If r is large, nearest neighbor interpolation gives
a blocky zoomed image.

2-D NN
interpolation

10 .	12 .
12 .	14 .

piecewise
constant
interpolation

If r is large, nearest neighbor interpolation gives
a blocky zoomed image.



FIGURE 2.25 Top row: images zoomed from 128×128 , 64×64 , and 32×32 pixels to 1024×1024 pixels, using nearest neighbor gray-level interpolation. Bottom row: same sequence, but using bilinear interpolation.

Bilinear interpolation - for each sample (x', y') in the zoomed image, find the closest 4 samples $(x_1, y_1), (x_2, y_2), (x_3, y_3), (x_4, y_4)$ in the original image $f_o(x, y)$.

$\times \quad x \circ \quad x \quad \circ \quad x \quad \times$

$\circ =$ original

$\times \quad x \quad x \quad x \quad x$

image samples

$\circ \quad \circ \quad \circ \quad \circ \quad \circ$

$x =$ zoomed

$\times \quad x \quad x \quad x \quad x$

image samples


$\circ \quad \circ \quad \circ \quad \circ \quad \circ$

$\times \quad x \quad x \quad x \quad x$

$\times \quad x \circ \quad x \quad \circ \quad x \quad \times$

Bilinear interpolation

Assume a continuous model for $f_0(x,y)$ near (x',y') of the form $f_0(x,y) = ax + by + cxy + d$



Bilinear interpolation

Solve for a, b, c, d using the equations

$$f_0(x_1, y_1) = ax_1 + by_1 + cx_1y_1 + d$$

$$f_0(x_2, y_2) = ax_2 + by_2 + cx_2y_2 + d$$

$$f_0(x_3, y_3) = ax_3 + by_3 + cx_3y_3 + d$$

$$f_0(x_4, y_4) = ax_4 + by_4 + cx_4y_4 + d$$

Bilinear interpolation

Solve for a, b, c, d using the equations

$$f_o(x_1, y_1) = ax_1 + by_1 + cx_1y_1 + d$$

$$f_o(x_2, y_2) = ax_2 + by_2 + cx_2y_2 + d$$

$$f_o(x_3, y_3) = ax_3 + by_3 + cx_3y_3 + d$$

$$f_o(x_4, y_4) = ax_4 + by_4 + cx_4y_4 + d$$

Assign the pixel value at x', y' in the zoomed image f_z as

$$f_z(x', y') = ax' + by' + cx'y' + d$$

Bilinear interpolation



FIGURE 2.25 Top row: images zoomed from 128×128 , 64×64 , and 32×32 pixels to 1024×1024 pixels, using nearest neighbor gray-level interpolation. Bottom row: same sequence, but using bilinear interpolation.

Methods for Shrink

Subsampling (Row-column deletion) - reduce M to $\frac{M}{r}$ and N to $\frac{N}{r}$ for an integer $r > 1$ by starting from the first and taking every r -th row and every r -th column.

Subsampling

(Ex) original 6×6 image

1	1	2	2	3	3
1	1	2	2	3	3
4	4	5	5	6	6
4	4	5	5	6	6
7	7	8	8	9	9
7	7	8	8	9	9

Subsampling

(Ex) original 6×6 image

1	1	2	2	3	3
1	1	2	2	3	3
4	4	5	5	6	6
4	4	5	5	6	6
7	7	8	8	9	9
7	7	8	8	9	9

row deletion

$r=2$

1	1	2	2	3	3
4	4	5	5	6	6
7	7	8	8	9	9

Subsampling

(Ex) original 6×6 image

1	1	2	2	3	3
1	1	2	2	3	3
4	4	5	5	6	6
4	4	5	5	6	6
7	7	8	8	9	9
7	7	8	8	9	9

row deletion

$r=2$


1	1	2	2	3	3
4	4	5	5	6	6
7	7	8	8	9	9

column deletion

$r=2$

1	2	3
4	5	6
7	8	9

Subsampling




32
64

FIGURE 2.19 A 1024×1024 , 8-bit image subsampled down to size 32×32 pixels. The number of allowable gray levels was kept at 256.

Methods for Shrink

Interpolation - reduce M to $\frac{M}{r}$ and N to $\frac{N}{r}$
for a real number $r > 1$ by generating a
 $\frac{M}{r} \times \frac{N}{r}$ sampling grid on the original image
and interpolating to get the pixel values on the
new sampling grid.

Changing the Gray-Level Resolution of a Digital Image



a b
c d

FIGURE 2.21
(a) 452×374 ,
256-level image.
(b)–(d) Image
displayed in 128,
64, and 32 gray
levels, while
keeping the
spatial resolution
constant.


Changing the Gray-Level Resolution of a Digital Image

e f
g h

FIGURE 2.21


(Continued)

(e)–(h) Image displayed in 16, 8, 4, and 2 gray levels. (Original courtesy of Dr. David R. Pickens, Department of Radiology & Radiological Sciences, Vanderbilt University Medical Center.)




Neighbor Sets

A pixel P at (x, y) has the 4 horizontal and vertical neighbors



Neighbor Sets


A pixel P at (x, y) has the 4 horizontal and vertical neighbors



Define $N_4(P)$ to be this set of 4 pixels called
4-neighbors of P


Neighbor Sets

A pixel P at (x, y) has the 4 horizontal and vertical neighbors




Define $N_4(P)$ to be this set of 4 pixels called 4-neighbors of P

A pixel P at (x, y) has the 4 diagonal neighbors




Neighbor Sets

A pixel P at (x, y) has the 4 horizontal and vertical neighbors



Define $N_4(P)$ to be this set of 4 pixels called 4-neighbors of P

A pixel P at (x, y) has the 4 diagonal neighbors



Define $N_8(P)$ to be the union of the 4 diagonal neighbors of P and $N_4(P)$

Let V be a set of gray levels that define adjacency

Let V be a set of gray levels that define adjacency

Pixels P and Q are 4-adjacent if $Q \in N_4(P)$ and
 P and Q both have values in V .

Let V be a set of gray levels that define adjacency

Pixels P and Q are 4-adjacent if $Q \in N_4(P)$ and
 P and Q both have values in V .

Pixels P and Q are 8-adjacent if $Q \in N_8(P)$ and
 P and Q both have values in V .

Let V be a set of gray levels that define adjacency

Pixels P and Q are 4-adjacent if $Q \in N_4(P)$ and P and Q both have values in V .

Pixels P and Q are 8-adjacent if $Q \in N_8(P)$ and P and Q both have values in V .

Ex Let $V = \{2, 3\}$

$$\begin{bmatrix} f(0,0) & f(0,1) & f(0,2) \\ f(1,0) & f(1,1) & f(1,2) \\ f(2,0) & f(2,1) & f(2,2) \end{bmatrix} = \begin{bmatrix} 2 & 3 & 4 \\ 5 & 6 & 2 \\ 2 & 7 & 7 \end{bmatrix}$$

Let V be a set of gray levels that define adjacency

Pixels P and Q are 4-adjacent if $Q \in N_4(P)$ and P and Q both have values in V .

Pixels P and Q are 8-adjacent if $Q \in N_8(P)$ and P and Q both have values in V .

Ex Let $V = \{2, 3\}$

$$\begin{bmatrix} f(0,0) & f(0,1) & f(0,2) \\ f(1,0) & f(1,1) & f(1,2) \\ f(2,0) & f(2,1) & f(2,2) \end{bmatrix} = \begin{bmatrix} 2 & 3 & 4 \\ 5 & 6 & 2 \\ 2 & 7 & 7 \end{bmatrix}$$

$f(0,0)$ and $f(0,1)$ are 4-adjacent

Let V be a set of gray levels that define adjacency

Pixels P and Q are 4-adjacent if $Q \in N_4(P)$ and P and Q both have values in V .

Pixels P and Q are 8-adjacent if $Q \in N_8(P)$ and P and Q both have values in V .

Ex Let $V = \{2, 3\}$

$$\begin{bmatrix} f(0,0) & f(0,1) & f(0,2) \\ f(1,0) & f(1,1) & f(1,2) \\ f(2,0) & f(2,1) & f(2,2) \end{bmatrix} = \begin{bmatrix} 2 & 3 & 4 \\ 5 & 6 & 2 \\ 2 & 7 & 7 \end{bmatrix}$$

$f(0,0)$ and $f(0,1)$ are 4-adjacent

$f(0,0)$ and $f(0,1)$ are 8-adjacent

Let V be a set of gray levels that define adjacency

Pixels P and Q are 4-adjacent if $Q \in N_4(P)$ and P and Q both have values in V .

Pixels P and Q are 8-adjacent if $Q \in N_8(P)$ and P and Q both have values in V .

Ex Let $V = \{2, 3\}$

$$\begin{bmatrix} f(0,0) & f(0,1) & f(0,2) \\ f(1,0) & f(1,1) & f(1,2) \\ f(2,0) & f(2,1) & f(2,2) \end{bmatrix} = \begin{bmatrix} 2 & 3 & 4 \\ 5 & 6 & 2 \\ 2 & 7 & 7 \end{bmatrix}$$

$f(0,0)$ and $f(0,1)$ are 4-adjacent

$f(0,0)$ and $f(0,1)$ are 8-adjacent

$f(0,1)$ and $f(1,2)$ are 8-adjacent

A path from the pixel at (x_0, y_0) to the pixel at (x_n, y_n) is defined by a sequence of distinct coordinates $(x_0, y_0), (x_1, y_1), \dots, (x_n, y_n)$ where the pixels corresponding to any consecutive pair of coordinates in the sequence are adjacent. Adjacent can be defined as 4-adjacent or 8-adjacent

A path from the pixel at (x_0, y_0) to the pixel at (x_n, y_n) is defined by a sequence of distinct coordinates $(x_0, y_0), (x_1, y_1), \dots, (x_n, y_n)$ where the pixels corresponding to any consecutive pair of coordinates in the sequence are adjacent. Adjacent can be defined as 4-adjacent or 8-adjacent.

Ex Let $V = \{2, 3\}$

$$\begin{bmatrix} f(0,0) & f(0,1) & f(0,2) \\ f(1,0) & f(1,1) & f(1,2) \\ f(2,0) & f(2,1) & f(2,2) \end{bmatrix} = \begin{bmatrix} 2 & 3 & 4 \\ 5 & 6 & 2 \\ 2 & 7 & 7 \end{bmatrix}$$

An 8-adjacent path from $f(0,0)$ to $f(1,2)$ is defined by $(0,0), (0,1), (1,2)$

Two pixels are connected if there exists a path between them.

Two pixels are connected if there exists a path between them.

Ex Let $V = \{2, 3\}$

$$\begin{bmatrix} f(0,0) & f(0,1) & f(0,2) \\ f(1,0) & f(1,1) & f(1,2) \\ f(2,0) & f(2,1) & f(2,2) \end{bmatrix} = \begin{bmatrix} 2 & 3 & 4 \\ 5 & 6 & 2 \\ 2 & 7 & 7 \end{bmatrix}$$

Two pixels are connected if there exists a path between them.

Ex Let $V = \{2, 3\}$

$$\begin{bmatrix} f(0,0) & f(0,1) & f(0,2) \\ f(1,0) & f(1,1) & f(1,2) \\ f(2,0) & f(2,1) & f(2,2) \end{bmatrix} = \begin{bmatrix} 2 & 3 & 4 \\ 5 & 6 & 2 \\ 2 & 7 & 7 \end{bmatrix}$$

Using 8-adjacency, $f(0,0)$ is connected to $f(1,2)$

Two pixels are connected if there exists a path between them.

Ex Let $V = \{2, 3\}$

$$\begin{bmatrix} f(0,0) & f(0,1) & f(0,2) \\ f(1,0) & f(1,1) & f(1,2) \\ f(2,0) & f(2,1) & f(2,2) \end{bmatrix} = \begin{bmatrix} 2 & 3 & 4 \\ 5 & 6 & 2 \\ 2 & 7 & 7 \end{bmatrix}$$

Using 8-adjacency, $f(0,0)$ is connected to $f(1,2)$

Using 4-adjacency, $f(0,0)$ is not connected to $f(1,2)$

Given a pixel P with a gray level in V , the set consisting of P and all pixels that are connected to P is called a connected component.

Given a pixel P with a gray level in V , the set consisting of P and all pixels that are connected to P is called a connected component.

(Ex) Using 4-adjacency, the image has 3 connected components

(2)	3	4
5	6	(2)
(2)	7	7

Given a pixel P with a gray level in V , the set consisting of P and all pixels that are connected to P is called a connected component.

(Ex) Using 4-adjacency, the image has 3 connected components

(2)	3	4
5	6	(2)
(2)	7	7

Using 8-adjacency, the image has 2 connected components

(2)	3	4
5	6	2
(2)	7	7

Operators

Operations of

- 1) Multiplication of an image by a scalar
- 2) Addition of two images

are defined the same as the corresponding operations
for matrices.

Operators

Operations of

1) Multiplication of an image by a scalar

2) Addition of two images

are defined the same as the corresponding operations
for matrices.

Operations of

1) Multiplying two images

2) Dividing two images

generate an output image by 1) multiplying or

2) dividing corresponding elements of the two images

Operators

Operations of

1) Multiplication of an image by a scalar

2) Addition of two images

are defined the same as the corresponding operations
for matrices.

Operations of

1) Multiplying two images

2) Dividing two images

generate an output image by 1) multiplying or

2) dividing corresponding elements of the two images

To add, multiply, or divide two images, the images
must be the same size.

Operators

Let H be an operator that maps an image to an image. H is a linear operator if

$$H[af(x,y) + bg(x,y)] = aH[f(x,y)] + bH[g(x,y)]$$

for any images $f(x,y)$ and $g(x,y)$ and for any scalars a and b .

An operator that is not linear is called nonlinear.

Ex $H[I(x,y)] = K(x,y) I(x,y)$

where $K(x,y)$ is an image that multiplies the input image.

Ex $H[I(x,y)] = K(x,y) I(x,y)$

where $K(x,y)$ is an image that multiplies the input image.

$$H[af(x,y) + bg(x,y)] = K(x,y)(af(x,y) + bg(x,y))$$

Ex $H[I(x,y)] = K(x,y) I(x,y)$

where $K(x,y)$ is an image that multiplies the input image.

$$\begin{aligned} H[af(x,y) + bg(x,y)] &= K(x,y)(af(x,y) + bg(x,y)) \\ &= aK(x,y)f(x,y) + bK(x,y)g(x,y) \end{aligned}$$

Ex $H[I(x,y)] = K(x,y) I(x,y)$

where $K(x,y)$ is an image that multiplies the input image.

$$\begin{aligned} H[af(x,y) + bg(x,y)] &= K(x,y)(af(x,y) + bg(x,y)) \\ &= aK(x,y)f(x,y) + bK(x,y)g(x,y) \\ &= aH[f(x,y)] + bH[g(x,y)] \end{aligned}$$

Ex $H[I(x,y)] = K(x,y) I(x,y)$

where $K(x,y)$ is an image that multiplies the input image.

$$\begin{aligned} H[af(x,y) + bg(x,y)] &= K(x,y)(af(x,y) + bg(x,y)) \\ &= aK(x,y)f(x,y) + bK(x,y)g(x,y) \\ &= aH[f(x,y)] + bH[g(x,y)] \end{aligned}$$

LINEAR

$$\textcircled{Ex} \quad H[I(x,y)] = I(x,y)I(x,y)$$

the operator multiplies the input image by itself

(Ex) $H[I(x,y)] = I(x,y)I(x,y)$

the operator multiplies the input image by itself

$$H[af(x,y) + bg(x,y)] = (af(x,y) + bg(x,y))(af(x,y) + bg(x,y))$$

(Ex) $H[I(x,y)] = I(x,y)I(x,y)$

the operator multiplies the input image by itself

$$\begin{aligned} H[a f(x,y) + b g(x,y)] &= (a f(x,y) + b g(x,y))(a f(x,y) + b g(x,y)) \\ &= a^2 f(x,y)f(x,y) + 2ab f(x,y)g(x,y) + b^2 g(x,y)g(x,y) \end{aligned}$$

(Ex) $H[I(x,y)] = I(x,y)I(x,y)$

the operator multiplies the input image by itself

$$H[a f(x,y) + b g(x,y)] = (a f(x,y) + b g(x,y))(a f(x,y) + b g(x,y)) \\ = a^2 f(x,y)f(x,y) + 2ab f(x,y)g(x,y) + b^2 g(x,y)g(x,y)$$

$$a H[f(x,y)] + b H[g(x,y)] = a f(x,y)f(x,y) + b g(x,y)g(x,y)$$

(Ex) $H[I(x,y)] = I(x,y)I(x,y)$

the operator multiplies the input image by itself

$$H[af(x,y) + bg(x,y)] = (af(x,y) + bg(x,y))(af(x,y) + bg(x,y)) \\ = a^2f(x,y)f(x,y) + 2abf(x,y)g(x,y) + b^2g(x,y)g(x,y)$$

$$aH[f(x,y)] + bH[g(x,y)] = af(x,y)f(x,y) + bg(x,y)g(x,y)$$

NONLINEAR