

Neural Networks: Learning (Backpropagation)

CS229: Machine Learning

Stanford University, Winter 2024

(Adapted from slides by Matgus Telgarsky and Alexander Schwing)

Goals of this lecture

- Understanding the forward and backward pass in deep networks
- Understand backpropagation in deep networks


Goals of this lecture

- Understanding the forward and backward pass in deep networks
- Understand backpropagation in deep networks

Reading material

- Course Notes, Section 7.3
- I. Goodfellow et al.; Deep Learning; Chapters 6-9

Lecture notation



Notation	Usage
$h(\cdot)$	Feature function; $h(\cdot)$ in the notes
$f(\cdot), F(\cdot)$	Prediction function; $h(\cdot)$ in the notes
$l(\cdot, \cdot)$	Loss function; $J(\cdot)$ in the notes
w, W	Model Parameters, θ in the notes
$x^{(i)}, x$	Input(s)
$y^{(i)}, y$	Label(s)
\hat{y}	Prediction; \hat{o} in the notes
α_k	step size in decent methods
λ	Regularization parameter(s); C in the notes
$\sigma(\cdot)$	Activation function, nonlinearity

Recap: Our (regularized) learning framework:

$$\min_{\mathbf{w}} -\log P(y|x; \mathbf{w}) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2 \quad \equiv \quad \min_{\mathbf{w}} \ell(y, f(x)) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2$$

Recap: Our (regularized) learning framework:

$$f(x) = \mathbf{w}^T h(x)$$

$$\min_{\mathbf{w}} -\log P(y|x; \mathbf{w}) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2 \quad \equiv \quad \min_{\mathbf{w}} \ell(y, f(x)) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2$$

What are possible issues/limitations?

Recap: Our (regularized) learning framework:

$$\min_{\mathbf{w}} -\log P(y|x; \mathbf{w}) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2 \quad \equiv \quad \min_{\mathbf{w}} \ell(y, f(x)) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2$$

What are possible issues/limitations?

Linearity in the feature space $h(x, y)$. Fix: use feature design. But still learning a model **linear** in the parameters \mathbf{w}

Recap: Our (regularized) learning framework:

$$\min_{\mathbf{w}} -\log P(y|x; \mathbf{w}) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2 \quad \equiv \quad \min_{\mathbf{w}} \ell(y, f(x)) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2$$

What are possible issues/limitations?

Linearity in the feature space $h(x, y)$. Fix: use feature design. But still learning a model **linear** in the parameters w

How to extend this?

Recap: Our (regularized) learning framework:

$$\min_{\mathbf{w}} -\log P(y|x; \mathbf{w}) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2 \quad \equiv \quad \min_{\mathbf{w}} \ell(y, f(x)) + \frac{\lambda}{2} \|\mathbf{w}\|_2^2$$

What are possible issues/limitations?


Linearity in the feature space $h(x, y)$. Fix: use feature design. But still learning a model **linear** in the parameters w

How to extend this?

Replace $\mathbf{w}^T h(x)$ with a general function $f(x)$

Deep Learning:

What function $f(x)$ to choose?



Deep Learning:

What function $f(x)$ to choose?

- Can choose any differentiable composite function

$$f(x; \mathbf{w}) = f_L(\mathbf{w}^L, f_{L-1}(\mathbf{w}^{L-1}, f_{L-2}(\dots f_1(\mathbf{w}^1, x) \dots)))$$

$$\sigma \begin{pmatrix} v_1 \\ \vdots \\ v_m \end{pmatrix} = \begin{bmatrix} \sigma(v_1) \\ \sigma(v_2) \\ \vdots \\ \sigma(v_m) \end{bmatrix}$$

sigmoid
ReLU

$\sigma(w \cdot x)$

$\sigma(w^{L-1} f_{L-2})$

Deep Learning:

What function $f(x)$ to choose?

- Can choose any differentiable composite function

$$f(x; \mathbf{w}) = f_L(\mathbf{w}^L, f_{L-1}(\mathbf{w}^{L-1}, f_{L-2}(\dots f_1(\mathbf{w}^1, x) \dots)))$$

- For deep learning, we choose the interleaved composition of linear functions and non-linear activations

$$f(x) = \mathbf{W}^{[L]} \sigma_{L-1} \left(\dots \sigma_1 (\mathbf{W}^{[1]} \mathbf{x}^{(i)} + \mathbf{b}^{[1]}) \dots \right)$$

Optimization.

Regularized learning now takes the form

$$\min_{\mathbf{W}^{[1]}, \dots, \mathbf{W}^{[L]}, \mathbf{b}^{[1]}, \dots, \mathbf{b}^{[L]}} \frac{1}{n} \sum_{i=1}^n \ell \left(y^{(i)}, \mathbf{W}^{[L]} \sigma_{L-1} \left(\dots \sigma_1 (\mathbf{W}^{[1]} \mathbf{x}^{(i)} + \mathbf{b}^{[1]}) \dots \right) \right) + \lambda \sum_{l=1}^L \|\mathbf{W}^{[l]}\|_2^2$$

Optimization.

Regularized learning now takes the form

$$\min_{\mathbf{W}^{[1]}, \dots, \mathbf{W}^{[L]}, \mathbf{b}^{[1]}, \dots, \mathbf{b}^{[L]}} \frac{1}{n} \sum_{i=1}^n \ell \left(y^{(i)}, \mathbf{W}^{[L]} \sigma_{L-1} \left(\dots \sigma_1 \left(\mathbf{W}^{[1]} \mathbf{x}^{(i)} + \mathbf{b}^{[1]} \right) \dots \right) \right) + \lambda \sum_{l=1}^L \|\mathbf{W}^{[l]}\|_2^2$$

In general, resulting optimization is "harder" than linear regression

Optimization.

Regularized learning now takes the form

$$\min_{\mathbf{W}^{[1]}, \dots, \mathbf{W}^{[L]}, \mathbf{b}^{[1]}, \dots, \mathbf{b}^{[L]}} \frac{1}{n} \sum_{i=1}^n \ell \left(y^{(i)}, \mathbf{W}^{[L]} \sigma_{L-1} \left(\dots \sigma_1 \left(\mathbf{W}^{[1]} \mathbf{x}^{(i)} + \mathbf{b}^{[1]} \right) \dots \right) \right) + \lambda \sum_{l=1}^L \|\mathbf{W}^{[l]}\|_2^2$$

In general, resulting optimization is "harder" than linear regression

Implications:

- Gradient-based optimization approaches is no longer guaranteed to find the global optimum
- Initialization of parameters matters

Optimization.

Regularized learning now takes the form

$$\min_{\mathbf{W}^{[1]}, \dots, \mathbf{W}^{[L]}, \mathbf{b}^{[1]}, \dots, \mathbf{b}^{[L]}} \frac{1}{n} \sum_{i=1}^n \ell \left(y^{(i)}, \mathbf{W}^{[L]} \sigma_{L-1} \left(\dots \sigma_1 \left(\mathbf{W}^{[1]} \mathbf{x}^{(i)} + \mathbf{b}^{[1]} \right) \dots \right) \right) + \lambda \sum_{l=1}^L \|\mathbf{W}^{[l]}\|_2^2$$

In general, resulting optimization is "harder" than linear regression

Implications:

- Gradient-based optimization approaches is no longer guaranteed to find the global optimum
- Initialization of parameters matters
- Stochastic gradient descent works well in practice

Notation for Multiclass classification

Recall: for multiclass classification with $y \in [1, \dots K]$, the prediction function

$$f(x) \in ?$$

Notation for Multiclass classification

Recall: for multiclass classification with $y \in [1, \dots, K]$, the prediction function

$$f(x) \in \mathbb{R}^K,$$

i.e., the prediction is a vector function.

Handwritten red annotations illustrating the prediction function $f(x)$ as a vector of probabilities. A large red bracket encloses the following expressions:

$$\begin{matrix} p(y=1|x) \\ \vdots \\ p(y=K|x) \end{matrix}$$

Two red arrows point from the text $f(x) \in \mathbb{R}^K$ to the top and bottom of the bracketed list, indicating that the vector components are the probabilities for each class.

Notation for Multiclass classification

Recall: for multiclass classification with $y \in [1, \dots K]$, the prediction function

$$f(x) \in \mathbb{R}^K,$$

i.e., the prediction is a vector function.

Convenient notation: replace $F(w, y, x) = [f(x)]_y$, i.e., the y^{th} index of $f(x)$

Notation for Multiclass classification

Recall: for multiclass classification with $y \in [1, \dots, K]$, the prediction function

$$f(x) \in \mathbb{R}^K,$$

i.e., the prediction is a vector function.

Convenient notation: replace $F(\mathbf{w}, y, x) = [f(x)]_y$, i.e., the y^{th} index of $f(x)$

Implemented as:


$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(\dots)))$$

$\{f_1(w_1, f_2(w_2, \dots))\}_y$


Computation Graph Representation:

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(\dots)))$$

Nodes are weights, data, and functions:



Internal representation used by deep net packages.




What are the individual functions/layers f_1 , f_2 etc.?

What are the individual functions/layers f_1, f_2 etc.?

- Fully connected layer(s)
- Convolutions
- Univariate activations e.g. rectified linear units (ReLU): $\max\{0, x\}$
- Maximum-/Average pooling (sometimes called subsampling)
- Soft-max layer

Recall: Convolutions



Recall: Convolutions


120	190	140	150	200
17	21	30	8	27
89	123	150	73	56
10	178	140	150	18
190	14	76	69	87

x

1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

=

	98	98		



Recall: Convolutions


120	190	140	150	200
17	21	30	8	27
89	123	150	73	56
10	178	140	150	18
190	14	76	69	87

x

1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

=

	98	98	93	



Recall: Convolutions


120	190	140	150	200
17	21	30	8	27
89	123	150	73	56
10	178	140	150	18
190	14	76	69	87

 \times

1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

 $=$

	98	98	93	
	84			



Recall: Convolutions


120	190	140	150	200
17	21	30	8	27
89	123	150	73	56
10	178	140	150	18
190	14	76	69	87

 \times

1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

 $=$

	98	98	93	
	84	97		



Recall: Convolutions


120	190	140	150	200
17	21	30	8	27
89	123	150	73	56
10	178	140	150	18
190	14	76	69	87

 \times

1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

 $=$

	98	98	93	
	84	97	72	



Recall: Convolutions


120	190	140	150	200
17	21	30	8	27
89	123	150	73	56
10	178	140	150	18
190	14	76	69	87

x

1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

=

	98	98	93	
	84	97	72	
	108			



Recall: Convolutions


120	190	140	150	200
17	21	30	8	27
89	123	150	73	56
10	178	140	150	18
190	14	76	69	87

 \times

1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

 $=$

	98	98	93	
	84	97	72	
	108	108		



Recall: Convolutions


120	190	140	150	200
17	21	30	8	27
89	123	150	73	56
10	178	140	150	18
190	14	76	69	87

x

1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

=

	98	98	93	
	84	97	72	
	108	108	91	



Recall: Convolutions

120	190	140	150	200
17	21	30	8	27
89	123	150	73	56
10	178	140	150	18
190	14	76	69	87

 \times


1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

 $=$

	98	98	93	
	84	97	72	
	108	108	91	

Trainable parameters w :

- Filters
- Bias
- Hyper-parameters (selected): width, height, depth, number, stride, padding




Example function architecture: Multilayer Perceptron (MLP)


The default, i.e., (multiple) fully connected layers
(often called MLP when used at the output).

$$f(x) = \sigma(w^2 \sigma(w^1 x))$$


$x \in \mathbb{R}^d$
 $z \in \mathbb{R}^m$
 $f(x) \in \mathbb{R}$




Example function architecture: LeNet



Example function architecture: AlexNet



Another deep net:




Note: These nets are structurally simple in that a layer's output is used as input for the next layer. This is not required.

Dropout:

Randomly set activations to zero

Trainable parameters w :

- None



Deep net training for multiclass classification (multiclass logistic loss):

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

Deep net training for multiclass classification (multiclass logistic loss):

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

Equivalently, as regularized cross entropy:

$$\max_{\mathbf{w}} -\frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \sum_{\hat{y}} p_{\text{GT}}^{(i)}(\hat{y}) \ln p(\hat{y} | x^{(i)}) \quad \text{with} \quad \begin{cases} p_{\text{GT}}^{(i)}(\hat{y}) = \delta(\hat{y} = y^{(i)}) \\ p(\hat{y} | x) \propto \exp F(\mathbf{w}, x, \hat{y}) \end{cases}$$

input
true
O/U

Deep net training for multiclass classification (multiclass logistic loss):

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

Equivalently, as regularized cross entropy:

$$\max_{\mathbf{w}} -\frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \sum_{\hat{y}} p_{\text{GT}}^{(i)}(\hat{y}) \ln p(\hat{y} | x^{(i)}) \quad \text{with} \quad \begin{cases} p_{\text{GT}}^{(i)}(\hat{y}) = \delta(\hat{y} = y^{(i)}) \\ p(\hat{y} | x) \propto \exp F(\mathbf{w}, x, \hat{y}) \end{cases}$$

What is λ ?

Deep net training for multiclass classification (multiclass logistic loss):

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

Equivalently, as regularized cross entropy:

$$\max_{\mathbf{w}} -\frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \sum_{\hat{y}} p_{\text{GT}}^{(i)}(\hat{y}) \ln p(\hat{y} | x^{(i)}) \quad \text{with} \quad \begin{cases} p_{\text{GT}}^{(i)}(\hat{y}) = \delta(\hat{y} = y^{(i)}) \\ p(\hat{y} | x) \propto \exp F(\mathbf{w}, x, \hat{y}) \end{cases}$$

What is λ ? Weight decay (aka regularization constant)

Deep net training for multiclass classification (multiclass logistic loss):

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

Equivalently, as regularized cross entropy:

$$\max_{\mathbf{w}} -\frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \sum_{\hat{y}} p_{\text{GT}}^{(i)}(\hat{y}) \ln p(\hat{y}|x^{(i)}) \quad \text{with} \quad \begin{cases} p_{\text{GT}}^{(i)}(\hat{y}) = \delta(\hat{y} = y^{(i)}) \\ p(\hat{y}|x) \propto \exp F(\mathbf{w}, x, \hat{y}) \end{cases}$$

What is λ ? Weight decay (aka regularization constant)

$$\min_{\mathbf{w}} \underbrace{\frac{\lambda}{2} \|\mathbf{w}\|_2^2}_{\text{weight decay}} - \underbrace{\sum_{i \in [N]} \sum_{\hat{y}} p_{\text{GT}}^{(i)}(\hat{y}) \ln p(\hat{y}|x^{(i)})}_{\ell(y, F)}$$

Optimization Problem:

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

How to optimize this?

Optimization Problem:

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$


How to optimize this?

Stochastic gradient descent: What was this again?

Use the Chain Rule! Gradient of

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

is:

$$\frac{\lambda \mathbf{w}}{2} + \sum_i \left[\left(\frac{e^{F(i)}}{\sum_{\hat{y}} e^{F(i)}} \right) - \delta(i) \right] \frac{\partial F(i)}{\partial \mathbf{w}}$$


Use the Chain Rule! Gradient of

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

is:

$$\lambda \mathbf{w} + \sum_{i \in [N]} \sum_{\hat{y}} \left(p(\hat{y} | x^{(i)}) - \delta(\hat{y} = y^{(i)}) \right) \frac{\partial F(\mathbf{w}, x^{(i)}, \hat{y})}{\partial \mathbf{w}}$$

$$\frac{e^F}{\sum e^F}$$

Use the Chain Rule! Gradient of

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

is:

$$\lambda \mathbf{w} + \sum_{i \in [N]} \sum_{\hat{y}} \left(p(\hat{y} | x^{(i)}) - \delta(\hat{y} = y^{(i)}) \right) \frac{\partial F(\mathbf{w}, x^{(i)}, \hat{y})}{\partial \mathbf{w}}$$

How to compute this numerically:

- $p(\hat{y} | x) = \frac{\exp F(\mathbf{w}, x, \hat{y})}{\sum_{\tilde{y}} \exp F(\mathbf{w}, x, \tilde{y})}$ via soft-max which takes F as input

Use the Chain Rule! Gradient of

$$\min_{\mathbf{w}} \frac{\lambda}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in [N]} \left(\ln \sum_{\hat{y}} \exp F(\mathbf{w}, x^{(i)}, \hat{y}) - F(\mathbf{w}, x^{(i)}, y^{(i)}) \right)$$

is:

$$\lambda \mathbf{w} + \sum_{i \in [N]} \sum_{\hat{y}} \left(p(\hat{y} | x^{(i)}) - \delta(\hat{y} = y^{(i)}) \right) \frac{\partial F(\mathbf{w}, x^{(i)}, \hat{y})}{\partial \mathbf{w}}$$

How to compute this numerically:

- $p(\hat{y} | x) = \frac{\exp F(\mathbf{w}, x, \hat{y})}{\sum_{\tilde{y}} \exp F(\mathbf{w}, x, \tilde{y})}$ via soft-max which takes F as input
- $\frac{\partial F(\mathbf{w}, x, \hat{y})}{\partial \mathbf{w}}$ via backpropagation

Backpropagation by example:

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(w_3, x))) \quad \text{with activations} \quad \begin{cases} z_2 = f_3(w_3, x) \\ z_1 = f_2(w_2, z_2) \end{cases}$$

$$f_1(w_1, y, z_1)$$

Backpropagation by example:

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(w_3, x))) \text{ with activations } \begin{cases} z_2 = f_3(w_3, x) \\ z_1 = f_2(w_2, z_2) \end{cases}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_3}$?

Backpropagation by example:

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(w_3, x))) \text{ with activations } \begin{cases} z_2 = f_3(w_3, x) \\ z_1 = f_2(w_2, z_2) \end{cases}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_3}$?

$$\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial z_2} \cdot \frac{\partial z_2}{\partial w_3} =$$

Backpropagation by example:

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(w_3, x))) \quad \text{with activations} \quad \begin{cases} z_2 = f_3(w_3, x) \\ z_1 = f_2(w_2, z_2) \end{cases}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_3}$?

$$\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial z_2} \cdot \frac{\partial z_2}{\partial w_3} = \underbrace{\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial z_2}}_{\frac{\partial f_1}{\partial f_2}} \cdot \frac{\partial f_2}{\partial f_3} \cdot \frac{\partial f_3}{\partial w_3}$$

Backpropagation by example:

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(w_3, x))) \quad \text{with activations} \quad \begin{cases} z_2 = f_3(w_3, x) \\ z_1 = f_2(w_2, z_2) \end{cases}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_3}$?

$$\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial z_2} \cdot \frac{\partial z_2}{\partial w_3} = \underbrace{\frac{\partial f_1}{\partial f_2}} \cdot \frac{\partial f_2}{\partial f_3} \cdot \frac{\partial f_3}{\partial w_3}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_2}$?

Backpropagation by example:

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(w_3, x))) \quad \text{with activations} \quad \begin{cases} z_2 = f_3(w_3, x) \\ z_1 = f_2(w_2, z_2) \end{cases}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_3}$?

$$\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial z_2} \cdot \frac{\partial z_2}{\partial w_3} = \underbrace{\frac{\partial f_1}{\partial f_2}} \cdot \frac{\partial f_2}{\partial f_3} \cdot \frac{\partial f_3}{\partial w_3}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_2}$?

$$\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial w_2} =$$

Backpropagation by example:

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(w_3, x))) \quad \text{with activations} \quad \begin{cases} z_2 = f_3(w_3, x) \\ z_1 = f_2(w_2, z_2) \end{cases}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_3}$?

$$\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial z_2} \cdot \frac{\partial z_2}{\partial w_3} = \underbrace{\frac{\partial f_1}{\partial f_2}}_{\checkmark} \cdot \frac{\partial f_2}{\partial f_3} \cdot \frac{\partial f_3}{\partial w_3}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_2}$?

$$\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial w_2} = \underbrace{\frac{\partial f_1}{\partial f_2}}_{\checkmark} \cdot \frac{\partial f_2}{\partial w_2}$$

$$\frac{\partial F}{\partial w_1}$$

Backpropagation by example:

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(w_3, x))) \quad \text{with activations} \quad \begin{cases} z_2 = f_3(w_3, x) \\ z_1 = f_2(w_2, z_2) \end{cases}$$

What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_3}$?

$$\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial z_2} \cdot \frac{\partial z_2}{\partial w_3} = \underbrace{\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial z_2}}_{\frac{\partial f_1}{\partial f_2}} \cdot \frac{\partial f_2}{\partial f_3} \cdot \frac{\partial f_3}{\partial w_3}$$


What is $\frac{\partial F(\mathbf{w}, x, y)}{\partial w_2}$?

$$\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial w_2} = \underbrace{\frac{\partial f_1}{\partial z_1} \cdot \frac{\partial z_1}{\partial f_2}}_{\frac{\partial f_1}{\partial f_2}} \cdot \frac{\partial f_2}{\partial w_2}$$

Generally: To avoid repeated computation, backpropagation on an acyclic graph.
Nodes in this graph are weights, data, and functions.

Composite function represented as acyclic graph: Forward Pass


$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(\dots)))$$



Composite function represented as acyclic graph:

Backward Pass

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(\dots)))$$




$$\frac{\partial}{\partial w} \sigma(w^T z_1) = \sigma(w^T z_1)(1 - \sigma(w^T z_1)) \cdot z_1$$

$$w_1^{t+1} = w_1^t - \lambda \frac{\partial f_1}{\partial w_1}$$

Composite function represented as acyclic graph:

Backward Pass


$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(\dots)))$$



Composite function represented as acyclic graph:

Backward Pass

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(\dots)))$$




$$\frac{\partial F}{\partial w_2}$$

Composite function represented as acyclic graph:


Backward Pass

$$F(\mathbf{w}, x, y) = f_1(w_1, y, f_2(w_2, f_3(\dots)))$$



Composite function represented as acyclic graph:

Backward Pass



Repeated use of chain rule for efficient computation of all gradients

Remark:

Can think of backpropagation as an efficient implementation of the chain rule on a computational graph.

Initialization matters:

Initialization matters:

- Not well understood in general

Initialization matters:

- Not well understood in general
- Heuristic: Random uniform

$$\text{Uniform} \left(-\frac{1}{\sqrt{\text{fan in}}}, \frac{1}{\sqrt{\text{fan in}}} \right)$$

Initialization matters:


- Not well understood in general
- Heuristic: Random uniform

$$\text{Uniform} \left(-\frac{1}{\sqrt{\text{fan in}}}, \frac{1}{\sqrt{\text{fan in}}} \right)$$


- Heuristic: Glorot and Bengio (2010)

$$\text{Uniform} \left(-\sqrt{\frac{6}{\text{fan in} + \text{fan out}}}, \sqrt{\frac{6}{\text{fan in} + \text{fan out}}} \right)$$

Example of feature transformations learned by deep networks



Example of feature transformations learned by deep networks




- **Remark:** A deep net with a single fully connected layer is a linear model


- Advantages of deep nets compared to using hand-crafted features:

- Advantages of deep nets compared to using hand-crafted features:
 - automatically learn feature space transformations (hierarchical abstractions of data) such that data is easily separable at the output

3rd layer 2nd layer




- Advantages of deep nets compared to using hand-crafted features:
 - automatically learn feature space transformations (hierarchical abstractions of data) such that data is easily separable at the output



- Disadvantage of deep nets compared to using hand-crafted features:

- Advantages of deep nets compared to using hand-crafted features:
 - automatically learn feature space transformations (hierarchical abstractions of data) such that data is easily separable at the output



- Disadvantage of deep nets compared to using hand-crafted features:
 - computationally demanding (routinely use GPUs)
 - require significant amounts of training data to perform well

Why this recent popularity:

Why this recent popularity:

- Sufficient computational resources
- Sufficient data
- Algorithmic advances
- Sufficient evidence that it works

Why this recent popularity:

- Sufficient computational resources
- Sufficient data
- Algorithmic advances
- Sufficient evidence that it works

This combination has led to significant performance improvements on many datasets (e.g., in language modeling, computer vision)

Algorithmic advances:

Algorithmic advances:

- Rectified linear unit ($\max\{0, x\}$) activation i.e., RELU instead of sigmoid
 - Fixed the vanishing gradient problem for lower layers close to the input

Algorithmic advances:

- Rectified linear unit ($\max\{0, x\}$) activation i.e., RELU instead of sigmoid
 - Fixed the vanishing gradient problem for lower layers close to the input
- Dropout
 - Decorrelates different units, i.e., they learn different features

Algorithmic advances:

- Rectified linear unit ($\max\{0, x\}$) activation i.e., RELU instead of sigmoid
 - Fixed the vanishing gradient problem for lower layers close to the input
- Dropout
 - Decorrelates different units, i.e., they learn different features
- Good initialization heuristics
 - Less prone to getting stuck in bad local optima

Algorithmic advances:


- Rectified linear unit ($\max\{0, x\}$) activation i.e., RELU instead of sigmoid
 - Fixed the vanishing gradient problem for lower layers close to the input
- Dropout
 - Decorrelates different units, i.e., they learn different features
- Good initialization heuristics
 - Less prone to getting stuck in bad local optima
- Batch-Normalization during training
 - Normalizes data when training really deep nets
 - Normalize by subtracting mean and dividing by standard deviation

Imagenet Challenge:

Imagenet Challenge:

- A large dataset: 1.2M images, 1000 categories
- AlexNet was run on the GPU, i.e., sufficient computational resources
- Rectified linear units rather than sigmoid units simplify optimization

Results:



Choices in deep learning packages:

Choices in deep learning packages:

- Use an appropriate loss function

Choices in deep learning packages:

- Use an appropriate loss function
- Design a composite function $F(\boldsymbol{w}, x, y)$

Choices in deep learning packages:

- Use an appropriate loss function
- Design a composite function $F(\boldsymbol{w}, x, y)$

Know what you are doing, i.e., know all the dimensions.

Loss functions:

- **CrossEntropyLoss**

$$\begin{aligned}\text{loss}(x, \text{class}) &= -\log(\exp(x[\text{class}]) / (\sum_j \exp(x[j]))) \\ &= -x[\text{class}] + \log(\sum_j \exp(x[j]))\end{aligned}$$

- **NLLLoss (negative log-likelihood)**

$$\text{loss}(x, \text{class}) = -x[\text{class}]$$

- **MSELoss (mean squared error)**

$$\text{loss}(x, y) = 1/n \sum_i |x_i - y_i|^2$$

- **BCELoss (binary cross-entropy)**

$$\text{loss}(o, t) = -1/n \sum_i i (t[i] * \log(o[i]) + (1 - t[i]) * \log(1 - o[i]))$$

- **BCEWithLogitsLoss**

$$\begin{aligned}\text{loss}(o, t) &= -1/n \sum_i (t[i] * \log(\text{sigmoid}(o[i])) \\ &\quad + (1 - t[i]) * \log(1 - \text{sigmoid}(o[i])))\end{aligned}$$

- **L1Loss**

- **KLDivLoss**

Why this form for the NLLLoss?

```
loss(x, class) = -x[class]
```

Intended to be used in combination with 'LogSoftmax':

$$f_i(x) = \log \frac{\exp x_i}{\sum_j \exp x_j}$$

Why this form for the NLLLoss?

```
loss(x, class) = -x[class]
```

Intended to be used in combination with 'LogSoftmax':

$$f_i(x) = \log \frac{\exp x_i}{\sum_j \exp x_j}$$

Why?

Why this form for the NLLLoss?

```
loss(x, class) = -x[class]
```

Intended to be used in combination with ‘LogSoftmax’:

$$f_i(x) = \log \frac{\exp x_i}{\sum_j \exp x_j}$$

Why? Numerical robustness (‘log-sum-exp trick’)

$$\log \sum_j \exp x_j = c + \log \sum_j \exp (x_j - c)$$

Don’t try without, it **will** fail!

Popular architectures:

Popular architectures:


- LeNet
- AlexNet

Popular architectures:

- LeNet
- AlexNet
- VGG (16/19 layers, mostly 3x3 convolutions)


Popular architectures:

- LeNet
- AlexNet
- VGG (16/19 layers, mostly 3x3 convolutions)
- GoogLeNet (inception module)




Popular architectures:

- LeNet
- AlexNet
- VGG (16/19 layers, mostly 3x3 convolutions)
- GoogLeNet (inception module)



- ResNet (residual connections)



Quiz:

Quiz:

- What are deep nets?

Quiz:

- What are deep nets?
- How do deep nets relate to linear models?

Quiz:

- What are deep nets?
- How do deep nets relate to linear models?
- What is backpropagation in deep nets?

Quiz:

- What are deep nets?
- How do deep nets relate to linear models?
- What is backpropagation in deep nets?
- What components of deep nets do you know?

Quiz:

- What are deep nets?
- How do deep nets relate to linear models?
- What is backpropagation in deep nets?
- What components of deep nets do you know?
- What algorithm is used to train deep nets?

Important topics of this lecture

- Deep nets
- Backpropagation

Up next:

- More deep learning architectures