


# File Handling through C++ Classes

In C++, files are mainly dealt by using three classes `fstream`, `ifstream`, `ofstream` available in `fstream` headerfile.

**ofstream:** Stream class to write on files

**ifstream:** Stream class to read from files

**fstream:** Stream class to both read and write from/to files.



Now the first step to open the particular file for read or write operation. We can open file by

1. passing file name in constructor at the time of object creation
2. using the open method

**For e.g.**

## Open File by using constructor

```
ifstream (const char* filename, ios_base::openmode mode =  
ios_base::in);  
ifstream fin(filename, openmode) by default openmode = ios::in  
ifstream fin("filename");
```

## Open File by using open method

```
Calling of default constructor  
ifstream fin;  
fin.open(filename, openmode)  
fin.open("filename");
```

## Modes :

Member Constant	Stands For	Access
in *	input	File open for reading: the internal stream buffer supports input operations.
out	output	File open for writing: the internal stream buffer supports output operations.
binary	binary	Operations are performed in binary mode rather than text.
ate	at end	The output position starts at the end of the file.
app	append	All output operations happen at the end of the file, appending to its existing contents.
trunc	truncate	Any contents that existed in the file before it is open are discarded.

## Default Open Modes :

```
ifstream ios::in
ofstream ios::out
fstream ios::in |
        ios::out
```

**Problem Statement :** To read and write a File in C++.

### Examples:

Input :  
Welcome in GeeksforGeeks. Best way to learn things.  
-1  
Output :  
Welcome in GeeksforGeeks. Best way to learn things.

Recommended: Please try your approach on **IDE** first, before moving on to the solution.

Below is the implementation by using **ifstream & ofstream classes**.

```
/* File Handling with C++ using ifstream & ofstream class object*/  
/* To write the Content in File*/  
/* Then to read the content of file*/  
#include <iostream>
```

```
/* fstream header file for ifstream, ofstream,  
   fstream classes */  
#include <fstream>
```

```
using namespace std;
```

```
// Driver Code
```

```
int main()
```

```
{
```

```
    // Creation of ofstream class object  
    ofstream fout;
```

```
    string line;
```

```
    // by default ios::out mode, automatically deletes  
    // the content of file. To append the content, open in ios::app  
    // fout.open("sample.txt", ios::app)  
    fout.open("sample.txt");
```

```
    // Execute a loop If file successfully opened  
    while (fout) {
```

```
        // Read a Line from standard input  
        getline(cin, line);
```

```
        // Press -1 to exit  
        if (line == "-1")  
            break;
```

```
        // Write line in file  
        fout << line << endl;
```

```
    }
```

```
    // Close the File  
    fout.close();
```

```
    // Creation of ifstream class object to read the file  
    ifstream fin;
```

```
    // by default open mode = ios::in mode  
    fin.open("sample.txt");
```

```
    // Execute a loop until EOF (End of File)  
    while (fin) {
```

```

        // Read a Line from File
        getline(fin, line);

        // Print line in Console
        cout << line << endl;
    }

    // Close the file
    fin.close();

    return 0;
}

```

Below is the implementation by using **fstream class**.

```

/* File Handling with C++ using ifstream class object */
/* To write the Content in File */
/* Then to read the content of file*/
#include <iostream>

/* ifstream header file for ifstream, ofstream,
   ifstream classes */
#include <fstream>

using namespace std;

// Driver Code
int main()
{
    // Creation of ifstream class object
    ifstream fio;

    string line;

    // by default openmode = ios::in|ios::out mode
    // Automatically overwrites the content of file, To append
    // the content, open in ios::app
    // fio.open("sample.txt", ios::in|ios::out|ios::app)
    // ios::trunc mode delete all content before open
    fio.open("sample.txt", ios::trunc | ios::out | ios::in);

    // Execute a loop If file successfully Opened
    while (fio) {

        // Read a Line from standard input
        getline(cin, line);

        // Press -1 to exit
        if (line == "-1")
            break;

        // Write line in file
    }
}

```

```
        fio << line << endl;
    }

    // Execute a loop until EOF (End of File)
    // point read pointer at beginning of file
    fio.seekg(0, ios::beg);

    while (fio) {

        // Read a Line from File
        getline(fio, line);

        // Print line in Console
        cout << line << endl;
    }

    // Close the file
    fio.close();

    return 0;
}
```