

exercise2 (Score: 14.0 / 14.0)

1. [Written response](#) (Score: 3.0 / 3.0)
2. [Test cell](#) (Score: 1.0 / 1.0)
3. [Test cell](#) (Score: 1.0 / 1.0)
4. [Test cell](#) (Score: 2.0 / 2.0)
5. [Test cell](#) (Score: 3.0 / 3.0)
6. [Test cell](#) (Score: 1.0 / 1.0)
7. [Test cell](#) (Score: 3.0 / 3.0)

Lab 2

1. 提交作業之前，建議可以先點選上方工具列的**Kernel**，再選擇**Restart & Run All**，檢查一下是否程式跑起來都沒有問題，最後記得儲存。
2. 請先填上下方的姓名(name)及學號(student_id)再開始作答，例如：

```
name = "我的名字"  
student_id= "B06201000"
```

3. 四個求根演算法的實作可以參考[lab-2 \(https://yuanyuyuan.github.io/itcm/lab-2.html\)](https://yuanyuyuan.github.io/itcm/lab-2.html)，裡面有教學影片也有範例程式可以套用。
4. **Deadline: 10/9(Wed.)**

In [1]:

```
name = "馬宗儀"  
student_id = "b06201006"
```

Exercise 2

Kepler's equation

In celestial mechanics, *Kepler's equation*

$$M = E - e \sin(E)$$

relates the mean anomaly M to the eccentric anomaly E of an elliptical orbit of eccentricity e , where $0 < e < 1$, see [Wiki website \(https://en.wikipedia.org/wiki/Kepler's_laws_of_planetary_motion\)](https://en.wikipedia.org/wiki/Kepler's_laws_of_planetary_motion) for the details.

1. Prove that fixed-point iteration using the iteration function

$$g(E) = M + e \sin(E)$$

is convergent locally.

[Hint: You may use Ostrowski's Theorem mentioned in the lecture note.]

proof.

By Ostrowski's Theorem, since $|g'(E)| = |e \cos(E)| < 1$, it convergent locally

2. Use the fixed-point iteration scheme in "Q.1" to solve Kepler's equation for the eccentric anomaly E corresponding to a mean anomaly $M = \frac{2\pi}{3}$ and an eccentricity $e = 0.5$.

Part 0. Import libraries

In [2]:

```
import matplotlib.pyplot as plt
import numpy as np
```

Part 1. Define the fixed point function

In [3]:

```

def fixed_point(
    func,
    x_0,
    tolerance=1e-7,
    max_iterations=5,
    report_history=False,
):
    '''Approximate solution of  $f(x)=0$  on interval  $[a,b]$  by the secant method.

    Parameters
    -----
    func : function
        The target function.
    x_0 : float
        Initial guess point for a solution  $f(x)=0$ .
    tolerance: float
        One of the termination conditions. Error tolerance.
    max_iterations : (positive) integer
        One of the termination conditions. The amount of iterations allowed.
    report_history: bool
        Whether to return history.

    Returns
    -----
    solution : float
        Approximation of the root.
    history: dict
        Return history of the solving process if report_history is True.
    ...

    # 請參考 hands-on 的 fixed point method
    #
    # ===== 請實做程式 =====
    x_n=x_0
    iterations=0

    if report_history:
        history={'estimation': [], 'error': []}

    while True:
        f_n=func(x_n)
        error=abs(f_n-x_n)

        if report_history:
            history['estimation'].append(x_n)
            history['error'].append(error)
        if error<tolerance :
            print('Found solution after', iterations, 'iterations.')
            if report_history:
                return x_n, history
            else:
                return x_n
        elif iterations>=max_iterations:
            print('Terminate since reached the maximum iterations.')
            if report_history:
                return x_n, history
            else:
                return x_n
        else:
            iterations+=1

        x_n=f_n

    # =====

```

Test your implementaion with the assertion below.

In [4]:

test_fixed_method

(Top)

```
root = fixed_point(lambda x: x - (x**2 - 4*x + 3.5), 2, tolerance=1e-7, max_iterations=100, report_history=False)

error = np.inf
for solution in np.roots([1, -4, 3.5]):
    if abs(root - solution) < error:
        exact_solution = solution
        error = abs(root - solution)

assert error < 1e-7
```

Found solution after 18 iterations.

Part 2. Assign values to variables anomaly mean " M " and eccentricity " e ".

$$M = \frac{2\pi}{3} \quad \text{and} \quad e = 0.5$$

In [5]:

(Top)

```
# Hint:
# M = ?
# e = ?
# ===== 請實做程式 =====
M = 2*np.pi/3
e = 0.5
# =====
```

In [6]:

M_and_e

(Top)

```
print('M =', M)
print('e =', e)

### BEGIN HIDDEN TESTS
assert M == 2*np.pi/3, 'M is wrong!'
assert e == 0.5, 'e is wrong!'
### END HIDDEN TESTS
```

```
M = 2.0943951023931953
e = 0.5
```

Part 3. Define the function of Kepler's equation

Recall Kepler's equation :

$$M = E - e \sin(E).$$

So we let the function $f(E) = E - e \sin(E) - M$, then

$$g(E) = E - f(E) = M + e \sin(E)$$

For the instance:

If we want to implement " $\sin(x)$ ", we will call `np.sin(x)` with numpy in python.

In [7]:

(Top)

```
def f(E):
    # Hint: return ...
    # ===== 請實做程式 =====
    return E-e*np.sin(E)-M
    # =====

def g(E):
    # Hint: return ...
    # ===== 請實做程式 =====
    return E-f(E)
    # =====
```

In [8]:

(Top)

test_f_and_g

```
print('M =', M)

# f(0) = -M, g(0) = M
print('f(0) =', f(0))
print('g(0) =', g(0))


### BEGIN HIDDEN TESTS
from random import random
rd_number = random()
assert f(rd_number) == rd_number - 0.5*np.sin(rd_number) - 2*np.pi/3, 'f is wrong!'
assert g(rd_number) == 2*np.pi/3 + 0.5*np.sin(rd_number), 'g is wrong!'
### END HIDDEN TESTS
```

```
M = 2.0943951023931953
f(0) = -2.0943951023931953
g(0) = 2.0943951023931953
```

Part 4. Plot the function $f(E)$ and $g(E)$


In [9]:

```
fig, ax = plt.subplots(figsize=(16, 4))
search_range = np.arange(-10, 10, 0.01)
ax.plot(search_range, f(search_range))
ax.set_title(r'$f(E) = E - e\sin(E) - M$')
ax.grid(True)
ax.axhline(y=0)
ax.axvline(x=0)
plt.show()
```



In [10]:

```
fig, ax = plt.subplots(figsize=(16, 4))
search_range = np.arange(-10, 10, 0.01)
ax.plot(search_range, g(search_range))
ax.set_title(r'$g(E) = M + e\sin(E)$')
ax.grid(True)
ax.axhline(y=0)
plt.ylim(1,3)
plt.show()
```



Part 5. Find the solution of "E"

In [11]:

```
root = fixed_point(
    # ===== 請實做程式 =====
    g,
    0,
    tolerance=1e-10,
    max_iterations=100,
    report_history=False,
    # =====
)
```

(Top)

Found solution after 24 iterations.

In [12]:

```
the_root_of_E

print('My estimation of root:', root)

### BEGIN HIDDEN TESTS
assert abs(root - 2.425) < 0.002, 'root is wrong!'
### END HIDDEN TESTS
```

(Top)

My estimation of root: 2.4234054585250298

3. An “ exact ” formula for E is known:

$$E = M + 2 \sum_{m=1}^{\infty} \frac{1}{m} J_m(me) \sin(mM);$$

where $J_m(x)$ is the Bessel function of the first kind of order m .

Use this formula to compute E. How many terms are needed to produce the value obtained in "Q.2" until convergence?

Part 0. Import package

In [13]:

```
from scipy.special import jn # Bessel function
```

Part 1. Define the function

For the convenience, we define the function $h(m)$ as

$$h(m) \triangleq \frac{2}{m} J_m(me) \sin(mM)$$

If we want to implement " **Bessel function** " $J_m(x)$, we can call `jn(m,x)` in Python.

In [14]:

```
def h(m):  
    # Hint: return ...  
    # ===== 請實做程式 =====  
    a=2*jn(m,m*e)*np.sin(m*M)/m  
    return a  
    # =====
```

In [15]:

```
h  
  
# test the function of h  
print('h(1) =', h(1))  
assert round(h(1), 5) == 0.41962  
  
### BEGIN HIDDEN TESTS  
from random import random  
rd_number = random()  
assert h(rd_number) == 2*jn(rd_number, rd_number*0.5)*np.sin(rd_number*(2*np.pi/3))/rd_number, 'h is wrong!'  
### END HIDDEN TESTS
```

$h(1) = 0.41962127776423175$

Part 2. Find how many terms we need to achieve the result obtained Q.2 in a tolerance 10^{-7} .

That is to find `_numterms` such that

$$\left| \text{root} - \left(M + \sum_{k=1}^{\text{num_terms}} h(k) \right) \right| < 10^{-7}$$

For example, the following cell shows the implementation with only 1 term.

In [16]:

```
LHS = root  
RHS = M + h(1)  
error = abs(LHS-RHS)  
print('Left hand side is the estimation of root by the fixed-point method:', LHS)  
print('Right hand side is the approximation by the formula in only 1 term:', RHS)  
print('The error between LHS and RHS:', error)
```

Left hand side is the estimation of root by the fixed-point method: 2.4234054585250298
Right hand side is the approximation by the formula in only 1 term: 2.514016380157427
The error between LHS and RHS: 0.09061092163239737

In [17]:

(Top)

```
LHS = root
RHS = M + h(1)
num_terms = 1
tolerance = 1e-7

# ===== 請實做程式 =====
def sum_h(n):
    s=M
    for i in range(1, n+1):
        s+=h(i)
    return s

# =====
```

In [18]:

```
while abs(LHS-sum_h(num_terms))>=tolerance:
    num_terms+=1
```

In [19]:

number_of_term

(Top)

```
print('Number of terms to approximate:', num_terms)

### BEGIN HIDDEN TESTS
assert num_terms > 20 , '%d is too few!' % num_terms
### END HIDDEN TESTS
```

Number of terms to approximate: 23

In []:

In []:

In []: