









	Description	Designator	Footprint	LibRef	Quantity
		C1, C2, C3, C4, C5,			
104	Capacitor	C8, C10, C12, C14	C-0805	Cap	9
22	Capacitor	C6, C7	C-0805	Сар	2
	100UF 50V				
330uF/50V	10x10.2MM	C9, C11, C13, C15	C-ALU-10x10.2mm	Cap2	4
	Typical INFRARED	D1, D2, D3, D4, D5,			_
SMD0805-RED	GaAs LED	D8	LED-0805	LED0	6
CCE4 CNAA	1 Amp General	D/ D7	D DO214 AD	Diode 1N4004	1
SS54-SMA	Purpose Rectifier  Magnetic-Core	D6, D7	D-DO214-AB	Diode 1114004	2
100mH/3A	Inductor	L1	L-SMD-12.5x12.5	Inductor Iron	1
	inductor	P1, P2, P3, P4, P5, P6		inductor from	'
KF128-2P	Header, 2-Pin	P7, P14	TER-KF128-2P	Header 2	8
JP2.54-M-4P	Header, 4-Pin	P11	JP2.54-M-1x04A	Header 4	1
1K	Resistor	R1	R-0805	Res1	1
4K7	Resistor	R2, R4, R8, R11	R-0805	Res1	4
10K	Resistor	R3, R6, R10, R14	R-0805	Res1	4
6K8	Resistor	R5, R9, R13	R-0805	Res1	3
2K2	Resistor	R7, R12	R-0805	Res1	2
1K5	Resistor	R15	R-0805	Res1	1
	JFET-Input				
	Operational				
LM358	Amplifier	U1	SK-DIP8-300	TL082D	1
	4-Pin Phototransisto				
EL3H7	Optocoupler	U2, U3, U4, U5, U6	SSOP-4	Optoisolator1	5
	Core: ARIVI® 32-bit				
	Cortex® -M0 CPU,				
	frequency up to 48				
STM32F051C8	MHz	U7	LQFP-48	STM32F051C8	1
	Simple Switcher 3A				
LM2576S-5	Step Down Voltage	110	TO 2/2 FI	LM257/C F O	1
LIVI25/65-5	Regulator	U8	TO-263-5L	LM2576S-5.0	'
	800mA Low-Dropout				
	Linear Regulator, 3-				
LM1117-3.3	pin TO-252	U9	SOT-223-3	LM1117DT-3.3	1
8MHz	Crystal Oscillator	Y1	XTAL-49S	XTAL	1