



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

- “Donat el caràcter i la finalitat exclusivament docent i eminentment il·lustrativa de les explicacions a classe d'aquesta presentació, l'autor s'acull a l'article 32 de la Llei de propietat intel·lectual vigent respecte de l'ús parcial d'obres alienes com ara imatges, gràfics o altre material contingudes en les diferents diapositives”
- “Dado el carácter y la finalidad exclusivamente docente y eminentemente ilustrativa de las explicaciones en clase de esta presentación, el autor se acoge al artículo 32 de la Ley de Propiedad Intelectual vigente respecto al uso parcial de obras ajenas como imágenes, gráficos u otro material contenidos en las diferentes diapositivas”.

1



UNIVERSITAT  
BARCELONA

# Complex Networks

**Albert Díaz Guilera**  
<http://diaz-guilera.net>  
@anduviera

**C lab B** COMPLEXITAT  
complexity lab barcelona

2



UNIVERSITAT  
de  
BARCELONA

# Models describing simple properties of Complex Networks

Albert Díaz Guilera  
<http://diaz-guilera.net>  
@anduviera



ClabB  
complexity lab barcelona



COMPLEXITAT

3




Big Data <-> Big Networks

Albert Diaz Guilera


## Why models?

- Generative models to understand real data
- Looking for vulnerabilities not available in the data

4



5




6

*Big Data <-> Big Networks*      Albert Diaz Guilera

## Alternative definition

- Binomial model: start with  $N$  nodes, every pair of nodes being connected with probability  $p$
- The expected total number of links,  $L$ , is a random variable
  - $E(L) = pN(N-1)/2$

7



8



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## Mean connectivity

- $\langle k \rangle = pN$
- If  $p \propto N^{-1}$  then  $\langle k \rangle$  is a constant
- If  $0 < \langle k \rangle < 1$  almost surely all clusters are either trees or clusters containing exactly one cycle
- At  $\langle k \rangle = 1$  the structure changes abruptly. Cycles appear and a giant cluster develops

9



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

### Defining Random Networks


There are two definitions of a random network:

- $G(N, L)$  Model:  $N$  labeled nodes are connected with  $L$  randomly placed links. Erdős and Rényi used this definition in their string of papers on random networks [2-9]
- $G(N, p)$  Model: Each pair of  $N$  labeled nodes is connected with probability  $p$ , a model introduced by Gilbert [10].


Hence, the  $G(N, p)$  model fixes the probability  $p$  that two nodes are connected and the  $G(N, L)$  model fixes the total number of links  $L$ . While in the  $G(N, L)$  model the average degree of a node is simply  $\langle k \rangle = 2L/N$ , other network characteristics are easier to calculate in the  $G(N, p)$  model. Throughout this book we will explore the  $G(N, p)$  model, not only for the ease that it allows us to calculate key network characteristics, but also because in real networks the number of links rarely stays fixed.



10



11



12

*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## Degree distribution

- The degree of a node follows a binomial distribution (in a random graph with p)

$$P(k_i = k) = \binom{N-1}{k} p^k (1-p)^{N-1-k}$$

- Probability that a given node has a connectivity k
- For large N, Poisson distribution

$$P(k) \approx e^{-pN} \frac{(pN)^k}{k!} = e^{-\langle k \rangle} \frac{\langle k \rangle^k}{k!}$$

13

$p_k = \binom{N-1}{k} p^k (1-p)^{N-1-k}$  (3.22)

that characterizes a random graph. We rewrite the first term on the r.h.s. as

$$\binom{N-1}{k} = \frac{(N-1)(N-1-1)(N-1-2)\dots(N-1-k+1)}{k!} \approx \frac{(N-1)^k}{k!}$$
 (3.23)

where in the last term we used that  $k \ll N$ . The last term of (3.22) can be simplified as

$$\ln[(1-p)^{(N-1)-k}] = (N-1-k) \ln\left(1 - \frac{\langle k \rangle}{N-1}\right)$$

and using the series expansion

$$\ln(1+x) = \sum_{n=1}^{\infty} \frac{(-1)^{n+1}}{n} x^n = x - \frac{x^2}{2} + \frac{x^3}{3} - \dots, \forall |x| \leq 1$$

we obtain

$$\ln[(1-p)^{(N-1)-k}] \approx (N-1-k) \frac{\langle k \rangle}{N-1} = -\langle k \rangle \left(1 - \frac{k}{N-1}\right) \approx -\langle k \rangle$$

which is valid if  $N \gg k$ . This represents the *small degree approximation* at the heart of this derivation. Therefore the last term of (3.22) becomes

$$(1-p)^{N-1-k} = e^{-\langle k \rangle} \quad (3.24)$$

Combining (3.22), (3.23), and (3.24) we obtain the Poisson form of the degree distribution

$$p_k = \binom{N-1}{k} p^k (1-p)^{N-1-k} = \frac{(N-1)^k}{k!} p^k e^{-\langle k \rangle} = \frac{(N-1)^k}{k!} \left(\frac{\langle k \rangle}{N-1}\right)^k e^{-\langle k \rangle}$$

or

$$p_k = e^{-\langle k \rangle} \frac{\langle k \rangle^k}{k!} \quad (3.25)$$

14



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## Mean short path

- Assume that the graph is homogeneous
- The number of nodes at distance  $l$  are  $\langle k^l \rangle$
- How to reach the rest of the nodes?
- $l_{\text{rand}}$  to reach all nodes  $\Rightarrow k^l=N$

$$l_{\text{rand}} \approx \frac{\ln N}{\ln \langle k \rangle} \approx \frac{\ln N}{\ln pN}$$

15



*Big Data <-> Big Networks*


*Albert Diaz Guilera*

The average path length for large  $n$  is

$$\bar{l}(H) = \frac{\ln n - \gamma}{\ln(pn)} + \frac{1}{2},$$

where  $\gamma \approx 0.577$  is the Euler–Mascheroni constant.

16



17



18

*Big Data <-> Big Networks*      Albert Diaz Guilera

## Clustering coefficient

- Probability that two nodes are connected (given that they are connected to a third)?




$$C_{rand} = p = \frac{\langle k \rangle}{N}$$

$$\frac{C_{rand}}{\langle k \rangle} \approx \frac{1}{N}$$

**while it is constant for real networks**

19



20



**Algorithm 4.17** Erdős and Rényi (ER). Version  $G_{N,K}^{ER}$

**Input:**  $V$  set of nodes (of size  $N$ ), and number of links  $K$  .  
**Output:**  $\mathcal{K}$  set of links

---

```

 $\mathcal{K} \leftarrow \emptyset$ 
while size( $\mathcal{K}$ ) <  $K$  do
    Choose at random a pair of nodes  $i \in V$  and  $j \in V$ 
    if the edge  $(i,j) \notin \mathcal{K}$  then
        add link  $(i,j)$  to  $\mathcal{K}$ 
    end if
end while
return  $\mathcal{K}$ 

```

---

**Algorithm 4.18** Erdős and Rényi (ER). Version  $G_{N,p}^{ER}$

**Input:**  $V$  set of nodes (of size  $N$ ), and  $p$ , the probability to connect any two pair of nodes.  
**Output:**  $\mathcal{K}$  set of links

---

```

size of  $\mathcal{K}=0$ 
for all Node  $i \in V$  do
    for all Node  $j \in V$ , with  $j > i$  do
        Generate a random number  $r$ 
        if  $r \leq p$  then
            add link  $(i,j)$  to  $\mathcal{K}$ 
        end if
    end for
end for
return  $\mathcal{K}$ 

```

21

*Big Data <-> Big Networks*

**Random Graphs**

Generators for random graphs.

<code>fast_gnp_random_graph(n, p[, seed, directed])</code>	Return a random graph $G_{\{n,p\}}$ (Erdős–Rényi graph, binomial graph).
<code>gnp_random_graph(n, p[, seed, directed])</code>	Return a random graph $G_{\{n,p\}}$ (Erdős–Rényi graph, binomial graph).
<code>dense_gnm_random_graph(n, m[, seed])</code>	Return the random graph $G_{\{n,m\}}$ .
<code>gnm_random_graph(n, m[, seed, directed])</code>	Return the random graph $G_{\{n,m\}}$ .
<code>erdos_renyi_graph(n, p[, seed, directed])</code>	Return a random graph $G_{\{n,p\}}$ (Erdős–Rényi graph, binomial graph).
<code>binomial_graph(n, p[, seed, directed])</code>	Return a random graph $G_{\{n,p\}}$ (Erdős–Rényi graph, binomial graph).
<code>newman_watts_strogatz_graph(n, k, p[, seed])</code>	Return a Newman–Watts–Strogatz small world graph.
<code>watts_strogatz_graph(n, k, p[, seed])</code>	Return a Watts–Strogatz small-world graph.
<code>connected_watts_strogatz_graph(n, k, p[, ...])</code>	Return a connected Watts–Strogatz small-world graph.
<code>random_regular_graph(d, n[, seed])</code>	Return a random regular graph of $n$ nodes each with degree $d$ .
<code>barabasi_albert_graph(n, m[, seed])</code>	Return random graph using Barabási–Albert preferential attachment model.
<code>powerlaw_cluster_graph(n, m, p[, seed])</code>	Holme and Kim algorithm for growing graphs with powerlaw
<code>random_lobster(n, p1, p2[, seed])</code>	Return a random lobster.
<code>random_shell_graph(constructorf[, seed])</code>	Return a random shell graph for the constructor given.
<code>random_powerlaw_tree(n[, gamma, seed, tries])</code>	Return a tree with a powerlaw degree distribution.
<code>random_powerlaw_tree_sequence(n[, gamma, ...])</code>	Return a degree sequence for a tree with a powerlaw distribution.



22



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## Generalized random graphs

- Any degree distribution, clustering, ...
- Later on ..... configurational model

23



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## 2. Watts-Strogatz: small-world model

- Small world: the average shortest path length in a real network is small
- Six degrees of separation (Milgram, 1967)
- Local neighborhood + long-range friends
- A random graph is a small world

24



*Big Data <-> Big Networks*

*Albert Diaz-Guilera*

## Networks in nature (empirical observations)

$l_{\text{network}} \approx \ln(N)$

$C_{\text{network}} \gg C_{\text{random graph}}$

25




*Big Data <-> Big Networks*

*Albert Diaz-Guilera*


## Model proposed

- Crossover from regular lattices to random graphs
- Tunable
- Small world network with (simultaneously):
  - Small average shortest path
  - Large clustering coefficient (not obeyed by RG)

26



27



28

*Big Data <-> Big Networks*      Albert Diaz-Guilera


## Original model

- Each node has  $K \geq 4$  nearest neighbors (local)
- Probability  $p$  of rewiring to randomly chosen nodes
- $p$  small: regular lattice
- $p$  large: classical random graph



29

*Big Data <-> Big Networks*      Albert Diaz-Guilera



Regular

Random

$p = 0$  —————→  $p = 1$

Increasing randomness

30

*Big Data <-> Big Networks*      *Albert Diaz Guilera*

## p=0 Ordered lattice

$$l \approx \frac{N}{2K} \gg 1$$

$$C = \frac{3(K - 2)}{4(K - 1)}$$


31

*Big Data <-> Big Networks*      *Albert Diaz Guilera*

## p=1 Random graph

$$l \approx \frac{\ln N}{\ln K} \quad \text{small}$$


$$C \approx \frac{K}{N} \quad \text{small}$$


32

*Big Data <-> Big Networks*      Albert Diaz-Guilera

- Small shortest path means small clustering?
- Large shortest path means large clustering?
- They discovered: there exists a broad region:
  - Fast decrease of mean distance
  - Constant clustering

33



34



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## Average shortest path

$$l(p \rightarrow 0) \approx N$$

$$l(p \rightarrow 1) \approx \ln N$$

- Rapid drop of  $l$ , due to the appearance of short-cuts between nodes
- It starts to decrease when  $p \geq 2/NK$  (existence of one short cut)

35



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

- The value of  $p$  at which we should expect the transition depends on  $N$
- There will exist a crossover value of the system size:

$$N < N^* \Rightarrow l \approx N$$

$$N > N^* \Rightarrow l \approx \ln N$$

36


Big Data <-> Big Networks

Albert Diaz Guilera

# Degree distribution

- $p=0$  delta-function
- $p>0$  broadens the distribution
- Edges left in place with probability  $(1-p)$
- Edges rewired towards  $i$  with probability  $1/N$

37



38



**Algorithm 4.19** Watts-Strogatz Small-world Model.

---

**Input:**  $V$  (set of nodes, whose size is  $N$ ),  $m$  (number of connections to clockwise neighbors) and  $p$  (rewiring probability).

```

for all node  $i \in V$  do
    add edge to the  $m$  clockwise nearest neighbors
end for
for all number of iterations (this is to assure that the resulting degree distribution is stable) do
    for all node  $i \in V$  do
        for all links to clockwise nearest neighbors of  $i$  do
            Generate a random number  $r$ 
            if  $r \leq p$  then
                select a random node  $j \in V$ 
                if link  $(i, j)$  does not exist then
                    add the edge  $(i, j)$ 
                else
                    go back and select another random node  $j \in V$ 
                end if
            end if
        end for
    end for
end for
return  $G(V, E)$ 
```

---

39

*Big Data <-> Big Networks*      *Albert Diaz-Guilera*


### Random Graphs

Generators for random graphs.


<code>fast_gnp_random_graph(n, p[, seed, directed])</code>	Return a random graph $G_{n,p}$ (Erdős-Rényi graph, binomial graph).
<code>gnp_random_graph(n, p[, seed, directed])</code>	Return a random graph $G_{n,p}$ (Erdős-Rényi graph, binomial graph).
<code>dense_gnm_random_graph(n, m[, seed])</code>	Return the random graph $G_{n,m}$ .
<code>gnm_random_graph(n, m[, seed, directed])</code>	Return the random graph $G_{n,m}$ .
<code>erdos_renyi_graph(n, p[, seed, directed])</code>	Return a random graph $G_{n,p}$ (Erdős-Rényi graph, binomial graph).
<code>binomial_graph(n, p[, seed, directed])</code>	Return a random graph $G_{n,p}$ (Erdős-Rényi graph, binomial graph).
<code>newman_watts_strogatz_graph(n, k, p[, seed])</code>	Return a Newman-Watts-Strogatz small world graph.
<code>watts_strogatz_graph(n, k, p[, seed])</code>	Return a Watts-Strogatz small-world graph.
<code>connected_watts_strogatz_graph(n, k, p[, ...])</code>	Return a connected Watts-Strogatz small-world graph.
<code>random_regular_graph(d, n[, seed])</code>	Return a random regular graph of $n$ nodes each with degree $d$ .
<code>barabasi_albert_graph(n, m[, seed])</code>	Return random graph using Barabási-Albert preferential attachment model.
<code>powerlaw_cluster_graph(n, m, p[, seed])</code>	Holme and Kim algorithm for growing graphs with powerlaw
<code>random_lobster(n, p1, p2[, seed])</code>	Return a random lobster.
<code>random_shell_graph(construct[, seed])</code>	Return a random shell graph for the constructor given.
<code>random_powerlaw_tree(n[, gamma, seed, tries])</code>	Return a tree with a powerlaw degree distribution.
<code>random_powerlaw_tree_sequence(n[, gamma, ...])</code>	Return a degree sequence for a tree with a powerlaw distribution.




40




41



42



43



44



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## Barabasi-Albert model (1999)

- ▶ Two generic mechanisms common in many real networks
  - Growth (www, research literature, ...)
  - Preferential attachment (idem): attractiveness of popularity
- ▶ The two are necessary

45




*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## Growth

- $t=0$ ,  $m_0$  nodes
- Each time step we add a new node with  $m$  ( $\leq m_0$ ) edges that link the new node to  $m$  different nodes already present in the system

46



47

*Big Data <-> Big Networks*      *Albert Diaz Guilera*

## Preferential attachment: rich gets richer

- When choosing the nodes to which the new connects, the probability  $\Pi$  that a new node will be connected to node  $i$  depends on the degree  $k_i$  of node  $i$

$$\Pi(k_i) = \frac{k_i}{\sum_j k_j}$$

**Linear attachment (more general models)  
Sum over all existing nodes**


48

*Big Data <-> Big Networks*      Albert Diaz-Guilera

## Numerical simulations

- Power-law  $P(k) \approx k^{-\gamma}$        $\gamma_{SF} = 3$
- The exponent does not depend on  $m$  (the only parameter of the model)

49



50

*Big Data <-> Big Networks*      Albert Diaz-Guilera

## Degree distribution

- Analytically

$$P(k) = \frac{2m(m+1)}{k(k+1)(k+2)}$$


51

*Big Data <-> Big Networks*      Albert Diaz-Guilera

## Clustering coefficient




5 times larger

$$C_{\text{SF}} \sim N^{-0.75}$$

$$C_{\text{RG}} = \langle k \rangle N^{-1}$$

SW: C is independent of N



N (Nodes)	C (Scale-Free Model)	C (Random Graph)
10^2	~8e-3	~0.0001
10^3	~2e-3	~1e-4
10^4	~5e-4	~1e-5
10^5	~1e-4	~1e-6

52

*Big Data <-> Big Networks*      Albert Diaz Guilera

	ER	WS	BA
• Degree distribution	👎	👎	👍
• Average length	👍	👍	👍
• Clustering Coefficient	👎	👍	👎

53


*Big Data <-> Big Networks*      Albert Diaz Guilera

## Alternative models

Scale-free with tunable  $\gamma$

$$\Pi_i(t) = \frac{k_i + \alpha}{\sum_{j=1}^{m_0+t-1} (k_j(t) + \alpha)}$$



$$\alpha \in (-m, \infty) \longrightarrow \gamma = 3 + \frac{\alpha}{m}$$



DOROGOVSEV-MENDES-SAMUKHIN  
PHYS. REV. LETT. 85, 4633 (2000)

Scale-free with high clustering

- First link: follow usual PA rule
- For each of the  $m - 1$  links:
  - With probability  $(1 - q)$ : usual PA
  - With probability  $q$ : Attach to one neighbor of the first chosen node

HOLME-KIM  
PHYS. REV. E 65, 026107 (2002)

54



*Big Data <-> Big Networks*

*Albert Diaz-Guilera*

**Algorithm 4.20 Barabási-Albert (BA) Scale-Free Model.**

---

**Input:**  $N$  (size of the network),  $m \leq m_0$  (number of connections of newly added nodes) and  $m_0$  (number of nodes in the initial core, should be small).

```

for all  $m_0$  initial nodes do
    create a fully connected network of  $m_0$  nodes
end for
for all time step  $t \leq N - m_0$  do
    add a new node  $j$ 
    number of newly added links  $\leftarrow 0$ 
 $\sum_i^{(m_0+t-1)} k_i = m_0(m_0 - 1) + 2m(t - 1) = S$ 
    while number of newly added links  $< m$  do
        add 1 to number of newly added links
        Generate a random number  $r$ 
        while  $\sum_{i \neq l} k_i < rS$  do
            add the edge  $(l, j)$  ( $l$  satisfies that  $\sum_i^{l-1} k_i < rS \leq \sum_i^l k_i$ )
             $S = S - k_l$ 
        end while
    end while
end for
return  $G_{N,K}^{BA}$ 

```

---

55



*Big Data <-> Big Networks*

*Albert Diaz-Guilera*

## Other (microscopic) models

- Fitness model
- Hidden variables
- Social distance
- Popularity
- Gravitational model

56

*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## Fitness model

**FITNESS** model (Caldarelli et al. Phys. Rev. Lett. 2002)

- Each vertex  $i$  is assigned a *fitness value*  $x_i$  drawn from a given distribution  $\rho(x)$ ;
- A link is drawn between each pair of vertices  $i$  and  $j$  with probability  $f(x_i, x_j)$  depending on  $x_i$  and  $x_j$ .

**Power-law degree distributions are obtained by choosing**

$$\rho(x) \propto x^{-\alpha}$$

$$f(x_i, x_j) \propto x_i x_j$$

or

$$\rho(x) = e^{-x}$$

$$f(x_i, x_j) \propto \theta(x_i + x_j - z)$$

**Figure:** Degree distribution  $P(k)$  versus degree  $k$  on a log-log scale. The data points show a power-law decay. Three theoretical curves are shown:  $k^{-2.5}$  (solid line),  $k^{-3}$  (dashed line), and  $k^{-4}$  (dotted line).

57

*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## Hidden variables

1. Each vertex  $i$  is assigned a variable  $h_i$ , independently drawn from the probability distribution  $\rho(h)$ .
2. For each pair of vertices  $i$  and  $j$ , with respective hidden variables  $h_i$  and  $h_j$ , an undirected edge is created with probability  $r(h_i, h_j)$  (the *connection probability*), where  $r(h, h') \geq 0$  is a symmetric function of  $h$  and  $h'$ .

58



*Big Data <-> Big Networks*

*Albert Diaz Guilera*

## A model based on social distance

- Properties of a nonbipartite network
- Relations are established between individuals that feel “close”
- Assign a position to each individual = a set of values in a number of social dimensions

59



*Big Data <-> Big Networks*

*Albert Diaz Guilera*


## 1 social dimension

- Position of individual  $i$  in social space  $h_i$
- Define a density  $\rho(h)$
- Probability of establishing a relation decreases with social distance


$$r_n(h_i^n, h_j^n) = \frac{1}{1 + [b_n^{-1} d_n(h_i^n, h_j^n)]^{\alpha_n}}$$

- $\alpha$  measures the degree of homophily


60




61




62



63



64

 Big Data <-> Big Networks Albert Diaz Guilera

## Gravity model

**9.2.1.1 The family of gravity models of transportation**

A first step towards modelling mobility was based on an analogy with a physical law which gave rise to the term *gravity law of transportation* proposed by Zipf in [184]. This model is based on assuming that each location has a mass  $M_i$  (which can be related to population, job availability, interest...) and that the number of trips between two locations can be approximated by:

$$\langle t_{ij} \rangle = KM_i M_j f(d_{ij}). \quad (122)$$

Where  $K$  is a normalizing constant ensuring that  $\sum_{ij} \langle t_{ij} \rangle = \hat{T}$  and  $f(d_{ij})$  is an arbitrary (decreasing) function of the cost or distance. Its most common version uses a power law  $f(d_{ij}) = d_{ij}^{-\gamma}$  but also exponential versions are present in the literature. In the urban context, we will only consider exponential versions of the deference function


65

 Big Data <-> Big Networks Albert Diaz Guilera


## Configurational model

- Choose  $P(k)$
- Stubs that are connected

66



67



68

<b>Random Graphs</b>	
Generators for random graphs.	
<code>fast_gnp_random_graph(n, p[, seed, directed])</code>	Return a random graph $G_{\{n,p\}}$ (Erdős–Rényi graph, binomial graph).
<code>gnp_random_graph(n, p[, seed, directed])</code>	Return a random graph $G_{\{n,p\}}$ (Erdős–Rényi graph, binomial graph).
<code>dense_gnm_random_graph(n, m[, seed])</code>	Return the random graph $G_{\{n,m\}}$ .
<code>gnm_random_graph(n, m[, seed, directed])</code>	Return the random graph $G_{\{n,m\}}$ .
<code>erdos_renyi_graph(n, p[, seed, directed])</code>	Return a random graph $G_{\{n,p\}}$ (Erdős–Rényi graph, binomial graph).
<code>binomial_graph(n, p[, seed, directed])</code>	Return a random graph $G_{\{n,p\}}$ (Erdős–Rényi graph, binomial graph).
<code>newman_watts_strogatz_graph(n, k, p[, seed])</code>	Return a Newman–Watts–Strogatz small world graph.
<code>watts_strogatz_graph(n, k, p[, seed])</code>	Return a Watts–Strogatz small-world graph.
<code>connected_watts_strogatz_graph(n, k, p[, ...])</code>	Return a connected Watts–Strogatz small-world graph.
<code>random_regular_graph(d, n[, seed])</code>	Return a random regular graph of $n$ nodes each with degree $d$ .
<code>barabasi_albert_graph(n, m[, seed])</code>	Return random graph using Barabási–Albert preferential attachment model.
<code>powerlaw_cluster_graph(n, m, p[, seed])</code>	Holme and Kim algorithm for growing graphs with powerlaw
<code>random_lobster(n, p1, p2[, seed])</code>	Return a random lobster.
<code>random_shell_graph(constructors[, seed])</code>	Return a random shell graph for the constructor given.
<code>random_powerlaw_tree(n[, gamma, seed, tries])</code>	Return a tree with a powerlaw degree distribution.
<code>random_powerlaw_tree_sequence(n[, gamma, ...])</code>	Return a degree sequence for a tree with a powerlaw distribution.

<b>Degree Sequence</b>	
Generate graphs with a given degree sequence or expected degree sequence.	
<code>configuration_model(deg_sequence[, ...])</code>	Return a random graph with the given degree sequence.
<code>directed_configuration_model(...[, ...])</code>	Return a directed_random graph with the given degree sequences.
<code>expected_degree_graph(w[, seed, selfloops])</code>	Return a random graph with given expected degrees.

69

*Big Data <-> Big Networks*      *Albert Diaz-Guilera*

# Null models

- Compare the number of patterns in **real** and **properly randomized** (null model) networks



70

*Big Data <-> Big Networks*      Albert Diaz Guilera

## Maslov-Sneppen

**switch partners**

- Randomly select and **rewire** two edges
- Repeat **many times**

S. Maslov,  
K. Sneppen,  
*Science* (2002)

R. Kannan,  
P. Tetali,  
S. Vempala,  
Random Structures  
and Algorithms (1999).

71

*Big Data <-> Big Networks*      Albert Diaz Guilera

## Random Network Generator

### RandNetGen

Random Network Generator

- <http://polcolomer.github.io/RandNetGen/>

73