

DCFT Deep Clean Conveyor Belt

To maintain effectiveness of the Prince Castle MCD DCFT conveyor belt

Frequency

Weekly

Models

DCFT

Estimated Time to Complete

20 minutes

Health and Safety Hazards



Chemicals



Hot Surface

Food Safety



Wash and dry hands **before and after** performing this task




Ensure nuts, bolts & screws are tight




Inspect equipment. Do not use if damaged

Equipment



1. Red border cloth




2. Grill cloth




3. Heat-resistant Gloves



4. Approved Detergent Solution



5. Solid Sense Sanitiser



6. KAY® QSR Hi-Temp Grill Cleaner



7. Approved Sanitizer Solution

Procedure

1

Turn the toaster OFF.

After waiting 15 minutes for unit to cool, put on the heat resistant gloves.

NOTE: Failure to wear heat-resistant gloves while performing this cleaning procedure can result in burns.




2

Remove the main release sheet from the toaster.

- Place release sheet on a clean, flat and dry surface.
- Inspect the release sheet for tears, cracks and sticking.
- Replace when necessary.

NOTE: DO NOT fold or cease release sheet or take to the 3-compartment sink to be cleaned.



3**Prepare grill cleaner**

- Dispense one packet of Hi Temp Grill Cleaner into a black Hi Temp grill cleaner tray

**4****Clean conveyor and club belts.**

- Using a none scratch pad and hi temp grill cleaner clean the front of the main conveyor belt. Wipe off hi temp cleaning solution grill with a grill cloth. The wipe over with red sanitised border cloth
- Wipe the club belt over belt over with red sanitised border cloth

**5**

- Close door, power unit ON, count 13 seconds to reveal unclean side of belts, power unit OFF, open door and repeat cleaning using the sanitizer-soaked towel.
- Close door, power unit ON, count 13 seconds again, power OFF, open door and repeat cleaning.

**6**

- Wipe down inner panel using a red border cloth
- Repeat process 5 and 6 for the rear belts.

**7****NOTE: Do not clean ANY belts while they are turning.**

- Close the conveyor access door and secure.
- Re-tighten top cover screws.

**8****Reinstall release sheet.**

NOTE: Make sure release sheet is completely dry before installing.

NOTE: When installing release sheet, you may flip inside-out and use the other side if needed.

