

Grills: Garland 2+1

Card No: GR046d

Temperature Calibration

Frequency	Twice a Month
Models	Garland 2+1
Estimated Time to Complete	10 Minutes per Unit

Health & Safety Hazards



Hot Surfaces

Food Safety



Critical Control Point




Inspect equipment. Do not use if damaged



Wash and dry hands **after** performing this task

Equipment



1 Pyrometer Surface Probe



Temperature Values.

Thermocouple Probes are located Front to Rear of the Grill Surface, Front and Back of the Top Platen.

NB The Teflon Sheet must be kept **OFF** when taking a reading.

	Probe Spots	Temp
5	Top Front	218°C
4	Top Rear	218°C
3	Bottom Rear	177°C
2	Bottom Middle	177°C
1	Bottom Front	177°C

3

2

1



4



5



1

PRESS the **SETTINGS** button.




2

ENTER the **STORE NUMBER** using exact number of digits, (i.e. store 1 enter 1, store 1500 enter 1500) and PRESS the **RETURN** button.




3

Scroll down using the **ARROW** button until you reach **THERMOCOUPLE CALIBRATION** and PRESS the **START** button.



4

Place the surface probe on probe **spot 1** lower platen and allow temperature to stabilize. (**Check temperature using Probe is the same as Control Panel display**).



5

PRESS the **UP/DOWN ARROWS** to change temperature values as needed.



6

Repeat steps 4 and 5 for all other probe spots. Once completed PRESS **SAVE**. Press the **HOME** button to exit.

