

Frymaster Fryer In-Built Filtering Models

Card No. **FR036**

Built-in Filtering System - Replace O-Rings

Frequency

Quarterly

Models

Frymaster models with in-built filtering systems

Estimated Time to Complete

2 minutes to prepare, 5 minutes to complete

Health & Safety Hazards



Sharp Objects / Surfaces



Moving Parts Hazard



Slippery Floors/Tripping



Hot Surfaces



Electrical Hazard



Hot Oil

Food Safety



Ensure nuts, bolts & screws are tight




Inspect equipment. Do not use if damaged



Wash & dry hands **before & after** performing task

Equipment

1



2



3



1 Flat tip screwdriver

2 No-scratch pad

3 O-Rings

(Only use approved O-Rings available from H+K Rugby Part No E-FM-8261392)

1

Warning
Prepare fryer for procedure.

Check to ensure that fryer is cool and that the fryer pan is empty before commencing to remove filter pan.



2

Remove filter pan.

Pull the filter pan out of the cabinet.



3

Replace O-Ring.

Remove the O-ring from the pan nozzle. Replace the O-Ring with a new O-ring. Use only the manufacturer's replacement O-ring. These rings are manufactured specifically for use with hot cooking oils. Generic O-rings cannot be used for this purpose.



4

Clean pickup tubes.

Clean the male and female pickup tubes with a non-scratch pad.



5

Reinstall Filter Pan.

Reinstall the pan in to the fryer cabinet.

