

	https://github.com/j0hn0hoste			
ports	PORTS	Protocol / Service	INFO	Vulnerabilities / Notes
	20 [data], 21 [control]	FTP-data, FTP-control	The File Transfer Protocol (FTP) uses port 21 to pass commands and port 20 to transfer data between a client and server.	Target for brute-forcing, credential stuffing, or identifying outdated software versions (e.g., old OpenSSH vulnerabilities).
	22	SSH	Establish an encrypted channel for remote command-line access and secure data communications between a client and a server.	Vulnerable to automated brute-force attacks against weak credentials, session hijacking, and remote code execution exploits.
	23	Telnet	Unencrypted, text-based communication channel for remote command-line access to a server or device.	High risk because it transmits data in cleartext; easily sniffed for credentials if traffic can be intercepted.
	25	SMTP	Route and transfer outbound email messages between mail servers across the internet.	Open relay exploitation (broadcast spam) email spoofing (no built-in authentication), and cleartext credential harvesting.
	53	DNS	The Domain Name System (DNS) protocol translates human-readable domain names into machine-readable IP addresses.	Checked for misconfigured "Zone Transfers" (AXFR), which can leak an entire organization's internal subdomain map.
	80	HTTP	Transfer unencrypted web page data, images, and other resources between a web server and a browser.	Used to map out web applications for further directory busting, API fuzzing, and vulnerability scanning.
	110	POP3	Retrieve emails from a remote server, downloading them directly to a local client and typically deleting them from the server.	POP3 exposes user credentials and email messages to network packet sniffing because it transmits all data in cleartext by default.
	119	NNTP	Distribute, inquire about, and post Usenet news articles and discussion group messages between news servers and clients.	NNTP lacks encryption, leaving Usenet discussion traffic and login details vulnerable. Susceptible to DoS attacks and spam injection.
	143	IMAP	Retrieve emails from a mail server to view, organize, and sync messages across devices. Original files are stored on the server.	Vulnerable to credential theft via eavesdropping on its unencrypted stream, as well as aggressive authentication brute-forcing.
	123	NTP	The Network Time Protocol (NTP) synchronizes the clocks of computers and network devices with highly accurate sources.	NTP is targeted for DDoS reflection and amplification attacks via the <i>monlist</i> command and time-spoofing to disrupt security logs.
	135	RPC	Allows a program on one computer to execute code on a remote server as if it were running locally.	Used for gathering system information, enumerating users, and interacting with Windows services.
	139 [and 445]	SMB	Uses 139 over NetBIOS to facilitate legacy file and printer sharing, as well as session handling, on local Windows networks.	Infamous for massive RCE exploits (like EternalBlue). Susceptible to LLMNR/NBT-NS spoofing and SMB relay attacks.
	161 / 162	SNMP	The Simple Network Management Protocol is used to monitor and manage network devices.	If the "community string" (password) is set to default, a pentester can get system configs, network routes, and software lists.
	389 [636]	LDAP [LDAPS]	Queries and manages user, group, and device information within a centralized directory service like Active Directory.	The backbone of Active Directory. Pentesters query this to map out domain users, groups, and computers.
	443	HTTPS	Transfer web page data over an encrypted TLS connection, ensuring secure communication between a browser and a server.	Used to map out web applications for further directory busting, API fuzzing, and vulnerability scanning.
	465	SMTPS	Securely transmit outbound email messages between mail servers or from a client using implicit TLS encryption.	Remains vulnerable to credential stuffing and traffic decryption if misconfigured with weak cipher suites or outdated TLS versions.
	563	NNTPS	Distribute, retrieve, and post Usenet news articles over an encrypted TLS connection.	Risks are generally limited to server software flaws and man-in-the-middle attacks caused by poor client-side certificate validation.
	993	IMAPS	Internet Message Access Protocol Secure (IMAPS) securely retrieves and synchronizes emails over an encrypted TLS connection.	Vulnerabilities are mostly weak user passwords targeted by credential stuffing or unpatched server vulnerabilities.
	989 [data], 990 [control]	FTPS	Uses 990 for the encrypted control connection and 989 for data transfer, securing traditional FTP traffic with implicit TLS encryption.	FTPS secures transfers using TLS but is at risk of firewall misconfigurations and remains vulnerable to credential guessing.
995	POP3S	Post Office Protocol 3 Secure securely downloads emails from a remote server to a local client using an encrypted TLS connection.	Primarily vulnerable to attacks against weak passwords and exploits targeting outdated cryptographic configurations.	
1433	Microsoft SQL Server	The Msoft SQL Server database engine accepts inbound connections/queries from client apps, managing database traffic.	If a database port is exposed, it is a prime target for credential attacks or direct exploitation.	
3389	RDP (Remote Desktop Protocol)	Provide users and administrators with a secure graphical interface to connect to and control a remote computer over a network.	Highly targeted for brute-force attacks and critical remote code execution (RCE) vulnerabilities (like BlueKeep).	