
steel substread 5-6 TYP Tread

body-0000 | QTY 8 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:3


01 / TOP - FACE A



02 / FRONT - EDGE VIEW



03 / BOTTOM - FACE B



F01 - X DIMENSIONS APPLY TO MATCHING COLUMNS


04 / SECTION A-A

X = 16-1/8" FROM END A



SECTION SCALE 1:3

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

X: FROM END A / Y: FROM EDGE C

Dimensions are to feature centers.

Shared columns use one X chain.

Equal row spacing is counted once.

NOTCH CENTRES / END A

FIRST: 2-13/16"

8 SPACES @ 7-1/2" TYP

DATUM / REVIEW

END A is the left material extent in both face views.


EDGE C is marked on the bottom face view.

Fractions rounded to 1/64; feature sizes kept decimal.


steel substread 5-6 BTM Riser

body-0001 | QTY 1 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:3

01 / TOP - FACE A




02 / FRONT - EDGE VIEW



03 / BOTTOM - FACE B


04 / SECTION A-A

X = 33-19/32" FROM END A



SECTION SCALE 1:2

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

No internal holes in the broad face.

TAB CENTRES / END A

FIRST: 2-13/16"

8 SPACES @ 7-1/2" TYP

DATUM / REVIEW

END A is the left material extent in both face views.


Profile views retain the source geometry.

Fractions rounded to 1/64; feature sizes kept decimal.

base shoe top mount plate Tread-Side

body-0002 | QTY 9 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:1


01 / TOP - FACE A



02 / FRONT - EDGE VIEW




03 / BOTTOM - FACE B




04 / SECTION A-A

X = 1-1/2" FROM END A



SECTION SCALE 1:1

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

X: FROM END A / Y: FROM EDGE C

Dimensions are to feature centers.

Shared columns use one X chain.

Equal row spacing is counted once.

STEP FEATURE: 5/16-18 TAPPED HOLE

Threads are not represented by the bore surfaces.

DATUM / REVIEW

END A is the left material extent in both face views.


EDGE C is marked on the bottom face view.

Fractions rounded to 1/64; feature sizes kept decimal.

structure box asm BTM 5-6 body 5

body-0004 | QTY 1 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:14


01 / TOP - FACE A



02 / FRONT - EDGE VIEW



03 / BOTTOM - FACE B




04 / SECTION A-A

X = 49-17/32" FROM END A



SECTION SCALE 1:13

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

No internal holes in the broad face.

NOTCH CENTRES / END A

FIRST: 12-53/64"

Irregular spacing follows source profile.

DATUM / REVIEW

END A is the left material extent in both face views.


Profile views retain the source geometry.

Fractions rounded to 1/64; feature sizes kept decimal.

structure box asm BTM 5-6 body 7


body-0006 | QTY 1 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:14

01 / TOP - FACE A




02 / FRONT - EDGE VIEW

03 / BOTTOM - FACE B




04 / SECTION A-A

X = 49-17/32" FROM END A



SECTION SCALE 1:13

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

No internal holes in the broad face.

NOTCH CENTRES / END A

FIRST: 12-53/64"

Irregular spacing follows source profile.

DATUM / REVIEW

END A is the left material extent in both face views.


Profile views retain the source geometry.

Fractions rounded to 1/64; feature sizes kept decimal.

structure box asm BTM 5-6 body 9

body-0008 | QTY 1 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:5


01 / TOP - FACE A



02 / FRONT - EDGE VIEW



03 / BOTTOM - FACE B



F01 - X DIMENSIONS APPLY TO MATCHING COLUMNS


04 / SECTION A-A

X = 2" FROM END A



SECTION SCALE 1:4

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

X: FROM END A / Y: FROM EDGE C

Dimensions are to feature centers.

Shared columns use one X chain.

Equal row spacing is counted once.

TAB CENTRES / END A

FIRST: 4-3/32"

Irregular spacing follows source profile.

DATUM / REVIEW

END A is the left material extent in both face views.


EDGE C is marked on the bottom face view.

Fractions rounded to 1/64; feature sizes kept decimal.

steel substread 5-6 TYP Riser

body-0018 | QTY 8 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:3


01 / TOP - FACE A



02 / FRONT - EDGE VIEW



03 / BOTTOM - FACE B




04 / SECTION A-A

X = 33-19/32" FROM END A

SECTION SCALE 1:2

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

No internal holes in the broad face.

TAB CENTRES / END A

FIRST: 2-13/16"

8 SPACES @ 7-1/2" TYP

DATUM / REVIEW

END A is the left material extent in both face views.


Profile views retain the source geometry.

Fractions rounded to 1/64; feature sizes kept decimal.

steel substread 5-6 SPLICE Tread

body-0038 | QTY 1 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:3


01 / TOP - FACE A



02 / FRONT - EDGE VIEW



03 / BOTTOM - FACE B



F01 - X DIMENSIONS APPLY TO MATCHING COLUMNS

04 / SECTION A-A

X = 16-1/8" FROM END A

SECTION SCALE 1:3

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

X: FROM END A / Y: FROM EDGE C

Dimensions are to feature centers.

Shared columns use one X chain.

Equal row spacing is counted once.

NOTCH CENTRES / END A

FIRST: 2-13/16"

Irregular spacing follows source profile.

DATUM / REVIEW

END A is the left material extent in both face views.


EDGE C is marked on the bottom face view.

Fractions rounded to 1/64; feature sizes kept decimal.

structure box asm BTM 5-6 body 56

body-0055 | QTY 1 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:14


01 / TOP - FACE A



02 / FRONT - EDGE VIEW




03 / BOTTOM - FACE B




04 / SECTION A-A

X = 49-17/32" FROM END A



SECTION SCALE 1:13

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

No internal holes in the broad face.

NOTCH CENTRES / END A

FIRST: 12-53/64"

Irregular spacing follows source profile.

DATUM / REVIEW

END A is the left material extent in both face views.


Profile views retain the source geometry.

Fractions rounded to 1/64; feature sizes kept decimal.

structure box asm BTM 5-6 body 58

body-0057 | QTY 1 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:14


01 / TOP - FACE A



02 / FRONT - EDGE VIEW



03 / BOTTOM - FACE B




04 / SECTION A-A

X = 49-17/32" FROM END A



SECTION SCALE 1:13

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

No internal holes in the broad face.

NOTCH CENTRES / END A

FIRST: 12-53/64"

Irregular spacing follows source profile.

DATUM / REVIEW

END A is the left material extent in both face views.


Profile views retain the source geometry.

Fractions rounded to 1/64; feature sizes kept decimal.

structure box asm BTM 5-6 body 60

body-0502 | QTY 1 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:5


01 / TOP - FACE A



02 / FRONT - EDGE VIEW



03 / BOTTOM - FACE B



F01 - X DIMENSIONS APPLY TO MATCHING COLUMNS


04 / SECTION A-A

X = 2" FROM END A



SECTION SCALE 1:4

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

X: FROM END A / Y: FROM EDGE C

Dimensions are to feature centers.

Shared columns use one X chain.

Equal row spacing is counted once.

TAB CENTRES / END A

FIRST: 4-3/32"

Irregular spacing follows source profile.

DATUM / REVIEW

END A is the left material extent in both face views.


EDGE C is marked on the bottom face view.

Fractions rounded to 1/64; feature sizes kept decimal.

structure box asm BTM 5-6 body 70

body-0068 | QTY 1 IN BTM RUN | INCHES | TOP / FRONT / BOTTOM SCALE 1:5


01 / TOP - FACE A



02 / FRONT - EDGE VIEW




03 / BOTTOM - FACE B




04 / SECTION A-A

X = 57-15/32" FROM END A



SECTION SCALE 1:2

05 / ISOMETRIC



ISOMETRIC REFERENCE / NTS

FEATURE / DATUM NOTES

HOLES / SLOTS LOCATED ON FACE B

No internal holes in the broad face.

DATUM / REVIEW

END A is the left material extent in both face views.

Profile views retain the source geometry.

Fractions rounded to 1/64; feature sizes kept decimal.