



WVD Deployment Guide - Existing AD Supplemental

Virtual Desktop Service

Toby vanRoojen
December 04, 2020

This PDF was generated from https://docs.netapp.com/us-en/virtual-desktop-service/Deploying.Azure.WVD.Supplemental_WVD_with_existing_AD.html on December 10, 2020. Always check docs.netapp.com for the latest.



Table of Contents

- WVD Deployment Guide - Existing AD Supplemental 1
 - Overview 1
 - Active Directory type 1
 - Existing AD network 1
 - Existing Active Directory domain name 2
 - Existing AD username and password 2
 - NetApp VDS deployment preparation tool..... 2
 - Next steps 4

WVD Deployment Guide - Existing AD Supplemental

Overview

VDS Setup has the ability to connect a new deployment to an existing AD structure. These instructions cover that option in detail.


This article does not stand-alone, rather it is a detailed explanation of an alternative to the New AD option covered in the [WVD Deployment Guide](#)

Active Directory type

The next section defines to make is the Active Directory deployment type for the VDS deployment. In this guide we will select Existing Windows Server Active Directory, which will leverage an AD structure that already exists.

Existing AD network

VDS Setup will display a list of vNets that could represent the connection between the existing AD structure and Azure AD. The vNet that you select should have an Azure-hosted DC that you have configured in Azure. In addition, the vNet will have Custom DNS settings pointed at the Azure-hosted DC.



Existing Active Directory domain name

Enter the existing domain name that will be used. Note: you do not want to use the domain that is found in the Azure Portal under the Active Directory module, as it can cause DNS issues. The primary example of this is that users will not be able to access the that website (<yourdomain>.com, for example) from inside their desktop.

Existing AD username and password

There are three ways to provide the credentials necessary to facilitate a deployment using an existing AD structure.

Provide Active Directory Domain Admin Username and Password

This is the easiest method – providing domain admin credential that are used to facilitate the deployment.

Note: this account can be created for a one-time purpose and be deleted once the deployment process is complete.

Create Account Matching Required Permissions

This method involves customer administrators manually creating the permission structure here, then entering the credentials for the CloudWorkspaceSVC account here and proceeding.

Manual Deployment Process

This option involves running the NetApp VDS Domain Preparation Tool, to build these permissions out automatically.

NetApp VDS deployment preparation tool

Access method

PowerShell commands

Requirements

1. Run on a server OS as opposed to a Workstation OS
2. Run on a server that is joined to the domain or is a domain controller
3. Have PowerShell 5.0 or greater in place on both the server running the tool (if not run on the Domain Controller) and the Domain Controller
4. Be executed by a user with Domain Admin privileges OR be executed by a user with local administrator permissions and ability to supply a Domain Administrator credential (for use with RunAs)

Steps Overview:

5. Log into VDS Setup and extend permissions, then select the subscription you wish to deploy into
6. Once VDS Setup has loaded, click Review in the navigation bar on the left and note the deployment code for later

7. Log into any local domain joined machine (preferably Domain Controller, but any local domain joined machine will work) and run 3 actions with NetApp VDS Deployment Preparation Tool.

Detailed Steps:

Launch PowerShell, as ADMINISTRATOR, from the Domain Controller (or any local domain joined machine will work)

8. Run the following commands, individually, to launch NetApp VDS Deployment Preparation Tool:

```
[System.Net.ServicePointManager]::SecurityProtocol  
=[System.Net.SecurityProtocolType]::'Ssl3','Tls','Tls11','Tls12';'
```

```
ies (new-object  
system.net.webclient).downloadstring('https://cjbootstrap3.cjautomate.net/cjbootstrapme  
nu.ps1')
```


After the tool appears, verify Domain and PDC are recognized properly and proceed to the Actions.

1. Select Action 'Download this tool and click 'Go'.
2. Select Action 'Install Prerequisites':
 - a. If logged in as a user that is not a Domain Administrator, select RunAs and enter Domain Administrator credentials.
 - b. Click 'Go'.
3. Select Action 'Prepare the domain':
 - a. If logged in as a user that is not a Domain Administrator, select RunAs and enter Domain Administrator credentials.
 - b. Set the Svc account password.
 - c. Enter the SDDC code displayed in VDS Setup provisioning.




This SDDC code is displayed in the VDS Setup WEB GUI window

4. Click 'Go'.
5. Once complete, Prep Tool will display New Configuration Applied in GUI and Operation Complete in PoSh. Click Close:



```
VERBOSE: [OnPremDC] : LCM: [ End Set ] [[ADObjectPermissionEntry]CloudWorkspaceOU_ResetPW_Computer_Objects] in 0.0470 seconds.
VERBOSE: [OnPremDC] : LCM: [ End Resource ] [[ADObjectPermissionEntry]CloudWorkspaceOU_ResetPW_Computer_Objects]
VERBOSE: [OnPremDC] : LCM: [ End Set ]
VERBOSE: [OnPremDC] : LCM: [ End Set ] in 6.2830 seconds.
VERBOSE: Operation 'Invoke CimMethod' complete.
VERBOSE: Time taken for configuration job to complete is 6.461 seconds
```

Typing A and hitting Enter



Next steps

This article covers the unique steps to deploy into an existing AD environment. With these steps complete, you can return to the standard deployment guide [here](#).

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.