Troubleshooting Failed VDS Actions

Virtual Desktop Service

Toby vanRoojen December 02, 2020

This PDF was generated from https://docs.netapp.com/us-en/virtual-desktop-service/Troubleshooting.reviewing_vds_logs.html on December 10, 2020. Always check docs.netapp.com for the latest.



Table of Contents

| Troublesh | nooting Fa | iled V | DS A | Action | ns . | | . 1 |
|-----------|------------|--------|------|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|-----|
| Overvi | ew | | | | | | . 1 |
| Automa | ation logs | | | | | | . 1 |

Troubleshooting Failed VDS Actions

Overview

Much of the logging that happens in VDS is not exposed in the web UI due to the sheer volume of it. More detailed logs are found on the end point. These logs are described below.

In VDS v5.4+, the logs are found in the following folder path:

C:\programdata\cloudworkspace

In previous version of VDS, they can reside in the following paths:

C:\Program Files\CloudWorkspace\

C:\Program Files\CloudJumper\

C:\Program Files\IndependenceIT\



File type also varies by VDS version, log files are either .txt or .log files found in subfolders of the above outlined path.

Automation logs

CW VM Automation Service log

CwVmAutomationService.log

The CW VM Automation service is a Windows Service that is responsible for the management of all Virtual Machines in the deployment. As a Windows Service it is always running in a deployment, but has two main modes of operation: Scheduled Task Mode and Event Mode.

Scheduled Task Mode consists of activities that are performed on the VMs as part of a schedule, including collection sizing and performance data, rebooting VMs, checking on state (on or off) vs rule sets generated by the Workload Schedule and Live Scaling features. The logs denote these action types in the 5th column with names like "Daily Actions", "Weekly Actions" and "Daily Maintenance". If you are troubleshooting questions like "Why did Server X reboot last night at 2:00 am" or "Why is this server on when I think it should be off" then the scheduled tasks for those specific VMs are usually the best place to look.

Event Mode is activated when a user or other VDS Service such as the CW Automation Service asks for a Task to be completed. Examples of this type of activity include a user request to Create a new Server

or CW Automation requesting the sizing and state of servers to be checked because more users were added to the workspace. These events typically have log entries with both the event name "Create Server" and the actual name of the VM right next to it (ex: Create Server NNXTS2). When troubleshooting these types of events, its usually best to scroll to the bottom of the log and then to an upwards search for the VM name. You can then scroll up more rows to see where the process started.

CW Automation Service log

CWAutomationService.log

The CW Automation Service log is the primary Windows services for managing the components of a Workspace deployment. It executes the tasks required to manage users, applications, data devices, and policy. In addition, it can create tasks for the CW VM Automation Service when changes need to be made to size, count, or state of the VMs in the deployment.

Like the CW VM Automation Service, the CW Automation service executes both scheduled tasks and event driven tasks, with the latter being the more frequent type. The log for the CW Automation Service starts each line with the entity and action being worked on (ex: Start Server NNXTS1) so searching for the entity name from the bottom of the file is the quickest way to find the specific log lines that apply to the task.

CW Agent Service log

CwAgent.log

The CW Agent Service performs all the tasks that are local to a specific VM, including checking the resource levels and utilization for the VM, checking that the VM has a valid certificate for TLS traffic, and checking to see if the mandatory reboot period has been reached. Besides checking on detail information on these tasks, this log can also be used to check for unexpected VM restarts or unexpected network or resource activity.

CWManagerX log

CWManagerX.log

CWManagerX is a web service that provides the communication link between the local Deployment and the VDS global control plane. Tasks and data requests that originate in the VDS Web Application or VDS API are communicated to the local deployment through this web service. From there, the tasks and requests are directed to the appropriate web service (described above) or in rare cases directly to Active Directory. Since this is mostly a communications link there isn't much logging that occurs during normal communication, but this log will contain errors when the communication link is broken or performing incorrectly.

DC Config log

```
DCConfig.log
```

DC Config is a Windows application that provides Deployment specific configuration parameters that are not exposed in the VDS Web Application interface. The DC Config log details the activities executed when configuration changes are made in DC Config.

CWvDCDeployment log

```
CWvDCDeployment.log
```

CW vDC Deployment is a Windows application that performs the tasks necessary to create a Deployment in Azure. The log tracks the configuration of the Cloud Workspace windows services, default GPOs, and routing and resource rules.


Miscellaneous logs

```
CwVmAutomationService-Installing.log
CwAgent-Installing.log
```


The remaining logs track the installation of the Windows Services and application described above. Since VDS services auto-update when a new version is targeted at that specific deployment, these logs track the upgrade process since the Service or application typically needs to be off while being upgraded. If you find the Services are consistently Stopped these logs can help identify if a failed upgrade to a specific service is the cause. In these cases, we would expect to see an error in these logs detailing why the upgrade failed.

Accessing logs and reviewing information


When requested actions like cloning a server, adding a user or restoring a backup you'll get feedback in the VDS UI.



1. VDS keeps detailed logs and exposes some of them on the Task History section of the Deployments page in VDS. Click on View can show details of the listed tasks.




- 2. Sometimes the Task History does not contain enough details to identify the true root cause. In order to keep the Task History section usable and not overwhelmed by all logged events, only a subset of task information is presented here. For a deeper look the text log files referenced above can provide more details.
 - a. To access this log, navigate to the Deployments Section and click the Gear Icon next to the CWMGR1 VM, then click Connect (or in the case of the CwAgent log, connect to the appropriate VM)




3. When connecting to a Platform Sever (Like the CWMGR1) you will not be automatically logged into the server (unlike connecting to a server in the tenant). You'll need to login with a Level3 .tech account.



4. Then navigate to the path as shown above and open the log file.



5. This text file contains a log of all events, listed form oldest to newest:



6. When opening a support case with NetApp VDS, being able to provide the errors found here will SIGNIFICANTLY accelerate the speed to resolution.

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval systemwithout prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.