

Appendix R5: Variable Selection

Multi-Collinearity, Subset Selection and Step Methods

J. Alberto Espinosa

2/3/2023

Contents

Overview	1
1. Multi-Collinearity	2
Condition Index (CI)	2
Variance Inflation Factors (VIFs)	5
2. Variable Selection	6
Subset Comparison	6
Step Methods	9
Forward Selection	12
Backward Selection	22
Stepwise Selection	28
Best Subset Selection	35

This script was created by J. Alberto Espinosa for educational and training purposes. Feel free to use this material for your own work, but please do not share or duplicate without the author's permission.

Overview

Dimensionality is an important issue in predictive modeling. As we add predictors and complex transformations in our model, the bias of the model decreases while the explanatory power of the model increases, but the model variance also increases. This is the well known bias vs. variance tradeoff in predictive modeling. This is not really a problem when the multi-collinearity of the model is tolerable, but it really affects its performance when multi-collinearity is severe. In such cases, we need to pay close attention to how we select our predictors and whether multi-collinearity is a concern. The methods described in this script can help correct for multi-collinearity when predictors causing the problem can be removed. If not, please refer to the methods described in Ch. 7, which are ideally suited for predictive modeling in the presence of multi-collinearity. I first discuss how to diagnose multi-collinearity and then illustrate how to do subset selection and run various step methods for variable selection.

1. Multi-Collinearity

High multi-collinearity causes a lot of variance in the model. Multi-collinearity is tolerable, unless it is severe, in which case it causes the the model to have high variance and become unstable to be reliable. If you drop a few observations, the resulting coefficients should not change much. But if they change substantially, chances are that your model suffers from high multi-collinearity.

Multicollinearity can be tested in two ways:

- Evaluate the multi-collinearity condition of the model as a whole, using the **Condition Index (CI)**. The CI evaluates the overall linear association of the predictors for the **entire model**.
- If the CI shows that the model is multi-collinear, you can then inspect which predictors contribute the most to collinearity by inspecting the **Variance Inflation Variable (VIF)** of **each predictor**. We discuss both methods below.

Condition Index (CI)

The Condition Index (CI) is a general collinearity statistic for the full model. It takes the covariance matrix and computes its corresponding eigenvalues. As I discuss in the main chapter, collinearity is associated with eigenvalues that vary widely because this indicates that there are one or a few dominant eigenvector directions where the predictors correlate strongly. If the eigenvalues don't vary much, it is an indication that there are no dominant linear trends among the predictors, so multi-collinearity is not a concern. The CI is a simple statistic that measures the ratio of the largest eigenvalue of the covariance matrix to the smallest. The CI is then evaluated as follows:

CI < 30 -> Multi-Collinearity is not a concern
30 < CI < 50 -> Multi-Collinearity is a concern, is somewhat tolerable
50 < CI -> Multi-Collinearity is severe and **must** be addressed

For the examples below, we will use the `ols_eigen_cindex()` function in the **{olsrr}** package to compute the CI using the **Boston** housing data set in the **{MASS}** package. But there are other packages like **{klaR}** and **{car}** with similar diagnostic tools.

```
library(olsrr) # Tools for OLS regressions
library(MASS)  # Contains the Boston housing market data set
```

Let's first analyze the Full model

```
lm.fit <- lm(medv ~ ., data = Boston)
summary(lm.fit)

##
## Call:
## lm(formula = medv ~ ., data = Boston)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -15.595  -2.730  -0.518   1.777  26.199
##
## Coefficients:
```

```
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept)  3.646e+01  5.103e+00   7.144 3.28e-12 ***
## crim        -1.080e-01  3.286e-02  -3.287 0.001087 **
## zn          4.642e-02  1.373e-02   3.382 0.000778 ***
## indus        2.056e-02  6.150e-02   0.334 0.738288
## chas         2.687e+00  8.616e-01   3.118 0.001925 **
## nox        -1.777e+01  3.820e+00  -4.651 4.25e-06 ***
## rm           3.810e+00  4.179e-01   9.116 < 2e-16 ***
## age          6.922e-04  1.321e-02   0.052 0.958229
## dis        -1.476e+00  1.995e-01  -7.398 6.01e-13 ***
## rad          3.060e-01  6.635e-02   4.613 5.07e-06 ***
## tax        -1.233e-02  3.760e-03  -3.280 0.001112 **
## ptratio     -9.527e-01  1.308e-01  -7.283 1.31e-12 ***
## black        9.312e-03  2.686e-03   3.467 0.000573 ***
## lstat       -5.248e-01  5.072e-02 -10.347 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.745 on 492 degrees of freedom
## Multiple R-squared:  0.7406, Adjusted R-squared:  0.7338
## F-statistic: 108.1 on 13 and 492 DF,  p-value: < 2.2e-16
```

Now let's compute the CI:

```
coll <- ols_eigen_cindex(lm.fit)
coll[, 1:2] # Eigenvalues are in column 1 and CI in column 2
```

```
##      Eigenvalue Condition Index
## 1  10.092840813      1.000000
## 2   1.594070113      2.516245
## 3   0.959881737      3.242633
## 4   0.661730799      3.905405
## 5   0.241115274      6.469852
## 6   0.166505870      7.785597
## 7   0.108356145      9.651169
## 8   0.074488723     11.640227
## 9   0.041575247     15.580784
## 10  0.025639575     19.840440
## 11  0.013189367     27.662710
## 12  0.012073860     28.912366
## 13  0.007208734     37.417710
## 14  0.001323741     87.318288
```

As I discussed earlier, if the eigenvalues change substantially, it is an indication that multi-collinearity is present. The output in the example above shows all 14 eigenvalues, from largest to smallest. For example, the CI for the second eigenvalue is the $\sqrt{10.09 / 1.59} = 2.51$, which is OK. But we need to evaluate all eigenvalues relative to each other, so we only need to focus on the largest CI, which is the CI for the model, which is the square root of the ratio of the largest eigenvalue to the lowest, or $\sqrt{10.09 / 0.0013} = 87.32$. Also note that the function above computes the CI on the correlation,

rather than the covariance matrix, which is equivalent to running the CI on a standardized data set with `scale=T` and `center=F`. Let's see if we can further correct this by removing non-significant predictors.

```
lm.fit.red <- lm(medv ~ crim + zn + chas + rm + dis +
                 rad + tax + ptratio + black + lstat,
                 data = Boston)
summary(lm.fit.red)
```

```
##
## Call:
## lm(formula = medv ~ crim + zn + chas + rm + dis + rad + tax +
##     ptratio + black + lstat, data = Boston)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -16.980  -2.869  -0.693   1.732  26.674
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) 22.605365   4.324998   5.227 2.55e-07 ***
## crim        -0.096497   0.033446  -2.885 0.004082 **
## zn           0.052811   0.013759   3.838 0.000140 ***
## chas         2.380299   0.871150   2.732 0.006513 **
## rm           3.940596   0.414703   9.502 < 2e-16 ***
## dis        -1.054766   0.166731  -6.326 5.63e-10 ***
## rad          0.282595   0.064772   4.363 1.56e-05 ***
## tax         -0.015723   0.003351  -4.692 3.51e-06 ***
## ptratio     -0.756520   0.125988  -6.005 3.71e-09 ***
## black        0.010239   0.002729   3.753 0.000196 ***
## lstat       -0.570699   0.047475 -12.021 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.846 on 495 degrees of freedom
## Multiple R-squared:  0.7279, Adjusted R-squared:  0.7224
## F-statistic: 132.4 on 10 and 495 DF,  p-value: < 2.2e-16
```

Let's look at the CI

```
coll.red <- ols_eigen_cindex(lm.fit.red)
coll.red [, 1:2]
```

```
##      Eigenvalue Condition Index
## 1  7.437083446      1.000000
## 2  1.486050685      2.237095
## 3  0.952366861      2.794468
## 4  0.610778278      3.489471
## 5  0.229718168      5.689887
## 6  0.144696149      7.169235
```

```
## 7  0.078266220      9.747969
## 8  0.033337026     14.936124
## 9  0.017108940     20.849218
## 10 0.008779415     29.105062
## 11 0.001814812     64.015555
```

Conclusion: The reduced model did not totally solve the multi-collinearity since the $CI = 64.02$, which is greater than 50, so the multi-collinearity condition is severe. Note that the predictor **nox** was significant in the full model, but it became non-significant when I removed the other non-significant predictors. The fact that **nox** lost its significance when I removed a few predictor is evidence of the issues that multi-collinearity causes. So, I removed **nox** too. Now, let's find out which predictors contribute the most to multi-collinearity by examining the VIF's.

Variance Inflation Factors (VIFs)

The VIF helps analyze each variable's contribution to multi-collinearity. There is one VIF for each predictor, measuring how much is the standard error of that coefficient, compared to the standard error of the coefficient for the same variable, if it were modeled as a single-predictor model. It also measures how much of the variance of the predictor can be explained by the remaining predictors. The VIF of predictor i is $VIF_i = 1 / (1 - R_i^2)$ where R_i^2 is the R-Squared of a regression with predictor i as an outcome and all other variables as predictors. Therefore, if $R_i^2 = 0$ (no correlation, perfectly independent) then $VIF_i = 1$. At the other extreme, $R_i^2 = 1$ (i.e., perfectly correlated, mathematically) will yield a $VIF_i = \text{infinite}$, with the standard error = infinite, and a model with no solution. A $R_i^2 = 0.80$ and 0.90 translate to $VIF_i = 5$ and 10 respectively. When examining VIF's, the typical thresholds are:

- $VIF < 5$ -> No concern, little or no contribution to multi-collinearity
- $5 < VIF < 10$ -> Some concern, but tolerable
- $VIF > 10$ -> The variable contributes significantly to multi-collinearity

To test VIF's, we can use the `vif()` function in the **{car}** (Companion to Applied Regression) package or the `ols_vif_tol()` function in the **{olsrr}** package. They are both equally good at reporting VIF's but the second function also reports the tolerance for each variable. The tolerance is simply how much variance in the predictor is not explained by the other predictors, so it is the opposite of the VIF, or the inverse, to be precise $VIF_i = 1 / \text{Tolerance } i$

```
ols_vif_tol(lm.fit) # Full model
```

```
##      Variables Tolerance      VIF
## 1      crim 0.5579761 1.792192
## 2       zn 0.4350175 2.298758
## 3     indus 0.2505263 3.991596
## 4      chas 0.9311027 1.073995
## 5      nox 0.2275976 4.393720
## 6       rm 0.5171314 1.933744
## 7      age 0.3224948 3.100826
## 8      dis 0.2527841 3.955945
## 9      rad 0.1336095 7.484496
## 10     tax 0.1110056 9.008554
```

```
## 11 ptratio 0.5558384 1.799084
## 12 black 0.7415531 1.348521
## 13 lstat 0.3399636 2.941491
```

```
ols_vif_tol(lm.fit.red) # Reduced model
```

```
## Variables Tolerance VIF
## 1 crim 0.5618248 1.779914
## 2 zn 0.4515421 2.214633
## 3 chas 0.9497271 1.052934
## 4 rm 0.5476704 1.825916
## 5 dis 0.3772279 2.650918
## 6 rad 0.1461844 6.840676
## 7 tax 0.1457620 6.860500
## 8 ptratio 0.6250006 1.599998
## 9 black 0.7493034 1.334573
## 10 lstat 0.4045582 2.471832
```

Interestingly, the CI is severe in both models, but none of the VIF's are greater than 10 in either model. This suggests strongly that the collinearity is between one or two predictors and the constant. This issue can be resolved by centering all the variables, including the outcome, in addition to scaling, and fitting the model this way. Generally, if the CI is severe, but the VIF's are not, there is less of a concern because none of the predictor coefficients' standard errors are severely inflated.

One final note is that the function `ols_coll_diag()` of the `{olsrr}` package will run the CI and VIF test in one pass. So, if you are interested in both statistics together, you can use that instead.

2. Variable Selection

We explore two approaches to select predictors for a model with statistical methods. As discussed in the main chapter, these methods only work when the models are nested. If the model specifications are not nested (i.e., they involve different predictors), if the models are of different types, or if they are not OLS or GLM models, these methods don't work and you will need to use cross-validation to select the best models. In this section, I discuss two approaches to variable selection: (1) Subset Selection, which are applicable when you have a finite number of nested models and you want to test which one has the strongest explanatory power; and (2) Step Methods, which are useful when you have many predictors and no pre-defined idea of how to select the most appropriate ones.

Subset Comparison

The most effective way to compare the difference in explanatory power of two or more nested models is with an ANOVA F-Test. Smaller models are more biased, but large models can have dimensionality problems, particularly if the multi-collinearity condition is severe. So, this is a balancing act. The best approach is to select the best predictors based on business knowledge and then test various subsets. When comparing two models, the larger model **always** has more explanatory power than the smaller model because we have added explanatory predictors to the model. But if the increase in explanatory power is not significant, then the added complexity of the larger model is undesirable, and the smaller model is preferred. But if the difference is significant, we would select the larger model. Naturally, after

a model has been selected, it is important to test for multi-collinearity. Let's use the baseball data to illustrate these concepts and fit three models: reduced, large and full.

```
library(ISLR) # Contains the Hitters baseball player salary data set
Hitters <- na.omit(Hitters) # Let's remove missing values

# Small Model, 3 predictors

lm.reduced <- lm(Salary ~ AtBat + Hits + Walks,
                 data = Hitters)

summary(lm.reduced) # Take a look
```

```
##
## Call:
## lm(formula = Salary ~ AtBat + Hits + Walks, data = Hitters)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -1007.5  -245.4   -70.8   165.4  2039.1
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) 121.0590     73.2481   1.653  0.09960 .
## AtBat       -2.0862      0.6324  -3.299  0.00111 **
## Hits         8.9252      1.9922   4.480 1.12e-05 ***
## Walks        7.1645      1.4097   5.082 7.16e-07 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 386.1 on 259 degrees of freedom
## Multiple R-squared:  0.2758, Adjusted R-squared:  0.2674
## F-statistic: 32.88 on 3 and 259 DF,  p-value: < 2.2e-16
```

```
# Large Model, 5 predictors

lm.large <- lm(Salary ~ AtBat + Hits + Walks + Division + PutOuts,
              data = Hitters)

summary(lm.large) # Take a look
```

```
##
## Call:
## lm(formula = Salary ~ AtBat + Hits + Walks + Division + PutOuts,
##     data = Hitters)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -907.58 -216.89  -62.37  169.87 1965.55
```

```
##
## Coefficients:
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept) 173.02126   75.85170   2.281  0.02336 *
## AtBat       -2.01116    0.62016  -3.243  0.00134 **
## Hits        8.28040    1.95398   4.238 3.15e-05 ***
## Walks       6.47059    1.38568   4.670 4.87e-06 ***
## DivisionW  -120.43396   46.83854  -2.571  0.01070 *
## PutOuts     0.26542    0.08795   3.018  0.00280 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 376.3 on 257 degrees of freedom
## Multiple R-squared:  0.3176, Adjusted R-squared:  0.3043
## F-statistic: 23.92 on 5 and 257 DF,  p-value: < 2.2e-16

# Full Model, 6 predictors

lm.full <- lm(Salary ~ AtBat + Hits + Walks + Division + PutOuts + Errors,
              data = Hitters)

summary(lm.full) # Take a look

##
## Call:
## lm(formula = Salary ~ AtBat + Hits + Walks + Division + PutOuts +
##     Errors, data = Hitters)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -875.38 -208.93  -61.53   186.63 1980.81
##
## Coefficients:
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept) 183.51751   76.18550   2.409  0.01671 *
## AtBat       -1.79757    0.64097  -2.804  0.00543 **
## Hits        7.90088    1.97334   4.004 8.17e-05 ***
## Walks       6.15433    1.40529   4.379 1.74e-05 ***
## DivisionW  -120.78703   46.77802  -2.582  0.01038 *
## PutOuts     0.26459    0.08784   3.012  0.00285 **
## Errors     -4.93036    3.81042  -1.294  0.19686
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 375.8 on 256 degrees of freedom
## Multiple R-squared:  0.322, Adjusted R-squared:  0.3061
## F-statistic: 20.27 on 6 and 256 DF,  p-value: < 2.2e-16
```

Now, let's use the `anova()` function to compare the models with **F-Test**. You can test these models in any order, but the convention is to go from smaller to larger model in the `anova()` function.


```
anova(lm.reduced, lm.large, lm.full)

## Analysis of Variance Table
##
## Model 1: Salary ~ AtBat + Hits + Walks
## Model 2: Salary ~ AtBat + Hits + Walks + Division + PutOuts
## Model 3: Salary ~ AtBat + Hits + Walks + Division + PutOuts + Errors
##   Res.Df      RSS Df Sum of Sq      F      Pr(>F)
## 1      259 38613147
## 2      257 36385237  2   2227910 7.8888 0.0004735 ***
## 3      256 36148827  1    236409 1.6742 0.1968614
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

The ANOVA output above compares 3 models. But the comparisons are pairwise. That is, there are only 2 comparisons. The first line simply shows the degrees of freedom and residual sum of squares of the first model. Line 2 has the first comparison between **lm.reduced** and **lm.large**. The F-statistic in this comparison is 7.88, which translates to a significant p-value = 0.00047. This means that the large model has more explanatory power than the reduced model and this difference is significant. Line 3 has the second comparison between **lm.large** and **lm.full**. The F-statistic is quite small at 1.674 and the p-value = 0.196 is not significant. The full model still has more explanatory power than the large model because it has more predictors, but the difference is not significant, so we retain the simpler large model. That is, the added size and complexity of the full model is not beneficial.

One important thing to note is that if the `anova()` test is significant, the added predictors will be significant too. Conversely, if the `anova()` test is not significant, the added predictors will not be significant either. This property is the foundation for the Step methods, which I discuss next.

Step Methods

Step methods are excellent for exploration when you don't have pre-selected subsets you would like to test. It is important to note that Step methods are no replacement for sound predictor selection from business domain familiarity, but they are very useful when the number of candidate predictors is quite large. For example, if you have 20 candidate predictors, there are $2^{20} = 1,048,576$ possible models, which is practically unfeasible to fully compare. For this purpose, we use the convenient `step()` function, which is included in the **{stats}** package that loads by default when you start R, which works with both `lm()` (OLS) and `glm()` (GLM) models. Let's illustrate its use with the **Hitters** baseball player data contained in the **{ISLR}** package.

There are three types of Step methods: forward, backward and stepwise (i.e., both). In all of these methods, there is a lower bound and an upper bound model. The Step method will add and remove predictors. The lower bound model is the minimum and thus the mandatory set of predictors to include in the model. I often use the Null model (i.e., no predictors) for the lower bound, but if there are a few predictors that you must include in the model, you can set the lower bound to some Small model that includes those predictors only. For the upper bound, you can use the Full model that contains all the candidate predictors you identified.

Let's start by specifying the lower and upper bound models

```
library(ISLR) # Contains the Hitters data set
options(scipen = 4) # To minimize the display of scientific notation
```

Lower bound model:

```
Hitters.null <- lm(Salary ~ 1, data = Hitters) # No predictors
```

```
summary(Hitters.null) # Take a look
```

```
##
## Call:
## lm(formula = Salary ~ 1, data = Hitters)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -468.4  -345.9  -110.9   214.1  1924.1
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    535.93      27.82   19.27  <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 451.1 on 262 degrees of freedom
```

Upper bound model:

```
Hitters.full <- lm(Salary ~ ., data = Hitters) # All predictors
```

```
summary(Hitters.full) # Take a look
```

```
##
## Call:
## lm(formula = Salary ~ ., data = Hitters)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -907.62  -178.35  -31.11   139.09  1877.04
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  163.10359   90.77854    1.797  0.073622 .
## AtBat        -1.97987    0.63398   -3.123  0.002008 **
## Hits          7.50077    2.37753    3.155  0.001808 **
## HmRun         4.33088    6.20145    0.698  0.485616
## Runs        -2.37621    2.98076   -0.797  0.426122
## RBI          -1.04496    2.60088   -0.402  0.688204
## Walks         6.23129    1.82850    3.408  0.000766 ***
```

```
## Years          -3.48905    12.41219   -0.281  0.778874
## CAtBat         -0.17134     0.13524   -1.267  0.206380
## CHits           0.13399     0.67455    0.199  0.842713
## CHmRun         -0.17286     1.61724   -0.107  0.914967
## CRuns           1.45430     0.75046    1.938  0.053795 .
## CRBI            0.80771     0.69262    1.166  0.244691
## CWalks         -0.81157     0.32808   -2.474  0.014057 *
## LeagueN        62.59942    79.26140    0.790  0.430424
## DivisionW     -116.84925    40.36695   -2.895  0.004141 **
## PutOuts         0.28189     0.07744    3.640  0.000333 ***
## Assists         0.37107     0.22120    1.678  0.094723 .
## Errors         -3.36076     4.39163   -0.765  0.444857
## NewLeagueN    -24.76233     79.00263   -0.313  0.754218
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 315.6 on 243 degrees of freedom
## Multiple R-squared:  0.5461, Adjusted R-squared:  0.5106
## F-statistic: 15.39 on 19 and 243 DF,  p-value: < 2.2e-16
```

A solution with any of the Step methods will yield a model in between the lower and upper bound models. The `step()` function can be set to perform forward, backward and stepwise variable selection between the two models.

The inclusion and exclusion p-value thresholds are $p < 0.15$ by default. This means that predictors will only be added to the model if they are significant at the $p < 0.15$ level and will only be removed if their p-values are greater than 0.15. This default can be changed as needed with the parameter `k`. The default is `k = 2`, which is approximately equivalent to $p < 0.15$. If you want lower significance levels you can use higher values of `k`. For example, `k = 2.7` yields approximately $p < 0.10$. To find exactly how `k` relates to p-values, you can use the chi-square distribution function `qchisq()`:

```
qchisq(0.01, 1, lower.tail = F) # the k value for p < 0.01 is 6.634
```

```
## [1] 6.634897
```

```
qchisq(0.05, 1, lower.tail = F) # the k value for p < 0.05 is 3.841
```

```
## [1] 3.841459
```

```
qchisq(0.10, 1, lower.tail = F) # the k value for p < 0.10 is 2.705
```

```
## [1] 2.705543
```

```
qchisq(0.15, 1, lower.tail = F) # the k value for p < 0.15 is 2.072
```

```
## [1] 2.072251
```

Because Step methods are exploratory in nature, there is no particular reason to change the default `k` value, as you will be able to observe the significance level of each predictor included. Nevertheless, you can use p-values smaller than 0.15 or `k` values higher than 2 to obtain smaller models, or use larger p-values or smaller `k` values to obtain larger models.

Forward Selection

To run a forward step variable selection use the lower and upper bound models in the `scope =` parameter using the `list()` function (i.e., the scope is passed to the `step()` function as a list object). The first model entered in the `step()` function is the starting point in the variable selection process. Since we are using the forward method, the starting point must be the **Null** model because we will only be adding predictors. We also need to use the `direction = "forward"` parameter, which will cause the `step()` function to only add predictors. Finally, we need to include the `test = F` parameter, which will cause the `step()` function to evaluate the inclusion of predictors based on the significance p-value of the added predictor, which is equivalent to an F-test. Otherwise, the default comparison criteria is the AIC (Akaike's Information Criterion), which is a generic statistic of predictive accuracy. You should get similar results, but the F-test is more robust.

```
Hitters.fwd <- step(Hitters.null,
  scope = list(lower = Hitters.null,
               upper = Hitters.full),
  direction = "forward",
  test = "F")

## Start:  AIC=3215.77
## Salary ~ 1
##
##           Df Sum of Sq      RSS      AIC  F value    Pr(>F)
## + CRBI      1  17139434 36179679 3115.8 123.6438 < 2.2e-16 ***
## + CRuns      1  16881162 36437951 3117.6 120.9174 < 2.2e-16 ***
## + CHits      1  16065140 37253973 3123.5 112.5518 < 2.2e-16 ***
## + CAtBat     1  14759710 38559403 3132.5  99.9052 < 2.2e-16 ***
## + CHmRun     1  14692193 38626920 3133.0  99.2744 < 2.2e-16 ***
## + CWalks     1  12792622 40526491 3145.6  82.3874 < 2.2e-16 ***
## + RBI        1  10771083 42548030 3158.4  66.0725 1.757e-14 ***
## + Walks      1  10504833 42814280 3160.1  64.0385 4.014e-14 ***
## + Hits       1  10260491 43058621 3161.6  62.1940 8.531e-14 ***
## + Runs       1   9399158 43919955 3166.8  55.8557 1.180e-12 ***
## + Years      1   8559105 44760007 3171.7  49.9090 1.463e-11 ***
## + AtBat      1   8309469 45009644 3173.2  48.1846 3.065e-11 ***
## + HmRun      1   6273967 47045145 3184.8  34.8071 1.125e-08 ***
## + PutOuts    1   4814100 48505013 3192.9  25.9041 6.871e-07 ***
## + Division   1   1976102 51343011 3207.8  10.0454 0.001709 **
## <none>                53319113 3215.8
## + Assists    1    34497 53284615 3217.6   0.1690 0.681361
## + League     1    10876 53308237 3217.7   0.0532 0.817687
## + Errors     1     1555 53317558 3217.8   0.0076 0.930538
## + NewLeague  1      428 53318684 3217.8   0.0021 0.963511
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3115.78
## Salary ~ CRBI
##
##           Df Sum of Sq      RSS      AIC  F value    Pr(>F)
```

```

## + Hits      1  5533119 30646560 3074.1 46.9420 5.275e-11 ***
## + Runs      1  5176532 31003147 3077.2 43.4117 2.450e-10 ***
## + Walks     1  4199733 31979946 3085.3 34.1442 1.526e-08 ***
## + AtBat     1  4064585 32115095 3086.4 32.9064 2.681e-08 ***
## + RBI       1  3308272 32871407 3092.6 26.1671 6.085e-07 ***
## + PutOuts   1  3267035 32912644 3092.9 25.8086 7.204e-07 ***
## + Division  1  1733887 34445793 3104.9 13.0875 0.0003571 ***
## + Years     1  1667339 34512340 3105.4 12.5610 0.0004669 ***
## + HmRun     1  1271587 34908092 3108.4  9.4709 0.0023108 **
## + CRuns     1   354561 35825119 3115.2  2.5732 0.1099006
## + Assists   1   346020 35833659 3115.2  2.5106 0.1142958
## <none>             36179679 3115.8
## + Errors    1   194403 35985276 3116.4  1.4046 0.2370372
## + CAtBat    1    92261 36087418 3117.1  0.6647 0.4156463
## + CHits     1    75469 36104210 3117.2  0.5435 0.4616584
## + CWalks    1    51974 36127705 3117.4  0.3740 0.5413451
## + NewLeague 1    17778 36161901 3117.7  0.1278 0.7209896
## + League    1    11825 36167855 3117.7  0.0850 0.7708606
## + CHmRun    1     515 36179165 3117.8  0.0037 0.9515485
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3074.13
## Salary ~ CRBI + Hits
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## + PutOuts   1  1397263 29249297 3063.8 12.3726 0.0005143 ***
## + Division  1  1279275 29367285 3064.9 11.2824 0.0009002 ***
## + AtBat     1   821767 29824793 3069.0  7.1363 0.0080327 **
## + Walks     1   781767 29864793 3069.3  6.7798 0.0097516 **
## + Years     1   254910 30391650 3073.9  2.1724 0.1417246
## <none>             30646560 3074.1
## + League    1   208880 30437680 3074.3  1.7774 0.1836405
## + CRuns     1   132614 30513946 3075.0  1.1256 0.2897011
## + NewLeague 1   118474 30528086 3075.1  1.0051 0.3170083
## + Runs      1   114198 30532362 3075.1  0.9687 0.3259179
## + Errors    1    99776 30546784 3075.3  0.8460 0.3585477
## + CAtBat    1    83517 30563043 3075.4  0.7077 0.4009684
## + Assists   1    44781 30601779 3075.7  0.3790 0.5386742
## + CWalks    1    23668 30622892 3075.9  0.2002 0.6549532
## + CHmRun    1     4790 30641769 3076.1  0.0405 0.8406802
## + CHits     1     4358 30642202 3076.1  0.0368 0.8479531
## + HmRun     1     2173 30644387 3076.1  0.0184 0.8923043
## + RBI       1     1137 30645423 3076.1  0.0096 0.9219997
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3063.85
## Salary ~ CRBI + Hits + PutOuts
##

```

```

##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## + Division    1   1278445 27970852 3054.1 11.7922 0.0006928 ***
## + AtBat       1   1009933 28239364 3056.6  9.2269 0.0026294 **
## + Walks       1    539490 28709807 3061.0  4.8481 0.0285617 *
## + CRuns       1    273649 28975648 3063.4  2.4366 0.1197606
## <none>                29249297 3063.8
## + Years       1    136906 29112391 3064.6  1.2133 0.2717085
## + League      1    122841 29126456 3064.8  1.0881 0.2978655
## + Runs        1    117930 29131367 3064.8  1.0444 0.3077496
## + Errors      1     97244 29152053 3065.0  0.8606 0.3544307
## + NewLeague   1     57839 29191458 3065.3  0.5112 0.4752699
## + CHits       1    35096 29214201 3065.5  0.3099 0.5781973
## + RBI         1    33965 29215331 3065.6  0.2999 0.5843887
## + HmRun       1    31227 29218070 3065.6  0.2757 0.5999583
## + CWalks      1    28572 29220725 3065.6  0.2523 0.6159089
## + CAtBat      1    20518 29228779 3065.7  0.1811 0.6707739
## + Assists     1     1681 29247616 3065.8  0.0148 0.9031641
## + CHmRun      1     1419 29247878 3065.8  0.0125 0.9109989
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:   AIC=3054.1
## Salary ~ CRBI + Hits + PutOuts + Division
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## + AtBat       1    820952 27149899 3048.3  7.7711 0.005705 **
## + Walks       1    491584 27479268 3051.4  4.5975 0.032956 *
## <none>                27970852 3054.1
## + CRuns       1    193604 27777248 3054.3  1.7913 0.181956
## + Years       1    166845 27804007 3054.5  1.5422 0.215424
## + League      1    110628 27860224 3055.1  1.0205 0.313351
## + Errors      1     81385 27889467 3055.3  0.7500 0.387296
## + Runs        1     65921 27904931 3055.5  0.6071 0.436592
## + RBI         1     53719 27917133 3055.6  0.4945 0.482553
## + NewLeague   1     52275 27918577 3055.6  0.4812 0.488502
## + CHits       1    33863 27936989 3055.8  0.3115 0.577240
## + HmRun       1    26390 27944462 3055.8  0.2427 0.622679
## + CAtBat      1    18751 27952101 3055.9  0.1724 0.678330
## + CWalks      1     5723 27965129 3056.0  0.0526 0.818791
## + Assists     1     1036 27969816 3056.1  0.0095 0.922368
## + CHmRun      1      165 27970687 3056.1  0.0015 0.968952
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:   AIC=3048.26
## Salary ~ CRBI + Hits + PutOuts + Division + AtBat
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## + Walks       1    954996 26194904 3040.8  9.3331 0.002488 **
## + Years       1    253362 26896537 3047.8  2.4115 0.121683

```

```

## + Runs      1      208743 26941157 3048.2  1.9835 0.160234
## <none>              27149899 3048.3
## + CRuns      1      185825 26964075 3048.5  1.7642 0.185279
## + League      1       95986 27053913 3049.3  0.9083 0.341471
## + NewLeague   1       52693 27097206 3049.8  0.4978 0.481101
## + CHmRun      1      43173 27106726 3049.8  0.4077 0.523692
## + Assists     1      28898 27121001 3050.0  0.2728 0.601926
## + CAtBat      1      20989 27128910 3050.1  0.1981 0.656665
## + CWalks      1      15599 27134301 3050.1  0.1472 0.701576
## + Errors      1       6265 27143634 3050.2  0.0591 0.808137
## + CHits       1       5305 27144594 3050.2  0.0500 0.823180
## + RBI         1       1236 27148663 3050.2  0.0117 0.914099
## + HmRun       1         11 27149888 3050.3  0.0001 0.991729
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3040.85
## Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks
##
##           Df Sum of Sq      RSS      AIC F value Pr(>F)
## + CWalks    1      240687 25954217 3040.4  2.3647 0.1253
## <none>              26194904 3040.8
## + Years     1      184508 26010396 3041.0  1.8089 0.1798
## + CRuns     1      110695 26084209 3041.7  1.0822 0.2992
## + League    1       77974 26116930 3042.1  0.7613 0.3837
## + Assists   1       75782 26119122 3042.1  0.7399 0.3905
## + NewLeague 1       40909 26153995 3042.4  0.3989 0.5282
## + CHits     1       37304 26157599 3042.5  0.3637 0.5470
## + RBI       1       11728 26183176 3042.7  0.1142 0.7357
## + HmRun     1        4747 26190157 3042.8  0.0462 0.8299
## + Errors    1        2727 26192177 3042.8  0.0266 0.8707
## + CAtBat    1        2630 26192274 3042.8  0.0256 0.8730
## + CHmRun    1         943 26193961 3042.8  0.0092 0.9237
## + Runs      1          37 26194867 3042.8  0.0004 0.9849
##
## Step:  AIC=3040.42
## Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks + CWalks
##
##           Df Sum of Sq      RSS      AIC F value  Pr(>F)
## + CRuns     1      794983 25159234 3034.2  8.0259 0.004981 **
## + CHits     1      273728 25680489 3039.6  2.7074 0.101122
## <none>              25954217 3040.4
## + Assists   1      138506 25815711 3041.0  1.3628 0.244155
## + CAtBat    1       89289 25864929 3041.5  0.8768 0.349959
## + RBI       1       86941 25867276 3041.5  0.8537 0.356382
## + League    1       77159 25877058 3041.6  0.7574 0.384977
## + Years     1       70126 25884091 3041.7  0.6881 0.407575
## + NewLeague 1       37807 25916410 3042.0  0.3705 0.543255
## + HmRun     1      33601 25920616 3042.1  0.3293 0.566603
## + CHmRun    1       9034 25945183 3042.3  0.0884 0.766406

```

```

## + Errors      1      6928 25947289 3042.3 0.0678 0.794746
## + Runs        1      82 25954135 3042.4 0.0008 0.977414
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3034.24
## Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks + CWalks +
##      CRuns
##
##              Df Sum of Sq      RSS      AIC F value Pr(>F)
## + CAtBat      1      345182 24814051 3032.6  3.5194 0.0618 .
## + Years       1      265068 24894165 3033.4  2.6939 0.1020
## <none>                25159234 3034.2
## + CHits       1      173215 24986019 3034.4  1.7539 0.1866
## + Assists     1      124676 25034558 3034.9  1.2600 0.2627
## + CHmRun      1       91728 25067505 3035.3  0.9258 0.3369
## + League      1       72985 25086248 3035.5  0.7361 0.3917
## + NewLeague   1      25244 25133990 3036.0  0.2541 0.6146
## + Runs        1      17700 25141534 3036.1  0.1781 0.6734
## + Errors      1       8531 25150703 3036.2  0.0858 0.7698
## + HmRun       1       2390 25156844 3036.2  0.0240 0.8769
## + RBI         1          0 25159234 3036.2  0.0000 0.9993
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3032.6
## Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks + CWalks +
##      CRuns + CAtBat
##
##              Df Sum of Sq      RSS      AIC F value  Pr(>F)
## + Assists     1      313650 24500402 3031.3  3.2261 0.07367 .
## <none>                24814051 3032.6
## + Runs        1      153499 24660553 3033.0  1.5686 0.21158
## + League      1      146017 24668034 3033.1  1.4917 0.22310
## + NewLeague   1       77209 24736842 3033.8  0.7866 0.37599
## + Years       1       47431 24766620 3034.1  0.4826 0.48788
## + CHits       1       47127 24766925 3034.1  0.4795 0.48928
## + Errors      1      43926 24770126 3034.1  0.4469 0.50443
## + HmRun       1      23132 24790919 3034.4  0.2351 0.62816
## + CHmRun      1      19917 24794134 3034.4  0.2024 0.65315
## + RBI         1      19027 24795024 3034.4  0.1934 0.66050
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3031.26
## Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks + CWalks +
##      CRuns + CAtBat + Assists
##
##              Df Sum of Sq      RSS      AIC F value Pr(>F)
## <none>                24500402 3031.3

```



```
## + League      1      113056 24387345 3032.0  1.1636 0.2818
## + Runs        1       75900 24424501 3032.4  0.7800 0.3780
## + NewLeague   1       64712 24435690 3032.6  0.6647 0.4157
## + CHits       1       37564 24462838 3032.8  0.3854 0.5353
## + Errors      1       35264 24465138 3032.9  0.3618 0.5481
## + Years       1       19883 24480519 3033.0  0.2039 0.6520
## + CHmRun      1        4356 24496046 3033.2  0.0446 0.8328
## + HmRun       1        1189 24499212 3033.2  0.0122 0.9122
## + RBI         1         359 24500043 3033.2  0.0037 0.9517
```

```
summary(Hitters.fwd)
```

```
##
## Call:
## lm(formula = Salary ~ CRBI + Hits + PutOuts + Division + AtBat +
##     Walks + CWalks + CRuns + CAtBat + Assists, data = Hitters)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -939.11 -176.87  -34.08   130.90  1910.55
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  162.53544    66.90784   2.429  0.015830 *
## CRBI          0.77431     0.20961   3.694  0.000271 ***
## Hits          6.91802     1.64665   4.201  0.0000369 ***
## PutOuts       0.29737     0.07444   3.995  0.0000850 ***
## DivisionW    -112.38006    39.21438  -2.866  0.004511 **
## AtBat        -2.16865     0.53630  -4.044  0.0000700 ***
## Walks         5.77322     1.58483   3.643  0.000327 ***
## CWalks       -0.83083     0.26359  -3.152  0.001818 **
## CRuns         1.40825     0.39040   3.607  0.000373 ***
## CAtBat       -0.13008     0.05550  -2.344  0.019858 *
## Assists       0.28317     0.15766   1.796  0.073673 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 311.8 on 252 degrees of freedom
## Multiple R-squared:  0.5405, Adjusted R-squared:  0.5223
## F-statistic: 29.64 on 10 and 252 DF,  p-value: < 2.2e-16
```

I cut the output above to limit the use of paper, but the `step()` outputs one model in each step, so that you can explore which variables entered the model when. In the first step of the output above you will notice two important things:

First, the predictors are ordered from smallest to largest p-value. These p-values are NOT the p-values in the model because initially there are no predictors in the Null model. Rather, these p-values indicate what the respective p-values will be if the predictor is added to the model.

Second, there is a $+$ symbol next to each predictor. This is NOT a coefficient sign. Rather, it is a symbol that indicates that the predictor is a candidate for inclusion in the model, thus the $+$. Because the first

step is the Null model, all predictors have a + symbol. Naturally, the first predictor in the output will be the first predictor to be added to the model, which in this case is **CRBI**, which will appear in the model output in the next step.

In the second step, you will notice that CRBI is no longer listed. This is so because it is already added to the model, so it is no longer a candidate for inclusion. You can also see that the model formula listed at the top of the step output includes **CRBI** in the model. Following the same logic, **Hits** will be the next predictor to be added to the model, and so on. You will notice in the very last step, that there are no more predictors with a p-value < 0.15, so no more predictors will be added to the model after this step and the process stops. The `summary()` function outputs the typical regression summary results.

Let's illustrate what happens when we increase k to 3.841. As you can see in the output below (cut to save paper), there are fewer predictors included because the p-value threshold is now 0.05. Notice that the all the final predictors included have a significance level of $p < 0.05$.

```
Hitters.fwd.3.8 <- step(Hitters.null,
                        scope = list(lower = Hitters.null,
                                     upper = Hitters.full),
                        direction = "forward",
                        test = "F",
                        k = 3.841)
```

```
## Start:  AIC=3217.61
## Salary ~ 1
##
##
```

	Df	Sum of Sq	RSS	AIC	F value	Pr(>F)
## + CRBI	1	17139434	36179679	3119.5	123.6438	< 2.2e-16 ***
## + CRuns	1	16881162	36437951	3121.3	120.9174	< 2.2e-16 ***
## + CHits	1	16065140	37253973	3127.2	112.5518	< 2.2e-16 ***
## + CAtBat	1	14759710	38559403	3136.2	99.9052	< 2.2e-16 ***
## + CHmRun	1	14692193	38626920	3136.7	99.2744	< 2.2e-16 ***
## + CWalks	1	12792622	40526491	3149.3	82.3874	< 2.2e-16 ***
## + RBI	1	10771083	42548030	3162.1	66.0725	1.757e-14 ***
## + Walks	1	10504833	42814280	3163.7	64.0385	4.014e-14 ***
## + Hits	1	10260491	43058621	3165.2	62.1940	8.531e-14 ***
## + Runs	1	9399158	43919955	3170.4	55.8557	1.180e-12 ***
## + Years	1	8559105	44760007	3175.4	49.9090	1.463e-11 ***
## + AtBat	1	8309469	45009644	3176.9	48.1846	3.065e-11 ***
## + HmRun	1	6273967	47045145	3188.5	34.8071	1.125e-08 ***
## + PutOuts	1	4814100	48505013	3196.6	25.9041	6.871e-07 ***
## + Division	1	1976102	51343011	3211.5	10.0454	0.001709 **
## <none>			53319113	3217.6		
## + Assists	1	34497	53284615	3221.3	0.1690	0.681361
## + League	1	10876	53308237	3221.4	0.0532	0.817687
## + Errors	1	1555	53317558	3221.4	0.0076	0.930538
## + NewLeague	1	428	53318684	3221.4	0.0021	0.963511

```
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3119.46
## Salary ~ CRBI
```

```
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## + Hits      1   5533119 30646560 3079.7 46.9420 5.275e-11 ***
## + Runs      1   5176532 31003147 3082.7 43.4117 2.450e-10 ***
## + Walks     1   4199733 31979946 3090.8 34.1442 1.526e-08 ***
## + AtBat     1   4064585 32115095 3092.0 32.9064 2.681e-08 ***
## + RBI       1   3308272 32871407 3098.1 26.1671 6.085e-07 ***
## + PutOuts   1   3267035 32912644 3098.4 25.8086 7.204e-07 ***
## + Division  1   1733887 34445793 3110.4 13.0875 0.0003571 ***
## + Years     1   1667339 34512340 3110.9 12.5610 0.0004669 ***
## + HmRun     1   1271587 34908092 3113.9  9.4709 0.0023108 **
## <none>                36179679 3119.5
## + CRuns     1    354561 35825119 3120.7  2.5732 0.1099006
## + Assists   1    346020 35833659 3120.8  2.5106 0.1142958
## + Errors    1    194403 35985276 3121.9  1.4046 0.2370372
## + CAtBat    1     92261 36087418 3122.6  0.6647 0.4156463
## + CHits     1     75469 36104210 3122.8  0.5435 0.4616584
## + CWalks    1     51974 36127705 3122.9  0.3740 0.5413451
## + NewLeague 1     17778 36161901 3123.2  0.1278 0.7209896
## + League    1     11825 36167855 3123.2  0.0850 0.7708606
## + CHmRun    1        515 36179165 3123.3  0.0037 0.9515485
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:   AIC=3079.65
## Salary ~ CRBI + Hits
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## + PutOuts   1   1397263 29249297 3071.2 12.3726 0.0005143 ***
## + Division  1   1279275 29367285 3072.3 11.2824 0.0009002 ***
## + AtBat     1    821767 29824793 3076.3  7.1363 0.0080327 **
## + Walks     1    781767 29864793 3076.7  6.7798 0.0097516 **
## <none>                30646560 3079.7
## + Years     1    254910 30391650 3081.3  2.1724 0.1417246
## + League    1    208880 30437680 3081.7  1.7774 0.1836405
## + CRuns     1    132614 30513946 3082.3  1.1256 0.2897011
## + NewLeague 1    118474 30528086 3082.5  1.0051 0.3170083
## + Runs      1    114198 30532362 3082.5  0.9687 0.3259179
## + Errors    1     99776 30546784 3082.6  0.8460 0.3585477
## + CAtBat    1     83517 30563043 3082.8  0.7077 0.4009684
## + Assists   1     44781 30601779 3083.1  0.3790 0.5386742
## + CWalks    1     23668 30622892 3083.3  0.2002 0.6549532
## + CHmRun    1      4790 30641769 3083.4  0.0405 0.8406802
## + CHits     1      4358 30642202 3083.4  0.0368 0.8479531
## + HmRun     1      2173 30644387 3083.5  0.0184 0.8923043
## + RBI       1       1137 30645423 3083.5  0.0096 0.9219997
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:   AIC=3071.22
```

```

## Salary ~ CRBI + Hits + PutOuts
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## + Division  1   1278445 27970852 3063.3 11.7922 0.0006928 ***
## + AtBat     1   1009933 28239364 3065.8  9.2269 0.0026294 **
## + Walks     1    539490 28709807 3070.2  4.8481 0.0285617 *
## <none>                        29249297 3071.2
## + CRuns     1    273649 28975648 3072.6  2.4366 0.1197606
## + Years     1    136906 29112391 3073.8  1.2133 0.2717085
## + League    1    122841 29126456 3073.9  1.0881 0.2978655
## + Runs      1    117930 29131367 3074.0  1.0444 0.3077496
## + Errors    1     97244 29152053 3074.2  0.8606 0.3544307
## + NewLeague 1     57839 29191458 3074.5  0.5112 0.4752699
## + CHits     1    35096 29214201 3074.7  0.3099 0.5781973
## + RBI       1    33965 29215331 3074.8  0.2999 0.5843887
## + HmRun     1    31227 29218070 3074.8  0.2757 0.5999583
## + CWalks    1    28572 29220725 3074.8  0.2523 0.6159089
## + CAtBat    1    20518 29228779 3074.9  0.1811 0.6707739
## + Assists   1     1681 29247616 3075.0  0.0148 0.9031641
## + CHmRun    1     1419 29247878 3075.1  0.0125 0.9109989
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3063.3
## Salary ~ CRBI + Hits + PutOuts + Division
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## + AtBat     1    820952 27149899 3059.3  7.7711 0.005705 **
## + Walks     1    491584 27479268 3062.5  4.5975 0.032956 *
## <none>                        27970852 3063.3
## + CRuns     1    193604 27777248 3065.3  1.7913 0.181956
## + Years     1    166845 27804007 3065.6  1.5422 0.215424
## + League    1    110628 27860224 3066.1  1.0205 0.313351
## + Errors    1     81385 27889467 3066.4  0.7500 0.387296
## + Runs      1     65921 27904931 3066.5  0.6071 0.436592
## + RBI       1     53719 27917133 3066.6  0.4945 0.482553
## + NewLeague 1     52275 27918577 3066.7  0.4812 0.488502
## + CHits     1    33863 27936989 3066.8  0.3115 0.577240
## + HmRun     1    26390 27944462 3066.9  0.2427 0.622679
## + CAtBat    1    18751 27952101 3067.0  0.1724 0.678330
## + CWalks    1     5723 27965129 3067.1  0.0526 0.818791
## + Assists   1     1036 27969816 3067.1  0.0095 0.922368
## + CHmRun    1      165 27970687 3067.1  0.0015 0.968952
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3059.31
## Salary ~ CRBI + Hits + PutOuts + Division + AtBat
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)

```

```

## + Walks      1      954996 26194904 3053.7  9.3331 0.002488 **
## <none>                27149899 3059.3
## + Years      1      253362 26896537 3060.7  2.4115 0.121683
## + Runs       1      208743 26941157 3061.1  1.9835 0.160234
## + CRuns      1      185825 26964075 3061.3  1.7642 0.185279
## + League     1       95986 27053913 3062.2  0.9083 0.341471
## + NewLeague  1       52693 27097206 3062.6  0.4978 0.481101
## + CHmRun     1       43173 27106726 3062.7  0.4077 0.523692
## + Assists    1      28898 27121001 3062.9  0.2728 0.601926
## + CAtBat     1      20989 27128910 3062.9  0.1981 0.656665
## + CWalks     1      15599 27134301 3063.0  0.1472 0.701576
## + Errors     1       6265 27143634 3063.1  0.0591 0.808137
## + CHits      1       5305 27144594 3063.1  0.0500 0.823180
## + RBI        1       1236 27148663 3063.1  0.0117 0.914099
## + HmRun      1        11 27149888 3063.2  0.0001 0.991729
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3053.73
## Salary ~ CRBI + Hits + PutOuts + Division + AtBat + Walks
##
##              Df Sum of Sq      RSS      AIC F value Pr(>F)
## <none>                26194904 3053.7
## + CWalks      1      240687 25954217 3055.2  2.3647 0.1253
## + Years       1      184508 26010396 3055.7  1.8089 0.1798
## + CRuns       1      110695 26084209 3056.5  1.0822 0.2992
## + League      1       77974 26116930 3056.8  0.7613 0.3837
## + Assists     1       75782 26119122 3056.8  0.7399 0.3905
## + NewLeague   1       40909 26153995 3057.2  0.3989 0.5282
## + CHits       1       37304 26157599 3057.2  0.3637 0.5470
## + RBI         1       11728 26183176 3057.5  0.1142 0.7357
## + HmRun       1        4747 26190157 3057.5  0.0462 0.8299
## + Errors      1        2727 26192177 3057.6  0.0266 0.8707
## + CAtBat      1        2630 26192274 3057.6  0.0256 0.8730
## + CHmRun      1         943 26193961 3057.6  0.0092 0.9237
## + Runs        1          37 26194867 3057.6  0.0004 0.9849

```

```
summary(Hitters.fwd.3.8)
```

```

##
## Call:
## lm(formula = Salary ~ CRBI + Hits + PutOuts + Division + AtBat +
##     Walks, data = Hitters)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -873.11 -181.72  -25.91  141.77 2040.47
##
## Coefficients:

```

```
##           Estimate Std. Error t value    Pr(>|t|)
## (Intercept)   91.51180    65.00006    1.408    0.160382
## CRBI          0.64302     0.06443    9.979    < 2e-16 ***
## Hits          7.60440     1.66254    4.574 0.00000746 ***
## PutOuts       0.26431     0.07477    3.535    0.000484 ***
## DivisionW    -122.95153   39.82029   -3.088    0.002239 **
## AtBat        -1.86859     0.52742   -3.543    0.000470 ***
## Walks         3.69765     1.21036    3.055    0.002488 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 319.9 on 256 degrees of freedom
## Multiple R-squared:  0.5087, Adjusted R-squared:  0.4972
## F-statistic: 44.18 on 6 and 256 DF,  p-value: < 2.2e-16
```

Backward Selection

Backward selection works just like forward selection, with the same lower and upper bound models, but this time the starting model must be the Full model because we can only remove predictors. We also need to change the attribute `direction` = to "backward". This will cause the process to proceed in a backward fashion. Just like in the forward process, the default k value is 2, which is approximately equivalent to $p < 0.15$. This means that any predictor that is not significant at the $p < 0.15$ level will be removed from the model. One more difference is that there is a - symbol next to each predictor, rather than +. This is so because predictors are candidates for removal, as there is no addition in backward step. The predictors are listed from least to most significance, so the first predictor to be removed is always the first one at the top.

```
Hitters.back <- step(Hitters.full,
                     scope = list(lower = Hitters.null,
                                   upper = Hitters.full),
                     direction = "backward",
                     test = "F")

## Start:  AIC=3046.02
## Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + Years +
##          CAtBat + CHits + CHmRun + CRuns + CRBI + CWalks + League +
##          Division + PutOuts + Assists + Errors + NewLeague
##
##           Df Sum of Sq    RSS    AIC F value    Pr(>F)
## - CHmRun     1      1138 24201837 3044.0  0.0114 0.9149671
## - CHits       1      3930 24204629 3044.1  0.0395 0.8427129
## - Years       1      7869 24208569 3044.1  0.0790 0.7788736
## - NewLeague   1      9784 24210484 3044.1  0.0982 0.7542178
## - RBI         1     16076 24216776 3044.2  0.1614 0.6882042
## - HmRun       1     48572 24249272 3044.6  0.4877 0.4856158
## - Errors     1     58324 24259023 3044.7  0.5856 0.4448566
## - League     1     62121 24262821 3044.7  0.6238 0.4304236
## - Runs       1     63291 24263990 3044.7  0.6355 0.4261225
## - CRBI       1    135439 24336138 3045.5  1.3599 0.2446905
```

```

## - CAtBat      1      159864 24360564 3045.8  1.6052 0.2063804
## <none>                24200700 3046.0
## - Assists     1      280263 24480963 3047.1  2.8141 0.0947232 .
## - CRuns       1      374007 24574707 3048.1  3.7554 0.0537951 .
## - CWalks      1      609408 24810108 3050.6  6.1191 0.0140574 *
## - Division    1      834491 25035190 3052.9  8.3791 0.0041408 **
## - AtBat       1      971288 25171987 3054.4  9.7527 0.0020077 **
## - Hits        1      991242 25191941 3054.6  9.9531 0.0018082 **
## - Walks       1     1156606 25357305 3056.3 11.6135 0.0007662 ***
## - PutOuts     1     1319628 25520328 3058.0 13.2504 0.0003329 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3044.03
## Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + Years +
##          CAtBat + CHits + CRuns + CRBI + CWalks + League + Division +
##          PutOuts + Assists + Errors + NewLeague
##
##              Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - Years       1         7609 24209447 3042.1  0.0767 0.7820312
## - NewLeague   1         10268 24212106 3042.2  0.1035 0.7479165
## - CHits       1         14003 24215840 3042.2  0.1412 0.7074399
## - RBI         1         14955 24216793 3042.2  0.1508 0.6981310
## - HmRun       1         52777 24254614 3042.6  0.5321 0.4664293
## - Errors      1         59530 24261367 3042.7  0.6002 0.4392618
## - League      1         63407 24265244 3042.7  0.6393 0.4247563
## - Runs        1         64860 24266698 3042.7  0.6539 0.4195043
## - CAtBat      1        174992 24376830 3043.9  1.7643 0.1853360
## <none>                24201837 3044.0
## - Assists     1        285766 24487603 3045.1  2.8811 0.0909022 .
## - CRuns       1        611358 24813196 3048.6  6.1636 0.0137136 *
## - CWalks      1        645627 24847464 3049.0  6.5091 0.0113434 *
## - Division    1        834637 25036474 3050.9  8.4147 0.0040618 **
## - CRBI        1        864220 25066057 3051.3  8.7130 0.0034675 **
## - AtBat       1        970861 25172699 3052.4  9.7881 0.0019700 **
## - Hits        1       1025981 25227819 3052.9 10.3438 0.0014747 **
## - Walks       1       1167378 25369216 3054.4 11.7694 0.0007069 ***
## - PutOuts     1       1325273 25527110 3056.1 13.3612 0.0003145 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3042.12
## Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + CAtBat +
##          CHits + CRuns + CRBI + CWalks + League + Division + PutOuts +
##          Assists + Errors + NewLeague
##
##              Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - NewLeague   1         9931 24219377 3040.2  0.1005 0.7515016
## - RBI         1        15989 24225436 3040.3  0.1618 0.6878453
## - CHits       1        18291 24227738 3040.3  0.1851 0.6673978

```

```

## - HmRun      1      54144 24263591 3040.7  0.5479 0.4598692
## - Errors     1      57312 24266759 3040.7  0.5800 0.4470438
## - Runs       1      63172 24272619 3040.8  0.6393 0.4247368
## - League     1      65732 24275178 3040.8  0.6652 0.4155208
## <none>              24209447 3042.1
## - CAtBat     1      266205 24475652 3043.0  2.6940 0.1020097
## - Assists    1      293479 24502926 3043.3  2.9700 0.0860827 .
## - CRuns      1      646350 24855797 3047.1  6.5411 0.0111444 *
## - CWalks     1      649269 24858716 3047.1  6.5706 0.0109657 *
## - Division   1      827511 25036958 3049.0  8.3744 0.0041483 **
## - CRBI       1      872121 25081568 3049.4  8.8259 0.0032652 **
## - AtBat      1      968713 25178160 3050.4  9.8034 0.0019534 **
## - Hits       1     1018379 25227825 3050.9 10.3060 0.0015033 **
## - Walks      1     1164536 25373983 3052.5 11.7851 0.0007008 ***
## - PutOuts    1     1334525 25543972 3054.2 13.5054 0.0002922 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3040.22
## Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + CAtBat +
##          CHits + CRuns + CRBI + CWalks + League + Division + PutOuts +
##          Assists + Errors
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - RBI      1      15800 24235177 3038.4  0.1605 0.6890609
## - CHits     1      15859 24235237 3038.4  0.1611 0.6885064
## - Errors    1      54505 24273883 3038.8  0.5536 0.4575530
## - HmRun     1      54938 24274316 3038.8  0.5580 0.4557745
## - Runs      1      62294 24281671 3038.9  0.6327 0.4271242
## - League    1     107479 24326856 3039.4  1.0917 0.2971253
## <none>              24219377 3040.2
## - CAtBat    1      261336 24480713 3041.1  2.6544 0.1045418
## - Assists   1      295536 24514914 3041.4  3.0018 0.0844249 .
## - CWalks    1      648860 24868237 3045.2  6.5906 0.0108443 *
## - CRuns     1      661449 24880826 3045.3  6.7184 0.0101129 *
## - Division  1      824672 25044049 3047.0  8.3763 0.0041427 **
## - CRBI      1      880429 25099806 3047.6  8.9427 0.0030687 **
## - AtBat     1      999057 25218434 3048.9 10.1476 0.0016316 **
## - Hits      1     1034463 25253840 3049.2 10.5072 0.0013534 **
## - Walks     1     1157205 25376583 3050.5 11.7539 0.0007117 ***
## - PutOuts   1     1335173 25554550 3052.3 13.5616 0.0002838 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3038.4
## Salary ~ AtBat + Hits + HmRun + Runs + Walks + CAtBat + CHits +
##          CRuns + CRBI + CWalks + League + Division + PutOuts + Assists +
##          Errors
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)

```



```

## - CHits      1      13483 24248660 3036.5  0.1374 0.7111808
## - HmRun      1      44586 24279763 3036.9  0.4544 0.5008777
## - Runs       1      54057 24289234 3037.0  0.5509 0.4586413
## - Errors     1      57656 24292833 3037.0  0.5876 0.4440753
## - League     1     108644 24343821 3037.6  1.1073 0.2937034
## <none>              24235177 3038.4
## - CAtBat     1     252756 24487934 3039.1  2.5760 0.1097704
## - Assists    1     294674 24529851 3039.6  3.0033 0.0843456 .
## - CWalks     1     639690 24874868 3043.2  6.5196 0.0112712 *
## - CRuns      1     693535 24928712 3043.8  7.0684 0.0083583 **
## - Division   1     808984 25044161 3045.0  8.2450 0.0044412 **
## - CRBI       1     893830 25129008 3045.9  9.1097 0.0028087 **
## - Hits       1    1034884 25270061 3047.4 10.5473 0.0013249 **
## - AtBat      1    1042798 25277975 3047.5 10.6280 0.0012706 **
## - Walks      1    1145013 25380191 3048.5 11.6697 0.0007426 ***
## - PutOuts    1    1340713 25575890 3050.6 13.6643 0.0002693 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3036.54
## Salary ~ AtBat + Hits + HmRun + Runs + Walks + CAtBat + CRuns +
##          CRBI + CWalks + League + Division + PutOuts + Assists + Errors
##
##           Df Sum of Sq      RSS      AIC F value      Pr(>F)
## - HmRun      1      40487 24289148 3035.0  0.4141 0.5205005
## - Errors     1      51930 24300590 3035.1  0.5311 0.4668297
## - Runs       1      79343 24328003 3035.4  0.8115 0.3685611
## - League     1     114742 24363402 3035.8  1.1735 0.2797336
## <none>              24248660 3036.5
## - Assists    1     283442 24532103 3037.6  2.8989 0.0898946 .
## - CAtBat     1     613356 24862016 3041.1  6.2730 0.0129017 *
## - Division   1     801474 25050134 3043.1  8.1970 0.0045548 **
## - CRBI       1     903248 25151908 3044.2  9.2379 0.0026244 **
## - CWalks     1    1011953 25260613 3045.3 10.3496 0.0014674 **
## - Walks      1    1246164 25494824 3047.7 12.7450 0.0004286 ***
## - AtBat      1    1339620 25588280 3048.7 13.7008 0.0002641 ***
## - CRuns      1    1390808 25639469 3049.2 14.2243 0.0002029 ***
## - PutOuts    1    1406023 25654684 3049.4 14.3799 0.0001877 ***
## - Hits       1    1607990 25856650 3051.4 16.4455 0.00006709 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3034.98
## Salary ~ AtBat + Hits + Runs + Walks + CAtBat + CRuns + CRBI +
##          CWalks + League + Division + PutOuts + Assists + Errors
##
##           Df Sum of Sq      RSS      AIC F value      Pr(>F)
## - Errors     1      44085 24333232 3033.5  0.4519 0.5020421
## - Runs       1      49068 24338215 3033.5  0.5030 0.4788415
## - League     1     103837 24392985 3034.1  1.0645 0.3031961

```

```

## <none>                24289148 3035.0
## - Assists      1      247002 24536150 3035.6  2.5321  0.1128176
## - CAtBat       1      652746 24941894 3040.0  6.6916  0.0102549 *
## - Division     1      795643 25084791 3041.5  8.1565  0.0046527 **
## - CWalks       1      982896 25272044 3043.4 10.0761  0.0016911 **
## - Walks        1     1205823 25494971 3045.7 12.3615  0.0005206 ***
## - AtBat        1     1300972 25590120 3046.7 13.3369  0.0003172 ***
## - CRuns        1     1351200 25640348 3047.2 13.8518  0.0002446 ***
## - CRBI         1     1353507 25642655 3047.2 13.8755  0.0002417 ***
## - PutOuts      1     1429006 25718154 3048.0 14.6494  0.0001638 ***
## - Hits         1     1574140 25863288 3049.5 16.1373  0.00007806 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3033.46
## Salary ~ AtBat + Hits + Runs + Walks + CAtBat + CRuns + CRBI +
##         CWalks + League + Division + PutOuts + Assists
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - Runs      1      54113 24387345 3032.0  0.5560 0.4565953
## - League    1      91269 24424501 3032.4  0.9377 0.3338061
## <none>                24333232 3033.5
## - Assists   1     220010 24553242 3033.8  2.2604 0.1339832
## - CAtBat    1     650513 24983746 3038.4  6.6834 0.0102988 *
## - Division  1     799455 25132687 3040.0  8.2136 0.0045117 **
## - CWalks    1     971260 25304493 3041.8  9.9787 0.0017784 **
## - Walks     1    1239533 25572765 3044.5 12.7350 0.0004301 ***
## - CRBI      1    1331672 25664904 3045.5 13.6816 0.0002663 ***
## - CRuns     1    1361070 25694302 3045.8 13.9837 0.0002287 ***
## - AtBat     1    1378592 25711824 3045.9 14.1637 0.0002089 ***
## - PutOuts   1    1391660 25724892 3046.1 14.2979 0.0001952 ***
## - Hits      1    1649291 25982523 3048.7 16.9448 0.0000523 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3032.04
## Salary ~ AtBat + Hits + Walks + CAtBat + CRuns + CRBI + CWalks +
##         League + Division + PutOuts + Assists
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - League    1     113056 24500402 3031.3  1.1636 0.2817552
## <none>                24387345 3032.0
## - Assists   1     280689 24668034 3033.1  2.8889 0.0904298 .
## - CAtBat    1     596622 24983967 3036.4  6.1406 0.0138700 *
## - Division  1     780369 25167714 3038.3  8.0317 0.0049703 **
## - CWalks    1     946687 25334032 3040.1  9.7435 0.0020102 **
## - Walks     1    1212997 25600342 3042.8 12.4844 0.0004883 ***
## - CRuns     1    1334397 25721742 3044.1 13.7339 0.0002591 ***
## - CRBI      1    1361339 25748684 3044.3 14.0112 0.0002253 ***
## - PutOuts   1    1455210 25842555 3045.3 14.9774 0.0001388 ***

```

```
## - AtBat      1   1522760 25910105 3046.0 15.6726 0.00009811 ***
## - Hits       1   1718870 26106215 3047.9 17.6910 0.00003619 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3031.26
## Salary ~ AtBat + Hits + Walks + CAtBat + CRuns + CRBI + CWalks +
## Division + PutOuts + Assists
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## <none>                24500402 3031.3
## - Assists    1     313650 24814051 3032.6   3.2261 0.0736726 .
## - CAtBat     1     534156 25034558 3034.9   5.4941 0.0198584 *
## - Division   1     798473 25298875 3037.7   8.2127 0.0045109 **
## - CWalks     1     965875 25466276 3039.4   9.9345 0.0018183 **
## - CRuns      1    1265082 25765484 3042.5  13.0121 0.0003731 ***
## - Walks      1    1290168 25790569 3042.8  13.2701 0.0003274 ***
## - CRBI       1    1326770 25827172 3043.1  13.6466 0.0002706 ***
## - PutOuts    1    1551523 26051925 3045.4  15.9583 0.00008504 ***
## - AtBat      1    1589780 26090181 3045.8  16.3518 0.00006996 ***
## - Hits       1    1716068 26216469 3047.1  17.6507 0.00003686 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
summary(Hitters.back)
```

```
##
## Call:
## lm(formula = Salary ~ AtBat + Hits + Walks + CAtBat + CRuns +
## CRBI + CWalks + Division + PutOuts + Assists, data = Hitters)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -939.11 -176.87  -34.08   130.90  1910.55
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  162.53544   66.90784   2.429  0.015830 *
## AtBat        -2.16865    0.53630  -4.044 0.0000700 ***
## Hits         6.91802    1.64665   4.201 0.0000369 ***
## Walks        5.77322    1.58483   3.643 0.0003274 ***
## CAtBat       -0.13008    0.05550  -2.344 0.0198584 *
## CRuns        1.40825    0.39040   3.607 0.0003731 ***
## CRBI         0.77431    0.20961   3.694 0.0002711 ***
## CWalks      -0.83083    0.26359  -3.152 0.0018183 **
## DivisionW   -112.38006   39.21438  -2.866 0.0045111 **
## PutOuts      0.29737    0.07444   3.995 0.0000850 ***
## Assists      0.28317    0.15766   1.796 0.0736731 .
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 311.8 on 252 degrees of freedom
## Multiple R-squared:  0.5405, Adjusted R-squared:  0.5223
## F-statistic: 29.64 on 10 and 252 DF,  p-value: < 2.2e-16
```

Stepwise Selection

The stepwise selection process is very similar, except that predictors can be either added or removed from the model. Unless you change the default value of `k`, any predictor that is significant at the $p < 0.15$ level will be added, and any that is not will be removed. Another difference in each step is that you may now see either a $+$ or a $-$. As before, a $+$ denotes that the predictor is not in the model and, therefore, it is a candidate for inclusion. Similarly, a $-$ symbol denotes that the predictor is already in the model and, therefore, it is a candidate for removal.

Two other important differences are:

First, the **direction** attribute is set to `direction = "both"`, which will trigger the stepwise process of either adding or removing predictors; and

Second, the starting models can be either the Null or the Full model, your choice. If you choose the Null model, your first step will be to add predictors to the Null model in a forward fashion, which is the only direction you can go because there are no predictors in the Null model yet. If you choose the Full model, your first step will be to remove predictors from the Full model in a backward fashion. Again, that's the only direction possible. But after the first step, predictors may either be added or removed in every step. Let's illustrate this method. Notice that we start with the Full model, so our first step is backward. You can try starting with the Null model on your own, but my preference is to always start with the Full and least biased model. So, all predictors have a $-$ symbol at the beginning, but notice that there is a predictor with a $+$ in the second step, indicating that the predictor has already been removed, but it is now a candidate to be added back to the model.

```
Hitters.step <- step(Hitters.full,
                     scope = list(lower = Hitters.null,
                                   upper = Hitters.full),
                     direction = "both",
                     test = "F")
```

```
## Start:  AIC=3046.02
## Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + Years +
##      CAtBat + CHits + CHmRun + CRuns + CRBI + CWalks + League +
##      Division + PutOuts + Assists + Errors + NewLeague
##
##      Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - CHmRun      1      1138 24201837 3044.0   0.0114 0.9149671
## - CHits       1      3930 24204629 3044.1   0.0395 0.8427129
## - Years       1      7869 24208569 3044.1   0.0790 0.7788736
## - NewLeague   1      9784 24210484 3044.1   0.0982 0.7542178
## - RBI         1     16076 24216776 3044.2   0.1614 0.6882042
## - HmRun       1     48572 24249272 3044.6   0.4877 0.4856158
## - Errors      1     58324 24259023 3044.7   0.5856 0.4448566
## - League      1     62121 24262821 3044.7   0.6238 0.4304236
```

```

## - Runs      1      63291 24263990 3044.7  0.6355 0.4261225
## - CRBI      1     135439 24336138 3045.5  1.3599 0.2446905
## - CAtBat    1     159864 24360564 3045.8  1.6052 0.2063804
## <none>      24200700 3046.0
## - Assists   1     280263 24480963 3047.1  2.8141 0.0947232 .
## - CRuns     1     374007 24574707 3048.1  3.7554 0.0537951 .
## - CWalks    1     609408 24810108 3050.6  6.1191 0.0140574 *
## - Division  1     834491 25035190 3052.9  8.3791 0.0041408 **
## - AtBat     1     971288 25171987 3054.4  9.7527 0.0020077 **
## - Hits      1     991242 25191941 3054.6  9.9531 0.0018082 **
## - Walks     1    1156606 25357305 3056.3 11.6135 0.0007662 ***
## - PutOuts   1    1319628 25520328 3058.0 13.2504 0.0003329 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3044.03
## Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + Years +
##          CAtBat + CHits + CRuns + CRBI + CWalks + League + Division +
##          PutOuts + Assists + Errors + NewLeague
##
##          Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - Years      1      7609 24209447 3042.1  0.0767 0.7820312
## - NewLeague  1     10268 24212106 3042.2  0.1035 0.7479165
## - CHits       1     14003 24215840 3042.2  0.1412 0.7074399
## - RBI         1     14955 24216793 3042.2  0.1508 0.6981310
## - HmRun       1     52777 24254614 3042.6  0.5321 0.4664293
## - Errors      1     59530 24261367 3042.7  0.6002 0.4392618
## - League     1     63407 24265244 3042.7  0.6393 0.4247563
## - Runs       1     64860 24266698 3042.7  0.6539 0.4195043
## - CAtBat     1    174992 24376830 3043.9  1.7643 0.1853360
## <none>      24201837 3044.0
## - Assists    1    285766 24487603 3045.1  2.8811 0.0909022 .
## + CHmRun     1      1138 24200700 3046.0  0.0114 0.9149671
## - CRuns      1    611358 24813196 3048.6  6.1636 0.0137136 *
## - CWalks     1    645627 24847464 3049.0  6.5091 0.0113434 *
## - Division   1    834637 25036474 3050.9  8.4147 0.0040618 **
## - CRBI       1    864220 25066057 3051.3  8.7130 0.0034675 **
## - AtBat      1    970861 25172699 3052.4  9.7881 0.0019700 **
## - Hits       1   1025981 25227819 3052.9 10.3438 0.0014747 **
## - Walks      1   1167378 25369216 3054.4 11.7694 0.0007069 ***
## - PutOuts    1   1325273 25527110 3056.1 13.3612 0.0003145 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3042.12
## Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + CAtBat +
##          CHits + CRuns + CRBI + CWalks + League + Division + PutOuts +
##          Assists + Errors + NewLeague
##
##          Df Sum of Sq      RSS      AIC F value    Pr(>F)

```

```

## - NewLeague 1      9931 24219377 3040.2  0.1005 0.7515016
## - RBI        1      15989 24225436 3040.3  0.1618 0.6878453
## - CHits      1      18291 24227738 3040.3  0.1851 0.6673978
## - HmRun      1      54144 24263591 3040.7  0.5479 0.4598692
## - Errors    1      57312 24266759 3040.7  0.5800 0.4470438
## - Runs      1      63172 24272619 3040.8  0.6393 0.4247368
## - League    1      65732 24275178 3040.8  0.6652 0.4155208
## <none>              24209447 3042.1
## - CAtBat    1      266205 24475652 3043.0  2.6940 0.1020097
## - Assists   1      293479 24502926 3043.3  2.9700 0.0860827 .
## + Years     1         7609 24201837 3044.0  0.0767 0.7820312
## + CHmRun    1         878 24208569 3044.1  0.0088 0.9251371
## - CRuns     1      646350 24855797 3047.1  6.5411 0.0111444 *
## - CWalks    1      649269 24858716 3047.1  6.5706 0.0109657 *
## - Division  1      827511 25036958 3049.0  8.3744 0.0041483 **
## - CRBI      1      872121 25081568 3049.4  8.8259 0.0032652 **
## - AtBat     1      968713 25178160 3050.4  9.8034 0.0019534 **
## - Hits      1     1018379 25227825 3050.9 10.3060 0.0015033 **
## - Walks     1     1164536 25373983 3052.5 11.7851 0.0007008 ***
## - PutOuts   1     1334525 25543972 3054.2 13.5054 0.0002922 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3040.22
## Salary ~ AtBat + Hits + HmRun + Runs + RBI + Walks + CAtBat +
##          CHits + CRuns + CRBI + CWalks + League + Division + PutOuts +
##          Assists + Errors
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - RBI      1      15800 24235177 3038.4  0.1605 0.6890609
## - CHits    1      15859 24235237 3038.4  0.1611 0.6885064
## - Errors   1      54505 24273883 3038.8  0.5536 0.4575530
## - HmRun    1      54938 24274316 3038.8  0.5580 0.4557745
## - Runs     1      62294 24281671 3038.9  0.6327 0.4271242
## - League   1     107479 24326856 3039.4  1.0917 0.2971253
## <none>              24219377 3040.2
## - CAtBat   1      261336 24480713 3041.1  2.6544 0.1045418
## - Assists  1      295536 24514914 3041.4  3.0018 0.0844249 .
## + NewLeague 1         9931 24209447 3042.1  0.1005 0.7515016
## + Years    1         7272 24212106 3042.2  0.0736 0.7864187
## + CHmRun   1         1307 24218070 3042.2  0.0132 0.9085489
## - CWalks   1      648860 24868237 3045.2  6.5906 0.0108443 *
## - CRuns    1      661449 24880826 3045.3  6.7184 0.0101129 *
## - Division 1      824672 25044049 3047.0  8.3763 0.0041427 **
## - CRBI     1      880429 25099806 3047.6  8.9427 0.0030687 **
## - AtBat    1      999057 25218434 3048.9 10.1476 0.0016316 **
## - Hits     1     1034463 25253840 3049.2 10.5072 0.0013534 **
## - Walks    1     1157205 25376583 3050.5 11.7539 0.0007117 ***
## - PutOuts  1     1335173 25554550 3052.3 13.5616 0.0002838 ***
## ---

```

```

## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3038.4
## Salary ~ AtBat + Hits + HmRun + Runs + Walks + CAtBat + CHits +
##      CRuns + CRBI + CWalks + League + Division + PutOuts + Assists +
##      Errors
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - CHits      1      13483 24248660 3036.5   0.1374 0.7111808
## - HmRun       1      44586 24279763 3036.9   0.4544 0.5008777
## - Runs        1      54057 24289234 3037.0   0.5509 0.4586413
## - Errors      1      57656 24292833 3037.0   0.5876 0.4440753
## - League     1     108644 24343821 3037.6   1.1073 0.2937034
## <none>                24235177 3038.4
## - CAtBat      1     252756 24487934 3039.1   2.5760 0.1097704
## - Assists     1     294674 24529851 3039.6   3.0033 0.0843456 .
## + RBI         1      15800 24219377 3040.2   0.1605 0.6890609
## + NewLeague   1       9741 24225436 3040.3   0.0989 0.7533960
## + Years       1       8280 24226897 3040.3   0.0841 0.7720891
## + CHmRun      1          9 24235168 3040.4   0.0001 0.9922301
## - CWalks      1     639690 24874868 3043.2   6.5196 0.0112712 *
## - CRuns       1     693535 24928712 3043.8   7.0684 0.0083583 **
## - Division    1     808984 25044161 3045.0   8.2450 0.0044412 **
## - CRBI        1     893830 25129008 3045.9   9.1097 0.0028087 **
## - Hits        1    1034884 25270061 3047.4  10.5473 0.0013249 **
## - AtBat       1    1042798 25277975 3047.5  10.6280 0.0012706 **
## - Walks       1    1145013 25380191 3048.5  11.6697 0.0007426 ***
## - PutOuts     1    1340713 25575890 3050.6  13.6643 0.0002693 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step:  AIC=3036.54
## Salary ~ AtBat + Hits + HmRun + Runs + Walks + CAtBat + CRuns +
##      CRBI + CWalks + League + Division + PutOuts + Assists + Errors
##
##           Df Sum of Sq      RSS      AIC F value    Pr(>F)
## - HmRun       1      40487 24289148 3035.0   0.4141 0.5205005
## - Errors      1      51930 24300590 3035.1   0.5311 0.4668297
## - Runs        1      79343 24328003 3035.4   0.8115 0.3685611
## - League     1     114742 24363402 3035.8   1.1735 0.2797336
## <none>                24248660 3036.5
## - Assists     1     283442 24532103 3037.6   2.8989 0.0898946 .
## + CHits       1      13483 24235177 3038.4   0.1374 0.7111808
## + RBI         1      13423 24235237 3038.4   0.1368 0.7117909
## + Years       1      11981 24236679 3038.4   0.1221 0.7270650
## + NewLeague   1       7510 24241150 3038.5   0.0765 0.7822973
## + CHmRun      1       5924 24242737 3038.5   0.0604 0.8061379
## - CAtBat      1     613356 24862016 3041.1   6.2730 0.0129017 *
## - Division    1     801474 25050134 3043.1   8.1970 0.0045548 **
## - CRBI        1     903248 25151908 3044.2   9.2379 0.0026244 **

```

```

## - CWalks      1    1011953 25260613 3045.3 10.3496 0.0014674 **
## - Walks       1    1246164 25494824 3047.7 12.7450 0.0004286 ***
## - AtBat       1    1339620 25588280 3048.7 13.7008 0.0002641 ***
## - CRuns       1    1390808 25639469 3049.2 14.2243 0.0002029 ***
## - PutOuts     1    1406023 25654684 3049.4 14.3799 0.0001877 ***
## - Hits        1    1607990 25856650 3051.4 16.4455 0.00006709 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3034.98
## Salary ~ AtBat + Hits + Runs + Walks + CAtBat + CRuns + CRBI +
## CWalks + League + Division + PutOuts + Assists + Errors
##
##           Df Sum of Sq      RSS      AIC F value      Pr(>F)
## - Errors      1      44085 24333232 3033.5  0.4519  0.5020421
## - Runs        1      49068 24338215 3033.5  0.5030  0.4788415
## - League      1     103837 24392985 3034.1  1.0645  0.3031961
## <none>                24289148 3035.0
## - Assists     1     247002 24536150 3035.6  2.5321  0.1128176
## + HmRun       1      40487 24248660 3036.5  0.4141  0.5205005
## + Years       1     11136 24278012 3036.9  0.1138  0.7361964
## + CHits       1      9384 24279763 3036.9  0.0959  0.7571211
## + NewLeague   1      9063 24280084 3036.9  0.0926  0.7611839
## + RBI         1      5230 24283918 3036.9  0.0534  0.8174246
## + CHmRun      1         47 24289101 3037.0  0.0005  0.9824929
## - CAtBat      1     652746 24941894 3040.0  6.6916  0.0102549 *
## - Division    1     795643 25084791 3041.5  8.1565  0.0046527 **
## - CWalks     1     982896 25272044 3043.4 10.0761  0.0016911 **
## - Walks      1    1205823 25494971 3045.7 12.3615  0.0005206 ***
## - AtBat      1    1300972 25590120 3046.7 13.3369  0.0003172 ***
## - CRuns      1    1351200 25640348 3047.2 13.8518  0.0002446 ***
## - CRBI       1    1353507 25642655 3047.2 13.8755  0.0002417 ***
## - PutOuts    1    1429006 25718154 3048.0 14.6494  0.0001638 ***
## - Hits      1    1574140 25863288 3049.5 16.1373  0.00007806 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3033.46
## Salary ~ AtBat + Hits + Runs + Walks + CAtBat + CRuns + CRBI +
## CWalks + League + Division + PutOuts + Assists
##
##           Df Sum of Sq      RSS      AIC F value      Pr(>F)
## - Runs        1     54113 24387345 3032.0  0.5560  0.4565953
## - League      1     91269 24424501 3032.4  0.9377  0.3338061
## <none>                24333232 3033.5
## - Assists     1     220010 24553242 3033.8  2.2604  0.1339832
## + Errors      1      44085 24289148 3035.0  0.4519  0.5020421
## + HmRun       1     32642 24300590 3035.1  0.3345  0.5635601
## + Years       1      8122 24325111 3035.4  0.0831  0.7733321
## + NewLeague   1      6890 24326342 3035.4  0.0705  0.7907946

```



```

## + CHits      1      5330 24327902 3035.4  0.0546 0.8155110
## + RBI        1      2382 24330851 3035.4  0.0244 0.8760656
## + CHmRun     1         9 24333223 3035.5  0.0001 0.9922430
## - CAtBat     1     650513 24983746 3038.4  6.6834 0.0102988 *
## - Division   1     799455 25132687 3040.0  8.2136 0.0045117 **
## - CWalks     1     971260 25304493 3041.8  9.9787 0.0017784 **
## - Walks      1    1239533 25572765 3044.5 12.7350 0.0004301 ***
## - CRBI       1    1331672 25664904 3045.5 13.6816 0.0002663 ***
## - CRuns      1    1361070 25694302 3045.8 13.9837 0.0002287 ***
## - AtBat      1    1378592 25711824 3045.9 14.1637 0.0002089 ***
## - PutOuts    1    1391660 25724892 3046.1 14.2979 0.0001952 ***
## - Hits       1    1649291 25982523 3048.7 16.9448 0.0000523 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3032.04
## Salary ~ AtBat + Hits + Walks + CAtBat + CRuns + CRBI + CWalks +
##      League + Division + PutOuts + Assists
##
##           Df Sum of Sq      RSS      AIC F value      Pr(>F)
## - League      1     113056 24500402 3031.3   1.1636  0.2817552
## <none>                24387345 3032.0
## - Assists     1     280689 24668034 3033.1   2.8889  0.0904298 .
## + Runs        1      54113 24333232 3033.5   0.5560  0.4565953
## + Errors      1      49130 24338215 3033.5   0.5047  0.4781239
## + CHits       1      22676 24364669 3033.8   0.2327  0.6299694
## + Years       1       8532 24378813 3033.9   0.0875  0.7676295
## + HmRun       1       5924 24381421 3034.0   0.0607  0.8055343
## + NewLeague   1       4287 24383058 3034.0   0.0440  0.8341147
## + CHmRun      1       1146 24386199 3034.0   0.0118  0.9137590
## + RBI         1         75 24387270 3034.0   0.0008  0.9778452
## - CAtBat      1     596622 24983967 3036.4   6.1406  0.0138700 *
## - Division    1     780369 25167714 3038.3   8.0317  0.0049703 **
## - CWalks      1     946687 25334032 3040.1   9.7435  0.0020102 **
## - Walks       1    1212997 25600342 3042.8  12.4844  0.0004883 ***
## - CRuns       1    1334397 25721742 3044.1  13.7339  0.0002591 ***
## - CRBI        1    1361339 25748684 3044.3  14.0112  0.0002253 ***
## - PutOuts     1    1455210 25842555 3045.3  14.9774  0.0001388 ***
## - AtBat       1    1522760 25910105 3046.0  15.6726  0.00009811 ***
## - Hits        1    1718870 26106215 3047.9  17.6910  0.00003619 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Step: AIC=3031.26
## Salary ~ AtBat + Hits + Walks + CAtBat + CRuns + CRBI + CWalks +
##      Division + PutOuts + Assists
##
##           Df Sum of Sq      RSS      AIC F value      Pr(>F)
## <none>                24500402 3031.3
## + League      1     113056 24387345 3032.0   1.1636  0.2817552

```

```
## + Runs      1      75900 24424501 3032.4 0.7800 0.3779884
## + NewLeague 1      64712 24435690 3032.6 0.6647 0.4156749
## - Assists   1     313650 24814051 3032.6 3.2261 0.0736726 .
## + CHits     1      37564 24462838 3032.8 0.3854 0.5352800
## + Errors    1      35264 24465138 3032.9 0.3618 0.5480572
## + Years     1      19883 24480519 3033.0 0.2039 0.6520127
## + CHmRun    1       4356 24496046 3033.2 0.0446 0.8328494
## + HmRun     1       1189 24499212 3033.2 0.0122 0.9121905
## + RBI       1        359 24500043 3033.2 0.0037 0.9517012
## - CAtBat    1     534156 25034558 3034.9 5.4941 0.0198584 *
## - Division  1     798473 25298875 3037.7 8.2127 0.0045109 **
## - CWalks    1     965875 25466276 3039.4 9.9345 0.0018183 **
## - CRuns     1    1265082 25765484 3042.5 13.0121 0.0003731 ***
## - Walks     1    1290168 25790569 3042.8 13.2701 0.0003274 ***
## - CRBI      1    1326770 25827172 3043.1 13.6466 0.0002706 ***
## - PutOuts   1    1551523 26051925 3045.4 15.9583 0.00008504 ***
## - AtBat     1    1589780 26090181 3045.8 16.3518 0.00006996 ***
## - Hits      1    1716068 26216469 3047.1 17.6507 0.00003686 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
summary(Hitters.step)
```

```
##
## Call:
## lm(formula = Salary ~ AtBat + Hits + Walks + CAtBat + CRuns +
##     CRBI + CWalks + Division + PutOuts + Assists, data = Hitters)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -939.11 -176.87  -34.08   130.90  1910.55
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  162.53544    66.90784   2.429  0.015830 *
## AtBat        -2.16865     0.53630  -4.044 0.0000700 ***
## Hits         6.91802     1.64665   4.201 0.0000369 ***
## Walks        5.77322     1.58483   3.643  0.000327 ***
## CAtBat       -0.13008     0.05550  -2.344  0.019858 *
## CRuns        1.40825     0.39040   3.607  0.000373 ***
## CRBI         0.77431     0.20961   3.694  0.000271 ***
## CWalks       -0.83083     0.26359  -3.152  0.001818 **
## DivisionW    -112.38006    39.21438  -2.866  0.004511 **
## PutOuts      0.29737     0.07444   3.995 0.0000850 ***
## Assists      0.28317     0.15766   1.796  0.073673 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 311.8 on 252 degrees of freedom
```

```
## Multiple R-squared:  0.5405, Adjusted R-squared:  0.5223
## F-statistic: 29.64 on 10 and 252 DF,  p-value: < 2.2e-16
```

Best Subset Selection

I only discuss this method briefly, because the Step methods accomplish the same purpose and are superior in my opinion. But it is a useful method to know. Best subset selection works similarly to the Step method, but there are additions or removals in steps. Rather, the first step will try all possible 1-predictor models and select the best of all in terms of explanatory power. It will then fit all possible 2-predictor models, and so on. We use the `regsubsets()` function from the `{leaps}` package for this purpose. By default, `regsubsets()` stops when the model has 8 predictors, but you can change this with the `nvmax=` parameter. Let's illustrate this:

```
library(leaps) # Contains the regsubsets() function

regfit.full <- regsubsets(Salary ~ ., Hitters)

summary(regfit.full)
```

```
## Subset selection object
## Call: regsubsets.formula(Salary ~ ., Hitters)
## 19 Variables (and intercept)
##           Forced in Forced out
## AtBat      FALSE     FALSE
## Hits       FALSE     FALSE
## HmRun       FALSE     FALSE
## Runs        FALSE     FALSE
## RBI         FALSE     FALSE
## Walks       FALSE     FALSE
## Years       FALSE     FALSE
## CAtBat      FALSE     FALSE
## CHits       FALSE     FALSE
## CHmRun      FALSE     FALSE
## CRuns       FALSE     FALSE
## CRBI        FALSE     FALSE
## CWalks      FALSE     FALSE
## LeagueN     FALSE     FALSE
## DivisionW   FALSE     FALSE
## PutOuts     FALSE     FALSE
## Assists     FALSE     FALSE
## Errors      FALSE     FALSE
## NewLeagueN  FALSE     FALSE
## 1 subsets of each size up to 8
## Selection Algorithm: exhaustive
##           AtBat Hits HmRun Runs RBI Walks Years CAtBat CHits CHmRun CRuns CRBI
## 1  ( 1 ) " "   " "   " "   " "   " "   " "   " "   " "   " "   "*"
## 2  ( 1 ) " "   "*"  " "   " "   " "   " "   " "   " "   " "   "*"
## 3  ( 1 ) " "   "*"  " "   " "   " "   " "   " "   " "   " "   "*"
## 4  ( 1 ) " "   "*"  " "   " "   " "   " "   " "   " "   " "   "*"
## 5  ( 1 ) " "   " "   " "   " "   " "   " "   " "   " "   " "   " "
## 6  ( 1 ) " "   " "   " "   " "   " "   " "   " "   " "   " "   " "
## 7  ( 1 ) " "   " "   " "   " "   " "   " "   " "   " "   " "   " "
## 8  ( 1 ) " "   " "   " "   " "   " "   " "   " "   " "   " "   " "
## 9  ( 1 ) " "   " "   " "   " "   " "   " "   " "   " "   " "   " "
## 10 ( 1 ) " "   " "   " "   " "   " "   " "   " "   " "   " "   " "
```

```
## 5 ( 1 ) "*" "*" " " " " " " " " " " " " " " " " "*"
## 6 ( 1 ) "*" "*" " " " " " " "*" " " " " " " " " " " "*"
## 7 ( 1 ) " " "*" " " " " " " "*" " " "*" "*" "*" " " " "
## 8 ( 1 ) "*" "*" " " " " " " "*" " " " " " " "*" "*" " "
##           CWalks LeagueN DivisionW PutOuts Assists Errors NewLeagueN
## 1 ( 1 ) " " " " " " " " " " " " " "
## 2 ( 1 ) " " " " " " " " " " " "
## 3 ( 1 ) " " " " " " "*" " " " " "
## 4 ( 1 ) " " " " "*" "*" " " " " "
## 5 ( 1 ) " " " " "*" "*" " " " " "
## 6 ( 1 ) " " " " "*" "*" " " " " "
## 7 ( 1 ) " " " " "*" "*" " " " " "
## 8 ( 1 ) "*" " " "*" "*" " " " " " "
```

The `****` in the output shows the predictors selected in each model. You can also view the R-Squared of each model with the `$rsq` attribute:

```
summary(regfit.full)$rsq # View the R-square of each model
```

```
## [1] 0.3214501 0.4252237 0.4514294 0.4754067 0.4908036 0.5087146 0.5141227
## [8] 0.5285569
```

Let's change the number of predictors in the model up to 10

```
regfit.full <- regsubsets(Salary ~ .,
                          data = Hitters,
                          nvmax = 10)
```

```
summary(regfit.full)
```

```
## Subset selection object
## Call: regsubsets.formula(Salary ~ ., data = Hitters, nvmax = 10)
## 19 Variables (and intercept)
##           Forced in Forced out
## AtBat      FALSE      FALSE
## Hits       FALSE      FALSE
## HmRun       FALSE      FALSE
## Runs       FALSE      FALSE
## RBI        FALSE      FALSE
## Walks      FALSE      FALSE
## Years      FALSE      FALSE
## CAtBat     FALSE      FALSE
## CHits      FALSE      FALSE
## CHmRun     FALSE      FALSE
## CRuns      FALSE      FALSE
## CRBI       FALSE      FALSE
## CWalks     FALSE      FALSE
## LeagueN    FALSE      FALSE
```

```

## DivisionW      FALSE      FALSE
## PutOuts        FALSE      FALSE
## Assists        FALSE      FALSE
## Errors         FALSE      FALSE
## NewLeagueN     FALSE      FALSE
## 1 subsets of each size up to 10
## Selection Algorithm: exhaustive
##               AtBat Hits HmRun Runs RBI Walks Years CAtBat CHits CHmRun CRuns CRBI
## 1 ( 1 ) " " " " " " " " " " " " " " " " " " " "
## 2 ( 1 ) " " "*" " " " " " " " " " " " " " " " "
## 3 ( 1 ) " " "*" " " " " " " " " " " " " " " " "
## 4 ( 1 ) " " "*" " " " " " " " " " " " " " " " "
## 5 ( 1 ) "*" "*" " " " " " " " " " " " " " " " "
## 6 ( 1 ) "*" "*" " " " " " " "*" " " " " " " " "
## 7 ( 1 ) " " "*" " " " " " " "*" " " "*" "*" " " "
## 8 ( 1 ) "*" "*" " " " " " " "*" " " " " "*" "*" "
## 9 ( 1 ) "*" "*" " " " " " " "*" " " " " "*" "*"
## 10 ( 1 ) "*" "*" " " " " " " "*" " " " " "*" "*"
##               CWalks LeagueN DivisionW PutOuts Assists Errors NewLeagueN
## 1 ( 1 ) " " " " " " " " " " " "
## 2 ( 1 ) " " " " " " " " " " " "
## 3 ( 1 ) " " " " " " "*" " " " " "
## 4 ( 1 ) " " " " "*" "*" " " " " "
## 5 ( 1 ) " " " " "*" "*" " " " " "
## 6 ( 1 ) " " " " "*" "*" " " " " "
## 7 ( 1 ) " " " " "*" "*" " " " " "
## 8 ( 1 ) "*" " " "*" "*" " " " " "
## 9 ( 1 ) "*" " " "*" "*" " " " " "
## 10 ( 1 ) "*" " " "*" "*" "*" " " "

```