## 1.0.10-alpha - Current Release

- Removed HtmlTree and HtmlTag as they were not useful in their current state
- Added IDomTree and IDomNode(Accessible methods outlined in the general documentation)
- Removed the below method:
  - List<By> GetAllBysUsingMatchingSelectorData(SelectorData selectorData, IWebDriverManager webDriverManager)
    - It had no practical usage in it's current state as the goal of this tooling was to remove the need it interact with By typed objects
- Added the below method(s)
  - bool IsElementDisplayed(IWebDriverManager webDriverManager, SelectorData selectorData)
    - Checks whether or not the provided element is visible(This requires IWebElement.Displayed evaluate to true)
    - selectorData -> Object representing the element to check
  - bool IsElementEnabled(IWebDriverManager webDriverManager, SelectorData selectorData)
    - Checks whether or not the provided element is enabled(This requires IWebElement.Enabled evaluate to true)
    - selectorData -> Object representing the element to check
  - bool IsElementDisplayedAndEnabled(IWebDriverManager webDriverManager, SelectorData selectorData)
    - Checks whether or not the provided element is visible(This requires IWebElement.Displayed and IWebElement.Enabled to both evaluate to true)
    - selectorData -> Object representing the element to check
  - ReadOnlyCollection<IWebElement> GetAllElementsUsingMatchingSelectorData(SelectorData selectorData, IWebDriverManager webDriverManager)
    - Finds and returns all elements matching the provided selector data
    - Data to check for in the current DOM instance

## 1.0.9-alpha

- Added method bool DoesUrlContainUsingRegex(IWebDriverManager webDriverManager, string pattern)
  - Checks whether or not the current url contains the provided pattern using regex IsMatch
- Added method void SetDriverOptions(ChromeOptions chromeOptions = null, FirefoxOptions firefoxOptions = null,
   InternetExplorerOptions internetExplorerOptions = null, EdgeOptions edgeOptions = null)
  - Sets the options for the associated driver. If the driver is active when this method is called it will be recreated
  - If no options objects are set the default options defined on the driver will be used
- Added method void SetFirefoxProfile(FirefoxProfile firefoxProfile)
  - Sets the profile for the firefox driver. If the driver is active when this method is called it will be recreated.
  - If no profile object is set the default profile defined on the browser will be used

## 1.0.8-alpha

 Updated signature of the method CheckChildElementExistsAndReturnIt to take an optional parameter of int nthParentElement

- $\circ$   $\;$  This is meant for cases where there are identical elements that could be returned for the parent
- o It is a zero based value used to select a specific parent element and then use it for the starting point of the child search
- o The default value is -1