SKYWORTH
Your Best Friend of Energy-Saving Solutions

SW 75/100/110/125kW

Three Phase On-grid Inverter

MODEL

SW075KTL-T1-L-G2	SW100KTL-T1-G2	SW110KTL-T1-G2	SW125KTL-T1-G2



Smart Control & Monitoring
- String level monitoring
- Remote or onsite upgrade supported

Friendly & Thoughtful Design
- Lightweight design and high power density for easy installation
- Easy & quick replacement of fan
- Fuse free design

Superb Safety & Reliability
- Type II SPD on AC & DC sides
- IP66 and optional C5 protection
- Optional AFCI protection

Optimal Generation for Higher Return
- 21A DC input current per string[2]
- 8/10 MPPTs, max. Efficiency 99.0%
- 150% DC input oversizing & 110% AC output overloading
- No derating at 45°C

1: Optional functions or devices are purchased separately.
2: Only for the SWH6000H-T1-G2, SWH8000H-T1-G2, SWH010KH-T1-G2 models.

Global-V1.04-2026EN

Shenzhen SKYWORTH Photovoltaic Technology Co., Ltd.
All Rights Reserved @Shenzhen SKYWORTH Photovoltaic Technology Co., LTD. Please refer to the latest version for any updates

Model	SW075KTL-T1-L-G2	SW100KTL-T1-G2	SW110KTL-T1-G2	SW125KTL-T1-G2
Input				
Max. Input Voltage (V)	800	1100[*11]	1100[*11]	1100[*11]
MPPT Operating Voltage Range (V) [*12]	180 ~ 800	180 ~ 1000	180 ~ 1000	180 ~ 1000
Start-up Voltage (V)	200			
Nominal Input Voltage (V)	370	600V @ 380 / 400Vac, 720V @ 480Vac		
Max. Input Current per MPPT (A)	42			
Max. Short Circuit Current per MPPT (A)	52.5			
Number of MPP Trackers	8	8	10	10
Number of Strings per MPPT	2			
Output				
Nominal Output Power (kW)	75.0	100.0[*1]	110.0	125.0
Nominal Output Apparent Power (kVA)	75.0	100.0[*1]	110.0	125.0
Max. AC Active Power (kW)[*3]	75.0[*6]	110.0[*1]	121.0[*4]	137.5[*2]
Max. AC Apparent Power (kVA)[*3]	75.0	110.0[*1]	121.0[*4]	137.5[*2]
Nominal Output Voltage (V)	127 / 220, 3L / N / PE or 3L / PE[*7]	220 / 380, 230 / 400, 277 / 480, 3L / N / PE or 3L / PE		
Output Voltage Range (V)	176 ~ 245	304 ~ 528	304 ~ 528	304 ~ 528
Nominal AC Grid Frequency (Hz)	50 / 60			
AC Grid Frequency Range (Hz)	45 ~ 55 / 55 ~ 65			
Max. Output Current (A)[*5]	196.9	167.1 @ 380V;158.8 @ 400V;132.3 @ 480V	183.4 @ 380V;174.7 @ 400V;145.5 @ 480V	199.4 @ 380V;198.5 @ 400V;165.4 @ 480V
Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)			
Max. Total Harmonic Distortion	<3%			
Efficiency				
Max. Efficiency	98.8%	98.8%	98.8%	99.0%
European Efficiency	98.3%	98.4%	98.4%	98.5%
Protection				
PV String Current Monitoring	●			
PV Insulation Resistance Detection	●			
Residual Current Monitoring	●			
PV Reverse Polarity Protection	●			
Anti-islanding Protection	●			
AC Overcurrent Protection	●			
AC Short Circuit Protection	●			
AC Overvoltage Protection	●			
DC Switch	●			
DC Surge Protection	Type II		Type II (Type I + II Optional)	
AC Surge Protection	Type II			
AFCI	○	○	○	○
Emergency Power Off	-	○	○	○
Rapid Shutdown	○			
Remote Shutdown	●	○	○	○
PID Recovery	○			
Reactive Power Compensation at Night	-	○	○	○
Power Supply at Night	○	○	○	○
General Data				
Operating Temperature Range (°C)	-35 ~ +60			
Relative Humidity	0 ~ 100%			
Max. Operating Altitude (m)	4000			
Cooling Method	Smart Fan Cooling			
User Interface	LED, LCD (Optional), WLAN + APP			
Communication	RS485, WiFi + LAN		RS485, WiFi + LAN or 4G	
Communication Protocols	Modbus-RTU (SunSpec Compliant)			
Weight (kg)	88	85	88	88
Dimension (W × H × D mm)	930 × 650 × 300			
Topology	Non-isolated			
Self-consumption at Night (W)	<1	<2	<2	<2
Ingress Protection Rating	IP66			
DC Connector	MC4 (4 ~ 6mm²)			
AC Connector	OT / DT terminal (Max. 240mm²)			

● Integrated ○ Optional

*1: For Australia is 99.99kW / kVA.

*2: For VDE4105 Max. AC Active Power (kW) and Max. AC Apparent Power (kVA): SW125KTL-T1-G2 is 134.9.

*3: For Chile, Brazil and Sri Lanka Max. AC Active Power (kW) and Max. AC Apparent Power (kVA): SW100KTL-T1-G2 is 100; SW110KTL-T1-G2 is 110; SW125KTL-T1-G2 is 125.

*4: For Australia is 110kW / kVA.

*5: For Australia Max. Output Current (A): SW100KTL-T1-G2 is 145@400V, SW110KTL-T1-G2 is 159.5@400V.

*6: For Colombia Max. AC Active Power (kW): SW075KTL-T1-L-G2 is 70.9@208V.

*7: For Colombia Nominal Output Voltage (V): SW075KTL-T1-L-G2 is 120 / 208, 3L / N / PE or 3L / PE.

*8: For Brazil, Colombia and Mexico is Integrated.

*9: For Australia, SW100KTL-T1-G2/SW110KTL-T1-G2/SW125KTL-T1-G2 AFCI: Integrated.

*10: For Australia, Brazil and Mexico, SW100KTL-T1-G2/SW110KTL-T1-G2/ SW125KTL-T1-G2 Power Supply at Night: Integrated.

*11: When the input voltage ranges from 1000V to 1100V, the inverter will enter the standby state. When the input voltage returns to the MPPT operating voltage range, the inverter will resume normal operating state.

*12: Please refer to the user manual for the MPPT Voltage Range at Nominal Power.

*:Please visit SKYWORTH website for the latest certificates.

*:All pictures shown are for reference only. Actual appearance may vary.

SKYWORTH
Your Best Friend of Energy-Saving Solutions

400-063-8989 solar.overseas@skyworth.com www.skyworth-pv.com

Add: Room No.0801, C Block, 5th Building, HuaQiang Creative Park,Guangming Street, Guangming District, Shenzhen