



MAXAM

MS907

L5 SKID STEER AND BACKHOE

Extra deep, aggressive L5 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full flat profile with self-cleaning stepped tread improves performance
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces chunking
- Increased net-to-gross for maximum tread life and lowest cost per hour

Applications:



Size	P.R.	Type	Rim	O.D.	S.W	T.D.	Inf. P.	L.C.C. (lbs/kg)
				in mm	in. mm	32nds mm	psi KPa	5 mph 10 kph
23x8.50-12	8	TL	7JA	22.6 574	8.4 213	35 28	65 450	2150 975
27x8.50-15	10	TL	7JA	27.0 686	8.7 221	38 30	75 515	3300 1500
10-16.5	14	TL	8.25	31.3 795	10.9 278	44 35	105 620	5680 1800
12-16.5	14	TL	9.75	33.1 842	13.0 330	44 35	90 620	6780 3075
14-17.5	16	TL	10.50	36.8 935	14.1 357	46 36	90 620	9100 4125
12.5/80-18	14	TL	W9	38.0 965	12.0 306	47 37	62 425	8260 3745
				38.0 965	12.0 306	47 37	70 480	8940 4055
	16	TL	W9	38.0 965	12.0 306	47 37	70 480	8940 4055
				38.0 965	12.0 306	47 37	70 480	8940 4055
16.9-28	14	TL	W15L	55.5 1410	17.7 450	48 38	45 310	10690 4850

