



MAXAM

MS300

E3/L3

Light duty E3/ L3 lug pattern ideally suited to municipalities, small sand and aggregate operations and other smooth surface applications.

- Excellent traction in all off-road conditions
- Thick undertread for improved puncture resistance
- High quality casing allows for excellent retreadability
- Wear and cut resistant tread compound

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	psi KPa	30 mph 50 kph	
15.5R25	★★	TL	12.00/1.3	50.2 1274	15.3 389	30 24	94 650	15700 7100	76 525	9900 4500	176A2/160B
17.5R25	★★	TL	14.00/1.5	53.0 1346	17.3 440	32 25	94 650	18700 8500	76 525	12000 5450	182A2/167B
20.5R25	★★	TL	17.00/2.0	58.4 1493	20.6 524	36 28	94 650	25400 11500	76 525	16100 7300	193A2/177B
23.5R25	★★	TL	19.50/2.5	63.2 1605	23.7 601	40 32	94 650	32000 14500	76 525	20400 9250	201A2/185B
26.5R25	★★	TL	22.00/3.0	68.7 1739	26.5 669	44 35	94 650	40800 18500	76 525	25400 11500	209A2/193B
29.5R25	★★	TL	25.00/3.5	73.5 1866	29.5 751	48 38	94 650	49400 22400	76 525	30900 14000	216A2/200B

