



**MAXAM**

# MS903

**BACKHOE - INDUSTRIAL SERVICE**

Modified R4 tread pattern for excellent traction and flotation in soft underfoot conditions.

- Tread design optimized with self-cleaning mud breakers
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Inf. P.	L.C.C. (lbs/kg)		L.I.
				in mm	in. mm	32nds mm	psi KPa	5 mph 10 kph	25 mph 40 kph	
18.4-26 (480/80-26)	12	TL	W16L	56.3	18.8	36	36	11000	8800	156A8
				1430	478	29	250	5000	4000	
	16	TL	W16L	56.3	18.8	36	45	13125	10500	162A8
				1430	478	29	310	5940	4750	
16.9-28 (440/80-28)	12	TL	W15L	55.5	17.2	34	38	9815	7850	152A8
				1410	437	27	260	4440	3550	
	14	TL	W15L	55.5	17.2	34	44	10690	8550	155A8
				1410	437	27	300	4840	3875	
16.9-30 (420/85-30)	12	TL	W15L	57.5	17.1	34	34	10060	8050	153A8
				1461	434	27	235	4560	3650	
	14	TL	W15L	57.5	17.1	34	45	11000	8800	156A8
				1461	434	27	310	5000	4000	
18.4-30 (460/85-30)	12	TL	W16L	60.2	18.5	36	36	11690	9350	158A8
				1529	470	29	250	5310	4250	
	14	TL	W16L	60.2	18.5	36	42	12375	9900	160A8
				1529	470.0	29.0	290	5625	4500	

