



**MAXAM**


# MS916

**SKID STEER**

Deep R4 tread pattern designed for skid steer, backhoe and telehandler applications.

- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces chunking

Applications:



| Size    | PR | Type | Rim   | O.D.     | S.W      | T.D.        | Infl. P.   | L.C.C. (lbs/kg) |                  |
|---------|----|------|-------|----------|----------|-------------|------------|-----------------|------------------|
|         |    |      |       | in<br>mm | in<br>mm | 32nds<br>mm | psi<br>KPa | 5 mph<br>10 kph | 30 mph<br>50 kph |
| 10-16.5 | 8  | TL   | 8.25  | 30.4     | 10.4     | 19          | 60         | 4140            | 2950             |
|         |    |      |       | 772      | 264      | 15          | 415        | 1900            | 1340             |
| 12-16.5 | 10 | TL   | 9.75  | 32.8     | 12.4     | 23          | 65         | 5680            | 3520             |
|         |    |      |       | 833      | 315      | 18          | 450        | 2575            | 1600             |
| 14-17.5 | 14 | TL   | 10.50 | 36.2     | 13.8     | 25          | 80         | 8550            | 5360             |
|         |    |      |       | 919      | 351      | 20          | 550        | 3875            | 2430             |

