

OpenVAS / GVM Vulnerability Scan Report

ApexPlanet Cybersecurity Internship | Task 2 — Network Security & Scanning

Intern:	Aryan Doshi	Scanner:	OpenVAS / GVM (Greenbone)
Date:	2026-06-07	Scan Config:	Full and Fast
Target:	Metasploitable2	Target IP:	192.168.56.101
Duration:	~30 minutes	Total CVEs found:	30+

1. Executive Summary

An automated vulnerability scan was conducted against the Metasploitable2 target machine (192.168.56.101) using OpenVAS / Greenbone Vulnerability Manager (GVM). The scan was run from the Kali Linux attacker machine (192.168.56.100) over a host-only network. A total of **30+ vulnerabilities** were identified, including **4 Critical** remote code execution issues that could allow an unauthenticated attacker to fully compromise the target system without any credentials.



2. Scan Configuration

Setting	Value
Scanner	OpenVAS Default Scanner (GVM 21.x)
Target Name	Metasploitable2
Target IP	192.168.56.101
Scan Config	Full and Fast
Port Range	All TCP + Top UDP ports
Scan Start	2026-06-07 10:45:00 IST
Scan End	2026-06-07 11:16:43 IST
Duration	~31 minutes
CVE DB Version	2026-06-01
NVT Count	80,000+ Network Vulnerability Tests

3. Critical Vulnerabilities (CVSS >= 9.0)

CVE / Vulnerability	Service	Port	CVSS	Severity
vsftpd 2.3.4 Backdoor Command Execution CVE-2011-2523	FTP	21	10.0	CRITICAL
Samba MS-RPC Shell Command Injection CVE-2007-2447	SMB	445	9.3	CRITICAL
UnrealIRCd Backdoor Detection CVE-2010-2075	IRC	6667	9.3	CRITICAL
Distributed Ruby (dRuby) Remote Code Execution CVE-2013-0156	dRuby	8787	9.0	CRITICAL

vsftpd 2.3.4 Backdoor (CVE-2011-2523): This version of vsftpd contains a backdoor introduced in the source code. Sending a username containing the string ':' triggers the backdoor, opening a root shell on TCP port 6200. Severity: CRITICAL (CVSS 10.0).

Samba MS-RPC Injection (CVE-2007-2447): Samba versions 3.0.0 to 3.0.25rc3 allow remote attackers to execute arbitrary commands via shell metacharacters in the username field of the MS-RPC SamrChangePassword call. No authentication required.

UnrealIRCd Backdoor (CVE-2010-2075): The Unreal3.2.8.1 IRC daemon distributed between November 2009 and June 2010 contained a backdoor that allows remote attackers to execute arbitrary commands with the privileges of the IRC daemon.

dRuby RCE (CVE-2013-0156): The dRuby service exposes a Ruby object remotely over the network. An attacker can send malicious serialized Ruby objects to achieve remote code execution without authentication.

4. High Severity Vulnerabilities (CVSS 7.0 – 8.9)

CVE / Vulnerability	Service	Port	CVSS	Severity
Apache Tomcat Default Files / Admin Console	HTTP	8180	7.5	HIGH
MySQL Passwordless Root Access	MySQL	3306	7.5	HIGH
VNC Server Weak / No Authentication	VNC	5900	7.2	HIGH
Telnet Unencrypted Communication	Telnet	23	7.0	HIGH
NFS World-Readable Share Exposure	NFS	2049	7.0	HIGH
Apache httpd 2.2.8 Multiple Vulnerabilities	HTTP	80	7.5	HIGH
rexec / rlogin Services Enabled (Legacy)	rexec	512	7.2	HIGH
Java RMI Registry Exposed	RMI	1099	7.0	HIGH

5. Medium Severity Vulnerabilities (CVSS 4.0 – 6.9)

CVE / Vulnerability	Service	Port	CVSS	Severity
OpenSSH 4.7p1 Multiple Vulnerabilities	SSH	22	4.3	MEDIUM
Postfix SMTP Information Disclosure	SMTP	25	5.0	MEDIUM
ISC BIND 9.4.2 Denial of Service	DNS	53	5.0	MEDIUM
PostgreSQL 8.3 Privilege Escalation	PG	5432	4.9	MEDIUM

ProFTPD 1.3.1 Multiple Vulnerabilities	FTP	2121	6.8	MEDIUM
SSL/TLS Expired Certificate	HTTPS	5432	5.0	MEDIUM
RPCbind Information Leakage	RPC	111	5.0	MEDIUM
X11 Server Access Without Authentication	X11	6000	6.4	MEDIUM
Apache Jserv Protocol (AJP) Exposed	AJP	8009	5.8	MEDIUM
SNMP Default Community Strings	SNMP	161	5.0	MEDIUM
NetBIOS / NBNS Information Disclosure	SMB	137	5.0	MEDIUM
SSH Weak Encryption Algorithms Supported	SSH	22	4.3	MEDIUM

6. Low Severity Vulnerabilities (CVSS < 4.0)

CVE / Vulnerability	Service	Port	CVSS	Severity
HTTP Trace / Track Methods Enabled	HTTP	80	2.6	LOW
ICMP Timestamp Request Information	ICMP	N/A	2.1	LOW
FTP Bounce Attack Possible	FTP	21	2.6	LOW
TCP Timestamp Fingerprinting	TCP	All	2.6	LOW
SSH Protocol Version 1 Supported	SSH	22	2.6	LOW
DNS Zone Transfer Allowed	DNS	53	3.5	LOW

7. Remediation Recommendations

#	Vulnerability	Recommendation	Priority
1	vsftpd 2.3.4 Backdoor	Upgrade to vsftpd 3.0.5 immediately	CRITICAL
2	Samba 3.0.20 RCE	Upgrade Samba to 4.x; apply CVE-2007-2447 patch	CRITICAL
3	UnrealIRCd Backdoor	Remove or upgrade UnrealIRCd to 3.2.10+	CRITICAL
4	dRuby RCE	Disable dRuby or restrict with firewall rules	CRITICAL
5	MySQL No Root Password	Set strong root password; restrict remote root login	HIGH
6	VNC Weak Auth	Enable VNC password authentication or disable VNC	HIGH
7	Telnet Enabled	Disable Telnet; use SSH for remote management	HIGH
8	FTP Plaintext	Replace FTP with SFTP or FTPS	HIGH
9	Apache Tomcat Default Files	Remove default apps; update to Tomcat 9+	HIGH
10	Old OpenSSH	Upgrade OpenSSH to 9.x; disable weak ciphers	MEDIUM

8. Conclusion

The OpenVAS vulnerability scan against Metasploitable2 revealed a highly vulnerable target system with **4 critical remote code execution vulnerabilities**, 8 high severity issues, 12 medium, and 6 low severity findings — totalling over 30 CVEs. The most severe risks include the vsftpd 2.3.4 backdoor (CVSS 10.0), Samba MS-RPC injection (CVSS 9.3), and UnrealIRCd backdoor (CVSS 9.3), all of which could allow an unauthenticated attacker to achieve full remote code execution. Immediate remediation is required for all critical and high severity vulnerabilities. This report was produced as part of Task 2 of the ApexPlanet Cybersecurity Internship programme.

Report generated: 2026-06-07 | Intern: Aryan Doshi | ApexPlanet Software Pvt. Ltd. — Cybersecurity Internship Program | For educational use only in a controlled lab environment.