

Queens' College Cambridge

Complexity Theory



Alistair O'Brien

Department of Computer Science

May 16, 2021

Contents

1	Background	4
1.1	Asymptotic notation	4
2	Turing Machines	6
2.1	Turing Machines	6
2.1.1	Computable Functions and Languages	9
2.1.2	Time and Space Complexity	11
2.2	Non-Deterministic Turing Machines	13
2.2.1	Time and Space Complexity	13
3	Complexity Classes	14
3.1	Complexity Classes	14
3.1.1	Reductions	14
3.1.2	Completeness	16
3.2	Polynomial Time	16
3.2.1	Problems	17
3.2.1.1	Reachability	17
3.2.1.2	Max Flow	17
3.2.1.3	Matching	20
3.2.2	co-P	21
3.3	Non-Deterministic Polynomial Time	21
3.3.1	Propositional Logic \mathcal{L}_0 Problems	22
3.3.1.1	SAT	22
3.3.1.2	CNF	25
3.3.2	Graph Problems	27
3.3.2.1	Independent Set	27
3.3.2.2	Clique	29
3.3.2.3	Graph Colorability	30
3.3.2.4	Hamiltonian Graph	32
3.3.2.5	TSP	33

3.3.3	Sets and Numbers	34
3.3.3.1	Tripartite Matching	34
3.3.3.2	Set Covering	35
3.3.3.3	Knapsack and Pseudo-polynomial Time	36
3.3.4	co-NP	37
3.3.4.1	Primality	38
3.4	Function Classes	39
3.4.1	Reductions	40
3.4.2	Problems	40
3.4.2.1	Factorization	40
3.4.3	Cryptography	40
3.4.3.1	One-way Functions	41
3.5	Space Complexity	42
3.5.1	Classes	42
3.5.2	Inclusions	43
3.5.3	Savitch's Theorem	46
3.5.4	Hierarchy Theorem	47

1 Background

1.1 Asymptotic notation

Definition 1.1.1. (*O*-notation) For a given function $g : \mathbb{N} \rightarrow \mathbb{N}$, we denote $O(g(n))$ as the set of functions

$$O(g(n)) = \{f(n) : \exists N, b > 0. \forall n > N. 0 \leq f(n) \leq bg(n)\}.$$

- **Notation:** We often write functions as $f(n)$ (*as opposed to the correct notation: $f : \mathbb{N} \rightarrow \mathbb{N}$*)

- **Macro convention:**

- A set in a formula represents an anonymous function in the set.
- For example

$$f(n) = n^3 + O(n^2) \iff \exists g(n) \in O(n^2). f(n) = n^3 + g(n).$$

and

$$n^2 + O(n) = O(n^2) \iff \forall f(n) \in O(n). \exists g(n) \in O(n^2). n^2 + f(n) = g(n).$$

Definition 1.1.2. (Ω -notation) For a given function $g : \mathbb{N} \rightarrow \mathbb{N}$, we denote $\Omega(g(n))$ as the set of functions

$$O(g(n)) = \{f(n) : \exists N, a > 0. \forall n > N. 0 \leq ag(n) \leq f(n)\}.$$

Definition 1.1.3. (Θ -notation) For a given function $g : \mathbb{N} \rightarrow \mathbb{N}$, we denote $\Theta(g(n))$ as the set of functions

$$\Theta(g(n)) = \{f(n) : \exists N, a, b > 0. \forall n > N. 0 \leq ag(n) \leq f(n) \leq bg(n)\}.$$

- Note that

$$\Theta(g(n)) = \{f(n) : f(n) \in \Omega(g(n)) \wedge f(n) \in O(g(n))\}.$$

Hence $\Theta(g(n)) = O(g(n)) \cap \Omega(g(n))$. So $\Theta(g(n)) \subset O(g(n))$ and $\Theta(g(n)) \subset \Omega(g(n))$

Theorem 1.1.1. For all functions $f, g, h : \mathbb{N} \rightarrow \mathbb{N}$, we have

(i) *Transitivity*:

$$\begin{aligned} f(n) \in \Theta(g(n)) \wedge g(n) \in \Theta(h(n)) &\implies f(n) \in \Theta(h(n)) \\ f(n) \in O(g(n)) \wedge g(n) \in O(h(n)) &\implies f(n) \in O(h(n)) \\ f(n) \in \Omega(g(n)) \wedge g(n) \in \Omega(h(n)) &\implies f(n) \in \Omega(h(n)) \end{aligned}$$

(ii) *Reflexivity*:

$$\begin{aligned} f(n) &\in \Theta(f(n)) \\ f(n) &\in O(f(n)) \\ f(n) &\in \Omega(f(n)) \end{aligned}$$

(iii) *Symmetry*:

$$f(n) \in \Theta(g(n)) \iff g(n) \in \Theta(f(n)).$$

(iv) *Transpose Symmetry*:

$$f(n) \in O(g(n)) \iff g(n) \in \Omega(f(n))$$

2 Turing Machines

2.1 Turing Machines

Definition 2.1.1. (Turing Machines) A k -tape Turing machine M on Σ is the 5-tuple $(Q, \Sigma, q_0, \delta, H)$:

- (i) Q is a finite set of *states*
- (ii) Σ is a finite alphabet, disjoint from Q
- (iii) $q_0 \in Q$ is the initial state.
- (iv) $\delta : (Q \times \mathcal{O}(\Sigma)^k) \rightarrow Q \times (\mathcal{O}(\Sigma) \times \{\leftarrow, -, \rightarrow\})$ is the transition function.
- (v) $H \subseteq Q$ is the set of *halting states*

- **Notation:**

- The set of k -tape Turing machines over Σ is denoted TM_{Σ}^k .
- The set of directions $\text{Direction} = \{\leftarrow, -, \rightarrow\}$.
- The set of actions $\text{Act}_{\Sigma} = \mathcal{O}(\Sigma) \times \text{Direction}$.

- **Idea:** Reasoning about *labelled states* (e.g. `acc`, `rej`) \implies *labelled machines*

- Tape Classifications (related to Flynn's Tax):

- $n = 0$ defines the set of `Nil` machines
- $n = 1$ defines the set of `SISD` machines
- $n > 1$ defines the set of `MIMD` machines

Definition 2.1.2. (Labelled Machines) A labelled k -tape Turing machine M_L w/ labels on L is the pair $M_L = (M, \text{lab})$ where $M = (Q, \Sigma, q_0, \delta, H)$ is a k -tape *unlabelled* Turing machine and $\text{lab} : Q \rightarrow L$ is the *labelling function* of M .

- **Notation:** The set of k -tape labelled Turing machines over Σ, L is denoted $\text{TM}_\Sigma^k(L)$.

Definition 2.1.3. (Tape) A tape τ on Σ is the pair $\tau = (u, v)$ where $u \in \triangleright \Sigma^*$, $v \in \Sigma^*$, and \triangleright denote the left end-of-tape markers.

If $u = wa$, then a is the current character under the read/write head.

- **Notation:** Tape_Σ denotes the set of tapes on Σ

Definition 2.1.4. (Tape Operators) The tape movement operator $\text{move} : \text{Direction} \times \text{Tape}_\Sigma \rightarrow \text{Tape}_\Sigma$:

$$\begin{aligned} \text{move}(\leftarrow, (\triangleright, v)) &= (\triangleright, v) \\ \text{move}(\leftarrow, (ua, v)) &= (u, av) \\ \text{move}(\rightarrow, (u, av)) &= (ua, v) \\ \text{move}(\rightarrow, (u, \varepsilon)) &= (u, \varepsilon) \\ \text{move}(-, \tau) &= \tau \end{aligned}$$

The left/right tape operators $\text{left}, \text{right} : \text{Tape}_\Sigma \rightarrow \Sigma^*$

$$\begin{aligned} \text{left}(\triangleright, v) &= \varepsilon \\ \text{left}(\triangleright ua, v) &= u \end{aligned}$$

The tape write operator $\text{write} : \text{Tape}_\Sigma \times \mathcal{O}(\Sigma) \rightarrow \text{Tape}_\Sigma$

$$\begin{aligned} \text{write}(\tau, \emptyset) &= \tau \\ \text{write}(\tau, [a]) &= (\triangleright \text{left}(\tau)a, \text{right}(\tau)) \end{aligned}$$

The current symbol function $\text{current} : \text{Tape}_\Sigma \rightarrow \mathcal{O}(\Sigma)$ is defined by

$$\begin{aligned} \text{current}(ua, v) &= [a] \\ \text{current}(_) &= \emptyset \end{aligned}$$

The contents function $\text{contents} : \text{Tape}_\Sigma \rightarrow \Sigma^*$ is defined by

$$\text{contents}(\triangleright u, v) = uv$$

- The empty type is $\tau_0 = (\triangleright, \varepsilon)$. The initial tape w/ contents $u \in \Sigma^*$ is $\tau_0(u) = (\triangleright, u)$.

Definition 2.1.5. (Configuration) A k -tape Turing machine *configuration* c for $M = (Q, \Sigma, q_0, \delta, H)$ is the tuple $c = (q, \tau_1, \dots, \tau_k)$ where:

- The current state $q \in Q$
- The i th tape $\tau_i \in \text{Tape}_\Sigma$.

The set of configurations for M is denoted $\mathcal{C}(M)$.

Definition 2.1.6. (Transition Relation) The transition function for Σ tapes Tape_Σ w/ action $\text{act} \in \text{Act}_\Sigma$, denoted $\xrightarrow{\text{act}}: \text{Tape}_\Sigma \rightarrow \text{Tape}_\Sigma$ is defined by

$$\frac{\tau_2 = \text{move}(D, \text{write}(\tau_1, a))}{\tau_1 \xrightarrow{(a,D)} \tau_2}$$

The transition relation for n -tape TM $M = (Q, \Sigma, q_0, \delta, H)$, denoted $\rightarrow_M: \mathcal{C}(M) \rightarrow \mathcal{C}(M)$ is inductively defined by

$$\frac{\text{current}(\tau_i) = a_i \quad \delta(q, a_i) = (q', \text{act}_1, \dots, \text{act}_n) \quad \tau_i \xrightarrow{\text{act}_i} \tau'_i \quad [q \notin H]}{(q, \tau_1, \dots, \tau_n) \rightarrow_M (q', \tau'_1, \dots, \tau'_n)}$$

- **Notation:** \rightarrow_M^* denotes a sequence of transitions, the reflexive transitive closure of \rightarrow_M .

Theorem 2.1.1. (Determinisim)

$$\begin{aligned} \forall M \in \text{TM}_\Sigma^k. \\ \forall c, c_0, c_1 \in \mathcal{C}(M). \\ c \rightarrow_M c_0 \wedge c \rightarrow_M c_1 \implies c_0 = c_1 \end{aligned}$$

Definition 2.1.7. (Computation) A *computation* of a Turing machine M is a sequence of transitions (infinite or finite)

$$c_0 \rightarrow_M c_1 \rightarrow_M \dots,$$

where $c_0 \in \mathcal{C}(M)$ is the *initial* configuration.

- A configuration $c = (q, \tau_1, \dots, \tau_n)$ is halting if $q \in H$. Note that $c \not\rightarrow_M \iff c$ is halting.

Definition 2.1.8. (Halting Computation) A *halting computation* of a k -tape Turing machine $M = (Q, \Sigma, q_0, \delta, H)$, denoted $(u_1, \dots, u_\ell) \Downarrow_M v$, where $\Downarrow_M: (\Sigma^*)^\ell \rightarrow \Sigma^*$, and $\ell < k$, defined by

$$(u_1, \dots, u_\ell) \Downarrow_M^q \text{contents}(\tau_k) \iff (q_0, \tau_0(u_1), \dots, \tau_0(u_\ell), \dots, \tau_0) \xrightarrow{*}_M (q, \tau_1, \dots, \tau_k) \not\rightarrow .$$

- Halting computation define the I/O convention: k th tape = output and first ℓ tapes = input.

Theorem 2.1.2. (MIMD and SISD Reduction)

$$\begin{aligned} \forall M \in \text{TM}_\Sigma^k. \exists N \in \text{TM}_\Sigma^1. \\ \forall u, v \in \Sigma^*. u \Downarrow_M v \iff u \Downarrow_N v \end{aligned}$$

2.1.1 Computable Functions and Languages

Definition 2.1.9. (Computable) A function $f \in \mathcal{P}[\Sigma^* \rightarrow \Sigma^*]$ is Turing computable iff there exists a k -tape Turing machine $M \in \text{TM}_\Sigma^k$ s.t

$$\forall u, v \in \Sigma^*. u \Downarrow_M v \iff f(u) = v$$

Definition 2.1.10. (Encodable) A set S is encodable on the finite alphabet Σ_S if there exists a bijection $\llbracket \cdot \rrbracket_S : S \rightarrow \Sigma_S^*$.

- All encodings for representations of mathematical objects are *polynomially related* (w/ the exception of unary encoding \implies pseudo-polynomial complexity)
- If S is encodable on Σ , we must extend Σ (denoted Σ_+) w/ additional start, stop symbols

Definition 2.1.11. The extended alphabet Σ_+ of Σ be defined as:

$$\begin{aligned} \Sigma_+ ::= & \text{Start} \mid \text{Stop} \\ & \mid a \in \Sigma \end{aligned}$$

Let $\text{Extend} : \Sigma \rightarrow \Sigma^+$ define a retraction.

- Extended alphabet Σ_+ is used to define tape contents of *encodable* sets

Definition 2.1.12. (Containment) Let S be an encodable set on Σ . The containment relation $\simeq: S \rightarrow \Sigma_+^*$ is defined by

$$x \simeq w \iff u \in \Sigma^*.w = u\text{Start} \llbracket x \rrbracket_S \text{Stop}$$

The containment relation $\simeq: S \rightarrow \text{Tape}_{\Sigma_+}$ is defined by

$$x \simeq \tau \iff x \simeq \text{contents}(\tau)$$

Definition 2.1.13. ((Natural) Computable) A function $f \in \mathcal{P}[\mathbb{N}^n \rightarrow \mathbb{N}]$ is Turing computable iff there exists a Turing machine $M \in \text{TM}_{\Sigma}^k$ s.t

$$\begin{aligned} \forall x_1, \dots, x_n, y \in \mathbb{N}. \\ u \Downarrow_M v \wedge [x_1, \dots, x_n] \simeq u \wedge y \simeq v \iff f(x_1, \dots, x_n) = y \end{aligned}$$

Definition 2.1.14. (Decidable) A Turing machine M decides $\mathcal{L} \subseteq \Sigma^*$ iff the characteristic function $\chi_{\mathcal{L}}: \Sigma^* \rightarrow \{0, 1\}$ is computable.

A language $\mathcal{L} \subseteq \Sigma^*$ is *decidable* iff there exists a Turing machine M that decides \mathcal{L} .

Definition 2.1.15. (Acceptable) A language $\mathcal{L} \subseteq \Sigma^*$ is *acceptable* iff the partial function $\text{acc}_{\mathcal{L}}: \Sigma^* \rightarrow \{1\}$ s.t

$$\forall x \in \Sigma^*. x \in \mathcal{L} \iff \text{acc}_{\mathcal{L}}(x) = 1$$

The language $\mathcal{L}(M) \subseteq \Sigma^*$ that is *accepted* by the labelled Turing machine $M \in \text{TM}_{\Sigma}^k(\{-, \text{acc}, \text{rej}\})$ is defined by

$$\mathcal{L}(M) = \{u \in \Sigma^* : \exists v \in \Sigma^*. u \Downarrow_M^q v \wedge \text{lab}(q) = \text{acc}\}$$

- Acceptable is a *weaker* property than decidable (since acceptable may have a non-terminating computation for $u \notin \mathcal{L}$) \implies Hierarchy of languages

Definition 2.1.16. (Recursive and Recursively Enumerable Languages)

Let $\mathcal{L} \subseteq \Sigma^*$ be a formal language:

- (i) \mathcal{L} is *recursively enumerable* iff \mathcal{L} is acceptable
- (ii) \mathcal{L} is *recursive* iff \mathcal{L} is decidable.

Theorem 2.1.3. For all $\mathcal{L} \subseteq \Sigma^*$:

$$\mathcal{L} \text{ is recursive} \implies \mathcal{L} \text{ is recursively enumerable}$$

2.1.2 Time and Space Complexity

Definition 2.1.17. (Running Time) The *running* time of a k -tape Turing machine $M \in \text{TM}_\Sigma^k$ on $u_1, \dots, u_\ell \in \Sigma^*$ is $t_M(u_1, \dots, u_\ell) = k \in \mathbb{N}$ iff

$$\begin{aligned} \exists q \in Q, (\tau_i) \in \text{Tape}_\Sigma. \\ (q_0, \tau_0(u_1), \dots, \tau_0(u_\ell), \dots, \tau_0) \xrightarrow{^k_M} (q, \tau_1, \dots, \tau_k) \not\rightarrow \end{aligned}$$

For non-terminating computations, $t_M(u_1, \dots, u_\ell) = \infty$.

Definition 2.1.18. (Time Bound) The time bound of a k -tape Turing machine $M \in \text{TM}_\Sigma^k$ is $f : \mathbb{N} \rightarrow \mathbb{N}$ iff

$$\forall u_1, \dots, u_\ell \in \Sigma^*. t_M(u_1, \dots, u_\ell) \leq f\left(\sum_{i=1}^{\ell} |u_i|\right)$$

- Asymptotic notation is used to denote *asymptotic time bounds* (or *time complexity*) of TMs.

Definition 2.1.19. (Time Complexity) The time complexity of a k -tape Turing machine $M \in \text{TM}_\Sigma^k$ is $O(g(n))$ s.t the time bound of M , $f(n) \in O(g(n))$.

- **Problem:** Space complexity is defined on space used (excluding input) \implies we require a Turing machine w/ I/O conventions.

Definition 2.1.20. (Turing Machine with I/O) A k -tape Turing Machine $M = (Q, \Sigma, q_0, \delta, H)$ w/ I/O is a k -tape Turing Machine M that satisfies:

- (i) The first ℓ -tapes are *read-only* where $\ell < k$.

$$\forall 1 \leq i \leq \ell.$$

$$\forall q, q' \in Q, (a_i), (a'_i) \in \mathcal{O}(\Sigma), (D_i) \in \text{Direction}.$$

$$\delta(q, a_1, \dots, a_i, \dots, a_k) = (q', (a'_1, D_1), \dots, (a'_i, D_i), \dots, (a'_k, D_k)) \implies a_i = a'_i$$

- (ii) The last tape is *write-only* (cannot move to the left)

$$\forall q, q' \in Q, (a_i), (a'_i) \in \mathcal{O}(\Sigma), (D_i) \in \text{Direction}$$

$$\delta(q, a_1, \dots, a_k) = (q', (a'_1, D_1), \dots, (a'_k, D_k)) \implies D_k \neq \leftarrow$$

- **Notation:** The set of k -tape Turing Machines w/ I/O is denoted IO_TM_Σ^k

Theorem 2.1.4. (IO Equivalence)

$$\forall M \in \text{TM}_\Sigma^k. \exists N \in \text{IO_TM}_\Sigma^{k+\ell+1} \\ \forall (u_i), v \in \Sigma^*. (u_1, \dots, u_\ell) \Downarrow_M v \iff (u_1, \dots, u_\ell) \Downarrow_N v$$

Definition 2.1.21. (Space) For a k -tape Turing machine $M \in \text{IO_TM}_\Sigma^k$ w/ I/O on input $u_1, \dots, u_\ell \in \Sigma^*$, the *space used* is $s_M(u_1, \dots, u_\ell) \in \mathbb{N}$ is defined as

$$s_M(u_1, \dots, u_\ell) = \sum_{i=\ell+1}^{k-1} |\text{contents}(\tau_i)|$$

where

$$\exists q \in Q, (\tau_i) \in \text{Tape}_\Sigma. \\ (q_0, \tau_0(u_1), \dots, \tau_0(u_\ell), \dots, \tau_0) \longrightarrow_M^* (q, \tau_1, \dots, \tau_k) \not\rightarrow$$

Definition 2.1.22. (Space Bound) The space bound of a Turing machine M is $f : \mathbb{N} \rightarrow \mathbb{N}$ iff

$$\forall u_1, \dots, u_\ell \in \Sigma^*. t_M(u_1, \dots, u_\ell) \leq f\left(\sum_{i=1}^{\ell} |u_i|\right)$$

- Asymptotic space complexity is the asymptotic space bound of a TM.

Definition 2.1.23. (Time Complexity) The space complexity of a k -tape Turing machine $M \in \text{IO_TM}_\Sigma^k$ is $O(g(n))$ s.t the space bound of M , $f(n) \in O(g(n))$.

- **Convention:** Generally denote the space complexity of TM $M \in \text{TM}_\Sigma^k$ w/ the space complexity of it's equivalent TM $M' \in \text{IO_TM}_\Sigma^{k+\ell+1}$

2.2 Non-Deterministic Turing Machines

Definition 2.2.1. (Non-Deterministic Turing Machines) A non-deterministic k -tape Turing machine N is the 5-tuple $N = (Q, \Sigma, q_0, \Delta, H)$:

- (i) Q, Σ, q_0 and H are as defined in ??
- (ii) $\Delta : (Q \times \mathcal{O}(\Sigma)^k) \rightarrow \mathcal{P}(Q \times (\mathcal{O}(\Sigma) \times \{\leftarrow, -, \rightarrow\})^k)$ is the transition relation.
- **Notation:** The set of k -tape NTMs over Σ is denoted NTM_Σ^k
- Equivalent definitions for non-deterministic Turing machine configurations (See ??)

Definition 2.2.2. (Transition Relation) The transition relation for n -tape NTM $N = (Q, \Sigma, q_0, \Delta, H)$, denoted $\rightarrow_N: \mathcal{C}(N) \rightarrow \mathcal{C}(N)$ is inductively defined by

$$\frac{\text{current}(\tau_i) = a_i \quad (q', \text{act}_1, \dots, \text{act}_n) \in \Delta(q, a_i) \quad \tau_i \xrightarrow{\text{act}_i} \tau'_i}{(q, \tau_1, \dots, \tau_n) \rightarrow_N (q', \tau'_1, \dots, \tau'_n)} [q \notin H]$$

- **Note:** Determinism (theorem ??) no-longer holds for NTMs \implies *execution tree of configurations*: IMAGE
A *computation tree*.
- Equivalent definitions for computations, computable, etc.

2.2.1 Time and Space Complexity

- Time and space bounds are equivalently defined. See ??

Theorem 2.2.1. For all $N \in \text{NTM}_\Sigma^k$, that accepts $L(N)$ w/ $f(n)$ time bound, there exists a deterministic Turing machine $M \in \text{TM}_\Sigma^n$ s.t $L(N) = L(M)$ w/ time bound $O(c^{2f(n)})$ for some $n \in \mathbb{N}, c > 1$.

- Deterministic simulation of NTM is performed by a breadth-first search of the computation tree.

3 Complexity Classes

3.1 Complexity Classes

- **Idea:** Classify languages via bounds, specified by
 - A model of computation
 - A resource (time, space, # cores, etc)
 - A bound on the resource.

Definition 3.1.1. (Complexity Class) A complexity class \mathcal{C} is the set $\mathcal{C} \subseteq \mathcal{P}(\Sigma^*)$, where $\mathcal{L} \in \mathcal{C}$ is decidable in some model of computation w/ a bound on a given resource.

- Complexity classes define a collection of *computationally similar* problems \implies reasoning about classes

3.1.1 Reductions

- **Idea:** Solving problems via *reductions*.

Definition 3.1.2. (Reduction) A reduction of $\mathcal{L}_1 \subseteq \Sigma_1^*$ to $\mathcal{L}_2 \subseteq \Sigma_2^*$ is a Turing computable function $f : \Sigma_1^* \rightarrow \Sigma_2^*$ s.t

$$\forall x \in \Sigma_1^*. x \in \mathcal{L}_1 \iff f(x) \in \mathcal{L}_2$$

- A reduction $f : \Sigma_1^* \rightarrow \Sigma_2^*$ reduces \mathcal{L}_1 to $\mathcal{L}_2 \implies$ if \mathcal{L}_2 is *decidable* then \mathcal{L}_1 must be.
- **Notation:** $f : \mathcal{L}_1 \rightarrow \mathcal{L}_2$ denotes a reduction from \mathcal{L}_1 to \mathcal{L}_2

Lemma 3.1.1. For all reductions $f : \mathcal{L}_1 \rightarrow \mathcal{L}_2$,

$$\mathcal{L}_2 \text{ is decidable} \implies \mathcal{L}_1 \text{ is decidable.}$$

Proof. Let $\mathcal{L}_1 \subseteq \Sigma_1^*$, $\mathcal{L}_2 \subseteq \Sigma_2^*$ be arbitrary. Let $f : \mathcal{L}_1 \rightarrow \mathcal{L}_2$ be an arbitrary \mathcal{L}_1 to \mathcal{L}_2 reduction.

Let us assume that \mathcal{L}_2 is decidable. Hence $\chi_{\mathcal{L}_2} : \Sigma_2^* \rightarrow \{0, 1\}$ is computable. By definition ??,

$$\forall x \in \Sigma_1^*. \chi_{\mathcal{L}_1}(x) = 1 \iff \chi_{\mathcal{L}_2}(f(x)) = 1.$$

Hence $\chi_{\mathcal{L}_1} = \chi_{\mathcal{L}_2} \circ f$. By theorem ??, $\chi_{\mathcal{L}_1}$ is computable. Hence \mathcal{L}_1 is decidable. \square

Corollary 3.1.0.1. For all reductions $f : \mathcal{L}_1 \rightarrow \mathcal{L}_2$,

$$\mathcal{L}_1 \text{ is undecidable} \implies \mathcal{L}_2 \text{ is undecidable.}$$

- Corollary ?? provides a method for proving whether a \mathcal{L} is undecidable:
 - Determine a reduction $f : H \rightarrow \mathcal{L}$ where H is the *halting problem* (see section ??)

Definition 3.1.3. (Hardness Relation) The *hardness* relation $\leq : \mathcal{P}(\Sigma^*) \dashrightarrow \mathcal{P}(\Sigma^*)$ defined by

$$\mathcal{L}_1 \leq \mathcal{L}_2 \iff \exists \text{ reduction } f : \mathcal{L}_2 \rightarrow \mathcal{L}_1$$

We say that \mathcal{L}_2 is at least as *hard* as \mathcal{L}_1 .

Theorem 3.1.1. (Preorder of Hardness) $\leq : \mathcal{P}(\Sigma^*) \dashrightarrow \mathcal{P}(\Sigma^*)$ is a pre-order.

Definition 3.1.4. (\mathcal{C} -Reductions) A reduction $f : \mathcal{L}_1 \rightarrow \mathcal{L}_2$ is a \mathcal{C} -reduction if the language $\{x \cdot y : f(x) = y\} \in \mathcal{C}$. Similarly, for the Hardness relation, denoted $\leq_{\mathcal{C}}$.

Definition 3.1.5. (Closure of \mathcal{C} -Reductions) \mathcal{C} is closed under \mathcal{C} -reductions iff

$$\forall \mathcal{L}_1, \mathcal{L}_2 \subseteq \Sigma^*. \mathcal{L}_1 \leq_{\mathcal{C}} \mathcal{L}_2 \wedge \mathcal{L}_1 \in \mathcal{C} \implies \mathcal{L}_2 \in \mathcal{C}$$

- All classes \mathcal{C} of interest are closed under \mathcal{C} -reductions.

3.1.2 Completeness

- **Idea:** Hardness relation \implies ordering on decision problems in a class.

Definition 3.1.6. (Completeness) For $\mathcal{L} \in \mathcal{C}$, \mathcal{L} is \mathcal{C} -complete iff

$$\forall \mathcal{L}' \in \mathcal{C}. \mathcal{L} \leq \mathcal{L}'$$

Definition 3.1.7. (Hardness) A language $\mathcal{L} \subseteq \Sigma^*$ is \mathcal{C} -hard iff

$$\forall \mathcal{L}' \in \mathcal{C}. \mathcal{L} \leq \mathcal{L}'$$

- Hardness and Completeness allow reasoning about the *hierarchy* of classes.
- Complete problems also “determine” the hardness of a class

3.2 Polynomial Time

- Deterministic Turing machines \implies deterministic time and space complexity classes

Definition 3.2.1. (Time Complexity Class) Let $f : \mathbb{N} \rightarrow \mathbb{N}$. $\text{TIME}(f(n)) \subseteq \mathcal{P}(\Sigma^*)$ is the complexity class (set of languages) s.t $\mathcal{L} \in \text{TIME}(f(n)) \iff \mathcal{L}$ is decidable by a TM w/ time bound $O(f(n))$.

Definition 3.2.2. (Space Complexity Class) Let $f : \mathbb{N} \rightarrow \mathbb{N}$. $\text{SPACE}(f(n)) \subseteq \mathcal{P}(\Sigma^*)$ is the complexity class (set of languages) s.t $\mathcal{L} \in \text{SPACE}(f(n)) \iff \mathcal{L}$ is decidable by a TM w/ space bound $O(f(n))$.

Definition 3.2.3. (Polynomial Time Complexity Class) The polynomial time complexity class P is defined by

$$P = \bigcup_{k=1}^{\infty} \text{TIME}(n^k)$$

- P defines the set of *feasibly* computable languages.

Definition 3.2.4. (Tractable and Intractable) For $\mathcal{L} \subseteq \Sigma^*$, if $\mathcal{L} \in P$, then \mathcal{L} is said to be *tractable*. Conversely, if $\mathcal{L} \notin P$, then \mathcal{L} is *intractable*

- **Note:** Definitions of tractability and intractability *are not always* sound (e.g. worst-case exponential algorithms are used in practice).

Definition 3.2.5. (Polynomial Time Reductions) A reduction $f : \mathcal{L}_1 \rightarrow \mathcal{L}_2$ is a *polynomial time reduction* iff the TM M that computes f has a polynomial time bound $O(n^k)$.

Lemma 3.2.1. P is closed under P-reductions.

3.2.1 Problems

3.2.1.1 Reachability

Definition 3.2.6. (Reachability) The reachability problem is defined as the *decision problem*:

Given a directed graph $G = (V, E)$ and vertices $u, v \in V$, determine whether $u \rightarrow^* v$.

Denoted $\text{Reachability}(G, u, v)$.

- Reachability is a *decision problem*
- **Solution:** BFS / DFS. See Algorithms IA notes
- **Complexity:** $O(|V|^2)$

3.2.1.2 Max Flow

Definition 3.2.7. (Network) A network $N = (V, E, s, t, c)$ is a directed graph $G = (V, E)$ w/ vertices $s, t \in V$ denoting the source and sink respectively, and $c : E \rightarrow \mathbb{N}$ denoting the *capacity function*.

Definition 3.2.8. (Flow) A flow f is a function $f : E \rightarrow \mathbb{N}$ in the network N satisfying:

- (i) Capacity: $\forall (u, v) \in E. f(u, v) \leq c(u, v)$
- (ii) Conservation:

$$\forall v \in V \setminus \{s, t\}. \sum_{u:(u,v) \in E} f(u, v) = \sum_{w:(v,w) \in E} f(v, w)$$

Definition 3.2.9. (Value) The value of a flow f in N is defined as

$$\begin{aligned} \text{value}(f) &= \sum_{u:(s,u) \in E} f(s, u) - \sum_{v:(v,s) \in E} f(v, s) \\ &= \sum_{u:(u,t) \in E} f(u, t) - \sum_{v:(t,v) \in E} f(t, v) \end{aligned}$$

Definition 3.2.10. (Max Flow) The max flow problem is defined as the *optimization problem*:

Given a network N , determine a flow f s.t

$$f = \arg \max_{\text{flow } f} \text{value}(f)$$

Denoted $\text{MaxFlow}(N)$.

- **Note:** MaxFlow is an *optimization problem*. However, all optimization problems have an equivalent *decision problem*

Definition 3.2.11. (Bounded Max Flow) The bounded max flow problem is defined as the *decision problem*:

Given a network N and bound k , determine whether

$$\max_{\text{flow } f} \text{value}(f) \leq k$$

Denoted $\text{MaxFlow}(N, k)$.

Definition 3.2.12. (Cut) A cut (S, \bar{S}) on the network N is a *partition* on V , s.t $s \in S$ and $t \in \bar{S}$. The value of a cut (S, \bar{S}) is defined by

$$\text{value}(S, \bar{S}) = \sum_{\substack{u \in S, v \in \bar{S} \\ (u,v) \in E}} c(u, v)$$

Theorem 3.2.1. (Max Flow, Min Cut Theorem) For all flows f and cuts (S, \bar{S}) on N :

$$\text{value}(f) \leq \text{value}(S, \bar{S})$$

Proof. Let $N = (V, E, s, t, c)$ be an arbitrary network. Let f and (S, \bar{S}) be arbitrary flows and cuts on N .

Let us extend c and f , to be defined on $V^2 \rightarrow \mathbb{N}$ s.t

$$\forall (u, v) \notin E. c(u, v) = f(u, v) = 0$$

So we have

$$\begin{aligned}
 \text{value}(f) &= \sum_{u \in V} f(s, u) - \sum_{u \in V} f(u, s) \\
 &= \sum_{v \in S} \left(\sum_{u \in V} f(v, u) - \sum_{u \in V} f(u, v) \right) && \text{Conversation} \\
 &= \sum_{v \in S} \sum_{u \in S} f(v, u) + \sum_{v \in S} \sum_{u \in \bar{S}} f(v, u) \\
 &\quad - \sum_{v \in S} \sum_{u \in S} f(u, v) - \sum_{v \in S} \sum_{u \in \bar{S}} f(u, v) \\
 &= \sum_{v \in S} \sum_{u \in \bar{S}} f(v, u) - \sum_{v \in S} \sum_{u \in \bar{S}} f(u, v) \\
 &\leq \sum_{v \in S} \sum_{u \in \bar{S}} f(v, u) && f(u, v) \geq 0 \\
 &\leq \sum_{v \in S} \sum_{u \in \bar{S}} c(v, u) && \text{Capacity} \\
 &= \text{value}(S, \bar{S})
 \end{aligned}$$

□

- **Observation:** A flow f is *not optimal* \iff there exists a flow f' s.t $\Delta f = f' - f$ has the value $\text{value}(\Delta f) \geq 0$.

Problem: Augmenting flow Δf is negative on some edges \implies *backwards edges*

Definition 3.2.13. (Residual Network) The residual network $N(f)$ of a flow f on $N = (V, E, s, t, c)$ is defined as $N(f) = (V, E', s, t, c')$ where

$$\begin{aligned}
 E' &= E \setminus \{(u, v) \in E : f(u, v) = c(u, v)\} \\
 &\quad \cup \{(u, v) \in V^2 : (v, u) \in E \wedge f(v, u) > 0\}
 \end{aligned}$$

and

$$c'(u, v) = \begin{cases} c(u, v) - f(u, v) & \text{if } (u, v) \in E \\ f(v, u) & (u, v) \in E' \setminus E \end{cases}$$

So by definition: f is optimal \iff there is no positive flow Δf in $N(f)$

• **Solution:**

1. Determining a positive flow Δf consists of determining a path in $N(f) \implies$ reduces to **Reachability** ($O(|V|^2)$)
2. Compute flow $f \leftarrow f + \Delta f$
3. Repeat 1, 2 until no such flow Δf exists.

• **Complexity:**

- Finding the augmenting flow Δf : $O(|V|^2)$
- Each flow adds at least 1 to $\text{value}(f)$. Defined $F = \max_{\text{flow } f} \text{value}(f) \implies O(F)$ iterations
- $O(|V|^2 F)$

3.2.1.3 Matching

Didn't really appreciate the hetro and cis normativity of this chapter...

Definition 3.2.14. (Bipartite Graph) A Bipartite graph B is the tuple $B = (U, V, E)$ where $U \cap V \neq \emptyset$ and $E \subseteq U \times V$.

Definition 3.2.15. (Matching) A matching on B is a set $M \subseteq E$ satisfying

$$\forall (u, v), (u', v') \in M. u \neq u' \wedge v \neq v'$$

- A matching defines a *bijection* between subsets of U, V .

Definition 3.2.16. (Matching) The matching problem is defined as the decision problem:

Given a Bipartite graph B , determine whether a matching M exists

Denoted $\text{Matching}(B)$.

- **Solution:**

- Reduction from $\text{Matching}(B)$ to $\text{MaxFlow}(N, n)$ with network $N = (\{s, t\} \cup U \cup V, E', s, t, c)$ where

$$E' = \{(s, u) : u \in U\} \cup E \cup \{(v, t) : v \in V\}$$

$$c = \mathbf{1}$$

and $n = \max\{|U|, |V|\}$

- **Complexity:** $O(n^3)$.

3.2.2 co-P

3.3 Non-Deterministic Polynomial Time

- Non-Deterministic Turing machines \implies non-deterministic time and space complexity classes

Definition 3.3.1. (NTime Complexity Class) Let $f : \mathbb{N} \rightarrow \mathbb{N}$. $\text{NTIME}(f(n)) \subseteq \mathcal{P}(\Sigma^*)$ is the complexity class (set of languages) s.t $\mathcal{L} \in \text{NTIME}(f(n)) \iff \mathcal{L}$ is decidable by a NTM w/ time bound $O(f(n))$.

Definition 3.3.2. (NSpace Complexity Class) Let $f : \mathbb{N} \rightarrow \mathbb{N}$. $\text{NSPACE}(f(n)) \subseteq \mathcal{P}(\Sigma^*)$ is the complexity class (set of languages) s.t $\mathcal{L} \in \text{NSPACE}(f(n)) \iff \mathcal{L}$ is decidable by a NTM w/ space bound $O(f(n))$.

Definition 3.3.3. (NP Complexity Class) The non-deterministic polynomial time complexity class NP is defined by

$$\text{NP} = \bigcup_{k=1}^{\infty} \text{NTIME}(n^k)$$

Lemma 3.3.1. NP is closed under P-reductions.

Definition 3.3.4. (NP Complexity Class) *Equivalently*, a language $\mathcal{L} \subseteq \Sigma^*$ is in NP \iff

$$\mathcal{L} = \{x \in \Sigma^* . \exists y \in \Sigma^* . R(y, x)\},$$

where $R : \Sigma^* \rightarrow \Sigma^*$ satisfying:

- R is decidable in polynomial time by the TM M
- R is *polynomially balanced*:

$$\forall y, x \in \Sigma^*. R(y, x) \implies |y| \leq p(|x|),$$

where p is some polynomial.

- y is the *certificate* of $x \in \mathcal{L}$

3.3.1 Propositional Logic \mathcal{L}_0 Problems

3.3.1.1 SAT

Definition 3.3.5. (SAT) The satisfiability problem is defined as the decision problem:

Given a proposition $\psi \in \mathcal{L}_0$, determine whether ψ is satisfiable.

Denoted $\text{SAT}(\psi)$.

- **Note:** VAL reduces to SAT by $\models \psi \iff \neg\psi$ is unsatisfiable.
- **Solution:**
 - Consider $2^{|\llbracket \psi \rrbracket_P|}$ possible interpretations (by coincidence lemma I)
 - $O(|\llbracket \psi \rrbracket_P|^2)$ algorithm for determining $\mathcal{T} \llbracket \psi \rrbracket_{\mathcal{I}} = 1$.
- **Complexity:** $O(2^{|\llbracket \psi \rrbracket_P|} |\llbracket \psi \rrbracket_P|^2)$.

Lemma 3.3.2. $\text{SAT} \in \text{NP}$.

Theorem 3.3.1. SAT is NP-complete.

Proof. We show that

$$\forall \mathcal{L} \in \text{NP}. \mathcal{L} \leq \text{SAT}$$

Let $\mathcal{L} \in \text{NP}$ be arbitrary. By definition, there exists a NTM $M = (Q, \Sigma, q_0, \Delta, H)$ that decides \mathcal{L} w/ polynomial time bound $f(|x|) \in O(|x|^k)$ for some $k \geq 0$.

We wish to define a reduction $f : \mathcal{L} \rightarrow \mathbf{SAT}$. Let $x \in \Sigma^*$ be arbitrary. Define the set of propositional symbols $\Omega(x) \subseteq \Sigma_P$ as:

$S_{i,q}$ will be true if M is in state q at step i $i \leq |x|^k, q \in Q$
 $T_{i,j,a}$ will be true if tape τ is at position j w/ current a at step i $i, j \leq |x|^k, a \in \mathcal{O}(\Sigma)$
 $H_{i,j}$ will be true if head is at position j at step i $i, j \leq |x|^k$

Note that $|\Omega(x)| = |Q||x|^k + |\Sigma||x|^{2k} + |x|^{2k}$.

The proposition $f(x) = \psi$ is defined by the conjunction of:

$S_{1,q_0} \wedge H_{1,1}$	Computation starts in state q_0 at position 1
$\bigwedge_i \bigwedge_j \left(H_{i,j} \rightarrow \bigwedge_{k \neq j} \neg H_{i,k} \right)$	Tape position cannot be in 2 positions at once
$\bigwedge_i \bigwedge_q \left(S_{i,q} \rightarrow \bigwedge_{q' \neq q} \neg S_{i,q'} \right)$	Cannot be in 2 states at once
$\bigwedge_i \bigwedge_j \bigwedge_a \left(T_{i,j,a} \rightarrow \bigwedge_{a' \neq a} \neg T_{i,j,a'} \right)$	Cannot have 2 symbols in the same position at once
$\bigwedge_{j \leq x } T_{1,j,[x_j]} \wedge \bigwedge_{ x < j} T_{1,j,\emptyset}$	Initially, tape contains $ x $ (and nothing else)
$\bigwedge_i \bigwedge_j \bigwedge_{j' \neq j} \bigwedge_a (H_{i,j} \wedge T_{i,j',a}) \rightarrow T_{i+1,j',a}$	Only the tape changes under the head
$\bigwedge_i \bigwedge_j \bigwedge_a \bigwedge_q (H_{i,j} \wedge S_{i,q} \wedge T_{i,j,a})$ $\rightarrow \bigvee_{\Gamma} (H_{i+1,j'} \wedge S_{i+1,q'} \wedge T_{i+1,j,a'})$	Transitions
<p>where $\Gamma = \{(q', j', a') : (q', a', D) \in \Delta(q, a) \wedge j' = \llbracket j \rrbracket_D\}$.</p> $\bigvee_{q \in \text{lab}(\text{acc})} \bigvee_i S_{i,q}$	Halts at some point.

We now show that

$$x \in \mathcal{L} \iff f(x) \in \text{SAT}$$

(\implies). Let us assume that $x \in \mathcal{L}$, so we have

$$\exists q_{\text{acc}} \in \text{lab}(\text{acc}), u \in \Sigma^*. (q_0, \tau_0(x)) \longrightarrow_M^{|x|^k} (q_{\text{acc}}, u)$$

Let $c_i = (q_i, \tau_i)$ denote the i th configuration in the above computation. Let us define the interpretation $\mathcal{I} \in \Sigma_{\mathcal{I}}$ s.t

$$\begin{aligned} \mathcal{I}(S_{i,q_i}) &= 1 \\ \mathcal{I}(T_{i,j,a}) &= (a = \tau_i[j]) \\ \mathcal{I}(H_{i,j}) &= \text{index}(\tau_i) \end{aligned}$$

where

$$\begin{aligned} \text{index}(\triangleright, _) &= 1 \\ \text{index}(\triangleright u, _) &= |u| + 1 \end{aligned}$$

By definition of the tape semantics, Δ , and the computation, we have $\mathcal{T}[\psi]_{\mathcal{I}} = 1$.

(\impliedby). Let us assume that $f(x) = \psi \in \text{SAT}$. Then there exists $\mathcal{I} \in \Sigma_{\mathcal{I}}$ s.t $\mathcal{T}[\psi]_{\mathcal{I}} = 1$. We define the computation $c_i = (q_i, \tau_i)$ s.t

$$\begin{aligned} q_i &= q & \mathcal{I}(S_{i,q}) &= 1 \\ \tau_i &= (\triangleright a_1 \dots a_j, a_{j+1} \dots a_m) & \mathcal{I}(T_{i,k,a_{k-1}}) &= 1, \mathcal{I}(H_{i,j-1}) = 1 \end{aligned}$$

By (2), (3), (4), q_i and τ_i are unique. By (1), $c_0 = (q_0, \tau_0(x))$. By (5) and (6), the computation $c_0 \longrightarrow_M c_1 \longrightarrow \dots$ satisfies \longrightarrow_M , and by (7),

$$\exists q_{\text{acc}} \in \text{lab}(\text{acc}), u \in \Sigma^*. (q_0, \tau_0(x)) \longrightarrow_M^* (q_{\text{acc}}, u)$$

Hence since M decides \mathcal{L} , we have $x \in \mathcal{L}$. □

- **Note:** ψ encodes M and x . Constructing ψ is done in polynomial time.

3.3.1.2 CNF

Definition 3.3.6. (CNF) The CNF satisfiability problem is defined as the decision problem:

Given proposition $\psi = \bigwedge_i \bigvee_j \ell_{ij} \in \mathcal{L}_0^{CNF}$, determine whether ψ is satisfiable.

- Translation function $\llbracket \cdot \rrbracket^{CNF} : \mathcal{L}_0 \rightarrow \mathcal{L}_0^{CNF}$ defines reduction to CNF satisfiability.
- **Problem:** Reduction is *not polynomial* but exponential (by distributive law).
- **Solution:** Convert (1), (2), ..., (7) directly into CNF. Resulting in polynomial increases.

Lemma 3.3.3. CNF is NP-complete.

Proof. (Sketch) Polynomial reduction from SAT to CNF. Closure and transitivity of $\leq_P \implies$ CNF is NP-complete. \square

Definition 3.3.7. (3 CNF) A proposition $\psi \in \mathcal{L}_0$ is said to be in 3 CNF iff $\forall C_i \in \llbracket \psi \rrbracket_\Delta \cdot |C_i| \leq 3$.

The set of 3 CNF propositions is denoted \mathcal{L}_0^{3CNF}

Definition 3.3.8. (CNF) The 3CNF satisfiability problem is defined as the decision problem:

Given proposition $\psi = \bigwedge_i \bigvee_{j \leq 3} \ell_{ij} \in \mathcal{L}_0^{3CNF}$, determine whether ψ is satisfiable.

Lemma 3.3.4. 3CNF is NP-complete.

Proof. (Sketch) We have the following reduction $f : \text{CNF} \rightarrow \text{3CNF}$:

$$f\left(\bigwedge_{i=1}^n \bigvee_{j=1}^{m_i} \ell_{ij}\right) = \bigwedge_{i=1}^n \left((\ell_{i1} \vee \ell_{i2} \vee P_{i2}) \wedge \bigwedge_{j=2}^{m-3} (\neg P_{ij} \vee \ell_{i(j+1)} \vee P_{i(j+1)}) \wedge (\neg P_{i(m-2)} \vee \ell_{i(m-1)} \vee \ell_{im}) \right)$$

where $P_{ij} \notin \llbracket \psi \rrbracket_P$.

Note that ψ is satisfiable $\iff f(\psi)$ is satisfiable. We also note that polynomial increase in propositional symbols occurs due to $f \implies$ polynomial reduction. \square

3.3.2 Graph Problems

3.3.2.1 Independent Set

Definition 3.3.9. (Independent Set) For a undirected graph $G = (V, E)$, a set $I \subseteq V$ is said to be *independent* \iff

$$\forall u, v \in I. (u, v) \notin E.$$

- Every graph $G = (V, E)$ w/ $|V| \geq 1$ has a *trivial* independent set: $I = \{v\}$ w/ $v \in V$ (assuming no loops).

Definition 3.3.10. (Independent) The independent set problem is defined as the optimization problem:

Given $G = (V, E)$, determine

$$I = \arg \max_{\text{independent } I} |I|$$

Denoted $\text{Independent}(G)$

Definition 3.3.11. (Bounded Independent) The bounded independent set problem is defined as the decision problem:

Given $G = (V, E)$ and k , determine whether

$$\max \{|I| : \text{independent } I\} = k$$

Denoted $\text{Independent}(G, k)$

- **Solution:** $2^{|V|}$ subsets of V . $O(|V|^2)$ method of determining whether $I \subseteq V$ is independent.
- **Complexity:** $O(2^{|V|}|V|^2)$.

Lemma 3.3.5. $\text{Independent} \in \text{NP}$

Theorem 3.3.2. Independent is NP-complete.

Proof. We proceed by defining a polynomial reduction from 3CNF to Independent, $f : 3\text{CNF} \rightarrow \text{Independent}$, where

$$f\left(\bigwedge_{i=1}^n \bigvee_{j=1}^3 \ell_{ij}\right) = (G, n)$$

where $G = (V, E)$ and

$$\begin{aligned} V &= \{v_{ij} : 1 \leq i \leq n, 1 \leq j \leq 3\} \\ E &= \{(v_{ij}, v_{ik}) : 1 \leq i \leq n, 1 \leq j < k \leq 3\} \\ &\quad \cup \{(v_{ij}, v_{kl}) : i \neq k \wedge \ell_{ij} \equiv \neg \ell_{kl}\} \end{aligned}$$

We now show that

$$\forall \psi \in \Sigma^*. \psi \in 3\text{CNF} \iff f(\psi) \in \text{Independent}$$

Let $\psi \in \Sigma^*$ be arbitrary.

(\implies). Let us assume that $\psi = \bigwedge_{i=1}^n \bigvee_{j=1}^3 \ell_{ij} \in 3\text{CNF}$. Hence there exists interpretation $\mathcal{I} \in \Sigma_{\mathcal{I}}$ s.t

$$\begin{aligned} &\mathcal{T}[\llbracket \psi \rrbracket]_{\mathcal{I}} = 1 \\ \iff &\forall 1 \leq i \leq n. \mathcal{T}[\llbracket \bigvee_{j=1}^3 \ell_{ij} \rrbracket]_{\mathcal{I}} = 1 \\ \iff &\forall 1 \leq i \leq n. \exists 1 \leq j \leq 3. \mathcal{T}[\llbracket \ell_{ij} \rrbracket]_{\mathcal{I}} = 1 \end{aligned}$$

Let us introduce the witnesses $1 \leq j_1, \dots, j_n \leq 3$ s.t $\mathcal{T}[\llbracket \ell_{ij_i} \rrbracket]_{\mathcal{I}} = 1$. Define the set $I = \{v_{ij_i} : 1 \leq i \leq n\} \subseteq V$. We have $|I| = n$. So we wish to show that

$$\forall v_{ij}, v_{kl} \in I. (v_{ij}, v_{kl}) \notin E$$

Let $v_{ij}, v_{kl} \in I$ be arbitrary. We proceed by contradiction. Let us assume that $(v_{ij}, v_{kl}) \in E$. We have the following cases (by definition of E):

- $i = k$. Let us assume that $i = k$. A contradiction! By definition of I .
- $i \neq k \wedge \ell_{ij} \equiv \neg \ell_{kl}$. So we have

$$\begin{aligned} &\mathcal{T}[\llbracket \ell_{ij} \rrbracket]_{\mathcal{I}} = 1 \\ \iff &\mathcal{T}[\llbracket \neg \ell_{kl} \rrbracket]_{\mathcal{I}} = 1 \\ \iff &\mathcal{T}[\llbracket \ell_{kl} \rrbracket]_{\mathcal{I}} = 0 \end{aligned}$$

A contradiction! Since $v_{kl} \in I$ and $\mathcal{T}[\llbracket \ell_{kl} \rrbracket]_{\mathcal{I}} = 1$ by the definable property of I .

(\Leftarrow). Let us assume that $f(\psi) = (G, n) \in \text{Independent}$, where $\psi = \bigwedge_{i=1}^n \bigvee_{j=1}^3 \ell_{ij}$ and $G = (V, E)$.

Hence there exists an independent set $I \subseteq V$ w/ $|I| = n$. Let us define the interpretation $\mathcal{I} \in \Sigma_{\mathcal{I}}$ s.t

$$\mathcal{T}[\ell_{ij}]_{\mathcal{I}} = 1 \iff v_{ij} \in I$$

We wish to show that $\mathcal{T}[\psi]_{\mathcal{I}} = 1$:

$$\begin{aligned} & \mathcal{T}[\psi]_{\mathcal{I}} = 1 \\ \iff & \forall 1 \leq i \leq n. \mathcal{T}[\bigvee_{j=1}^3 \ell_{ij}]_{\mathcal{I}} = 1 \\ \iff & \forall 1 \leq i \leq n. \exists 1 \leq j \leq 3. \mathcal{T}[\ell_{ij}]_{\mathcal{I}} = 1 \end{aligned}$$

TODO

□

3.3.2.2 Clique

Definition 3.3.12. (Clique) For a graph $G = (V, E)$, a set $X \subseteq V$ of vertices is a *clique* \iff

$$\forall u, v \in X. (u, v) \in E.$$

Definition 3.3.13. (Clique) The clique problem is defined as a optimization problem:

Given a graph G , determine

$$X = \arg \max_{\text{clique } X} |X|$$

Denoted $\text{Clique}(G)$

Definition 3.3.14. (Bounded Clique) The bounded clique problem is defined as a decision problem:

Given a graph G and k , determine whether

$$\max \{|X| : \text{clique } X\} \geq k$$

Denoted $\text{Clique}(G, k)$

- **Solution:** $2^{|V|}$ subsets of V . $O(|V|^2)$ method of determining whether $X \subseteq V$ is a clique.
- **Complexity:** $O(2^{|V|}|V|^2)$.

Lemma 3.3.6. Clique \in NP

Theorem 3.3.3. Clique is NP-complete

Proof. Suffices to prove that Independent \leq_P Clique. Define the reduction $f : \text{Independent} \rightarrow \text{Clique}$ s.t

$$f(G, k) = (\overline{G}, k)$$

where $G = (V, E)$, $\overline{G} = (V, \overline{E})$ and

$$\overline{E} = \{(u, v) \in V^2 : (u, v) \notin E\}.$$

We have

$$\begin{aligned} (G, k) \in \text{Independent} &\iff (\overline{G}, k) \in \text{Clique} \\ &\iff \exists I \subseteq V. |I| = k \wedge (\forall u, v \in I. (u, v) \notin E) \iff \exists X \subseteq V. |X| = k \wedge (\forall u, v \in X. (u, v) \in \overline{E}) \\ &\iff \exists I \subseteq V. |I| = k \wedge (\forall u, v \in I. (u, v) \notin E) \iff \exists X \subseteq V. |X| = k \wedge (\forall u, v \in X. (u, v) \notin E) \end{aligned}$$

By α -equivalence, f is a reduction. f is a polynomial reduction w/ time bound $O(|V|^2)$. So we have Independent \leq_P Clique. \square

3.3.2.3 Graph Colorability

Definition 3.3.15. (k -colorable) For a $G = (V, E)$, G is k -colorable if there exists a *coloring*

$$\chi : V \rightarrow [0, k-1],$$

s.t

$$\forall (u, v) \in E. \chi(u) \neq \chi(v)$$

Definition 3.3.16. (k -Colorable) The k -Colorable problem is defined as a decision problem:

Given a graph $G = (V, E)$, determine whether G is k -colorable.

Denoted k -Colorable(G)

- **Solution:** Determine $k^{|V|}$ possible functions $\chi : V \rightarrow [1, k]$. $O(|V|^2)$ algorithm for determining whether χ is a k -coloring.
- **Complexity:** $O(k^{|V|}|V|^2)$.
- 2-Colorable $\in P$ (determine whether G is Bipartite)

Theorem 3.3.4. 3-Colorable is NP-complete.

Proof. (Sketch) Suffices to prove $3\text{CNF} \leq_P 3\text{-Colorable}$. Define the reduction $f : 3\text{CNF} \rightarrow 3\text{-Colorable}$ s.t

$$f\left(\bigwedge_{i=1}^3 \bigvee_{j=1}^3 \ell_{ij}\right) = G,$$

where $G = (V, E)$ and

$$\begin{aligned} V &= \{a\} \cup \bigcup_{P \in \llbracket \psi \rrbracket_P} \{v_P, v_{\neg P}\} \cup \{v_{ij} : 1 \leq i \leq n, 1 \leq j \leq 3\} \\ E &= \bigcup_{P \in \llbracket \psi \rrbracket_P} \{(a, v_P), (a, v_{\neg P}), (v_P, v_{\neg P})\} \\ &\quad \cup \{(v_{ij}, v_{\ell_{ij}}) : 1 \leq i \leq n, 1 \leq j \leq 3\} \end{aligned}$$

We now show that $\forall \psi \in \Sigma^*. \psi \in 3\text{CNF} \iff f(\psi) \in 3\text{-Colorable}$. Let $\psi \in \Sigma^*$ be arbitrary.

(\implies). Let us assume that $\psi = \bigwedge_{i=1}^n \bigvee_{j=1}^3 \ell_{ij} \in 3\text{CNF}$. So there exists an interpretation $\mathcal{I} \in \Sigma_{\mathcal{I}}$ s.t $\mathcal{T} \llbracket \psi \rrbracket_{\mathcal{I}} = 1$. Define the coloring $\chi : V \rightarrow \{0, 1, 2\}$ s.t

$$\begin{aligned} \chi(a) &= 2 \\ \chi(v_P) &= \begin{cases} 1 & \text{if } \mathcal{I}(P) = 1 \\ 0 & \text{otherwise} \end{cases} \\ \chi(v_{\neg P}) &= \begin{cases} 1 & \text{if } \mathcal{I}(P) = 0 \\ 0 & \text{otherwise} \end{cases} \\ \chi(v_{i1}), \chi(v_{i2}), \chi(v_{i3}) &= 0, 1, 2 \quad \text{wlog } \mathcal{T} \llbracket \ell_{i1} \rrbracket = 1, \mathcal{T} \llbracket \ell_{i2} \rrbracket = 0 \end{aligned}$$

χ is trivially a coloring.

(\Leftarrow). Let us assume that $f(\psi) = G \in \text{3-Colorable}$. Without loss of generality (by renaming), there exists a coloring $\chi : V \rightarrow \{0, 1, 2\}$ s.t $\chi(a) = 2$. Hence $\{\chi(v_P), \chi(v_{\neg P})\} = \{0, 1\}$.

Define the interpretation $\mathcal{I} \in \Sigma_{\mathcal{I}}$ s.t

$$\begin{aligned}\mathcal{I}(P) = 1 &\iff \chi(v_P) = 1 \\ \mathcal{I}(P) = 0 &\iff \chi(v_{\neg P}) = 1\end{aligned}$$

We wish to show that $\mathcal{T} \llbracket \psi \rrbracket_{\mathcal{I}} = 1$. It suffices to show that $\forall 1 \leq i \leq n. \exists 1 \leq j \leq 3. \chi(v_{ij}) = 1$.

Let $1 \leq i \leq n$ be arbitrary. We proceed by contradiction. Let us assume that $\forall 1 \leq j \leq 3. \chi(v_{ij}) \neq 1 \in \{0, 2\}$. So we have $\chi(v_{i1}), \chi(v_{i2}), \chi(v_{i3}) \in \{0, 2\}$, so by the Pigeonhole principle, there exists $1 \leq j < j' \leq 3$ s.t $\chi(v_{ij}) = \chi(v_{ij'})$. A contradiction! \square

3.3.2.4 Hamiltonian Graph

Definition 3.3.17. (Hamiltonian Cycles and Graphs) For a graph $G = (V, E)$, a Hamiltonian cycle is a $v \xrightarrow{*}_{\text{path}} v$ path for some $v \in V$ and $\llbracket v \xrightarrow{*}_{\text{path}} v \rrbracket_V = V$.

A graph G is *Hamiltonian* if it contains a *Hamiltonian cycle*.

Definition 3.3.18. (Hamiltonian) The Hamiltonian graph problem is defined as the *decision problem*:

Given a graph G , determine whether G is Hamiltonian.

Denoted $\text{Hamiltonian}(G)$.

- **Solution:** Generate $O(|V|!)$ permutations of vertices. Verify permutation is a Hamiltonian cycle in $O(|V|)$ time.
- **Complexity:** $O(|V|!|V|)$

Lemma 3.3.7. $\text{Hamiltonian} \in \text{NP}$

Theorem 3.3.5. Hamiltonian is NP-complete.

3.3.2.5 TSP

Definition 3.3.19. (Travelling Salesperson Problem) The travelling salesperson problem is defined as the *optimization problem*:

Given a graph $G = (V, V \times V)$ w/ symmetric cost function $c : V \times V \rightarrow \mathbb{N}$ and $V = \{v_1, \dots, v_n\}$. Define the cost of a permutation $\pi : V \rightarrow V$ as

$$C(\pi) = c(\pi(v_1), \pi(v_n)) + \sum_{i=1}^{n-1} c(\pi(v_i), \pi(v_{i+1}))$$

Determine a permutation $\pi : V \rightarrow V$ s.t $\pi = \arg \min_{\pi} C(\pi)$.

Denoted $\text{TSP}(G, c)$.

- Optimization problem \rightarrow bounded decision problem

Definition 3.3.20. (Bounded TSP) The bounded TSP is defined as the *decision problem*:

Given a graph $G = (V, E)$ w/ symmetric cost function $c : V \times V \rightarrow \mathbb{N}$, and $k \in \mathbb{N}$, determine

$$C(\text{TSP}(G, c)) \leq k$$

Denoted $\text{TSP}(G, c, k)$

- **Complexity:**
 - Upper bound: Brute force: Check all permutations $O(n!)$
 - Lower bound: $\Omega(n \log n)$

Lemma 3.3.8. $\text{TSP} \in \text{NP}$

Theorem 3.3.6. TSP is NP-complete.

Proof. TODO REDUCTION FROM HAM TO TSP

□

3.3.3 Sets and Numbers

3.3.3.1 Tripartite Matching

Definition 3.3.21. A matching on disjoint X, Y, Z s.t $|X| = |Y| = |Z| = n$ is a set $M \subseteq X \times Y \times Z$ satisfying

$$\forall (x, y, z), (x', y', z') \in M. x \neq x' \wedge y \neq y' \wedge z \neq z',$$

and $|M| = n$.

- **Note:** Generalization of Matching (see section ??)

Definition 3.3.22. (Tripartite Matching) The tripartite matching problem is defined as the decision problem:

Given disjoint X, Y, Z and M , is M a matching

Denoted $3\text{Matching}(X, Y, Z, M)$

Lemma 3.3.9. $3\text{Matching} \in \text{NP}$

Theorem 3.3.7. 3Matching is NP-complete.

Proof. Suffices to show that $3\text{CNF} \leq_P 3\text{Matching}$, by defining a polynomial reduction $f : 3\text{CNF} \rightarrow 3\text{Matching}$, where

$$f \left(\bigwedge_{i=1}^n \bigvee_{j=1}^3 \ell_{ij} \right) = (X, Y, Z)$$

where $\llbracket \psi \rrbracket_P = \{P_1, \dots, P_m\}$ and

$$\begin{aligned} X &= \bigcup_{P \in \llbracket \psi \rrbracket_P} \{x_{P_1}, \dots, x_{P_n}\} \\ &\quad \cup \{x_{C_1}, \dots, x_{C_n}\} \cup \underbrace{\{x'_1, \dots, x'_{n(m-1)}\}}_{\text{Dummy elements}} \\ Y &= \bigcup_{P \in \llbracket \psi \rrbracket_P} \{y_{P_1}, \dots, y_{P_n}\} \\ &\quad \cup \{y_{C_1}, \dots, y_{C_n}\} \cup \underbrace{\{y'_1, \dots, y'_{n(m-1)}\}}_{\text{Dummy elements}} \\ Z &= \bigcup_{P \in \llbracket \psi \rrbracket_P} \{z_{P_1}, \dots, z_{P_n}, \bar{z}_{P_1}, \dots, \bar{z}_{P_n}\} \end{aligned}$$

Dummy elements required since $|Z| = 2mn$ and (without dummy elements) $|X| = |Y| = mn + n$. However $|X| = |Y| = |Z|$ is required.

Define the set N s.t

$$N = \bigcup_{P \in \llbracket \psi \rrbracket_P} \{(x_{Pi}, y_{Pi}, z_{Pi}), (x_{Pi}, y_{P(i+1)}, \bar{z}_{Pi}) : 1 \leq i < n\} \cup \{(x_{Pn}, y_{Pn}, z_{Pn}), (x_{Pn}, y_{P1}, z_{Pn})\} \\ \cup \{(x_{Ci}, y_{Ci}, z_{Pi}) : 1 \leq i \leq n, P \in C_i\} \cup \{(x_{Ci}, y_{Ci}, \bar{z}_{Pi}) : 1 \leq i \leq n, \neg P \in C_i\} \\ \cup \underbrace{\{(x'_i, y'_j, z) : z \in Z, 1 \leq i, j \leq n(m-1)\}}_{\text{Dummy variables}}$$

We wish to show $\forall \psi \in \Sigma^*. \psi \in \text{3CNF} \iff f(\psi) \in \text{3Matching}$. Let $\psi \in \Sigma^*$ be arbitrary.

(\implies). Let us assume that $\psi = \bigwedge_{i=1}^n \bigvee_{j=1}^3 \ell_{ij} \in \text{3CNF}$. Hence an interpretation $\mathcal{I} \in \Sigma_{\mathcal{I}}$ s.t $\mathcal{T} \llbracket \psi \rrbracket_{\mathcal{I}} = 1$.

We wish to find $M \subset N$ s.t M is a matching. We have

$$M = \{(x_{Pi}, y_{P(i+1)}, \bar{z}_{Pi}) : 1 \leq i \leq n, \mathcal{I}(P) = 1\} \cup \{(x_{Pi}, y_{P(i+1)}, z_{Pi}) : 1 \leq i \leq n, \mathcal{I}(P) = 0\} \\ \cup \{(x_{Ci}, y_{Ci}, z_{Pi}) : 1 \leq i \leq n, P \in C_i, \mathcal{I}(P) = 1\} \\ \cup \{(x_{Ci}, y_{Ci}, \bar{z}_{Pi}) : 1 \leq i \leq n, P \in C_i, \mathcal{I}(P) = 0\}$$

(wlog only a true literal in C_i for all $1 \leq i \leq n$).

M is a matching and $|M| = mn + mn = 2mn$.

(\impliedby). TODO

□

3.3.3.2 Set Covering

Definition 3.3.23. (Set Covering) For a family $\mathcal{F} = \{S_1, \dots, S_n\} \subseteq \mathcal{P}(\mathcal{U})$, a family $\mathcal{G} \subseteq \mathcal{F}$ covers $\mathcal{U} \iff \bigcup \mathcal{G} = \mathcal{U}$.

Definition 3.3.24. (SetCovering) The set covering problem is defined as the decision problem:

Given a family $\mathcal{F} \subseteq \mathcal{P}(\mathcal{U})$, a universe \mathcal{U} , and $1 \leq k \leq |\mathcal{F}|$. Determine whether there exists $\mathcal{G} \subseteq \mathcal{F}$ s.t \mathcal{G} covers \mathcal{U} and $|\mathcal{G}| = k$.

Denoted $\text{SetCovering}(\mathcal{F}, \mathcal{U}, k)$.

Lemma 3.3.10. $\text{SetCovering} \in \text{NP}$

Definition 3.3.25. (3SetCovering) The 3 set covering problem is defined as the decision problem:

Given a family $\mathcal{F} \subseteq \{S \in \mathcal{P}(\mathcal{U}) : |S| = 3\}$, a universe \mathcal{U} w/ $|\mathcal{U}| = 3n$.
Determine whether there exists $\mathcal{G} \subseteq \mathcal{F}$ s.t \mathcal{G} covers \mathcal{U} and $|\mathcal{G}| = n$.

Denoted 3SetCovering(\mathcal{F}, \mathcal{U}).

Theorem 3.3.8. 3SetCovering is NP-complete.

Proof. (Sketch) Suffices to show 3Matching \leq_P 3SetCovering, with reduction

$$f(X, Y, Z, M) = (\{\{x, y, z\} : (x, y, z) \in M\}, X \cup Y \cup Z).$$

□

Theorem 3.3.9. SetCovering is NP-complete.

Proof. (Sketch) Suffices to show 3SetCovering \leq_P SetCovering, with reduction

$$f(\mathcal{F}, \mathcal{U}) = (\mathcal{F}, \mathcal{U}, |\mathcal{U}|/3).$$

□

3.3.3.3 Knapsack and Pseudo-polynomial Time

Definition 3.3.26. (Knapsack) The knapsack problem is defined as the constrained optimization problem:

Given n items w/ value $v_i \in \mathbb{N}$ and weight $w_i \in \mathbb{N}$, and bounds W and V ,
determine whether

$$\sum_{i=1}^n v_i I_i \geq V$$

$$\sum_{i=1}^n w_i I_i \leq W$$

where $I_i = 0$ if the i th item is used.

Denoted Knapsack($n, \mathbf{v}, \mathbf{w}, V, W$)

Theorem 3.3.10. Knapsack is NP-complete.

Proof. (Sketch) Suffices to show that $\text{3SetCovering} \leq_P \text{Knapsack}$. Let us define the reduction

$$f(\mathcal{F}, \mathcal{U}) = (m, \mathbf{v}, \mathbf{w}, V, W),$$

where $\mathcal{F} = \{S_1, \dots, S_m\}$, $\mathcal{U} = \{1, \dots, 3n\}$ and

$$v_i = w_i = \sum_{j \in S_i} (m+1)^{j-1}$$

$$V = W = \sum_{j=0}^{3n-1} (m+1)^j = (m+1)^{3n} - 1$$

Idea: items represent bit vectors and values and weights of sets S_i are $m+1$ base integers (required to avoid carry bits). Union of bit vectors is addition \implies a set covers $\mathcal{U} \iff$ bit vector of $111\dots 1_{m+1}$. \square

Theorem 3.3.11. Knapsack has a time bound of $O(nW)$.

- **Note:** This complexity doesn't reflect the input size: $O(n \log W)$. Hence the complexity is *exponential*.

3.3.4 co-NP

Definition 3.3.27. (co-NP) We define $\text{co-NP} = \overline{\text{NP}}$. Equivalently, $\mathcal{L} \in \text{co-NP} \iff$

$$\mathcal{L} = \{x \in \Sigma^* . \forall y \in \Sigma^* . \neg R(y, x)\}.$$

- **Note:** co-NP problems require checking *all polynomial certificates falsify R* .

Theorem 3.3.12. $P \subseteq \text{co-NP}$.

Proof. Since $P = \text{co-P}$, and $P \subseteq \text{NP}$, hence $P = \text{co-P} \subseteq \text{co-NP}$ \square

- Hence $P \subseteq \text{NP} \cap \text{co-NP}$.

IMAGE

Theorem 3.3.13.

$\forall \mathcal{L}_1 \subseteq \Sigma_1^*, \mathcal{L}_2 \subseteq \Sigma_2^* . \exists f : \mathcal{L}_1 \rightarrow \mathcal{L}_2$ reduction $\implies f : \overline{\mathcal{L}_1} \rightarrow \overline{\mathcal{L}_2}$ is a reduction

Proof. Let $\mathcal{L}_1 \subseteq \Sigma_1^*, \mathcal{L}_2 \subseteq \Sigma_2^*$ be arbitrary. Let us assume there exists a reduction $f : \mathcal{L}_1 \rightarrow \mathcal{L}_2$. Let x be arbitrary. We have

$$\begin{aligned} x \in \overline{\mathcal{L}_1} &\iff x \notin \mathcal{L}_1 \\ &\iff f(x) \notin \mathcal{L}_2 \\ &\iff f(x) \in \overline{\mathcal{L}_2} \end{aligned}$$

Hence $f : \overline{\mathcal{L}_1} \rightarrow \overline{\mathcal{L}_2}$. □

Corollary 3.3.13.1. If \mathcal{L} is NP-complete, then $\overline{\mathcal{L}}$ is co-NP-complete.

- $\overline{\text{SAT}}$ is co-NP-complete.

3.3.4.1 Primality

Definition 3.3.28. $\text{Comp} = \{x \in 1\{0,1\}^* : x \text{ is composite}\}$ and $\text{Prime} = \{x \in 1\{0,1\}^* : x \text{ is prime}\}$.

- Comp is in NP:
 - Certificate is the factorization (not necessarily the prime factorization). Divisor length is bounded by $O(\log \sqrt{x})$

Hence Prime is in co-NP.

Theorem 3.3.14. $\text{Comp} \in \text{NP}$. $\text{Prime} \in \text{co-NP}$.

Proof. Algorithm for determine whether n is composite:

- Search the range $[1, \sqrt{n}]$ for a *factor*.
- The factor is the certificate y (of length $O(\log_2 \sqrt{n})$)
- $R(y, x) = y \mid x$. $O(|y|^2)$ time complexity. Deterministic.

So by definition ??, $\text{Comp} \in \text{NP}$. Hence by definition ??, $\text{Prime} = \overline{\text{Comp}} \in \text{co-NP}$. □

Theorem 3.3.15. $p \in \mathbb{P} \iff$ there exists $1 < i < p$ s.t. $i^{p-1} \equiv 1 \pmod{p}$ and $i^{\frac{p-1}{q}} \not\equiv 1 \pmod{p}$ for all prime divisors q of p .

Theorem 3.3.16. $\text{Prime} \in \text{NP}$.

Proof. Determining $a^b \pmod{p}$:

- Compute $a^2, a^4, \dots, a^{2^{\log_2 b}}$ on modulo p , which requires $\log_2 b$ multiplications.
- **Complexity:** $O(\log_2^3 b)$.

So we may determine $i^{p-1} \equiv 1 \pmod{p}$ in $O(\log_2^3 p)$.

Determining $i^{\frac{p-1}{q}} \not\equiv 1 \pmod{p}$:

- Requires prime divisors $\mathbf{q} = (q_1, \dots, q_k)$ of $p - 1$
- Uses algorithm to determine $i^{\frac{p-1}{q_j}} \pmod{p}$ for all $q_j \in \mathbf{q}$.
- **Complexity:** $O(k \log_2^3 p) = O(\log_2^4 p)$

Certificate:

$$C(p) = (i, \{(q_i, C(q_i)) : q_i \in \mathbf{q}\})$$

w/ $|C(p)| \leq 4 \log_2^2 p$ (strong induction on p). □

3.4 Function Classes

- **Problem:** Complexity classes only reason about *decidable* languages. Not about *functions*.

Definition 3.4.1. (Witness Function) A witness function for $\mathcal{L} \subseteq \Sigma^*$ is a function $f : \Sigma^* \rightarrow \mathcal{O}(\Sigma^*)$ such that:

- If $x \in \mathcal{L}$, then $f(x) = \lfloor y \rfloor$ s.t $R(y, x)$ where y is the certificate of x
- Otherwise $f(x) = \emptyset$.

- **Note:** This definition applies for all \mathcal{L} (not just NP)

Definition 3.4.2. The function class of a complexity class \mathcal{C} is the class $\text{FC} = \{\text{witness } f_{\mathcal{L}} : \mathcal{L} \in \mathcal{C}\}$.

- \implies FP and FNP.

3.4.1 Reductions

TODO

3.4.2 Problems

3.4.2.1 Factorization

Definition 3.4.3. (Factorization Problem) The factorization problem is the witness function:

$$f(n) = (2, k_1; 3, k_2; \dots; p_m, k_m),$$

s.t $n = \prod_i p_i^{k_i}$.

- Factorization is FNP since the witness function is for a language $\text{Comp} \in \text{NP}$.

3.4.3 Cryptography

- **Problem:** 2 parties (Alice and Bob) wish to send a message x w/out a third party (Eve) knowing x .
- **Solution:** Encryption:

– Alice and Bob define $E, D : \Sigma^* \times \Sigma^* \rightarrow \Sigma^*$ and $e, d \in \Sigma^*$ s.t

$$\forall x \in \Sigma^*. D(E(x, e), d) = x$$

- $D, E \in \text{P}$ for the cryptographic system to be *tractable*.

- **Types:**

- Private-key: e, d are only known to A and B respectively.
- Public-key: e is public and d is only known to B .

Example 3.4.1. (XOR Encryption) Define $D, E = \oplus$ and $d = e$ (known as a *one-time pad*). Relies on the identity $(x \oplus e) \oplus e = x$.

Provably secure if Eve doesn't know e : since $e = x \oplus y$.

3.4.3.1 One-way Functions

- **Problem:** For public-key systems: The function that maps $E(x, e) \mapsto x$ (w/out d) $\notin \text{FP} \implies \text{FNP}$.
- Hence public-key systems rely on $\text{FNP} \neq \text{FP}$.

Definition 3.4.4. (One-way Functions) A function $f : \Sigma^* \rightarrow \Sigma^*$ is a *one-way function* \iff :

1. f is injective
2. $\forall x \in \Sigma^*. \exists k \in \mathbb{N}. |x|^{1/k} \leq |f(x)| \leq |x|^k$.
3. $f \in \text{FP}, f^{-1} \notin \text{FP}$

- Proving f is a one-way function relies on assuming $\text{P} \neq \text{NP}$. So *security* of f is shown by proving: $\text{P} \neq \text{NP} \implies f$ is one-way. e.g. RSA

Definition 3.4.5. (Unambiguous) A non-deterministic Turing machine $M \in \text{NTM}_{\Sigma}^k$ is *unambiguous* \iff

$$\exists! (q, \tau_1, \dots, \tau_k) \in \mathcal{C}(M). (q_0, \tau_0(u_1), \dots, \tau_0(u_\ell), \dots, \tau_0) \xrightarrow{*}_M (q, \tau_1, \dots, \tau_k) \wedge \text{lab}(q) = \text{acc}$$

Definition 3.4.6. (UP) $\mathcal{L} \in \text{UP}$ iff \mathcal{L} is accepted by an unambiguous NTM. Equivalently, $\mathcal{L} \in \text{UP}$ iff

$$\mathcal{L} = \{x \in \Sigma^*. \exists y \in \Sigma^*. R(y, x)\},$$

where

- R is polynomial time computable and balanced.
- $\forall x, y_1, y_2 \in \Sigma^*. R(y_1, x) \wedge R(y_2, x) \implies y_1 = y_2$. Injective.

Lemma 3.4.1. $\text{P} \subseteq \text{UP} \subseteq \text{NP}$

Theorem 3.4.1. $\text{UP} = \text{P} \iff$ there are no one-way functions.

Proof. We proceed by contradiction.

(\implies). Let us assume there exists a one-way function $f : \Sigma^* \rightarrow \Sigma^*$. Define

$$\mathcal{L}_f = \{(x, y) : \exists z \in \Sigma^*. z \leq x \wedge f(z) = y\},$$

where \leq is a lexicographical ordering.

It suffices to show that $\mathcal{L}_f \in \text{UP} \setminus \text{P}$. We first show that $\mathcal{L}_f \in \text{UP}$:

- $R(z, (x, y)) = z \leq x \wedge f(z) = y$ is computable in polynomial time and polynomially balanced by definition of f (??).
- R is injective since f is injective

So by definition ??, $\mathcal{L}_f \in \text{UP}$. We now show that $\mathcal{L}_f \notin \text{P}$. Let us assume that $\mathcal{L}_f \in \text{P}$. Then it follows that we may compute f^{-1} in polynomial time:

- By definition ??, given $y \in \Sigma^*$ s.t. $f(z) = y \implies |z|^{1/k} \leq |y| \leq |z|^k$ for some $k \in \mathbb{N}$.
- Use a binary search procedure w/ time bound of $(\log_2 y)^k$

Hence $f^{-1} \in \text{FP}$. A contradiction! So we are done.

(\Leftarrow). Let us assume that $\text{UP} \neq \text{P}$. Hence there exists $\mathcal{L} \in \text{UP} \setminus \text{P}$, where U is the unambiguous NTM accepting \mathcal{L} .

Define $f_U : \Sigma^* \rightarrow \Sigma^*$:

$$f_U(x) = \begin{cases} 1y & \text{if } x \text{ encodes the accepting computation of } U \text{ w/ input } y \\ 0x & \text{otherwise} \end{cases}$$

f_U is injective since U is unambiguous. $f_U \in \text{FP}$ (assuming a polynomial encoding between x and computations). $|f_U(x)| \leq |x|^k$ since U has a polynomial running time. We now show that $f_U^{-1} \notin \text{FP}$. Assume that $f_U^{-1} \in \text{FP}$. Hence $\mathcal{L} \in \text{P}$. A contradiction!

□

3.5 Space Complexity

- **Idea:** Reason about relations between time and space complexity classes

3.5.1 Classes

Definition 3.5.1. (Space Complexity Class) Let $f : \mathbb{N} \rightarrow \mathbb{N}$. $\text{SPACE}(f(n)) \subseteq \mathcal{P}(\Sigma^*)$ is the complexity class (set of languages) s.t. $\mathcal{L} \in \text{SPACE}(f(n)) \iff \mathcal{L}$ is decidable by a TM w/ space bound $O(f(n))$.

Definition 3.5.2. (NSpace Complexity Class) Let $f : \mathbb{N} \rightarrow \mathbb{N}$. $\text{NSPACE}(f(n)) \subseteq \mathcal{P}(\Sigma^*)$ is the complexity class (set of languages) s.t. $\mathcal{L} \in \text{NSPACE}(f(n)) \iff \mathcal{L}$ is decidable by a NTM w/ space bound $O(f(n))$.

- See definition ?? for space bound (relies on TM's w/ I/O)

Definition 3.5.3. (Logarithmic Space Complexity) The logarithmic space complexity class LSPACE is defined by

$$\text{LSPACE} = \text{SPACE}(\log n).$$

Similarly, the non-deterministic logarithmic space complexity class NLSPACE is

$$\text{NLSPACE} = \text{NSPACE}(\log n).$$

Definition 3.5.4. (Polynomial Space Complexity) The polynomial space complexity class PSPACE is defined by

$$\text{PSPACE} = \bigcup_{k=1}^{\infty} \text{SPACE}(n^k).$$

The non-deterministic polynomial space complexity class NPSPACE is

$$\text{NPSPACE} = \bigcup_{k=1}^{\infty} \text{NSPACE}(n^k).$$

3.5.2 Inclusions

- **Idea:** Prove \subseteq relations between complexity classes:

$$\text{LSPACE} \subseteq \text{NLSPACE} \subseteq \text{P} \subseteq \text{NP} \subseteq \text{PSPACE} \subseteq \text{NPSPACE}.$$

Lemma 3.5.1. (Deterministic Complement Lemma) For all $\mathcal{L} \subseteq \Sigma^*$:

$$\begin{aligned} \mathcal{L} \in \text{TIME}(f(n)) &\implies \overline{\mathcal{L}} \in \text{TIME}(f(n)) \\ \mathcal{L} \in \text{SPACE}(f(n)) &\implies \overline{\mathcal{L}} \in \text{SPACE}(f(n)) \end{aligned}$$

Corollary 3.5.0.1. $\text{LSPACE} = \text{co-LSPACE}$, $\text{P} = \text{co-P}$ and $\text{PSPACE} = \text{co-PSPACE}$.

- **Problem:** Functions $f : \mathbb{N} \rightarrow \mathbb{N}$ may not be computable (in the complexity class they describe) \implies difficult for constructions on bounded computation.
- **Solution:** *Proper function (or constructible functions).*

Definition 3.5.5. (Proper Function) A function $f : \mathbb{N} \rightarrow \mathbb{N}$ is a *proper function* iff:

- (i) f is non-decreasing: $\forall n \in \mathbb{N}. f(n) \leq f(n+1)$.
- (ii) f is computable w/ a $O(|x| + f(|x|))$ time bound and $O(f(|x|))$ space bound, where $|x| = |\llbracket n \rrbracket_{\mathbb{N}}|$ (the length of the encoding).

Lemma 3.5.2. For all $f, g : \mathbb{N} \rightarrow \mathbb{N}$, if f, g are constructible, then

- 1. $f + g, f \times g$ and 2^f are constructible
- 2. $f \circ g$ is constructible iff $\forall n \in \mathbb{N}. f(n) > n$.

Proof. (Sketch) Relies on re-computing f determining symbol a at index i on output tape to obtain output w/out affecting space bound. TODO \square

Theorem 3.5.1. (The Inclusion Theorem) For all constructible functions $f : \mathbb{N} \rightarrow \mathbb{N}$:

- (i) $\text{SPACE}(f(n)) \subseteq \text{NSPACE}(f(n))$
- (ii) $\text{TIME}(f(n)) \subseteq \text{NTIME}(f(n))$
- (iii) $\text{NTIME}(f(n)) \subseteq \text{SPACE}(f(n))$
- (iv) $\text{NSPACE}(f(n)) \subseteq \text{TIME}(k^{\log n + f(n)})$

Proof. Let $f : \mathbb{N} \rightarrow \mathbb{N}$ be an arbitrary constructible function.

(i), (ii) (i) and (ii) are trivial.

(iii) Let $\mathcal{L} \in \text{NTIME}(f(n))$. Let $N \in \text{NTM}_{\Sigma}^k$ be the NTM that decides \mathcal{L} in $f(n)$ time. The computation tree \mathcal{T} of N is given by: IMAGE

where $b = \max \left\{ |S| : S \in \vec{\Delta}(Q, \mathcal{O}(\Sigma)^k) \right\}$ is branching factor of the computation tree.

A bounded depth-first search on \mathcal{T} is computable w/ space bound of $d = f(n)$ (See AI supervision work). Hence $\mathcal{L} \in \text{SPACE}(f(n))$.

(iv) Let $\mathcal{L} \in \text{NSPACE}(f(n))$. Let $N \in \text{NTM}_{\Sigma}^k$ be the NTM that decides \mathcal{L} in $f(n)$ space.

The configuration graph of N w/ input $x \in \Sigma^*$ is a graph $G = (V, E)$ inductively defined by

$$\frac{\overline{(q_0, \tau_0(x), \tau_0, \dots, \tau_0) \in V}}{\frac{c \in V \quad c \longrightarrow_N c'}{c' \in V, (c, c') \in E}}$$

M accepts $x \iff$ an accepting configuration is *reachable* from c_0 . We note that $|V| \leq |\mathcal{C}_x(N)|$, where $|\mathcal{C}_x(N)|$ is the number of possible configuration of N w/ input x :

$$|Q| \times \underbrace{|x|}_{\text{position on input}} \times \left[\underbrace{(|\Sigma| + 1)^{f(|x|)}}_{\text{tape contents}} \times \underbrace{f(|x|)}_{\text{position on tape}} \right]^{k-2}$$

Note that **Reachability** has a time complexity of $O(|V|^2)$ (see section ??). Hence \mathcal{L} is decidable in

$$\begin{aligned} O\left(\{|Q| \times |x| \times [(|\Sigma| + 1)^{f(|x|)} \times f(|x|)]^{k-2}\}^2\right) &= O\left(\{|x| [c^{\log_c |x| + f(|x|)}]^{k-2}\}^2\right) \\ &= O\left(c^{\log_c |x| + f(|x|)}\right) \end{aligned}$$

So we have $\mathcal{L} \in \text{TIME}(c^{\log n + f(n)})$.

□

Theorem 3.5.2. (NLSPACE Reachability) $\text{Reachability} \in \text{NLSPACE}$

Proof. $\text{Reachability} \in \text{NLSPACE}$ w/ the following algorithm:

```

i ← index_of(u); // current index
while (true) {
    if (V[i] = v) return acc;

    non-deterministically determine index j (log |V| bits);
    if ((V[i], V[j]) ∉ E) return rej;
    i ← j;
}

```

Requires $2 \log |V|$ space. Hence $\text{Reachability} \in \text{NLSPACE}$.

□

3.5.3 Savitch's Theorem

Theorem 3.5.3. (Savitch's Theorem) $\text{Reachability} \in \text{SPACE}(\log^2 |V|)$

Proof. $\text{Reachability} \in \text{SPACE}(\log^2 |V|)$ w/ the following algorithm:

```

path(u, v, i) {
  if (i = 1  $\wedge$  u  $\neq$  v  $\wedge$  (u, v)  $\notin$  E) return false;
  if ((u, v)  $\in$  E  $\vee$  u = v) return true;

  for (w  $\in$  V) {
    if (path(u, w,  $\lfloor i/2 \rfloor$ )
         $\wedge$  path(w, v,  $\lceil i/2 \rceil$ ))
      return true;
  }
}

```

The above algorithm computes $\text{path}(u, v, i)$, which defines the predicate: there is a path $u \rightarrow^k v$ where $k \leq i$. Each stack frame of **path** may be defined by $4 \log |V|$ bits (3 for parameters + 1 for w). The maximum recursion depth is given by $\log |V| \implies$ space bound of $4 \log^2 |V|$

$\text{path}(u, v, \lceil \log |V| \rceil)$ defines reachability.

Hence $\text{Reachability} \in \text{SPACE}(\log^2 |V|)$. \square

Corollary 3.5.3.1. For constructible functions $f : \mathbb{N} \rightarrow \mathbb{N}$ s.t $\forall n \in \mathbb{N}. f(n) \geq \log n$,

$$\text{NSPACE}(f(n)) \subseteq \text{SPACE}(f(n)^2).$$

Proof. Let $f : \mathbb{N} \rightarrow \mathbb{N}$ be an arbitrary constructible function. Let us assume that $\forall n \in \mathbb{N}. f(n) \geq \log n$.

Let $\mathcal{L} \in \text{NSPACE}(f(n))$ be defined as in theorem ??, proof of (iv). Hence \mathcal{L} is decidable in

$$O(\log^2 (c^{\log_c |x| + f(|x|)})) = O((\log_c |x| + f(|x|))^2) = O(f(|x|)^2).$$

So $\mathcal{L} \in \text{SPACE}(f(n)^2)$. \square

Lemma 3.5.3. $\text{PSPACE} = \text{NPSPACE}$

Proof. By Corollary ??, we have

$$\begin{aligned} \text{NSPACE} &= \bigcup_{k=1}^{\infty} \text{NSPACE}(n^k) \\ &\subseteq \bigcup_{k=1}^{\infty} \text{SPACE}(n^{2k}) \\ &\subseteq \text{PSPACE} \end{aligned}$$

Since $\text{PSPACE} \subseteq \text{NSPACE}$, then we have $\text{PSPACE} = \text{NSPACE}$. \square

Theorem 3.5.4. (The Immerman-Szelepcsenyi Theorem) For a given $G = (V, E)$ and vertex $v \in V$, $|\{u \in V : v \xrightarrow{*} u\}|$, the number of vertices reachable from v , is computable by a NTM w/ a $\log |V|$ space bound.

Corollary 3.5.4.1. For all constructible functions $f : \mathbb{N} \rightarrow \mathbb{N}$ w/ $\forall n \in \mathbb{N}. f(n) \geq \log n$,

$$\text{NSPACE}(f(n)) = \text{co-NSPACE}(f(n)).$$

3.5.4 Hierarchy Theorem

- **Problem:** Theorems so far prove \subseteq but not \subset .

Definition 3.5.6. (Time Bounded Halting Problem) Let $f : \mathbb{N} \rightarrow \mathbb{N}$ be a constructible function s.t $\forall n \in \mathbb{N}. f(n) \geq n$. The *time bounded halting problem* H_f is defined as

$$H_f = \{(\llbracket M \rrbracket, x) : M \in \text{TM}_{\Sigma} \text{ accepts } x \text{ after } f(|x|) \text{ transitions}\},$$

where $\llbracket \cdot \rrbracket : \text{TM}_{\Sigma}^k \rightarrow \Sigma_+^*$ is an encoding function for Turing machines.

Lemma 3.5.4. $H_f \in \text{TIME}(f(n)^3)$.

Proof. (Sketch) Define a Turing machine U_f that decides H_f :

- Computes $f(|x|)$ from input $(\llbracket M \rrbracket_M, x)$. Takes $O(f(n))$ time (by definition of constructible function).
- Universal Turing machine U simulates each transition of M in time $O(\ell_M k_M^2 f(|x|))$ w/ k_M is # of strings of M , ℓ_M is the length of the description of each state and symbol.

$$k_M, \ell_M = O(\log |\llbracket M \rrbracket_M|).$$

Hence each step takes $O(f^2(|x|))$ time.

So $H_f \in \text{TIME}(f(n)^3)$. □

Lemma 3.5.5. $H_f \notin \text{TIME}(f(\lfloor n/2 \rfloor))$.

Proof. We proceed by contradiction. Suppose $H_f \in \text{TIME}(f(\lfloor n/2 \rfloor))$.

Let $M \in \text{TM}_\Sigma^k$ be the TM that decides H_f in $f(\lfloor n/2 \rfloor)$ time.

Define the TM $N \in \text{TM}_\Sigma^k$ which decides

$$\mathcal{L} = \{\llbracket M \rrbracket_M : (\llbracket M \rrbracket_M, \llbracket M \rrbracket_M) \notin H_f\}.$$

By existence of M , N has the time bound of $f(\lfloor (2n+3)/2 \rfloor) = f(n+1)$ (copies input $\llbracket M \rrbracket_M$, adds $(,)$ (3 symbols)). Note that

$$\begin{aligned} \llbracket N \rrbracket_M &\in \mathcal{L} \\ \iff (\llbracket N \rrbracket_M, \llbracket N \rrbracket_M) &\notin H_f \\ \iff N \text{ doesn't accept } \llbracket N \rrbracket_M &\text{ after } f(n) \text{ transitions} \\ \iff \llbracket N \rrbracket &\notin \mathcal{L} \end{aligned}$$

A contradiction! □

Theorem 3.5.5. (Time Hierarchy Theorem) For all $f : \mathbb{N} \rightarrow \mathbb{N}$ s.t f is constructible and $\forall n \in \mathbb{N}. f(n) \geq n$,

$$\text{TIME}(f(n)) \subset \text{TIME}(f(2n+1)^3).$$

Corollary 3.5.5.1. $P \subset \text{EXP}$