

## Section 1: Identification

- **Product Name:** Sodium Hydroxide and Potassium Permanganate Solution
- **Synonyms:** NaOH and KMnO<sub>4</sub> solution
- **Product Code:** Wecks No. 1 Reagent
- **Manufacturer:**  
PACE Technologies  
3601 E. 34<sup>th</sup> St.  
Tucson, AZ 85713  
+1-520-882-6598
- **Emergency Phone Number:**  
CHEMTREC 800-424-9300 (US) Day or night  
Customer No. 16568

---

## Section 2: Hazard Identification

### Classification of the Substance or Mixture (GHS Classification)

- **Sodium Hydroxide (NaOH):**
  - Skin Corrosion/Irritation: Category 1A
  - Serious Eye Damage/Irritation: Category 1
- **Potassium Permanganate (KMnO<sub>4</sub>):**
  - Oxidizing Solid: Category 2
  - Acute Toxicity (Oral): Category 4
  - Skin Corrosion/Irritation: Category 1B
  - Aquatic Acute Toxicity: Category 1
  - Aquatic Chronic Toxicity: Category 1

## Label Elements

- **Pictograms:**



- **Signal Word: Danger**

- **Hazard Statements:**

- H271: May cause fire or explosion; strong oxidizer.
- H302: Harmful if swallowed.
- H314: Causes severe skin burns and eye damage.
- H318: Causes serious eye damage.
- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long-lasting effects.

- **Precautionary Statements:**

- **Prevention:**

- P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
    - P220: Keep/store away from clothing/combustible materials.
    - P260: Do not breathe dust/fume/gas/mist/vapors/spray.
    - P264: Wash hands thoroughly after handling.
    - P280: Wear protective gloves/protective clothing/eye protection/face protection.

- **Response:**

- P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
    - P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P310: Immediately call a POISON CENTER/doctor.
- **Storage:**
    - P405: Store locked up.
  - **Disposal:**
    - P501: Dispose of contents/container to an approved waste disposal facility in accordance with local, regional, national, and international regulations.

---

## Section 3: Composition/Information on Ingredients

Substance	CAS Number	Concentration (% w/w)
<b>Sodium Hydroxide (NaOH)</b>	1310-73-2	1-10%
<b>Potassium Permanganate (KMnO<sub>4</sub>)</b>	7722-64-7	1-10%
<b>Water (H<sub>2</sub>O)</b>	7732-18-5	80-95%

---

## Section 4: First-Aid Measures

- **Inhalation:** Move to fresh air. If breathing is difficult, administer oxygen. Seek medical attention if symptoms persist.
- **Skin Contact:** Immediately flush with plenty of water for at least 15 minutes. Remove contaminated clothing and wash before reuse. Seek medical attention.
- **Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses if possible. Seek immediate medical attention.
- **Ingestion:** Do NOT induce vomiting. Rinse mouth with water. Seek immediate medical attention.

---

## Section 5: Fire-Fighting Measures

- **Suitable Extinguishing Media:** Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide. Avoid direct contact of water jets with potassium permanganate.

- **Special Hazards Arising from the Mixture:** Potassium permanganate is a strong oxidizer and can intensify fires in contact with combustible materials. Sodium hydroxide can react with metals to form flammable hydrogen gas.
- **Protective Equipment for Firefighters:** Use self-contained breathing apparatus and full protective gear.

---

## Section 6: Accidental Release Measures

- **Personal Precautions:** Evacuate area. Use personal protective equipment (PPE). Ensure adequate ventilation. Avoid inhalation of dust and contact with skin and eyes.
- **Environmental Precautions:** Prevent from entering drains, waterways, or soil. Potassium permanganate is highly toxic to aquatic life.
- **Methods for Containment and Cleanup:** Neutralize with a dilute sodium bisulfite solution to reduce the oxidizing power of potassium permanganate. Absorb with inert material, and dispose of in accordance with local regulations.

---

## Section 7: Handling and Storage

- **Precautions for Safe Handling:** Avoid contact with skin, eyes, and clothing. Use only in well-ventilated areas. Keep away from combustible materials.
- **Conditions for Safe Storage:** Store in tightly closed, corrosion-resistant containers in a cool, dry, and well-ventilated area, away from incompatible materials (e.g., reducing agents, acids, organic materials).

---

## Section 8: Exposure Controls/Personal Protection

### Control Parameters

- **Sodium Hydroxide:**
  - **OSHA PEL:** 2 mg/m<sup>3</sup> (ceiling)
  - **ACGIH TLV:** 2 mg/m<sup>3</sup> (ceiling)

### Personal Protective Equipment (PPE)

- **Respiratory Protection:** If airborne concentrations exceed exposure limits, use NIOSH-approved respirators.
- **Hand Protection:** Use chemical-resistant gloves (e.g., nitrile, butyl rubber).

Copyright 2024-2025 © · All rights reserved

PACE Technologies · 3601 E. 34<sup>th</sup> St · Tucson, AZ 85713 USA  
Telephone +1-520-882-6598 · FAX +1-520-882-6599 · [pace@metallographic.com](mailto:pace@metallographic.com)  
Emergency phone number (CHEMTREC 800-424-9300)

- **Eye Protection:** Use safety goggles or a full face shield.
- **Skin Protection:** Wear protective clothing (e.g., aprons, long sleeves) as necessary to prevent contact.
- **Engineering Controls:** Ensure adequate ventilation, especially in confined areas.

---

## Section 9: Physical and Chemical Properties

- **Appearance:** Purple solution (due to potassium permanganate)
- **Odor:** Odorless
- **pH:** Strongly basic (due to sodium hydroxide)
- **Melting/Freezing Point:** Approx. 0°C (for water-based solution)
- **Boiling Point:** Approx. 100°C (for water-based solution)
- **Flash Point:** Not applicable
- **Solubility:** Completely soluble in water
- **Vapor Pressure:** Similar to water (for dilute solutions)
- **Density:** Varies with concentration
- **Viscosity:** Similar to water (for dilute solutions)

---

## Section 10: Stability and Reactivity

- **Reactivity:** Potassium permanganate is a strong oxidizer and may react with organic materials, reducing agents, and acids. Sodium hydroxide is highly reactive with acids and metals.
- **Chemical Stability:** Stable under normal conditions.
- **Conditions to Avoid:** Avoid heat, sparks, open flame, and contact with organic or combustible materials.
- **Incompatible Materials:** Strong acids, reducing agents, organic materials, metals, and combustibles.
- **Hazardous Decomposition Products:** Potassium permanganate decomposes to manganese oxides and oxygen; sodium hydroxide may produce hydrogen gas when in contact with metals.

---

## Section 11: Toxicological Information

- **Acute Toxicity:**
    - **Sodium Hydroxide:** Corrosive, may cause severe burns to skin and eyes.
    - **Potassium Permanganate:** Harmful if swallowed, may cause irritation or burns to skin and eyes.
  - **Skin Corrosion/Irritation:** Causes severe burns.
  - **Serious Eye Damage/Irritation:** Causes severe eye damage.
  - **Respiratory or Skin Sensitization:** No known significant effects.
  - **Carcinogenicity:** No known significant effects.
  - **Reproductive Toxicity:** No known significant effects.
- 

## Section 12: Ecological Information

- **Ecotoxicity:** Potassium permanganate is highly toxic to aquatic organisms.
  - **Persistence and Degradability:** Potassium permanganate decomposes into manganese oxides.
  - **Bioaccumulative Potential:** Low potential for bioaccumulation.
  - **Mobility in Soil:** High mobility due to water solubility.
- 

## Section 13: Disposal Considerations

- **Waste Disposal:** Dispose of contents and containers in accordance with local, regional, national, and international regulations. Neutralize potassium permanganate before disposal.
- 

## Section 14: Transport Information

- **UN Number:** UN 3266
- **Proper Shipping Name:** Corrosive liquid, basic, inorganic, n.o.s. (contains sodium hydroxide and potassium permanganate)

- **Hazard Class:** 8 (Corrosive)
- **Packing Group:** II
- **Environmental Hazards:** Marine pollutant (potassium permanganate)

---


## Section 15: Regulatory Information

- **OSHA:** Hazardous according to OSHA Hazard Communication Standard.
- **SARA 313:** Potassium permanganate is subject to reporting under SARA Title III.
- **TSCA:** All components are listed on the TSCA Inventory.

---

## Section 16: Other Information

### 16.1 NFPA 704



- **Health (Blue):** 3 (Serious health hazard due to corrosiveness)
- **Flammability (Red):** 0 (Non-flammable)
- **Reactivity (Yellow):** 2 (Reactive with organic materials and reducing agents)
- **Special (White):** OX (Oxidizer due to potassium permanganate)

#### Product Use:

Laboratory Reagent.

#### Disclaimer:

PACE Technologies, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. PACE TECHNOLOGIES, INC. MAKES NO REPRESENTATIONS OR

**WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, PACE TECHNOLOGIES, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.**

DATE REVISED: 7/22/2025 DZ