Small Signal Diode

LL4148

Features

- This is a Pb−Free and Halide Free Device

ABSOLUTE MAXIMUM RATINGS

(Values are at T_A = 25°C unless otherwise noted.) (Notes 1 and 2)

Symbol	Parameter		Value	Unit
V_{RRM}	Maximum Repetitive Reverse Voltage		100	V
$I_{F(AV)}$	Average Rectified Forward Current		200	mA
I_f	Recurrent Peak Forward Current		500	mA
I_{FSM}	Non−Repetitive Peak Forward Surge Current	Pulse Width = 1.0 s	1.0	A
		Pulse Width = 1.0 μs	2.0	
T_{STG}	Storage Temperature Range		−65 to +200	°C
T_J	Operating Junction Temperature Range		−55 to +175	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.
1. These ratings are based on a maximum junction temperature of 200°C.
2. These are steady−state limits. **onsemi** should be consulted on applications involving pulsed or low−duty−cycle operations.

THERMAL CHARACTERISTICS

(Values are at T_A = 25°C unless otherwise noted.) (Note 3)

Symbol	Parameter	Value	Unit
P_D	Power Dissipation	500	mW
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	300	°C/W

3. JEDEC Standard 51−3 method (PCB Board size $76 \times 114 \times 0.6T$ mm^3)

SOD−80
CASE 100AD

MARKING DIAGRAM

Cathode Band (Black)

ORDERING INFORMATION

Device	Package	Shipping†
LL4148	SOD−80 (Pb−Free/ Halide Free)	2500 / Tape & Reel (7″)

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

ELECTRICAL CHARACTERISTICS (Values are at T_A = 25°C unless otherwise noted.)

Symbol	Parameter	Conditions	Min	Max	Unit
V_R	Breakdown Voltage	I_R = 100 μA	100	–	V
		I_R = 5.0 μA	75	–	
V_F	Forward Voltage	I_F = 10 mA	–	1.0	V
I_R	Reverse Leakage	V_R = 20 V	–	25	nA
		V_R = 20 V, T_A = 150°C	–	50	μA
C_T	Total Capacitance	V_R = 0, f = 1.0 MHz	–	4.0	pF
t_{rr}	Reverse Recovery Time	I_F = 10 mA, V_R = 6.0 V (60 mA), I_{rr} = 1.0 mA, R_L = 100 Ω	–	4.0	ns

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

LL4148

## TYPICAL PERFORMANCE CHARACTERISTICS

Figure 1. Reverse Voltage vs. Reverse Current
BV – 1.0 to 100 μA

Figure 2. Reverse Voltage vs. Reverse Current
I_R – 10 to 100 A

Figure 3. Forward Voltage vs. Forward Current
V_F – 1 to 100 μA

Figure 4. Forward Voltage vs. Forward Current
V_F – 0.1 to 10 mA

Figure 5. Forward Voltage vs. Forward Current
V_F – 10 to 800 mA

Figure 6. Forward Voltage vs. Ambient Temperature
V_F – 0.01 to 20 mA (–40 to +65°C)

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

Figure 7. Total Capacitance

Figure 8. Reverse Recovery Time vs. Reverse Recovery Current

Figure 9. Average Rectified Current ($I_{F(AV)}$) vs. Ambient Temperature (T_A)

Figure 10. Power Derating Curve

MiniMELF / SOD−80
CASE 100AD
ISSUE O

DATE 30 APR 2012

Cathode mark

0. 4±0. 1

3. 4±0. 2

φ1. 4±0. 1

NOTES: UNLESS OTHERWISE SPECIFIED

A) PACKAGE STANDARD REFERENCE:
   JEDEC DO-213, VARIATION AC.

B) ALL DIMENSIONS ARE IN MILLIMETERS.

C) CORNER RADIUS IS OPTIONAL.

D) DRAWING FILE NAME: SOD80A   REV01

DOCUMENT NUMBER:	98AON79582E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	MINIMELF / SOD−80		PAGE 1 OF 1

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical–documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales

◊