Unveiling Machine Learning

Dr. Shailesh Sivan

WHAT IS MACHINE LEARNING?

"Learning is any process by which a system improves performance from experience."
- Herbert Simon

Definition by Tom Mitchell (1998):

Machine Learning is the study of algorithms that
- improve their performance **P**
- at some task **T**
- with experience **E**.

A well-defined learning task is given by **<P,T,E>**

Machine Learning is a process where a computer uses *data* to learn ***hidden patterns*** through a ***Machine Learning algorithm***, and the output of this learning is a ***Machine Learning model*** that can make ***predictions*** on new data with minimum error.

This is a shirt we used to wear.

Is this a shirt ?

Ok



This is also a shirt

Is this a shirt ?

Ok

This is also a shirt

Yes, these are all shirts

PROGRAMMING VS LEARNING

Traditional Programming

Machine Learning

MACHINE LEARNING



Problems with Uncertainity

Approximating the patterns to Generalization

Data with hidden patterns

Minimum error to predict unseen data

MACHINE LEARNING PIPELINE





MACHINE LEARNING PIPELINE





DATA AS FEATURE VECTORS

Raw Data







Name	Region	Amount	Period
Jim	East	223	1/1/2022
Jim	West	228	1/1/2022
Jim	North	104	1/1/2022
Jim	South	143	1/1/2022

Textual presentation of data means **presenting** data in the form of words, sentences and paragraphs. ... Data can be presented in one of the three forms: text, tables, and/or graphs. The selection of the method of **presentation** depends on the type of data, method of analysis, and type of information sought from the data.

Feature Engineering

Feature Vector

1.000000	0.129459	0.141282	-0.061672	-0.073535	0.017683	-0.033523	0.544341	0.221898
0.129459	1.000000	0.152590	0.057328	0.331357	0.221571	0.137337	0.263514	0.466581
0.141282	0.152590	1.000000	0.207371	0.088933	0.261605	0.041265	0.239526	0.065088
-0.061672	0.057328	0.207371	1.000000	0.436783	0.365715	0.183508	-0.113975	0.074752
-0.073535	0.331357	0.088933	0.436783	1.000000	0.197859	0.185571	-0.042153	0.130548
0.017683	0.221571	0.261605	0.365715	0.197859	1.000000	0.140647	0.036242	0.292995
-0.033523	0.137337	0.041265	0.183508	0.185571	0.140647	1.000000	0.033561	0.173844
0.544341	0.263514	0.239526	-0.113975	-0.042153	0.036242	0.033561	1.000000	0.238356
0.221898	0.466581	0.065088	0.074752	0.130548	0.292995	0.173844	0.238356	1.000000

DATA AS FEATURE VECTORS

- Each data point with n features can be viewed as a vector in $\mathbb{R}^n$.
- A dataset with m samples becomes a collection of such vectors:

$$D = \{\mathbf{x}^{(1)}, \mathbf{x}^{(2)}, \ldots, \mathbf{x}^{(m)}\} \subset \mathbb{R}^n$$

- Here, $\mathbf{x}^{(i)} = \begin{bmatrix} x_1^{(i)} \\ x_2^{(i)} \\ \vdots \\ x_n^{(i)} \end{bmatrix}$ represents the ith sample.
- This view allows us to apply geometric and algebraic operations in n-dimensional space.

Raw Tabular Data:

Student	Height	Weight	Age
S1	170	65	21
S2	160	60	22
S3	180	70	20

$$\left\{ \begin{bmatrix} 170 \\ 65 \\ 21 \end{bmatrix} \begin{bmatrix} 160 \\ 60 \\ 22 \end{bmatrix} \begin{bmatrix} 180 \\ 70 \\ 20 \end{bmatrix} \right\}$$

DATA AS MATRIX($R^{m \times n}$)

Raw Tabular Data:

Student	Height	Weight	Age
S1	170	65	21
S2	160	60	22
S3	180	70	20

Matrix Form:

$$A = \begin{bmatrix} 170 & 65 & 21 \\ 160 & 60 & 22 \\ 180 & 70 & 20 \end{bmatrix} \quad \text{(Rows: Students, Columns: Features)}$$

$$\begin{array}{c} \\ \mathbf{S1} \\ \mathbf{S2} \\ \mathbf{S3} \end{array} \begin{array}{c} \begin{array}{ccc} \textbf{Height} & \textbf{Weight} & \textbf{Age} \end{array} \\ \begin{bmatrix} 170 & 65 & 21 \\ 160 & 60 & 22 \\ 180 & 70 & 20 \end{bmatrix} \end{array}$$

NEURAL NETWORKS





PERCEPTRON AND MULTILAYER PRECEPTRON



ILLUSTRATION WITH ANN

X (features)	Y (labels)
$x_{11}, x_{12}, x_{13}, x_{14}$	a_{11}, a_{12}, a_{13}
. . .	. . .
$x_{k1}, x_{k2}, x_{k3}, x_{k4}$	a_{k1}, a_{k2}, a_{k3}



WHEN TO MACHINE LEARNING?

ML is used when:

- Human expertise does not exist (navigating on Mars)
- Humans can't explain their expertise (speech recognition)
- Models must be customized (personalized medicine)
- Models are based on huge amounts of data (genomics)

Learning isn't always useful - There is no need to "learn" to calculate payroll

TYPES OF LEARNING



SUPERVISED LEARNING

Input : Labeled Data

X (features)	Y (labels)
$x_{11}, x_{12}, x_{13}, \dots \dots \dots \dots \dots x_{1n}$	y_1
.	.
.	.
$x_{k1}, x_{k2}, x_{k3} \dots \dots \dots \dots \dots x_{kn}$	y_k



Goal : Construct a predictor $f : X \rightarrow Y$

to minimize the error between $\hat{Y}, Y$
where, $\hat{Y} = f(X)$

Use : using predictor to predict $\hat{y} = f(\hat{x})$

For the unknown input $\hat{x}$

SUPERVISED LEARNING







Classification

- features and discrete labels
- maps an input to discrete label(class)
- Eg: spam or not, type of cancer

Regression

- features and continues real values
- Predict a real value for an input
- Eg: gold price, temperature

REGRESSION ALGORITHMS

Weight (lbs)	Height (inches)
140	60
155	62
159	67
179	70
192	71
200	72
212	75

Linear Regression





CLASSIFICATION ALGORITHMS



Logistic Regression





UNSUPERVISED LEARNING

Input : Unlabeled Data

X (features)
$x_{11}, x_{12}, x_{13}, \dots \dots \dots \dots \dots x_{1n}$
. . .
$x_{k1}, x_{k2}, x_{k3} \dots \dots \dots \dots \dots x_{kn}$



Goal : Construct a analyzer to find the hidden relationship between inputs

$$x_1, x_2, x_3, \dots, x_k$$

Use : Group or associate inputs according to their similarity

UNSUPERVISED LEARNING

Clustering





ID	Items
1	{Bread, Milk}
2	{Bread, Diapers, Beer, Eggs}
3	{Milk, Diapers, Beer, Cola}
4	{Bread, Milk, Diapers, Beer}
5	{Bread, Milk, Diapers, Cola}
...	...

market basket transactions

{Diapers, Beer} Example of a frequent itemset

{Diapers} → {Beer} Example of an association rule



Itemset and rule mining

CLUSTERING ALGORITHM

K-Means Clustering



Type of Clustering Algorithm	Visual Overview	Description	Algorithm(s)
Centroid-based		Cluster points based on proximity to centroid	KMeans KMeans++ KMedoids
Connectivity-based		Cluster points based on proximity between clusters	Hierarchical Clustering (Agglomerative and Divisive)
Density-based		Cluster points based on their density instead of proximity	DBSCAN OPTICS HDBSCAN
Graph-based		Cluster points based on graph distance	Affinity Propagation Spectral Clustering
Distribution-based		Cluster points based on their likelihood of belonging to the same distribution.	Gaussian Mixture Models
Compression-based		Transform data to a lower dimensional space and then perform clustering	BIRCH

REINFORCEMENT LEARNING



- Use software agents
- Based on rewards
- Objective is to maximize rewards for better learning

SEMI SUPERVISED LEARNING



In a nutshell, semi-supervised learning (SSL) is a machine learning technique that uses a small portion of labeled data and lots of unlabeled data to train a predictive model

BIAS VARIANCE AND ISSUES IN ML





Dr. Shailesh Sivan
+91 8907230664
shaileshsivan@cusat.ac.in
https://shaileshsivan.info