Low-Level Design (LLD)

TaskFlow – Intelligent Task Allocation & Tracking System

> **Document:** Low-Level Design – Overall (shared design, Authentication, Legal, index of 16 sub-module LLDs) · **Version:** 1.0 · **Status:** Draft
> **Project type:** Personal Project (Skill Development) · **Date:** 31-Oct-2026
> **Author:** Jojo George (jojogeorge3344@gmail.com)
> **Based on:** FRD-TaskFlow-Overall v1.0, BRD-TaskFlow-Overall v1.0, TDD-TaskFlow v2.0, code snapshot of 31-Oct-2026
> © 2026 Jojo George. All rights reserved.

Document Control

Version	Date	Author	Summary of changes
1.0	31-Oct-2026	Jojo George	Initial version: code structure and layer rules, cross-cutting design (validation, errors, unit of work, middleware, MFA gate, session validation, permission policies, `TaskAccess`, logging, time zone), shared identity tables and the ER overview of all 31 entities, enums, migrations, configuration, test projects, full design of Authentication (7 actions) and Legal (frontend only), index of the 16 sub-module LLDs (114 actions in total)

Related documents:

Document	Location
BRD – Overall (`REQ-AUTH-nn`, `REQ-LEGAL-nn`, `BR-nn`)	`../../BRD/00-Overall/BRD-TaskFlow-Overall.md`
FRD – Overall (`FR-AUTH-01` – `FR-AUTH-51`, `FR-LEGAL-01` – `FR-LEGAL-16`, `UC-AUTH-01` – `UC-AUTH-05`, `UC-LEGAL-01` – `UC-LEGAL-02`)	`../../FRD/00-Overall/FRD-TaskFlow-Overall.md`
HLD – Overall	`../../HLD/00-Overall/HLD-TaskFlow-Overall.md`
Sub-module LLDs (16)	Section 1.3 (links relative to this file)
TDD	`TDD-TaskFlow.md` v2.0 (§6 architecture, §7 data model, §8 API, §9 security)
Module technical docs (verified from code)	`TFTechnicalWorkflow` – `01-Auth` (01.1 – 01.4), `10-Legal` (10.1 – 10.2)

1. Introduction

1.1 Purpose

This document holds the low-level design that is **shared by every module** of TaskFlow as built: the backend and frontend code structure and its layer rules, the cross-cutting mechanisms that every request passes through, the shared identity and access tables, the ER overview of all 31 entities, every enumeration, every migration, all configuration keys and the test projects. It also gives the **full module design of Authentication** (the only module whose controllers have no sub-module LLD) and of **Legal** (frontend only). The detail of every other module lives in its sub-module LLD (section 1.3) and is not repeated here.

1.2 Scope & Conventions

- **Modules covered in full (section 4):** Authentication (`AuthController` 5 actions, `PasswordRecoveryController` 2 actions = **7 actions**) and Legal (0 actions, 5 public client routes). The self-service MFA endpoints used by Security Setup are `ProfileController` actions and are designed in the My Profile LLD (`../07-My-Profile/07.1-My-Profile/LLD-My-Profile.md`, child module 4.1.3 Two-Step Verification); the administrator MFA reset is designed in the Employee Management LLD.
- Naming: `*Controller`, `I*Service` / `*Service`, `I*Repository` / `*Repository`, request DTOs `*Request`, response DTOs `*Response` / `*Dto`, validators `*RequestValidator` (FluentValidation), options `*Options`.
- API base path `/api/v1`; JSON camelCase; enums travel as their names (`JsonStringEnumConverter`); errors are RFC 7807 `ProblemDetails` (`application/problem+json`), field errors as `ValidationProblemDetails` with an `errors` map.
- Backend paths are relative to `backend/src/TaskFlow.Api/`, frontend paths to `frontend/src/app/`, test paths to `backend/tests/`.
- Target framework `net10.0`; EF Core 10 with SQLite; Angular 19 (standalone components, signals).

1.3 Sub-module LLD Index and Endpoint Count

Endpoint counts are the controller actions of facts.md §3, counted by controller and route. Every action is counted exactly once; the Board's `GET /api/v1/tasks/board` is a `TasksController` action and is documented in both the Task Management and the Board LLD, so it is counted once (under Board) in the total column.

#	Code	Sub-module	LLD	Controllers (actions)	Actions in the LLD	Counted toward the total
0	ALL	Overall – Authentication, Legal	This document	`AuthController` (5), `PasswordRecoveryController` (2)	7	7
1	DASH	Dashboard	LLD-Dashboard	`DashboardController` (3), `AnalyticsController` (5)	8	8

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

#	Code	Sub-module	LLD	Controllers (actions)	Actions in the LLD	Counted toward the total
2	TASK	Task Management (incl. comments, activity)	LLD-Task-Management	`TasksController` (12), `TaskCommentsController` (4), `TaskActivityController` (3)	19	18
3	WORK	Employee Workload	LLD-Employee-Workload	`WorkloadController` (1)	1	1
4	BOARD	Board	LLD-Board	`TasksController` – `GET /api/v1/tasks/board` (1)	1	1
5	EMP	Employee Management	LLD-Employee-Management	`EmployeesController` (8)	8	8
6	PROJ	Project Management (incl. positions)	LLD-Project-Management	`ProjectsController` (9), `PositionsController` (2)	11	11
7	DEPT	Department Management	LLD-Department-Management	`DepartmentsController` (7)	7	7
8	MAIL	Mail	LLD-Mail	`MailController` (16)	16	16
9	NOTIF	Notification (incl. reminder engine)	LLD-Notification	`NotificationsController` (4)	4	4
10	RPT	Reports	LLD-Reports	`ReportController` (2)	2	2
11	REM	Reminder Settings	LLD-Reminder-Settings	`ReminderSettingsController` (2)	2	2
12	APP	Application Settings	LLD-Application-Settings	`ApplicationSettingsController` (2)	2	2
13	TFAS	TFA Settings	LLD-TFA-Settings	`AiProvidersController` (4)	4	4
14	ROLE	Role Configuration	LLD-Role-Configuration	`RolesController` (9)	9	9
15	PROF	My Profile (profile, password, two-step verification)	LLD-My-Profile	`ProfileController` (7)	7	7
16	TFA	Assistant	LLD-Assistant	`AssistantController` (7)	7	7
		Total		**23 controllers**	**115** (1 shared)	**114**

Check: 7 + 8 + 18 + 1 + 1 + 8 + 11 + 7 + 16 + 4 + 2 + 2 + 4 + 9 + 7 + 7 = **114**, equal to "Total HTTP actions: **114**" of facts.md §3 (83 distinct routes). The Task Management LLD lists 19 actions because it documents all 12 `TasksController` actions including the board query; subtracting that one shared action gives 18. The Board also calls `GET /api/v1/tasks/assignees` and `PATCH /api/v1/tasks/{id}/status`, which are Task Management actions and are not counted again. The development-only `/api/v1/diagnostics/throw` (mapped in `Program.cs`, not a controller action) is not counted.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

2. Code Structure

2.1 Backend Folder Layout

```
TaskFlow.Api/
  Program.cs                      startup: storage check, migrate, seed, middleware pipeline
  Controllers/<Module>/           Assistant, Auth, Communication, Dashboard, Management,
Monitoring, Profile, Reports, Settings
  Services/<Module>/<SubModule>/  e.g. Auth/{Login, Mfa, PasswordRecovery, Sessions,
AttemptLimits}
  Repositories/<Module>/<SubModule>/  e.g. Auth/{Accounts, RefreshTokens, Mfa,
PasswordRecovery}
  Repositories/Base/              IBaseRepository, BaseRepository, IUnitOfWork, UnitOfWork
  Dtos/<Module>/<SubModule>/      requests / responses (+ Validators/)
  Models/Entities/, Models/Enums/ 31 entities, 14 stored enums
  Integrations/                   Ai/{KeyProtection, Providers, Registry},
Security/{MfaSecrets, OneTimeCodes, Tokens}, Storage/
  Middleware/                     GlobalExceptionHandler, MfaSetupGateMiddleware,
RequestLoggingMiddleware, SessionValidation
  Filters/                        ValidationFilter
  Authorization/                  Policies/ (RequirePermissionAttribute, AuthPolicies),
TaskAccess/, Auditing/, Assistant/
  Common/                         Constants/, Exceptions/, Models/ (PagedResult), Rules/,
Security/, Utils/
  Config/                         CrossCuttingRegistration, RepositoryRegistration,
ServiceRegistration, IntegrationRegistration, *Options
  Persistence/                    AppDbContext, AppDbContextFactory, DatabasePathResolver,
StorageRoot, Migrations/, Seeders/
```

2.2 Frontend Folder Layout

```
src/app/
  config/          app.config.ts (router, HTTP interceptors, provideAppInitializer), api-base-
url.ts, api-base-url.interceptor.ts
  routes/          app.routes.ts (root table: auth, legal, shell with authGuard +
mfaSetupGuard, wildcard -> login)
  layouts/         shell.component.*, nav-items.ts, layout.service.ts, theme-menu.component.*
  modules/<module>/<module>.routes.ts
  modules/<module>/<sub-module>/{pages,components,services,models,utils}
                   assistant, auth, communication, dashboard, legal, management, monitoring,
profile, reports, settings
  shared/auth/     auth.service.ts, auth.interceptor.ts, auth.guard.ts, auth.models.ts,
token.store.ts,
                   role-routes.ts, login-reasons.ts, permissions.ts
  shared/          components/ (backdrop, confirm-dialog, drawer, icon, legal-footer, toast-
host), directives/, services/,
                   testing/, utils/
```

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

2.3 Layer Rules

Rule	Enforced by
Controller → Service → Repository; controllers never use `AppDbContext`; repositories never call services	`TaskFlow.UnitTests/Architecture/ArchitectureTests.cs`
Repositories stage changes only; the service that owns the use case commits through `IUnitOfWork`	`IUnitOfWork` contract (`Repositories/Base/IUnitOfWork.cs`), code review
Each layer registers its own types (`AddCrossCutting`, `AddRepositories`, `AddServices`, `AddIntegrations`)	`Config/*Registration.cs`; `TaskFlow.IntegrationTests/Common/DependencyInjectionTests.cs`
Request DTOs are validated only by FluentValidation validators picked up from the assembly	`ValidationFilter` (global MVC filter)
Every protected action carries a policy (`RequirePermission`, `Authorize(Policy = PermissionPolicy.Prefix + ...)`) or `[Authorize]`; public actions are explicit `[AllowAnonymous]`	`TaskFlow.IntegrationTests/Common/ApiConventionsTests.cs`, `PermissionAuthorizationTests.cs`, `ModuleBasedPermissionEndpointsTests.cs`
Frontend: one folder per module and sub-module with `pages`, `components`, `services`, `models`, `utils`; module routes in `<module>.routes.ts`	`npm run check:structure` (`scripts/check-frontend-structure.mjs`, runs before `ng test`)
The access token is held in memory only (`TokenStore`), never in browser storage	`shared/auth/token.store.ts`

> ⚠️ To be confirmed: the bodies of `ArchitectureTests.cs` and `scripts/check-frontend-structure.mjs` are not in the snapshot (only the file names); the rules above are the ones the code comments and the sub-module LLDs state.

3. Cross-Cutting Design

Concern	Design
Validation	`ValidationFilter` (`Filters/ValidationFilter.cs`) is added to every controller (`AddControllers(options => options.Filters.Add<ValidationFilter>())`). Before the action runs it resolves `IValidator<T>` for every bound argument, runs it, and on any failure short-circuits with **400** `ValidationProblemDetails` whose `errors` map is keyed by property name. Validators are registered with `AddValidatorsFromAssemblyContaining<LoginRequestValidator>()`. Services repeat critical rules and throw `RequestValidationException` / `BusinessRuleException`
Error handling	`GlobalExceptionHandler : IExceptionHandler` (registered with `AddExceptionHandler`, used by `UseExceptionHandler`) is the one place that maps exceptions to responses (section 3.1). `AppException` messages are safe to show; anything else is logged with method, path and trace id and returned as **500** "Something went wrong. Please try again.". Controllers also return `Problem(...)` directly for expected outcomes (for example the sign-in and recovery messages)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Concern	Design
Transactions	`IUnitOfWork` / `UnitOfWork` over the request-scoped `AppDbContext`: `SaveChangesAsync` (turns `DbUpdateConcurrencyException` into `ConcurrencyConflictException` and a SQLite `UNIQUE` failure into `UniqueConstraintException`), `ExecuteInTransactionAsync` (one transaction, joins an open one, commit on return, rollback on throw) and `DetachAll` (clears the change tracker after a failed write). All repositories of a request share the context, so one save commits everything they staged
Authentication	JWT bearer (HMAC-SHA256, `Jwt:Key`), `MapInboundClaims = false`, issuer and lifetime validated, audience not validated. `JwtBearerEvents.OnTokenValidated = SessionValidation.ValidateAsync` re-reads the session on every request (section 3.4)
MFA gate	`MfaSetupGateMiddleware` between `UseAuthentication` and `UseAuthorization` (section 3.3)
Authorization	One policy per catalogue permission `perm:{key}` (`PermissionPolicy.NameFor`, `RequireClaim("permission", key)`), applied with `[RequirePermission(PermissionKeys.X)]` or `[Authorize(Policy = PermissionPolicy.Prefix + PermissionKeys.X)]`; the resource policy `TaskAccess` (section 3.6); refused authorizations logged by `DeniedActionAuditHandler` (section 3.5)
Data scope	Services take the caller's id from `ClaimTypes.NameIdentifier`, never from the request; a resource owned by another user is reported as **404** (notifications, mail, assistant conversations)
Concurrency	EF concurrency tokens (`Users.MfaLastUsedStep`, `Users.MfaFailedAttempts`, `MfaBackupCodes.UsedAt`, `PasswordResetGrants.UsedAt`, `Tasks.ActualHours`) → `ConcurrencyConflictException` → **409** "Someone else changed this record while you were saving. Reload it and try again."
Logging	Section 3.7
Time & time zone	Section 3.8
JSON	`JsonStringEnumConverter` – enums as names; `AddProblemDetails()` for standard problem shapes; `AddOpenApi()` (mapped only in Development)
CORS	Policy `SpaClient` (`CorsPolicies.SpaClient`): origins from `Cors:AllowedOrigins`, any header, any method, credentials allowed (needed for the refresh cookie)
Forwarded headers	`ForwardedHeadersOptions` with `XForwardedFor`; only loopback proxies plus `Proxy:KnownProxies` are trusted, so the recovery throttle sees the real caller address

3.1 Exception → HTTP Status

Exception (`Common/Exceptions/`)	Status	When
`RequestValidationException` (and `MailValidationException`)	400 `ValidationProblemDetails`	A service-level field rule fails (for example unknown mail recipients, attachment limits)
`BusinessRuleException` (and `AnalyticsFilterException`)	400	A business rule is broken (for example "Authenticator MFA is not on.")
`AssistantRequestException`	400, title "TFA could not handle that"	The assistant cannot handle the request; nothing was sent to a provider
`ForbiddenException` (and `AnalyticsForbiddenException`)	403	The caller may not see or change the resource

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Exception (`Common/Exceptions/`)	Status	When
`NotFoundException` (and `AnalyticsEntityNotFoundException`)	404	The resource does not exist or is not the caller's
`ConflictException`	409	The resource is not in a state that allows the change
`ConcurrencyConflictException`	409, title "The record was changed at the same time."	Lost save race (raised by `UnitOfWork`)
`UniqueConstraintException`	409 "That value is already in use."	A save broke a unique index
`AssistantActionConflictException`	409, title "This action can no longer be done"	Pending action expired, done or cancelled
`RateLimitedException`	429, title "Too many requests", optional `Retry-After`	An allowance is used up
`AssistantRateLimitedException`	429 + `Retry-After`	More assistant messages per minute than allowed
`RoleException` (`RoleFailure`)	`NotFound` 404, `Invalid` 400, `ReadOnly` 403, `Duplicate` / `InUse` 409	Role and permission rules (Role Configuration LLD)
`DbUpdateConcurrencyException` (not wrapped)	409	Same message as `ConcurrencyConflictException`
Any other exception	500 "Something went wrong. Please try again."	Logged with `LogError` and trace id
(filter) `ValidationFilter`	400 `ValidationProblemDetails`	FluentValidation failure before the action
(authentication) JWT invalid / `SessionValidation` fails	401	Expired token, stale security stamp, inactive or deleted user
(middleware) `MfaSetupGateMiddleware`	403, `code` = `mfa_setup_required`	MFA setup pending and the path is not on the allow-list
(authorization) policy refused	403	Missing `perm:{key}` claim or `TaskAccess` failure


3.2 Request Pipeline and Startup Order

`Program.cs` builds the pipeline in this order (each step is real code):

#	Step	Purpose
S1	`AddJsonFile("appsettings.Environment.json", optional: true)`, `AddEnvironmentVariables()`	Per-environment values (CORS, `Jwt:Key`, seeding) override `appsettings.json`
S2	`AddCrossCutting`, `AddRepositories`, `AddServices`, `AddIntegrations`	Registration per layer
S3	`StorageRoot.Resolve` + `EnsureAvailable`; `FindLegacyDatabase` warning	Data folder must exist and be writable (`Storage:Root`, default `C:\TaskFlow` on Windows)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

#	Step	Purpose
S4	Windows only: `KeyRingProtectionCheck.Check`	Warns about unprotected AI key-ring keys
S5	`Database.MigrateAsync()` → `SettingsInitializer.InitializeAsync()` → `AccessControlSeeder.SeedAsync()` → `AiProviderSeeder.SeedAsync()` → `DatabaseSeeder.SeedAsync()`	Schema, settings rows, system roles and permission catalogue, AI defaults, optional demo accounts (`Seed:Enabled`)
S6	Development only: `MapOpenApi()` , `/api/v1/diagnostics/throw`	OpenAPI document and a test route for the 500 path
P1	`UseForwardedHeaders()`	Real client address
P2	`RequestLoggingMiddleware`	One log entry per request, outside the exception handler so the final status is logged
P3	`UseExceptionHandler()` → `GlobalExceptionHandler`	Exception → ProblemDetails
P4	`UseHttpsRedirection()`	HTTPS
P5	`UseCors(CorsPolicies.SpaClient)`	SPA origin with credentials
P6	`UseAuthentication()`	JWT bearer + `SessionValidation` (claims refreshed from the database)
P7	`MfaSetupGateMiddleware`	Mandatory MFA enrolment
P8	`UseAuthorization()`	`perm:*` policies, `TaskAccess` , `DeniedActionAuditHandler`
P9	`MapControllers()`	MVC: `ValidationFilter` → action



© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

3.3 MFA Setup Gate

`Middleware/MfaSetupGateMiddleware.cs` is the server-side enforcement of mandatory two-step verification (FR-AUTH-28, FR-AUTH-29). The Angular `mfaSetupGuard` only mirrors it.

1. Runs for every request after `UseAuthentication`.
2. Acts only when the user is authenticated, carries the claim `mfa_setup_required` (`AuthClaims.MfaSetupRequired`, added by `SessionValidation` when `Mfa:Required` is true and `Users.MfaEnabledAt` is null) and the path starts with `/api`.
3. Allow-list: prefixes `/api/v1/auth/` and `/api/v1/users/me/mfa/`, and exactly `/api/v1/users/me` (trailing slash trimmed, case-insensitive). Everything else is refused.
4. Refusal: **403** `ProblemDetails` with `detail` "Set up two-step verification to continue." and extension `code` = `mfa_setup_required` (`MfaSetupGateMiddleware.ErrorCode`). The SPA `authInterceptor` reacts with `markMfaRequired()` and navigates to `/security-setup`.
5. Break-glass: `Mfa:Required = false` (`Mfa__Required=false`) removes the claim, so the gate lets everything through.

3.4 Session Validation

`Middleware/SessionValidation.ValidateAsync(TokenValidatedContext)` runs as `JwtBearerEvents.OnTokenValidated` on every authenticated request (FR-AUTH-44, FR-AUTH-45, FR-AUTH-48):

1. `ClaimTypes.NameIdentifier` must parse as an int, otherwise `context.Fail("Invalid token subject.")`.
2. Reads the token's `sstamp` claim (`AuthClaims.SecurityStamp`; empty for tokens issued before stamps existed).
3. `ISessionService.GetAsync(userId)` → `SessionService` → `IAccountRepository.GetSessionAsync` (`AsNoTracking` projection to `SessionUser`: stamp, `IsActive`, `MfaEnabledAt`, role name, stored role permission keys; soft-deleted users are excluded by the `Users` query filter) → `SessionState` with `EffectivePermissions.Expand(...)` applied and `MfaSetupRequired = Mfa:Required && MfaEnabledAt == null`.
4. Missing, inactive or stamp mismatch → `context.Fail("The session is no longer valid. Sign in again.")` → **401**.
5. Otherwise removes the token's role, `permission` and `mfa_setup_required` claims and adds the current role name, one `permission` claim per effective key, and `mfa_setup_required` when setup is pending.

Effect: a password change (My Profile), a password reset (4.1.2), an administrator MFA reset (Employee Management), deactivation or deletion end every session on the next request; a role or permission change applies on the next request without signing in again. `EffectivePermissions.Expand` adds the finer keys behind the six legacy keys (`dashboard.admin`, `dashboard.manager`, `projects.manage`, `departments.manage`, `employees.manage`, `settings.ai.manage`) and the lower levels of a scope group (Organization ⊃ Team ⊃ Own; `tasks.view.all` ⊃ `tasks.view.own`); always-on keys are not stored as grants.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

3.5 Permission Policies

Item	Design
Catalogue	`Common/Security/PermissionCatalog.cs` – `PermissionCatalog.All` (64 visible entries with name, description, module, sub-module, section, action, `AlwaysGranted`, `IsAssignable`, `ScopeGroup`, `ScopeRank`, role defaults); `PermissionCatalog.Stored` = entries that are not always granted. `PermissionKeys.cs` holds 70 constants = 64 catalogue keys + 6 legacy keys
Policy names	`PermissionPolicy.Prefix` = `perm:`; `PermissionPolicy.NameFor(key)`; one policy per `PermissionCatalog.All` entry, created in `CrossCuttingRegistration.AddCrossCutting` with `RequireClaim(AuthClaims.Permission, key)`
Attribute	`RequirePermissionAttribute : AuthorizeAttribute` – `[RequirePermission(PermissionKeys.X)]` sets the policy name; `[Authorize(Policy = PermissionPolicy.Prefix + PermissionKeys.X)]` is the equivalent long form used by several controllers
Claims source	`permission` claims are rebuilt from the database on every request (section 3.4), so policies never use stale tokens
Always-on keys	`dashboard.view.own`, `tasks.view.own`, `profile.view`, `profile.edit`, `profile.password.change`, `profile.mfa.manage` – not stored, not attribute-checked; their endpoints use `[Authorize]`
Administrator-only keys	`IsAssignable: false` entries such as `roles.administrator.assign`
Seeding	`AccessControlSeeder` inserts missing catalogue rows into `Permissions`, grants every permission to the Administrator role (id 1) on every start, and gives a new permission to Manager / Employee only when it is first created, from the catalogue defaults
Denied-action audit	`DeniedActionAuditHandler : IAuthorizationMiddlewareResultHandler` (singleton) logs `LogWarning("Denied action: user {UserId} attempted {Method} {Path}; authorization policy {Policy} refused.")` for authenticated forbidden results, then delegates to the default handler (401/403 unchanged); identifiers only, never bodies or query strings

Permission keys of the catalogue (all 70, by module): dashboard – `dashboard.view.own`, `dashboard.view.team`, `dashboard.view.organization`, `dashboard.analytics.view`, `dashboard.filters.use`, legacy `dashboard.admin`, `dashboard.manager`; tasks – `tasks.view.own`, `tasks.view.all`, `tasks.create`, `tasks.update`, `tasks.delete`, `tasks.status.change`, `tasks.reassign`, `tasks.recipients.manage`, `tasks.comment.create`, `tasks.comment.edit`, `tasks.comment.delete`, `tasks.activity.view`; projects – `projects.view`, `projects.create`, `projects.edit`, `projects.delete`, `projects.members.manage`, `positions.create`, legacy `projects.manage`; departments – `departments.view`, `departments.create`, `departments.edit`, `departments.delete`, `departments.members.manage`, legacy `departments.manage`; employees – `employees.view`, `employees.create`, `employees.edit`, `employees.status.change`, `employees.delete`, `employees.role.assign`, `employees.mfa.reset`, legacy `employees.manage`; reports – `reports.view`, `reports.export`; workload – `workload.view`, `workload.filters.use`, `workload.tasks.open`; board – `board.view`, `board.filters.use`; settings – `settings.reminders.manage`, `settings.application.manage`, `settings.ai.view`, `settings.ai.edit`, `settings.ai.test`, `settings.ai.model.remove`, legacy `settings.ai.manage`; roles – `roles.manage`, `roles.view.all`, `roles.modify.access`, `roles.administrator.assign`; profile – `profile.view`, `profile.edit`, `profile.password.change`, `profile.mfa.manage`; mail – `mail.read`, `mail.compose`, `mail.organize`, `mail.attachments`; notifications –

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

`notifications.view`, `notifications.manage`; assistant – `assistant.chat`, `assistant.actions.confirm`. Which endpoint needs which key is listed in each sub-module LLD.

3.6 TaskAccess Resource Handler

Item	Design
Policy	`AuthPolicies.TaskAccess` = `"TaskAccess"`, registered with `TaskAccessRequirement`
Handler	`Authorization/TaskAccess/TaskAccessHandler : AuthorizationHandler<TaskAccessRequirement>` (scoped)
Resource	The task id (`int`); any other resource → `Fail()`
Rule	`ITaskAccessService.CanAccessAsync(taskId, userId, canViewAll)` – allowed for the assignee, the creator, an additional recipient, or a user holding `tasks.view.all` (`HasClaim("permission", "tasks.view.all")`)
Callers	Task-scoped actions of `TasksController`, `TaskCommentsController` and `TaskActivityController` call `IAuthorizationService.AuthorizeAsync(User, id, AuthPolicies.TaskAccess)` before the service; failure → `Forbid()` (403). The exact action list and the extra Manager team scope are in the Task Management LLD §3

3.7 Logging

Source	Level	Content
`RequestLoggingMiddleware`	Information	"HTTP {Method} {Path} responded {StatusCode} in {ElapsedMs} ms for user {UserId} (trace {TraceId})"; bodies are never logged
`GlobalExceptionHandler`	Error	"Unhandled exception for {Method} {Path} (trace {TraceId})" with the exception; the client gets only the generic 500 and the trace id in the problem
`DeniedActionAuditHandler`	Warning	Denied action (section 3.5)
`Program.cs`	Warning / Information	Legacy database found; unprotected AI key-ring keys; key ring not fully checked
`AppClock`	Error	Unknown application time zone, UTC used
Services	Warning	Best-effort side effects that failed (notifications, mail copies, recovery notice) – never undo the main change
Configuration	–	`Logging:LogLevel:Default` = Information, `Logging:LogLevel:Microsoft.AspNetCore` = Warning

3.8 Time and Time Zone

- All timestamps are stored in UTC (`TimeProvider.System`, registered as a singleton; `GetUtcNow()`), as SQLite `TEXT`.
- `IAppClock` / `AppClock` (`Services/Settings/ApplicationSettings/Clock/`): `UtcNow`, `GetTimeZoneAsync()` (stored setting `Application.Timezone` in `ApplicationSettings`, else `Application:Timezone` from configuration, default `Asia/Kolkata`; an unknown id logs an error and falls back to UTC), `TodayLocalAsync()`.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

- Local-day logic (task stage, deadline buckets, dashboard and report date bounds, reminder due dates) converts at the edge with the application time zone; details in the Dashboard, Task Management, Notification and Application Settings LLDs.
- Tests use `FakeTimeProvider` (`TaskFlow.UnitTests/TestSupport/FakeTimeProvider.cs`) and `AppClockTests.cs`.

---

4. Module Designs

4.1 Module: Authentication (`AUTH`)

Purpose: password sign-in with mandatory authenticator-app MFA, self-service password recovery with the authenticator, the session lifecycle (access token, rotating refresh cookie), and the first-time Security Setup screen. Traces to `FR-AUTH-01` – `FR-AUTH-51` and `UC-AUTH-01` – `UC-AUTH-05` of the overall FRD.

Endpoints of this module (facts.md §3): 7 – `AuthController` 5 + `PasswordRecoveryController` 2, all documented below. Security Setup uses 6 `ProfileController` actions that belong to My Profile (designed in `../07-My-Profile/07.1-My-Profile/LLD-My-Profile.md` §4.1.1 and §4.1.3) and the MFA gate (§3.3).

#	Child	Method	Route	Action
1	4.1.1 Login	POST	`/api/v1/auth/login`	`AuthController.Login`
2	4.1.1 Login	POST	`/api/v1/auth/mfa/verify`	`AuthController.VerifyMfa`
3	4.1.1 Login	GET	`/api/v1/auth/me`	`AuthController.Me`
4	4.1.2 Account Recovery	POST	`/api/v1/auth/password-recovery/authenticator/verify`	`PasswordRecoveryController.VerifyAuthenticator`
5	4.1.2 Account Recovery	POST	`/api/v1/auth/password-recovery/reset`	`PasswordRecoveryController.Reset`
6	4.1.3 Sessions and Tokens	POST	`/api/v1/auth/refresh`	`AuthController.Refresh`
7	4.1.3 Sessions and Tokens	POST	`/api/v1/auth/logout`	`AuthController.Logout`

Module class / file inventory (shared by the children)

Layer	Type	File	Responsibility
Controller	`AuthController`	`Controllers/Auth/AuthController.cs`	Route `api/v1/auth`; login, MFA verify, refresh, logout, me; writes / clears the refresh cookie
Controller	`PasswordRecoveryController`	`Controllers/Auth/PasswordRecoveryController.cs`	Route `api/v1/auth/password-recovery`; one failure message for every reason

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Type	File	Responsibility
Service	`IAuthService` / `AuthService`	`Services/Auth/Login/`	`LoginAsync`, `VerifyMfaAsync`, `RefreshAsync`, `LogoutAsync`, `GetCurrentAsync`; private `IssueTokens`, `ToDtoAsync`
Service	`IPasswordRecoveryService` / `PasswordRecoveryService`	`Services/Auth/PasswordRecovery/`	`VerifyAuthenticatorAsync`, `IssueResetTokenAsync`, `ResetPasswordAsync`; `TokenLifetime` 10 min
Service	`IMfaService` / `MfaService`	`Services/Auth/Mfa/`	`VerifyAsync` (used here; enrolment in My Profile LLD); `LockedMessage`
Service	`ISessionService` / `SessionService`	`Services/Auth/Sessions/`	`GetAsync(userId)` → `SessionState`
Service	`IAttemptLimiter` / `AttemptLimiter` (singleton)	`Services/Auth/AttemptLimits/`	Sliding 5-minute window; `AttemptsPerAccount` 5, `AttemptsPerAddress` 20, `MaxTrackedKeys` 10 000; keys `user:{id}`, `name:{UPPER}`, `pwd:{id}`
Repository	`IAccountRepository` / `AccountRepository`	`Repositories/Auth/Accounts/`	`FindByLoginForUpdateAsync`, `FindActiveByLoginForUpdateAsync`, `FindWithRoleForUpdateAsync`, `FindLiveForUpdateAsync`, `GetPermissionKeysAsync`, `GetSessionAsync` (`SessionUser`)
Repository	`IRefreshTokenRepository` / `RefreshTokenRepository`	`Repositories/Auth/RefreshTokens/`	`FindByHashWithUserForUpdateAsync`, `FindByHashForUpdateAsync`, `GetActiveForUsersForUpdateAsync`, `Add`
Repository	`IPasswordResetGrantRepository` / `PasswordResetGrantRepository`	`Repositories/Auth/PasswordRecovery/`	`FindUnusedByHashWithUserForUpdateAsync`, `GetOtherUnusedForUpdateAsync`, `Add`
Repository	`IMfaBackupCodeRepository` / `MfaBackupCodeRepository`	`Repositories/Auth/Mfa/`	`FindUnusedForUpdateAsync` (backup code at sign-in), `GetForUserForUpdateAsync`
DTOs	`LoginRequest`, `AuthResponse`, `AuthenticatedUserResponse`, `AuthResult`, `MfaSignInResult`, `AuthTokens`, `UserDto`, `SessionState`	`Dtos/Auth/`	Contracts and internal results
DTOs	`MfaVerifyRequest`, `MfaChallengeResponse`, `MfaVerifyOutcome`	`Dtos/Auth/Mfa/`	Second sign-in step


© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Type	File	Responsibility
DTOs	`AuthenticatorRecoveryRequest`, `RecoverPasswordRequest`, `RecoveryTokenResponse`, `RecoveryVerifyStatus`, `RecoveryVerifyResult`	`Dtos/Auth/PasswordRecovery/PasswordRecoveryRequests.cs`	Recovery
Validators	`LoginRequestValidator`; `MfaVerifyRequestValidator`; `AuthenticatorRecoveryRequestValidator`, `RecoverPasswordRequestValidator`	`Dtos/Auth/Validators/`, `Dtos/Auth/Mfa/Validators/`, `Dtos/Auth/PasswordRecovery/Validators/`	Input rules
Integrations	`ITokenService` / `JwtTokenService`, `AccessToken`, `RefreshTokenValue`	`Integrations/Security/Tokens/`	`CreateAccessToken(user)`, `CreateRefreshToken()`, `HashRefreshToken(token)`
Integrations	`IMfaSecretProtector` / `MfaSecretProtector` (singleton)	`Integrations/Security/MfaSecrets/`	Data Protection purposes `TaskFlow.MfaSecrets` and `TaskFlow.MfaChallenge`; `CreateChallenge`, `ReadChallenge`, `Protect`
Integrations	`Totp`, `Base32`	`Integrations/Security/OneTimeCodes/`	RFC 6238 TOTP (SHA1, 6 digits, 30 s, ±1 step)
Common	`AuthClaims`, `RefreshTokenCookie`, `EffectivePermissions`, `PermissionCatalog`, `PermissionKeys`, `PermissionPolicy`, `SystemRoles`	`Common/Security/`	Claim names, cookie options, permission expansion
Config	`JwtOptions`, `MfaOptions`	`Config/`	`Jwt:*`, `Mfa:*`
Middleware	`SessionValidation`, `MfaSetupGateMiddleware`	`Middleware/`	Sections 3.3 and 3.4
Frontend routes	`AUTH_ROUTES`	`modules/auth/auth.routes.ts`	`login`, `account-recovery`, `security-setup` (`canActivate: [authGuard, securitySetupGuard]`), all outside the shell
Frontend pages	`LoginComponent` (+ `LoginBackgroundComponent`, `remembered-identifier.ts`), `AccountRecoveryComponent` (`RecoveryStep`), `SecuritySetupComponent` (`SetupStep`, `StepInfo`)	`modules/auth/login/`, `modules/auth/account-recovery/`, `modules/auth/security-setup/`	The four screens of the FRD

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Type	File	Responsibility
Frontend service	`AuthService` (Angular)	`shared/auth/auth.service.ts`	`login`, `verifyMfa`, `verifyAuthenticatorRecovery`, `recoverPassword`, `refresh`, `restoreSession`, `logout`, `checkSession`, `hasPermission`, `clearSession`, `applyProfile`, `markMfaConfigured`, `markMfaRequired`; `currentUser` signal
Frontend infra	`authInterceptor`, `authGuard`, `mfaSetupGuard`, `securitySetupGuard`, `permissionGuard`, `TokenStore`, `dashboardRouteFor` / `ROLE_ROUTES` / `DEFAULT_ROUTE`, `LOGIN_REASON_*` / `LOGIN_REASON_MESSAGES`	`shared/auth/`	Bearer header, silent refresh, routing, notices

Class diagram



(Dependencies are drawn from the interfaces for brevity; the concrete `AuthService` and `PasswordRecoveryService` receive them by constructor injection.)

4.1.1 Child module: Login

Screens: Login and its Two-step verification step (FRD 4.1.1, 4.1.2). Actions 1 – 3.

Class / file inventory – `AuthController.Login`, `VerifyMfa`, `Me`; `AuthService.LoginAsync`, `VerifyMfaAsync`, `GetCurrentAsync`; `MfaService.VerifyAsync`; `MfaSecretProtector.CreateChallenge` / `ReadChallenge`; `AccountRepository`; `RefreshTokenRepository.Add`; `MfaBackupCodeRepository.FindUnusedForUpdateAsync`; frontend `LoginComponent` (`modules/auth/login/pages/login.component.ts` / `.html`, `challenge` signal for the code step), `remembered-identifier.ts` (`localStorage` key `taskflow.lastIdentifier`), `dashboardRouteFor`.

API contracts

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

#	Method	Route	Permission / policy	Request	Response	Status codes
1	POST	`/api/v1/auth/login`	`[AllowAnonymous]`	`LoginRequest` (`emailOrUsername`, `password`)	`AuthResponse` + `Set-Cookie: taskflow_refresh`, or `MfaChallengeResponse` (`mfaRequired`, `challengeToken`)	200, 400 (validation), 401 (empty body)
2	POST	`/api/v1/auth/mfa/verify`	`[AllowAnonymous]`	`MfaVerifyRequest` (`challengeToken`, `code`)	`AuthResponse` + cookie	200, 400, 429
3	GET	`/api/v1/auth/me`	`[Authorize]` (no permission key)	–	`AuthenticatedUserResponse` (`id`, `fullName`, `username`, `email`, `role`, `employeeCode`, `permissions`, `mfaSetupRequired`)	200, 401

Request / response example

```
{ "emailOrUsername": "jane.doe@taskflow.com", "password": "S3cret!" }
```

```
{ "mfaRequired": true, "challengeToken": "CfDJ8...protected..." }
```

```
{ "challengeToken": "CfDJ8...protected...", "code": "123456" }
```

```
{
  "accessToken": "eyJhbGciOiJIUzI1NiIs...",
  "expiresAt": "2026-10-31T10:30:00Z",
  "user": { "id": 7, "fullName": "Jane Doe", "username": "jane", "email":
"jane.doe@taskflow.com", "role": "Employee",
            "employeeCode": "EMP007", "permissions": ["dashboard.analytics.view",
"tasks.status.change"], "mfaSetupRequired": false }
}
```

Service logic – `AuthService.LoginAsync(LoginRequest)`

1. `ValidationFilter` has run `LoginRequestValidator` (required, 256 / 128 characters).
2. `IAccountRepository.FindByLoginForUpdateAsync(request.EmailOrUsername.Trim())` – `Username == identifier || Email == identifier`, `Include(Role)`, tracked; soft-deleted users excluded by the query filter.
3. Null or `!IsActive` → `AuthResult.Failure()` → controller `Unauthorized()` (401, empty body; the SPA shows "Invalid email or password.") – one answer for every reason (FR-AUTH-03).
4. `IPasswordHasher<User>.VerifyHashedPassword` (PBKDF2): `Failed` → failure; `SuccessRehashNeeded` → store the new hash (FR-AUTH-04).
5. `MfaEnabledAt` set → save a rehash if needed and return `AuthResult.RequiresMfa(IMfaSecretProtector.CreateChallenge(user.Id, user.SecurityStamp, Mfa:ChallengeMinutes))`; no token, no `LastLoginAt` (FR-AUTH-08, FR-AUTH-12).

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

6. Otherwise set `LastLoginAt`, `UpdatedAt`; `IssueTokens` (`ITokenService.CreateAccessToken`, `CreateRefreshToken`, add a `RefreshToken` row with the SHA-256 hash); `IUnitOfWork.SaveChangesAsync` (FR-AUTH-07).
7. `ToDtoAsync`: permissions = `EffectivePermissions.Expand(GetPermissionKeysAsync(roleId))` ordered ordinally; `MfaSetupRequired = Mfa:Required && MfaEnabledAt == null` (FR-AUTH-10).
8. Controller appends the cookie (`RefreshTokenCookie.CreateOptions(expiresAt)`) and returns `AuthResponse`.

Service logic – `AuthService.VerifyMfaAsync(challengeToken, code)`

1. `IMfaSecretProtector.ReadChallenge` – null for forged, tampered, malformed or expired (5 min) challenges → `Invalid`.
2. `FindWithRoleForUpdateAsync(userId)`; invalid when null, inactive, MFA off or `SecurityStamp` differs from the stamp in the challenge (FR-AUTH-12).
3. `IMfaService.VerifyAsync(user, code, allowBackupCode: true)` → `Success`, `Invalid` or `LockedOut`. Core (`MfaService.VerifyCoreAsync`, My Profile LLD 4.1.3): lock check; 6 ASCII digits → `Totp.TryValidate` (current step ±1, constant-time, step must be greater than `MfaLastUsedStep`, then stored – FR-AUTH-13); otherwise an unused backup code (`NormalizeBackupCode` → `FindUnusedForUpdateAsync` → `UsedAt`); wrong code increments `MfaFailedAttempts`, 5 in a row set `MfaLockedUntil` = now + 5 min (FR-AUTH-14).
4. Success → `LastLoginAt`, `UpdatedAt`, `IssueTokens`, save → `MfaSignInResult(…, Success)`.
5. Controller: `Success` → cookie + `AuthResponse`; `LockedOut` → `Problem(MfaService.LockedMessage, 429)`; otherwise `Problem("The code is incorrect, or the sign-in has expired. Try again or sign in again.", 400)`.


Service logic – `AuthService.GetCurrentAsync(userId)` – loads the user with role and maps with `ToDtoAsync`; the controller returns 401 when the subject claim is not an int or the user is not found. The shell calls it every 15 s (`checkSession`, section 4.1.3).

Frontend logic – `LoginComponent`

1. Pre-fills **Email** from `taskflow.lastIdentifier` (FR-AUTH-06); eye button toggles the password (FR-AUTH-05).
2. Shows the notice for `reason` = `session-ended`, `credentials-changed` or `password-reset` from `LOGIN_REASON_MESSAGES` (FR-AUTH-11).
3. `AuthService.login` → `isMfaChallenge()` → code step; `verifyMfa`; a refused code clears the code box; ← **Back to sign in** clears the password (FR-AUTH-15).
4. On success navigates to `returnUrl` when it is an internal path, else `dashboardRouteFor(role, permissions)`: `Administrator` → `/admin`, `Manager` → `/manager`, custom role with `dashboard.view.organization` → `/admin`, with `dashboard.view.team` → `/manager`, else `/me` (FR-AUTH-09). `mfaSetupRequired` → `mfaSetupGuard` sends the user to `/security-setup` (FR-AUTH-10).

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Sequence diagram



Repository methods

Method	Query / purpose	Notes
`AccountRepository.FindByLoginForUpdateAsync(identifier)`	User by username or email, with role	Tracked; exact comparison; unique indexes `IX_Users_Username`, `IX_Users_Email`
`AccountRepository.FindWithRoleForUpdateAsync(userId)`	User by id with role	Tracked
`AccountRepository.GetPermissionKeysAsync(roleId)`	Stored permission keys of the role	`AsNoTracking`, `RolePermissions` → `Permission.Key`
`RefreshTokenRepository.Add(RefreshToken)`	New refresh-token row	`BaseRepository`
`MfaBackupCodeRepository.FindUnusedForUpdateAsync(userId, codeHash)`	Unused backup code	Index `IX_MfaBackupCodes_UserId_CodeHash`; `UsedAt` concurrency token

Validation rules


© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Field	Rule	Message
`LoginRequest.EmailOrUsername`	`NotEmpty`, `MaximumLength(256)`	FluentValidation default; screen: "Email is required." / "Enter a valid email address."
`LoginRequest.Password`	`NotEmpty`, `MaximumLength(128)`	FluentValidation default; screen: "Password is required."
`MfaVerifyRequest.ChallengeToken`	`NotEmpty`, `MaximumLength(2048)`	FluentValidation default
`MfaVerifyRequest.Code`	`NotEmpty`, `MaximumLength(32)`	FluentValidation default; screen: "Enter the code to continue."

Error cases

Case	Exception / result	Status
Unknown, inactive or deleted account; wrong password	`AuthResult.Failure()` → `Unauthorized()`	401
Wrong, reused or expired code; challenge forged or stale stamp	`MfaVerifyOutcome.Invalid` → `Problem` "The code is incorrect, or the sign-in has expired. Try again or sign in again."	400
5 wrong codes in a row	`MfaVerifyOutcome.LockedOut` → `Problem` "Too many wrong codes. Try again in a few minutes."	429
Parallel code spend	`ConcurrencyConflictException`	409
`GET /api/v1/auth/me` with a bad subject or missing user	`Unauthorized()`	401

State machine – sign-in attempt



4.1.2 Child module: Account Recovery

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Screen: Forgot your password? (`/account-recovery`, FRD 4.1.3). Actions 4 – 5.

Class / file inventory – `PasswordRecoveryController`; `PasswordRecoveryService`; `AttemptLimiter`; `MfaService.VerifyAsync`; `PasswordResetGrantRepository`; `AccountRepository.FindActiveByLoginForUpdateAsync`; `RefreshTokenRepository.GetActiveForUsersForUpdateAsync`; `INotificationPublisher` (Notification LLD); entity `PasswordResetGrant`; frontend `AccountRecoveryComponent` (`RecoveryStep` = `verify` / `password`, inline template with `app-legal-footer variant="dark"`), `AuthService.verifyAuthenticatorRecovery`, `recoverPassword`.

API contracts

#	Method	Route	Permission / policy	Request	Response	Status codes
4	POST	`/api/v1/auth/password-recovery/authenticator/verify`	`[AllowAnonymous]`	`AuthenticatorRecoveryRequest` (`identifier`, `code`)	`RecoveryTokenResponse` (`resetToken`)	200, 400, 429
5	POST	`/api/v1/auth/password-recovery/reset`	`[AllowAnonymous]`	`RecoverPasswordRequest` (`resetToken`, `newPassword`, `confirmPassword`)	–	204, 400

Request / response example

```
{ "identifier": "jane", "code": "654321" }
```

```
{ "resetToken": "q3V0b2tlbl9leGFtcGxlX2Jhc2U2NHVybA" }
```

```
{ "resetToken": "q3V0b2tlbl9leGFtcGxlX2Jhc2U2NHVybA", "newPassword": "NewPass1",
"confirmPassword": "NewPass1" }
```

Service logic – `PasswordRecoveryService.VerifyAuthenticatorAsync(identifier, code, remoteAddress)`

1. Trim the identifier; `IAttemptLimiter.IsAddressBlocked(remoteAddress)` → `Throttled` before any database work.
2. `FindActiveByLoginForUpdateAsync(identifier)` – active, not deleted.
3. Budget key `IAttemptLimiter.AccountKey(user.Id)` (`user:{id}`) or `UnknownKey(identifier)` (`name:{UPPER}`); `TryAcquire(accountKey, remoteAddress)` reserves an attempt **before** the code check; refused → `Throttled` (FR-AUTH-20: 5 per account, 20 per address, sliding 5 minutes).
4. User null or `MfaEnabledAt` null → `Failed` (FR-AUTH-17, FR-AUTH-19).
5. `IMfaService.VerifyAsync(user, code, allowBackupCode: false, countFailure: false)` – backup codes refused (FR-AUTH-18); a wrong code does not touch `MfaFailedAttempts`, an existing lock still refuses (FR-AUTH-21).
6. Success → `Reset(accountKey)`, `IssueResetTokenAsync(user.Id)` → `Verified`.
7. Controller: `Verified` → 200; `Throttled` → 429 "Too many attempts. Try again in a few minutes."; otherwise 400 "The details are incorrect, or the code has expired. Check them and try again.". Address from `HttpContext.Connection.RemoteIpAddress` (after `UseForwardedHeaders`).


© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Service logic – `IssueResetTokenAsync(userId)` – 32 random bytes, Base64Url without padding; a `PasswordResetGrant` with `TokenHash` = SHA-256 hex, `ExpiresAt` = now + 10 minutes; save (FR-AUTH-22).

Service logic – `ResetPasswordAsync(resetToken, newPassword)`

1. `ValidationFilter` has run `RecoverPasswordRequestValidator` (6 – 128 characters, confirmation equal – FR-AUTH-23); a rejected password does not touch the grant, so it stays usable until it expires.
2. `FindUnusedByHashWithUserForUpdateAsync(hash)`; false when no grant, no user, expired, deleted or inactive.
3. Hash the new password; rotate `SecurityStamp` (`Guid.NewGuid().ToString("N")`); `UpdatedAt`; `grant.UsedAt`.
4. Revoke every active refresh token (`GetActiveForUsersForUpdateAsync`) and mark every other unused grant used (`GetOtherUnusedForUpdateAsync`) (FR-AUTH-22, FR-AUTH-24).
5. `IUnitOfWork.SaveChangesAsync`; `ConcurrencyConflictException` (token spent in parallel – `UsedAt` concurrency token) → false.
6. `INotificationPublisher.PublishAsync(..., NotificationType.System, ...)` "Your password was reset with your authenticator app. If this was not you, contact an administrator now."; failure logged as a warning (FR-AUTH-25).
7. Controller: true → 204; false → 400 "This reset link is no longer valid. Start again from the login page."; the SPA shows **Start over** (FR-AUTH-27) and after success opens `/login?reason=password-reset` (FR-AUTH-26).

Sequence diagram



© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Repository methods

Method	Query / purpose	Notes
`AccountRepository.FindActiveByLoginForUpdateAsync(identifier)`	Active, not deleted user by username or email	Tracked, no role include
`PasswordResetGrantRepository.FindUnusedByHashWithUserForUpdateAsync(tokenHash)`	Unused grant with user	`UsedAt == null`; index `IX_PasswordResetGrants_TokenHash`
`PasswordResetGrantRepository.GetOtherUnusedForUpdateAsync(userId, exceptGrantId)`	The user's other open grants	Index `IX_PasswordResetGrants_UserId_UsedAt`
`RefreshTokenRepository.GetActiveForUsersForUpdateAsync(userIds)`	Unrevoked tokens of the users	`RevokedAt == null`; index `IX_RefreshTokens_UserId`

Validation rules


Field	Rule	Message
`AuthenticatorRecoveryRequest.Identifier`	`NotEmpty`, `MaximumLength(256)`	FluentValidation default; screen "Email or username is required."
`AuthenticatorRecoveryRequest.Code`	`NotEmpty`, `MaximumLength(32)`	FluentValidation default; screen "Enter the 6-digit code from the app." (exactly 6 digits on the screen)
`RecoverPasswordRequest.ResetToken`	`NotEmpty`	FluentValidation default
`RecoverPasswordRequest.NewPassword`	`NotEmpty`, `MinimumLength(ChangePasswordRequestValidator.MinPasswordLength)` = 6, `MaximumLength(MaxPasswordLength)` = 128	FluentValidation default; screen "Use at least 6 and at most 128 characters."
`RecoverPasswordRequest.ConfirmPassword`	`Equal(NewPassword)`	"Passwords do not match."

Error cases

Case	Exception / result	Status
Address or account budget used up	`RecoveryVerifyStatus.Throttled`	429
Unknown or inactive account, MFA off, wrong code, backup code, MFA locked	`RecoveryVerifyStatus.Failed`	400 (one message)
Reset token unknown, used, expired, cancelled; user inactive or deleted	`false`	400
Token spent in parallel	`ConcurrencyConflictException` caught → `false`	400
Notification write fails	Logged warning only	204 (reset kept)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

State machine – `PasswordResetGrant`



(`Used` and `Cancelled` both set `UsedAt`; `Expired` is evaluated at read time from `ExpiresAt`.)

4.1.3 Child module: Sessions and Tokens

Screen: Sessions and Sign out (FRD 4.1.5). Actions 6 – 7, plus `GET /api/v1/auth/me` (action 3) as the session check and the session validation of section 3.4.

Class / file inventory – `AuthController.Refresh`, `Logout`; `AuthService.RefreshAsync`, `LogoutAsync`, `IssueTokens`; `JwtTokenService` (`CreateAccessToken` – claims `sub`, `ClaimTypes.NameIdentifier`, `ClaimTypes.Name`, `ClaimTypes.Role`, `sstamp`, `jti`; issuer `Jwt:Issuer`; HMAC-SHA256; `CreateRefreshToken` – 64 random bytes Base64, `ExpiresAt` = now + `Jwt:RefreshTokenDays`; `HashRefreshToken` – SHA-256 hex); `RefreshTokenCookie` (`taskflow_refresh`, path `/api/v1/auth`, HttpOnly, Secure, SameSite Strict); `SessionValidation`; `SessionService`; frontend `authInterceptor`, `AuthService.refresh` / `restoreSession` / `logout` / `checkSession`, `TokenStore`, `authGuard`, `ShellComponent` (`SESSION_CHECK_INTERVAL_MS` = 15 000 and `visibilitychange`), `provideAppInitializer(restoreSession)`.

API contracts

#	Method	Route	Permission / policy	Request	Response	Status codes
6	POST	`/api/v1/auth/refresh`	`[AllowAnonymous]`; cookie `taskflow_refresh`	– (cookie)	`AuthResponse` + new cookie	200, 401 (cookie cleared)
7	POST	`/api/v1/auth/logout`	`[AllowAnonymous]`; cookie	– (cookie)	–	204

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Request / response example

```
{ "accessToken": "eyJhbGciOiJIUzI1NiIs...", "expiresAt": "2026-10-31T11:00:00Z",
  "user": { "id": 7, "role": "Employee", "permissions": ["tasks.status.change"],
"mfaSetupRequired": false } }
```

(Request: empty body, `Cookie: taskflow_refresh=...`; response also sets a new `taskflow_refresh` cookie.)

Service logic – `AuthService.RefreshAsync(refreshToken)`

1. Empty → failure. `FindByHashWithUserForUpdateAsync(ITokenService.HashRefreshToken(token))` (with user and role).
2. Failure when not found, revoked, expired, user missing or inactive (tokens of deleted users are hidden by the `RefreshTokens` query filter) (FR-AUTH-43).
3. Revoke the presented token (`RevokedAt` = now) and issue a new pair with `IssueTokens` (rotation); save; map to `UserDto` with the current permissions.
4. Controller: failure → `ClearRefreshCookie()` + 401; success → new cookie + `AuthResponse` (FR-AUTH-41, FR-AUTH-42).


Service logic – `AuthService.LogoutAsync(refreshToken)` – no token, unknown or already revoked → no-op; otherwise `FindByHashForUpdateAsync` and set `RevokedAt`; save. The controller always deletes the cookie and returns 204 (FR-AUTH-46).

Frontend logic

1. `restoreSession()` runs at start-up (`provideAppInitializer`): a refresh restores the session after a reload (FR-AUTH-41).
2. `authInterceptor` adds `Authorization: Bearer` (except for login and refresh); on 401 from a non-credential endpoint calls `refresh()` once (shared in-flight observable) and repeats the request; refresh failure → `clearSession()` and `/login?reason=session-ended` (FR-AUTH-42, FR-AUTH-47); on 403 with `code` = `mfa_setup_required` → `markMfaRequired()` and `/security-setup`.
3. `ShellComponent` calls `checkSession()` (`GET /api/v1/auth/me`) every 15 s and when the tab becomes visible, and updates the `currentUser` signal, menus and guards (FR-AUTH-44, FR-AUTH-50).
4. `authGuard` sends visitors to `/login?returnUrl=…`; the root wildcard `**` and the empty path redirect to `login` (FR-AUTH-51); `permissionGuard` sends a user without the screen's permission to `dashboardRouteFor(...)`.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Sequence diagram



Repository methods

Method	Query / purpose	Notes
`RefreshTokenRepository.FindByHashWithUserForUpdateAsync(tokenHash)`	Token with user and role	`Include(User).ThenInclude(Role)`; index `IX_RefreshTokens_TokenHash`
`RefreshTokenRepository.FindByHashForUpdateAsync(tokenHash)`	Token only (logout)	Tracked
`AccountRepository.GetSessionAsync(userId)`	Stamp, active flag, `MfaEnabledAt`, role name, role keys	`AsNoTracking` projection to `SessionUser`; runs on every authenticated request

Validation rules


Field	Rule	Message
Cookie `taskflow_refresh`	Present, known, not revoked, not expired, user active	401 (no body)

Error cases

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Case	Exception / result	Status
Refresh cookie missing, unknown, revoked or expired; user inactive or deleted	`AuthResult.Failure()`; cookie cleared	401
Access token with stale `sstamp`, inactive user	`SessionValidation` → `context.Fail(...)`	401
Logout without cookie or with a revoked one	No-op	204

State machine – `RefreshToken`



4.1.4 Child module: Security Setup (first-time MFA enrolment)

Screen: Let's secure your account (`/security-setup`, FRD 4.1.4, `FR-AUTH-28` – `FR-AUTH-40`). This child has **no controller action of its own**: the screen calls `ProfileController` actions, whose design is in LLD-My-Profile – §4.1.1 User Profile (`GET` / `PUT` `/api/v1/users/me`) and §4.1.3 Two-Step Verification (`POST /api/v1/users/me/mfa/setup`, `POST /api/v1/users/me/mfa/enable`, also `/api/v1/users/me/mfa/check` and `/api/v1/users/me/mfa/backup-codes`, which the setup screen does not call). The server-side enforcement is the MFA gate (§3.3) and `SessionValidation` (§3.4). The administrator reset (`POST /api/v1/users/{id}/mfa/reset`, `employees.mfa.reset`) is in the Employee Management LLD.

Class / file inventory

Layer	Type	File	Responsibility
Route	`security-setup`	`modules/auth/auth.routes.ts`	`canActivate: [authGuard, securitySetupGuard]`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com


Layer	Type	File	Responsibility
Page	`SecuritySetupComponent`, `SetupStep`, `StepInfo`	`modules/auth/security-setup/pages/security-setup.component.ts`, `security-setup.model.ts`	Steps **Your details** → **Authenticator app** → **Backup codes**; QR code via the `qrcode` package
Frontend service	`ProfileService` (Angular)	`modules/profile/services/profile.service.ts`	`get()`, `update(...)`, `startMfaSetup(currentPassword)`, `enableMfa(code)` on `/api/v1/users/me`
Frontend service	`AuthService`	`shared/auth/auth.service.ts`	`applyProfile`, `markMfaConfigured`, `logout`
Guards	`mfaSetupGuard`, `securitySetupGuard`	`shared/auth/auth.guard.ts`	Shell → setup while `mfaSetupRequired`; setup → dashboard once done (FR-AUTH-30)
Backend gate	`MfaSetupGateMiddleware`	`Middleware/MfaSetupGateMiddleware.cs`	403 `mfa_setup_required` outside the allow-list (FR-AUTH-29)
Backend services	`ProfileService` → `MfaService` (`BeginSetupAsync` / `EnableAsync` behind `BeginMfaSetupAsync`, `EnableMfaAsync`)	`Services/Profile/`, `Services/Auth/Mfa/`	Password re-entry (limiter key `pwd:{id}`), `Totp.NewSecret()`, `MfaSecretProtector.Protect`, 10 backup codes `XXXXX-XXXXX` stored as SHA-256 hashes – designed in My Profile LLD §4.1.3

Frontend logic – `SecuritySetupComponent`

1. Step 1: `ProfileService.get()` shows the read-only facts; **Save and continue** → `update(...)` with **Full name**, **Email** (`@taskflow.com` fixed) and **Mobile number** (FR-AUTH-31); load failure → "We could not load your details." with **Try again** (FR-AUTH-40); **Sign out** → `AuthService.logout()` (FR-AUTH-39).
2. Step 2: **Show my QR code** → `startMfaSetup(currentPassword)` → key and `otpauth://` URI rendered as QR code and typed key with **Copy key** (FR-AUTH-32, FR-AUTH-33); **Verify and turn on** → `enableMfa(code)` (FR-AUTH-34); **Start over** requests a new key.
3. Step 3: shows the 10 backup codes once with **Copy all** / **Download** (FR-AUTH-36); **Open TaskFlow** is enabled only after the check box (FR-AUTH-37); `markMfaConfigured()` clears `mfaSetupRequired` and the guard lets the shell open.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Sequence diagram



Error cases – any other API call while setup is pending → 403 "Set up two-step verification to continue." (`code` `mfa_setup_required`); wrong password → "Current password is incorrect."; 6th password attempt in 5 minutes → "Too many attempts. Try again in a few minutes."; wrong code → "The code is incorrect or has expired."; MFA already on → "Authenticator MFA is already on. Turn it off first to set it up again." (all designed in My Profile LLD §4.1.3).

4.2 Module: Legal (`LEGAL`)

Purpose: five public, read-only legal documents and an ownership footer, built entirely in the frontend (`FR-LEGAL-01` – `FR-LEGAL-16`, `UC-LEGAL-01` – `UC-LEGAL-02`). **Endpoints: 0** (no controller, service, table or permission key; a search of the backend found no legal code). 5 public client routes.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

4.2.1 Child module: Legal Documents


Class / file inventory

Layer	Type	File	Responsibility
Routes	`LEGAL_ROUTES`	`modules/legal/legal.routes.ts`	`legal/copyright`, `legal/terms`, `legal/privacy`, `legal/disclaimer`, `legal/licenses`; each `loadComponent` → `LegalPageComponent` with `data: { documentId }`; registered at root, outside the shell (no `authGuard`, no `mfaSetupGuard`)
Page	`LegalPageComponent`	`modules/legal/pages/legal-page.component.ts` / `.html`	Heading, **Contents**, sections by block kind, back link, not-found fallback
Models	`LegalDocumentId`, `LegalBlock` (`paragraph` / `list` / `note` / `table`), `LegalSection`, `LegalDocument`	`modules/legal/models/legal-document.model.ts`	Document shape
Data	`LEGAL_DOCUMENTS`, `getLegalDocument(id)`, `LEGAL_DOCUMENT_IDS`	`modules/legal/utils/legal-documents.ts`	Static registry of the five documents
Owner record	`LEGAL_OWNER`, `LEGAL_APPLICATION`, `LEGAL_TOKENS`, `resolveLegalTokens(text)`, `legalOwnershipLine()`	`modules/legal/utils/legal-owner.ts`	Owner name "Jojo George", year 2026, email "jojogeorge3344@gmail.com", rights "All Rights Reserved"
Used	`AuthService.currentUser()`, `dashboardRouteFor`	`shared/auth/`	Back-link target only

#	Route	`documentId`	Title	Footer label	Sections
1	`/legal/copyright`	`copyright`	Copyright Notice	Copyright	8
2	`/legal/terms`	`terms`	Terms of Use	Terms of Use	14
3	`/legal/privacy`	`privacy`	Privacy Policy	Privacy Policy	11
4	`/legal/disclaimer`	`disclaimer`	Disclaimer	Disclaimer	7
5	`/legal/licenses`	`licenses`	Third-Party Licence Notices	Licences	3

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Class diagram




API contracts – *Not applicable for this module.* (no HTTP call).

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Frontend logic – `LegalPageComponent`

1. `routeData` = `toSignal(route.data.pipe(map(d => d['documentId'])))`.
2. `document` (`computed`) = `getLegalDocument(id)` (`Array.find` in `LEGAL_DOCUMENTS`); undefined → fallback "Legal document not found" / "The document you requested is not available." (FR-LEGAL-07).
3. `resolvedDocument` deep-clones the document and runs `resolveLegalTokens()` over title, summary, headings and every block text, so owner values come from the single owner record (FR-LEGAL-05).
4. `ownershipLine` = `legalOwnershipLine()` → "© 2026 Jojo George. All Rights Reserved." (FR-LEGAL-03).
5. **Contents** anchors `#section.id` scroll to the section (FR-LEGAL-04).
6. `backLink`: signed in → `{ path: dashboardRouteFor(user.role), label: 'Back to the application' }`, otherwise `{ path: '/login', label: 'Back to sign in' }` (FR-LEGAL-06).
7. All text is rendered through Angular interpolation (HTML-escaped; no `innerHTML`); nothing is stored or sent (FR-LEGAL-08).

Sequence diagram



Validation rules / error cases

Case	Handling	Status
Route without a matching registry entry	Not-found fallback in the page	– (client)
Any other `/legal/...` path	Root wildcard `**` → `/login`	– (client)

4.2.2 Child module: Legal Footer and Ownership Notice


Class / file inventory

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Type	File	Responsibility
Shared component	`LegalFooterComponent` (`app-legal-footer`), `LegalFooterVariant` = `'surface'` / `'dark'`	`shared/components/legal-footer/legal-footer.component.ts` / `.html`, `legal-footer.model.ts`	Ownership line "… · TaskFlow — Intelligent Task Allocation & Tracking System." and five links in the fixed order built from `LEGAL_DOCUMENTS` (FR-LEGAL-12 – FR-LEGAL-14)
Consumers	`ShellComponent` (`variant="surface"`), `LoginComponent` (`variant="dark"`), `AccountRecoveryComponent` (`variant="dark"`)	`layouts/shell.component.html`, `modules/auth/login/pages/login.component.html`, `modules/auth/account-recovery/pages/account-recovery.component.ts`	Embed the footer; legal pages do not (FR-LEGAL-15)
Metadata	`AppComponent.ngOnInit`	`app.component.ts`	`Title.setTitle('TaskFlow — Intelligent Task Allocation & Tracking System')`; `Meta.updateTag` for `author` "Jojo George", `description` (`LEGAL_APPLICATION.description`), `copyright` (`legalOwnershipLine()`) (FR-LEGAL-16)

API contracts – *Not applicable for this module.*

Sequence diagram



© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com


5. Database Design

SQLite through EF Core 10; one `AppDbContext` (`Persistence/AppDbContext.cs`) with 31 `DbSet`s. Soft delete with global query filters on `Users`, `Projects`, `Departments` (and dependent filters on `RefreshTokens`, `UserProjectAllocations`, `UserDepartments`). Timestamps are UTC `TEXT`; booleans `INTEGER`.


5.1 ER Diagram

The 31 entities are split into five diagrams (≤ 14 nodes each); `Users` appears in each. Detail of every table outside the shared identity tables is in the owning sub-module LLD (table in 5.2.2).

5.1.1 Identity and access (shared – this document)




5.1.2 Organisation (Employee, Project, Department Management)




© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com


5.1.3 Tasks, notifications and reminders (Task Management, Notification, Settings)



5.1.4 Mail



5.1.5 TFA Assistant and TFA Settings



© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

5.2 Tables

5.2.1 Shared identity and access tables

`Users` (User)

Column	Type	Null	Key / index	Default	Description
Id	int (INTEGER)	No	PK	identity	JWT subject, challenge user id
EmployeeCode	string(32) (TEXT)	Yes	–	–	Employee code
FullName	string(200) (TEXT)	No	–	`""`	Display name
Username	string(100) (TEXT)	No	Unique `IX_Users_Username`	`""`	Sign-in name (matched exactly)
Email	string(256) (TEXT)	No	Unique `IX_Users_Email`	`""`	Sign-in email, stored lower-case `@taskflow.com` (`EmailPolicy`)
MobileNumber	string(20) (TEXT)	Yes	–	–	E.164 number (`MobileNumberPolicy`)
MfaSecretProtected	string(512) (TEXT)	Yes	–	–	Data-Protection-encrypted TOTP key (purpose `TaskFlow.MfaSecrets`)
MfaEnabledAt	DateTime (TEXT)	Yes	–	–	MFA on since; null = off
MfaLastUsedStep	long (INTEGER)	No	Concurrency token	0	Last accepted TOTP step (replay protection)
MfaFailedAttempts	int (INTEGER)	No	Concurrency token	0	Consecutive wrong codes
MfaLockedUntil	DateTime (TEXT)	Yes	–	–	Code lockout end
PasswordHash	string (TEXT)	No	–	`""`	`PasswordHasher<User>` (PBKDF2)
SecurityStamp	string(64) (TEXT)	No	–	`""`	Rotated on password change, reset, MFA reset; compared with JWT `sstamp`
RoleId	int (INTEGER)	No	FK → `Roles.Id` (Restrict), `IX_Users_RoleId`	–	Role
IsActive	bool (INTEGER)	No	–	true	Inactive users cannot sign in or keep a session
CreatedAt / UpdatedAt	DateTime (TEXT)	No	–	–	UTC audit times
LastLoginAt	DateTime (TEXT)	Yes	–	–	Last successful sign-in
IsDeleted	bool (INTEGER)	No	Global query filter `!IsDeleted`	false	Soft delete

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Navigation collections (not columns): `ProjectAllocations`, `DepartmentMemberships`, `ManagerProjects`, `ManagedDepartments`, `RefreshTokens`, `MfaBackupCodes`.

`Roles` (Role)

Column	Type	Null	Key / index	Default	Description
Id	int (INTEGER)	No	PK	identity; system ids 1, 2, 3	`SystemRoles.AdministratorId` 1, `ManagerId` 2, `EmployeeId` 3
Name	string(100) (TEXT, collation `NOCASE`)	No	Unique `IX_Roles_Name`	`""`	Case-insensitive unique
IsSystem	bool (INTEGER)	No	–	false	System roles are read-only (triggers)
CreatedAt	DateTime (TEXT)	No	–	–	UTC

`Permissions` (Permission)

Column	Type	Null	Key / index	Default	Description
Id	int (INTEGER)	No	PK	identity	–
Key	string(100) (TEXT)	No	Unique `IX_Permissions_Key`	`""`	Permission key, e.g. `employees.mfa.reset`
Name	string(200) (TEXT)	No	–	`""`	Display name
Description	string(500) (TEXT)	No	–	`""`	Description
Group	string(100) (TEXT)	No	–	`""`	Catalogue module
IsAssignable	bool (INTEGER)	No	–	true	False = Administrator only

`RolePermissions` (RolePermission)

Column	Type	Null	Key / index	Default	Description
RoleId	int (INTEGER)	No	PK (`RoleId`, `PermissionId`); FK → `Roles.Id` Cascade	–	Role
PermissionId	int (INTEGER)	No	PK; FK → `Permissions.Id` Restrict; `IX_RolePermissions_PermissionId`	–	Granted permission

`RefreshTokens` (RefreshToken)

Column	Type	Null	Key / index	Default	Description
Id	int (INTEGER)	No	PK	identity	–

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Column	Type	Null	Key / index	Default	Description
UserId	int (INTEGER)	No	FK → `Users.Id` Cascade; `IX_RefreshTokens_UserId`	–	Owner; query filter hides tokens of deleted users
TokenHash	string (TEXT)	No	`IX_RefreshTokens_TokenHash`	`""`	SHA-256 hex of the cookie value
ExpiresAt	DateTime (TEXT)	No	–	–	now + `Jwt:RefreshTokenDays`
CreatedAt	DateTime (TEXT)	No	–	–	Issued
RevokedAt	DateTime (TEXT)	Yes	–	–	Set on rotation, logout, password change / reset, MFA reset, custom-role grant change

`PasswordResetGrants` (PasswordResetGrant)

Column	Type	Null	Key / index	Default	Description
Id	int (INTEGER)	No	PK	identity	–
UserId	int (INTEGER)	No	FK → `Users.Id` Cascade; `IX_PasswordResetGrants_UserId_UsedAt` (`UserId`, `UsedAt`)	–	Owner
TokenHash	string(64) (TEXT)	No	`IX_PasswordResetGrants_TokenHash`	`""`	SHA-256 hex of the reset token
CreatedAt	DateTime (TEXT)	No	–	–	Issued
ExpiresAt	DateTime (TEXT)	No	–	–	Issued + 10 minutes
UsedAt	DateTime (TEXT)	Yes	Concurrency token	–	Spent or cancelled

`MfaBackupCodes` (MfaBackupCode)

Column	Type	Null	Key / index	Default	Description
Id	int (INTEGER)	No	PK	identity	–
UserId	int (INTEGER)	No	FK → `Users.Id` Cascade; `IX_MfaBackupCodes_UserId_CodeHash` (`UserId`, `CodeHash`)	–	Owner
CodeHash	string(64) (TEXT)	No	(in the index above)	`""`	SHA-256 hex of the normalised 10-character code
CreatedAt	DateTime (TEXT)	No	–	–	Issued

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Column	Type	Null	Key / index	Default	Description
UsedAt	DateTime (TEXT)	Yes	Concurrency token	–	Spent

5.2.2 All entities – owning LLD

#	Entity	Table (`DbSet`)	Owning LLD (column detail)	Notes
1	`User`	`Users`	This document (5.2.1); also Employee Management, My Profile	Soft delete
2	`RefreshToken`	`RefreshTokens`	This document; My Profile	–
3	`PasswordResetGrant`	`PasswordResetGrants`	This document	Only Account Recovery uses it
4	`MfaBackupCode`	`MfaBackupCodes`	This document; My Profile	–
5	`Role`	`Roles`	This document; Role Configuration	Triggers
6	`Permission`	`Permissions`	This document; Role Configuration	Read-only catalogue
7	`RolePermission`	`RolePermissions`	This document; Role Configuration	Composite PK
8	`Project`	`Projects`	Project Management	Soft delete, filtered unique name
9	`ManagerProject`	`ManagerProjects`	Project Management	Composite PK
10	`Department`	`Departments`	Department Management	Soft delete, filtered unique name
11	`DepartmentManager`	`DepartmentManagers`	Department Management	Composite PK
12	`Position`	`Positions`	Project Management	Seeded 1 – 6, `NOCASE` unique name
13	`UserProjectAllocation`	`UserProjectAllocations`	Project Management (also Employee Management)	Check `CK_UserProjectAllocations_AllocationPercent` 1 – 100
14	`UserDepartment`	`UserDepartments`	Department Management	Composite PK
15	`Task`	`Tasks`	Task Management	Unique `TaskCode`; `ActualHours` concurrency token
16	`TaskRecipient`	`TaskRecipients`	Task Management	Unique (`TaskId`, `UserId`)
17	`TaskComment`	`TaskComments`	Task Management	Index (`TaskId`, `CreatedAt`)
18	`TaskActivityLog`	`TaskActivityLogs`	Task Management	Index (`TaskId`, `CreatedAt`)
19	`Notification`	`Notifications`	Notification	Index (`UserId`, `IsRead`)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

#	Entity	Table (DbSet)	Owning LLD (column detail)	Notes
20	ReminderHistory	ReminderHistory	Notification	Unique dedup index
21	ApplicationSetting	ApplicationSettings	Application Settings (also Reminder Settings)	Unique Key
22	MailMessage	MailMessages	Mail	Filtered unique ReminderHistoryId
23	MailRecipient	MailRecipients	Mail	Unique (MessageId, UserId)
24	MailboxItem	MailboxItems	Mail	Unique (MessageId, OwnerUserId, Folder)
25	MailAttachment	MailAttachments	Mail	File stored under Mail:AttachmentsPath by StorageKey
26	AiProviderConfig	AiProviderConfigs	TFA Settings	Unique Kind; encrypted API key
27	AiModel	AiModels	TFA Settings	Unique (Kind, Name)
28	AssistantConversation	AssistantConversations	Assistant	–
29	AssistantMessage	AssistantMessages	Assistant	–
30	AssistantPendingAction	AssistantPendingActions	Assistant	Guid PK
31	AssistantAudit	AssistantAudits	Assistant	Index (UserId, At)

5.3 Indexes, Constraints & Triggers (shared tables)

Object	Definition	Purpose
IX_Users_Username, IX_Users_Email	Unique (Username), unique (Email)	Sign-in lookup, uniqueness
IX_Users_RoleId	(RoleId)	FK lookup, holder counts
Query filter Users	!IsDeleted	Soft delete; dependent filters on RefreshTokens, UserProjectAllocations, UserDepartments
Concurrency tokens	Users.MfaLastUsedStep, Users.MfaFailedAttempts, MfaBackupCodes.UsedAt, PasswordResetGrants.UsedAt	A code or a reset token wins a race exactly once
IX_RefreshTokens_TokenHash, IX_RefreshTokens_UserId	(TokenHash), (UserId)	Refresh / logout lookup; revoke all

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Object	Definition	Purpose
`IX_PasswordResetGrants_TokenHash`, `IX_PasswordResetGrants_UserId_UsedAt`	(`TokenHash`), (`UserId`, `UsedAt`)	Reset lookup; cancel other open grants
`IX_MfaBackupCodes_UserId_CodeHash`	(`UserId`, `CodeHash`)	Backup code lookup
`IX_Roles_Name`	Unique (`Name`), `NOCASE`	Case-insensitive role names
`IX_Permissions_Key`	Unique (`Key`)	One row per key
`IX_RolePermissions_PermissionId`	(`PermissionId`)	FK lookup
`TR_Roles_SystemNoUpdate`, `TR_Roles_SystemNoDelete`	BEFORE UPDATE / DELETE ON `Roles` WHEN `OLD.IsSystem = 1` → `RAISE(ABORT, ...)`	System roles read-only
`TR_Permissions_NoUpdate`, `TR_Permissions_NoDelete`	BEFORE UPDATE / DELETE ON `Permissions`	Catalogue read-only
`TR_RolePermissions_SystemNoUpdate`, `TR_RolePermissions_SystemNoDelete`	BEFORE UPDATE / DELETE ON `RolePermissions` for system roles	Inserts stay allowed so the seeder can add grants

Indexes, checks and filters of the other tables: see the owning LLD (5.2.2).

5.4 Enumerations

All enums in `Models/Enums/` (facts.md §6) and how they are stored:

Enum	Values	Stored as	Owning LLD
`TaskStatus`	ToDo, InProgress, Blocked, Completed, Cancelled, InQA	INTEGER (0 – 5; InQA appended last) in `Tasks.Status`	Task Management, Board
`TaskPriority`	Low, Medium, High, Critical	INTEGER (0 – 3)	Task Management
`ReminderFrequency`	Daily, Weekly	INTEGER in `Tasks.OverdueReminderFrequency`	Task Management, Reminder Settings
`TaskActivityEventType`	Created, Assigned, Reassigned, StatusChanged, DeadlineChanged, PriorityChanged, Completed, CommentAdded, Administrative, HoursLogged, TimeLogged, Deleted, CommentEdited, CommentDeleted	TEXT (name, max 32)	Task Management
`NotificationType`	TaskAssigned, Reassigned, DeadlineReminder, Overdue, System, TaskComment	TEXT (max 32); `System` used by Account Recovery and the MFA reset	Notification

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Enum	Values	Stored as	Owning LLD
`ReminderType`	FirstReminder, SecondReminder, DueToday, Overdue	TEXT (max 32)	Notification
`ReminderStatus`	Pending, Sent, Failed, Skipped	TEXT (max 32)	Notification
`MailFolder`	Inbox, Sent, Drafts	TEXT (max 16)	Mail
`MailRecipientKind`	To, Cc	TEXT (max 8)	Mail
`AiProviderKind`	Ollama, Gemini, OpenAI	TEXT (max 16) in `AiProviderConfigs`, `AiModels`, `AssistantMessages.ProviderKind`	TFA Settings, Assistant
`AssistantMessageRole`	User, Assistant, Tool	TEXT (max 16)	Assistant
`AssistantActionKind`	SendMail, UpdateOwnProfile, ChangeUserRole	TEXT (max 32)	Assistant
`AssistantActionStatus`	Pending, Confirmed, Cancelled, Expired, Refused, Failed	TEXT (max 16)	Assistant
`ProviderFailureKind`	RateLimited, InvalidKey, Timeout, Unreachable, ModelUnavailable, Unexpected	Not stored (provider error mapping)	TFA Settings, Assistant

Auth-only result enums (not stored): `MfaVerifyOutcome` (Success, Invalid, LockedOut – `Dtos/Auth/Mfa/MfaResults.cs`), `RecoveryVerifyStatus` (Verified, Failed, Throttled); shared: `RoleFailure` (NotFound, Invalid, ReadOnly, Duplicate, InUse).

5.5 Migrations

All 21 migrations in `Persistence/Migrations/`, applied by `Database.MigrateAsync()` at start-up:

#	Migration	Change
1	`20261011171611_InitialAuth`	`Users`, `RefreshTokens`
2	`20261012104823_AddDepartmentsAndUserDepartment`	`Departments`, `Users.DepartmentId` (reshaped by 15 and 18)
3	`20261012124843_AddTasks`	`Tasks`, `TaskRecipients`
4	`20261012173144_AddUserSecurityStamp`	`Users.SecurityStamp`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

#	Migration	Change
5	`20261013075057_AddTaskTracking`	`TaskComments`, `TaskActivityLogs`, `Notifications`
6	`20261013104629_AddTaskReminderSettings`	`Tasks.FirstReminderDays`, `SecondReminderDays`, `OverdueReminderFrequency`; removes duplicate assignee / creator columns
7	`20261017062735_AddReminderEngine`	`ApplicationSettings`, `ReminderHistory` with the dedup index
8	`20261017074817_AddEmailDelivery`	`EmailDeliveryLogs` (SMTP – superseded)
9	`20261017090431_AddInternalMail`	Drops `EmailDeliveryLogs` and the SMTP settings; adds `MailMessages`, `MailRecipients`, `MailboxItems`, `MailAttachments`
10	`20261018183210_AddAssistant`	`AiProviderConfigs`, `AssistantConversations`, `AssistantMessages`, `AssistantPendingActions`, `AssistantAudits`
11	`20261019133820_AddRolesAndPermissions`	`Roles`, `Permissions`, `RolePermissions`, system roles; `Users.Role` → `Users.RoleId`; rotates security stamps; the six triggers
12	`20261019163241_AddAiModels`	`AiModels`
13	`20261019173718_NormalizeEmailDomain`	Data migration: every email moved to `@taskflow.com` (idempotent, irreversible)
14	`20261019174259_AddManagerAssignments`	Manager link table and `Users.ManagerId` (reshaped by 15 and 18)
15	`20261020173455_RenameDepartmentsToProjectsAndAddDepartments`	Old departments become `Projects` / `ManagerProjects`; new `Departments`, `DepartmentManagers`
16	`20261021070943_FixDepartmentFollowUps`	Grants `projects.*` to roles that held the old `departments.*` keys; indexes
17	`20261023101938_AddMfaAndAccountRecovery`	`MfaBackupCodes`, `PasswordResetGrants`; `Users.MfaSecretProtected`, `MfaEnabledAt`, `MfaLastUsedStep`, `MfaFailedAttempts`, `MfaLockedUntil`, `MobileNumber`
18	`20261023160825_UserProjectAllocationsAndDepartments`	`Positions` (seeded), `UserProjectAllocations`, `UserDepartments`; drops `Users.ProjectId`, `DepartmentId`, `ManagerId`
19	`20261023173211_AddProjectManagerFlag`	`UserProjectAllocations.IsProjectManager`
20	`20261024074305_AddTaskActualHours`	`Tasks.ActualHours`
21	`20261024122725_AddTaskCommentEditDelete`	`TaskComments.EditedAt`, `TaskComments.IsDeleted`

Seeders after migration: `SettingsInitializer`, `AccessControlSeeder`, `AiProviderSeeder`, `DatabaseSeeder` (demo accounts only when `Seed:Enabled`).

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

6. Algorithms & Background Jobs

Job / algorithm	Trigger / schedule	Steps	Idempotency
Session validation (`SessionValidation`)	Every authenticated request	Section 3.4	Read-only
MFA gate (`MfaSetupGateMiddleware`)	Every authenticated `/api` request	Section 3.3	Stateless
TOTP (`Totp`, `Base32`)	Code step, recovery, setup, check	HMAC-SHA1, 6 digits, 30 s period, window current ±1, constant-time compare; accepted step must be greater than `MfaLastUsedStep`	Step stored; concurrency token
Code lockout (`MfaService`)	Wrong code	`MfaFailedAttempts` + 1; at `Mfa:MaxFailedAttempts` (5) set `MfaLockedUntil` = now + `Mfa:LockoutMinutes` (5); success resets	Concurrency token
Attempt limiter (`AttemptLimiter`, singleton, in memory)	Recovery verify; password re-entry for MFA setup	Sliding 5-minute window; 5 per account key, 20 per address (IPv6 pooled by /64, IPv4-mapped normalised); at most 10 000 keys (oldest evicted); idle keys swept	Reset on success; lost on restart
Refresh-token rotation (`AuthService.RefreshAsync`)	Every refresh	Revoke presented token, issue a new pair	A used token is refused
Reset token (`PasswordRecoveryService`)	Recovery step 1	32 random bytes Base64Url, SHA-256 hex stored, 10-minute single use	`UsedAt` concurrency token
Permission expansion (`EffectivePermissions.Expand`)	Sign-in, refresh, every request	Legacy key → finer keys; scope group → lower ranks	Pure function
Access-control seeding (`AccessControlSeeder`)	Every start	Ensure system roles; insert missing catalogue permissions; grant all to Administrator; first-time defaults to Manager / Employee	Inserts only
Reminder scheduler (`ReminderSchedulerService`, hosted service)	Every `Reminders:TickSeconds` (60 s) when `Reminders:SchedulerEnabled`	Designed in the Notification LLD	Unique index on `ReminderHistory`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

7. Security Design (detailed)

Item	Implementation
Password hashing	ASP.NET Core Identity `PasswordHasher<User>` (PBKDF2, salted); rehash on `SuccessRehashNeeded`
Access token	JWT HMAC-SHA256 with `Jwt:Key`; issuer `Jwt:Issuer`; lifetime `Jwt:AccessTokenMinutes` (30); claims `sub`, `NameIdentifier`, `Name`, `Role`, `sstamp`, `jti`; kept in memory by `TokenStore`
Refresh token	64 random bytes; cookie `taskflow_refresh`, HttpOnly, Secure, SameSite Strict, path `/api/v1/auth`, `Jwt:RefreshTokenDays` (7); stored only as SHA-256 hex; rotated on every refresh
Session revocation	`SecurityStamp` rotation + revoke all refresh tokens on password change, password reset and MFA reset; stamp and active flag checked on every request
MFA	TOTP key encrypted with Data Protection (`TaskFlow.MfaSecrets`); sign-in challenge protected with `TaskFlow.MfaChallenge`, bound to user id and stamp, `Mfa:ChallengeMinutes` (5); key ring under `AiProviders:KeyRingPath` (DPAPI-protected on Windows); backup codes SHA-256 hashed, single use
Mandatory enrolment	`Mfa:Required` + `MfaSetupGateMiddleware` (server) + `mfaSetupGuard` (client)
Anti-enumeration	Login: bare 401 for every failure; recovery: one message for every failure; recovery code failures do not lock the owner's sign-in
Throttling	`AttemptLimiter` (recovery, password re-entry); code lockout; assistant per-minute limit (Assistant LLD). Password sign-in itself has no attempt limit (section 10)
Permission checks	Policy per endpoint (`perm:{key}`), claims refreshed per request; `TaskAccess` resource handler; service re-checks and own-data scoping; denied actions logged
Transport / browser	HTTPS redirection; CORS `SpaClient` with explicit origins and credentials; forwarded headers trusted only from known proxies
Output safety	ProblemDetails only carry safe `AppException` messages; 500s are generic; Angular interpolation escapes all text
Secrets	`Jwt:Key`, connection string, seed passwords, AI API keys are not in `appsettings.json` (environment / `appsettings.Environment.json`; AI keys encrypted in `AiProviderConfigs.EncryptedApiKey`); request bodies are never logged

8. Configuration

`appsettings.json` keys (facts.md §8) plus keys read with code defaults. Secrets are shown as `<secret>`.

Key	Default	Purpose
`Logging:LogLevel:Default`	`Information`	Default log level
`Logging:LogLevel:Microsoft.AspNetCore`	`Warning`	Framework log level

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Key	Default	Purpose
`ConnectionStrings:Default`	`<secret>`	SQLite database (file under the storage root)
`Storage:Root`	`""` → `C:\TaskFlow` (Windows) or the common application data folder	Data folder for database, key ring, attachments
`Jwt:Issuer`	`TaskFlow`	Token issuer, validated
`Jwt:Key`	`<secret>`	HMAC signing key (environment / `appsettings.Environment.json` only)
`Jwt:AccessTokenMinutes`	`30`	Access token lifetime
`Jwt:RefreshTokenDays`	`7`	Refresh token / cookie lifetime
`Application:Timezone`	`Asia/Kolkata`	Seeds and backs up the `Application.Timezone` setting
`Reminders:SchedulerEnabled`	`true`	Runs `ReminderSchedulerService`
`Reminders:TickSeconds`	`60`	Scheduler tick
`Mail:AttachmentsPath`	`mail-attachments`	Attachment folder under the storage root
`Mail:AppBaseUrl`	– (code, optional)	Base URL for links in mail
`Proxy:KnownProxies`	`[]`	Trusted reverse proxies for `X-Forwarded-For`
`Cors:AllowedOrigins`	– (environment file)	SPA origins of policy `SpaClient`
`Mfa:Issuer`	`TaskFlow`	Name shown in the authenticator app
`Mfa:Required`	`true`	Mandatory MFA (break-glass `Mfa__Required=false`)
`Mfa:MaxFailedAttempts`	`5` (code)	Wrong codes before lockout
`Mfa:LockoutMinutes`	`5` (code)	Lockout length
`Mfa:BackupCodeCount`	`10` (code)	Backup codes per set
`Mfa:ChallengeMinutes`	`5` (code)	Sign-in challenge lifetime
`AiProviders:KeyRingPath`	`<secret>` (default folder `dp-keys`)	Data Protection key ring (AI keys, MFA keys, challenges)
`AiProviders:TimeoutSeconds`	`60`	AI provider HTTP timeout
`Seed:Enabled`	`false` (code)	Demo accounts on start
`Seed:AdministratorPassword`, `Seed:ManagerPassword`, `Seed:EmployeePassword`	`<secret>`	Demo account passwords
`AllowedHosts`	`*`	Host filtering

Frontend: API base URL in `config/api-base-url.ts` (`apiBaseUrlInterceptor`); `SESSION_CHECK_INTERVAL_MS` = 15 000 in the shell. Hard-coded: `RefreshTokenCookie.Name` `taskflow_refresh`, `PasswordRecoveryService.TokenLifetime` 10 min, `AttemptLimiter` limits.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

9. Testing Design

Two backend test projects under `backend/tests/` (150 files in `tests-filelist.json`): `TaskFlow.UnitTests` (xUnit, service and rule tests with in-memory SQLite harnesses) and `TaskFlow.IntegrationTests` (`TaskFlowApiFactory` – `WebApplicationFactory<Program>` end-to-end over HTTP). No frontend spec files are in the snapshot; `npm test` runs `check:structure` and `ng test` (Karma / Jasmine).

Area	Test class / file	Type	Covers
Architecture	`TaskFlow.UnitTests/Architecture/ArchitectureTests.cs`	Unit	Layer rules (2.3)
Exceptions	`TaskFlow.UnitTests/Common/AppExceptionTests.cs`	Unit	Status, title, `Retry-After` of `AppException` types
Exception handler	`TaskFlow.IntegrationTests/Common/GlobalExceptionHandlerTests.cs`	Integration	ProblemDetails mapping, generic 500
API conventions	`TaskFlow.IntegrationTests/Common/ApiConventionsTests.cs`	Integration	Attributes and conventions on every controller
DI	`TaskFlow.IntegrationTests/Common/DependencyInjectionTests.cs`	Integration	Every registered type resolves
Forwarded headers	`TaskFlow.IntegrationTests/Common/ForwardedHeadersTests.cs`	Integration	Trusted proxies only
Key ring	`TaskFlow.IntegrationTests/Common/KeyRingStartupWarningTests.cs`; `TaskFlow.UnitTests/Integrations/Ai/KeyProtection/KeyRingProtectionCheckTests.cs`	Integration / Unit	Start-up warnings
Permissions	`TaskFlow.IntegrationTests/Common/PermissionAuthorizationTests.cs`, `ModuleBasedPermissionEndpointsTests.cs`; `TaskFlow.UnitTests/Settings/RoleConfiguration/PermissionCatalogTests.cs`	Integration / Unit	`perm:*` policies, catalogue
Authentication wiring	`TaskFlow.IntegrationTests/Common/AuthenticationWiringTests.cs`	Integration	JWT validation, `SessionValidation`
Login and sessions	`TaskFlow.IntegrationTests/Auth/Login/AuthEndpointsTests.cs`; `TaskFlow.UnitTests/Auth/Login/AuthServiceLoginTests.cs`, `AuthServiceRefreshAndLogoutTests.cs` (harness `AuthServiceHarness.cs`)	Integration / Unit	Actions 1, 3, 6, 7
MFA sign-in	`TaskFlow.IntegrationTests/Auth/Mfa/MfaSignInEndpointsTests.cs`; `TaskFlow.UnitTests/Auth/Mfa/AuthServiceMfaTests.cs`	Integration / Unit	Action 2, challenge, lockout

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Area	Test class / file	Type	Covers
MFA core	`TaskFlow.UnitTests/Auth/Mfa/MfaServiceTests.cs`; `TaskFlow.UnitTests/Integrations/Security/OneTimeCodes/TotpTests.cs`	Unit	TOTP, backup codes, lockout
Account recovery	`TaskFlow.IntegrationTests/Auth/PasswordRecovery/PasswordRecoveryEndpointsTests.cs`, `TaskFlow.IntegrationTests/Auth/Mfa/MfaRecoveryEndpointsTests.cs`; `TaskFlow.UnitTests/Auth/PasswordRecovery/PasswordRecoveryServiceTests.cs`; `TaskFlow.UnitTests/Auth/AttemptLimits/AttemptLimiterTests.cs`	Integration / Unit	Actions 4, 5, throttling
Security Setup	`TaskFlow.IntegrationTests/Auth/Mfa/MfaEnrolmentEndpointsTests.cs`, `MfaSetupGateEndpointsTests.cs`, `MfaStepUpEndpointsTests.cs`, `MfaAdminResetEndpointsTests.cs`	Integration	Enrolment via `ProfileController`, gate, step-up, admin reset
Tokens	`TaskFlow.UnitTests/Integrations/Security/Tokens/JwtTokenServiceTests.cs`	Unit	JWT claims, refresh token
Time	`TaskFlow.UnitTests/Settings/ApplicationSettings/Clock/AppClockTests.cs`	Unit	Time zone fallback
Persistence	`TaskFlow.UnitTests/Persistence/RolesMigrationTests.cs`, `EmailDomainMigrationTests.cs`, `DepartmentFollowUpMigrationTests.cs`, `UserProjectAllocationsMigrationTests.cs`, `DatabaseSeederTests.cs`, `SettingsInitializerTests.cs`, `StorageRootTests.cs`	Unit	Migrations, seeders, storage root
Shared rules	`TaskFlow.UnitTests/Common/EmailDomainTests.cs`, `MobileNumberPolicyTests.cs`, `TaskBucketRulesTests.cs`	Unit	`EmailPolicy`, `MobileNumberPolicy`, buckets
Test support	`TaskFlow.IntegrationTests/TestSupport/TaskFlowApiFactory.cs`, `MfaTestSupport.cs`, `CapturingLoggerProvider.cs`, `ScriptedChatProvider.cs`, `WindowsOnlyFactAttribute.cs`; `TaskFlow.UnitTests/TestSupport/*` (`FakeTimeProvider`, `TestAccessControl`, `AcceptingMfaService`, harnesses)	Support	Factories, fakes, harnesses
Legal	None	–	No backend code; no frontend spec in the snapshot

Module tests: see section 9 of each sub-module LLD.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

10. Known Limitations & Open Issues

- Password sign-in (`POST /api/v1/auth/login`) has no attempt limit or lockout; only codes, recovery and password re-entry are throttled.
- `AttemptLimiter` is in memory: a restart resets it and it is not shared between API instances.
- Refresh-token rotation does not detect reuse of a rotated token (no token-family revocation); a reused token is only refused.
- `FindByLoginForUpdateAsync` compares the identifier with `==` without lower-casing it, while emails are stored lower-case. > ⚠️ To be confirmed: whether a mixed-case email fails to sign in at runtime on SQLite.
- The login screen applies `Validators.email` and labels the field **Email**, so a plain username cannot be submitted from the UI although the API accepts it (FR-AUTH-01).
- > ⚠️ To be confirmed: the API accepts an unused backup code at `/api/v1/auth/mfa/verify`, but the code box has `maxlength="6"`, so 11-character `XXXXX-XXXXX` codes cannot be typed (FRD 4.1.2).
- `role-routes.ts` routes Administrator / Manager by role name before permissions; the legal back link calls `dashboardRouteFor(user.role)` without permissions, so a custom role with organization or team dashboard access is sent to `/me`.
- The Account Recovery note says "turned on two-step verification from your Profile", but setup happens on `/security-setup`; `auth.models.ts` comments still describe the reset as "SMS".
- `POST /api/v1/users/me/mfa/backup-codes` exists but no UI calls it (My Profile LLD).
- Legal: content is hard-coded (rebuild needed for changes, "Last updated" typed by hand); the not-found fallback cannot be reached by URL; `trackBlock` uses `block.kind`, so two blocks of the same kind in a section produce duplicate track keys; the footer's `aria-current` is never set because the footer is not rendered on legal pages.
- > ⚠️ To be confirmed: `login.component.css`, `security-setup.component.css`, `legal-page.component.css` and `legal-footer.component.css` are referenced by `styleUrl` but are not in the snapshot.
- > ⚠️ To be confirmed: bodies of `ArchitectureTests.cs` and `scripts/check-frontend-structure.mjs` (not in the snapshot).

11. Traceability (FRD → code)

FRD requirement	Endpoint / class	Test
FR-AUTH-01	`POST /api/v1/auth/login` · `AccountRepository.FindByLoginForUpdateAsync` (username or email)	`AuthServiceLoginTests`, `AuthEndpointsTests`
FR-AUTH-02	`LoginRequestValidator` (256 / 128) · `LoginComponent` form validators	`AuthEndpointsTests`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

FRD requirement	Endpoint / class	Test
FR-AUTH-03	`AuthService.LoginAsync` → `AuthResult.Failure()` → 401	`AuthServiceLoginTests`, `AuthEndpointsTests`
FR-AUTH-04	`PasswordHasher<User>.VerifyHashedPassword`, rehash on `SuccessRehashNeeded`	`AuthServiceLoginTests`
FR-AUTH-05	`LoginComponent` show / hide password	None (no frontend spec)
FR-AUTH-06	`remembered-identifier.ts` (`taskflow.lastIdentifier`)	None (no frontend spec)
FR-AUTH-07	`AuthService.LoginAsync` / `VerifyMfaAsync` set `Users.LastLoginAt`	`AuthServiceLoginTests`, `AuthServiceMfaTests`
FR-AUTH-08	`AuthService.LoginAsync` → `AuthResult.RequiresMfa` · `MfaChallengeResponse`	`AuthServiceMfaTests`, `MfaSignInEndpointsTests`
FR-AUTH-09	`dashboardRouteFor` / `ROLE_ROUTES` · `LoginComponent` `returnUrl`	None (no frontend spec)
FR-AUTH-10	`UserDto.MfaSetupRequired` · `mfaSetupGuard`	`MfaSetupGateEndpointsTests`
FR-AUTH-11	`LOGIN_REASON_MESSAGES` · `LoginComponent` notice	None (no frontend spec)
FR-AUTH-12	`POST /api/v1/auth/mfa/verify` · `MfaSecretProtector.ReadChallenge` (5 min, stamp-bound)	`AuthServiceMfaTests`, `MfaSignInEndpointsTests`
FR-AUTH-13	`MfaService.VerifyAsync` → `Totp.TryValidate` (±1 step, `MfaLastUsedStep`)	`MfaServiceTests`, `TotpTests`
FR-AUTH-14	`MfaService` lockout (`Mfa:MaxFailedAttempts`, `Mfa:LockoutMinutes`) → 429	`MfaServiceTests`, `MfaSignInEndpointsTests`
FR-AUTH-15	`LoginComponent` clears code / password	None (no frontend spec)
FR-AUTH-16	`POST /api/v1/auth/password-recovery/authenticator/verify` · `PasswordRecoveryService.VerifyAuthenticatorAsync`	`PasswordRecoveryServiceTests`, `MfaRecoveryEndpointsTests`
FR-AUTH-17	`FindActiveByLoginForUpdateAsync`; `MfaEnabledAt` null → `Failed`	`PasswordRecoveryServiceTests`
FR-AUTH-18	`VerifyAsync(allowBackupCode: false)`	`PasswordRecoveryServiceTests`, `MfaRecoveryEndpointsTests`
FR-AUTH-19	`PasswordRecoveryController.FailureMessage` (one message)	`PasswordRecoveryEndpointsTests`
FR-AUTH-20	`AttemptLimiter` (5 per account, 20 per address, 5 min) → 429	`AttemptLimiterTests`, `PasswordRecoveryEndpointsTests`
FR-AUTH-21	`VerifyAsync(countFailure: false)`; existing lock refuses	`PasswordRecoveryServiceTests`
FR-AUTH-22	`IssueResetTokenAsync` (10 min) · `PasswordResetGrants.UsedAt` · `GetOtherUnusedForUpdateAsync`	`PasswordRecoveryServiceTests`, `PasswordRecoveryEndpointsTests`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

FRD requirement	Endpoint / class	Test
FR-AUTH-23	`POST /api/v1/auth/password-recovery/reset` · `RecoverPasswordRequestValidator`	`PasswordRecoveryEndpointsTests`
FR-AUTH-24	`ResetPasswordAsync` – stamp rotation, `GetActiveForUsersForUpdateAsync` revoke	`PasswordRecoveryServiceTests`
FR-AUTH-25	`INotificationPublisher.PublishAsync(NotificationType.System)`	`PasswordRecoveryServiceTests`
FR-AUTH-26	`AccountRecoveryComponent` → `/login?reason=password-reset`	None (no frontend spec)
FR-AUTH-27	400 "This reset link is no longer valid..." · **Start over**	`PasswordRecoveryEndpointsTests`
FR-AUTH-28	`MfaOptions.Required` · `SessionValidation` claim	`MfaSetupGateEndpointsTests`
FR-AUTH-29	`MfaSetupGateMiddleware` (403 `mfa_setup_required`)	`MfaSetupGateEndpointsTests`
FR-AUTH-30	`securitySetupGuard`	None (no frontend spec)
FR-AUTH-31	`GET` / `PUT /api/v1/users/me` (My Profile LLD 4.1.1) · `SecuritySetupComponent` step 1	`UserProfileEndpointsTests`, `UpdateOwnProfileRequestValidatorTests`
FR-AUTH-32	`POST /api/v1/users/me/mfa/setup` (My Profile LLD 4.1.3) · limiter key `pwd:{id}`	`MfaEnrolmentEndpointsTests`, `MfaServiceTests`
FR-AUTH-33	`SecuritySetupComponent` **Copy key**	None (no frontend spec)
FR-AUTH-34	`POST /api/v1/users/me/mfa/enable` (My Profile LLD 4.1.3)	`MfaEnrolmentEndpointsTests`, `MfaServiceTests`
FR-AUTH-35	`MfaService` "Authenticator MFA is already on..."	`MfaServiceTests`
FR-AUTH-36	`MfaService` backup codes (`Mfa:BackupCodeCount`) · `MfaBackupCodes`	`MfaServiceTests`, `MfaEnrolmentEndpointsTests`
FR-AUTH-37	`SecuritySetupComponent` step 3 check box	None (no frontend spec)
FR-AUTH-38	`MfaSecretProtector.Protect` ; `MfaBackupCodes.CodeHash`	`MfaServiceTests`
FR-AUTH-39	`SecuritySetupComponent` **Sign out** → `POST /api/v1/auth/logout`	`AuthEndpointsTests`
FR-AUTH-40	`SecuritySetupComponent` load error	None (no frontend spec)
FR-AUTH-41	`IssueTokens` · `RefreshTokenCookie.CreateOptions` · `restoreSession`	`AuthEndpointsTests`, `JwtTokenServiceTests`
FR-AUTH-42	`POST /api/v1/auth/refresh` · `authInterceptor` retry	`AuthServiceRefreshAndLogoutTests`, `AuthEndpointsTests`
FR-AUTH-43	`AuthService.RefreshAsync` rotation, refusal of revoked / expired	`AuthServiceRefreshAndLogoutTests`
FR-AUTH-44	`GET /api/v1/auth/me` · `ShellComponent` 15 s check · `SessionValidation` claims	`AuthEndpointsTests`, `AuthenticationWiringTests`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

FRD requirement	Endpoint / class	Test
FR-AUTH-45	`SessionValidation.ValidateAsync` · `SessionService.GetAsync`	`AuthenticationWiringTests`
FR-AUTH-46	`POST /api/v1/auth/logout` · `AuthService.LogoutAsync`	`AuthServiceRefreshAndLogoutTests`, `AuthEndpointsTests`
FR-AUTH-47	`authInterceptor` → `/login?reason=session-ended`	None (no frontend spec)
FR-AUTH-48	`SecurityStamp` rotation + refresh-token revocation (recovery, My Profile, Employee Management)	`PasswordRecoveryServiceTests`, `MfaAdminResetEndpointsTests`, `AuthenticationWiringTests`
FR-AUTH-49	`perm:*` policies · `RequirePermissionAttribute` · `DeniedActionAuditHandler`	`PermissionAuthorizationTests`, `ModuleBasedPermissionEndpointsTests`
FR-AUTH-50	`nav-items.ts` · `permissionGuard`	None (no frontend spec)
FR-AUTH-51	`routes/app.routes.ts` (public auth and legal routes, `**` → `login`) · `authGuard`	None (no frontend spec)
UC-AUTH-01	Actions 1 – 3 · `AuthService` · `LoginComponent`	`AuthEndpointsTests`, `MfaSignInEndpointsTests`
UC-AUTH-02	Actions 4 – 5 · `PasswordRecoveryService` · `AccountRecoveryComponent`	`PasswordRecoveryEndpointsTests`, `MfaRecoveryEndpointsTests`
UC-AUTH-03	`SecuritySetupComponent` · `ProfileController` MFA actions · `MfaSetupGateMiddleware`	`MfaEnrolmentEndpointsTests`, `MfaSetupGateEndpointsTests`
UC-AUTH-04	Action 6 · `SessionValidation` · `authInterceptor` · `ShellComponent`	`AuthServiceRefreshAndLogoutTests`, `AuthenticationWiringTests`
UC-AUTH-05	Action 7 · `AuthService.LogoutAsync`	`AuthEndpointsTests`
FR-LEGAL-01	`LEGAL_ROUTES` (5 routes) · `LEGAL_DOCUMENTS`	None (no frontend spec)
FR-LEGAL-02	`LEGAL_ROUTES` registered outside the shell (no guard)	None (no frontend spec)
FR-LEGAL-03	`LegalPageComponent` heading · `legalOwnershipLine()`	None (no frontend spec)
FR-LEGAL-04	`LegalPageComponent` **Contents** anchors	None (no frontend spec)
FR-LEGAL-05	`resolveLegalTokens` · `LEGAL_OWNER`	None (no frontend spec)
FR-LEGAL-06	`LegalPageComponent.backLink` · `dashboardRouteFor`	None (no frontend spec)
FR-LEGAL-07	`LegalPageComponent` not-found fallback	None (no frontend spec)
FR-LEGAL-08	No backend, no write; interpolation only	None (no frontend spec)
FR-LEGAL-09	`LEGAL_DOCUMENTS` – `privacy` (11 sections)	None (no frontend spec)
FR-LEGAL-10	`LEGAL_DOCUMENTS` – `terms`, `privacy`	None (no frontend spec)
FR-LEGAL-11	`LEGAL_DOCUMENTS` – `disclaimer`	None (no frontend spec)
FR-LEGAL-12	`LegalFooterComponent` in shell, login, recovery	None (no frontend spec)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

FRD requirement	Endpoint / class	Test
FR-LEGAL-13	`LegalFooterComponent` links from `LEGAL_DOCUMENTS`	None (no frontend spec)
FR-LEGAL-14	`legal-owner.ts` shared by footer and pages	None (no frontend spec)
FR-LEGAL-15	Legal pages do not embed `app-legal-footer`	None (no frontend spec)
FR-LEGAL-16	`AppComponent.ngOnInit` (`Title`, `Meta`)	None (no frontend spec)
UC-LEGAL-01	`LegalPageComponent`	None (no frontend spec)
UC-LEGAL-02	`LegalFooterComponent` → router	None (no frontend spec)

Coverage: FR-AUTH-01 – FR-AUTH-51 (51 of 51) and FR-LEGAL-01 – FR-LEGAL-16 (16 of 16) trace to an endpoint or class; 7 of 7 Authentication actions documented; all other requirements trace in their sub-module LLD (section 1.3).

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.