Low-Level Design – Employee Workload

TaskFlow – Intelligent Task Allocation & Tracking System

> **Document:** Low-Level Design (sub-module 02.2 Employee Workload, code `WORK`) · **Version:** 1.0 · **Status:** Draft
> **Project type:** Personal Project (Skill Development) · **Date:** 31-Oct-2026
> **Author:** Jojo George (jojogeorge3344@gmail.com)
> **Based on:** FRD-Employee-Workload v1.0, BRD-Employee-Workload v1.0, HLD-Employee-Workload v1.0, TDD v2.0
> © 2026 Jojo George. All rights reserved.

Document Control

Version	Date	Author	Summary of changes
1.0	31-Oct-2026	Jojo George	Initial version, derived from the code (`WorkloadController`, `WorkloadService`, `WorkloadRepository`, `WorkloadComponent`) and FRD-Employee-Workload v1.0

Related documents: BRD · FRD · HLD · TDD · Specs

Document	Location
BRD – Employee Workload	`../../../BRD/02-TaskFlow-Monitoring/02.2-Employee-Workload/BRD-Employee-Workload.md`
FRD – Employee Workload (`FR-WORK-nn`)	`../../../FRD/02-TaskFlow-Monitoring/02.2-Employee-Workload/FRD-Employee-Workload.md`
HLD – Employee Workload	`../../../HLD/02-TaskFlow-Monitoring/02.2-Employee-Workload/HLD-Employee-Workload.md`
Overall LLD (stack, cross-cutting design, all tables)	`../../00-Overall/LLD-TaskFlow-Overall.md`
Sibling LLD – Task Management (owner of `Tasks`)	`../02.1-Task-Management/LLD-Task-Management.md`
TDD v2.0	`TDD-TaskFlow.md` §6.6, §8.5

1. Introduction

1.1 Purpose

Detailed design of the Employee Workload screen (`/workload`): the single read-only endpoint, its service and repository logic, the four task counts, the client-side average / "High load" rule, the filters

and the **Tasks** → link, the tables it reads, its security checks and its tests. It is detailed enough to maintain the code without reading it first.

1.2 Scope & Conventions

- Covered: sub-module `WORK` – backend `WorkloadController`, `IWorkloadService` / `WorkloadService`, `IWorkloadRepository` / `WorkloadRepository`, `WorkloadEmployee`, `WorkloadCounts`, `EmployeeWorkloadDto`; frontend `WorkloadComponent`, `WorkloadService` (Angular), `EmployeeWorkload`, `WorkloadSummary`.
- Not covered here (see the overall LLD and sibling LLDs): authentication, the `Tasks` table design (Task Management), `UserProjectAllocations` maintenance (Employee / Project Management), role and permission storage (Role Configuration).
- Naming: `*Controller`, `I*Service` / `*Service`, `I*Repository` / `*Repository`, DTOs `*Dto`; repository result records (`WorkloadEmployee`, `WorkloadCounts`) keep EF queries inside the repository layer.
- API base path: `/api/v1`; JSON camelCase with enums as names (`JsonStringEnumConverter`); errors as ProblemDetails.
- **Endpoint count:** facts.md §3 lists **1** controller action for this sub-module – `WorkloadController` `GET /api/v1/workload`. The screen also calls GET `/api/v1/projects` (owned by Project Management) to fill the Project filter.

---

2. Code Structure

2.1 Backend Folder Layout

```
backend/src/TaskFlow.Api/
  Controllers/Monitoring/WorkloadController.cs
  Services/Monitoring/EmployeeWorkload/IWorkloadService.cs, WorkloadService.cs
  Repositories/Monitoring/EmployeeWorkload/IWorkloadRepository.cs, WorkloadRepository.cs,
                                          WorkloadEmployee.cs, WorkloadCounts.cs
  Dtos/Monitoring/EmployeeWorkload/WorkloadDto.cs            (EmployeeWorkloadDto)
  Dtos/Management/EmployeeManagement/UserDto.cs              (ProjectAllocationDto, reused)
  Authorization/Policies/RequirePermissionAttribute.cs       (shared)
  Services/Settings/ApplicationSettings/Clock/IAppClock.cs   (shared clock)
  Config/ServiceRegistration.cs, Config/RepositoryRegistration.cs (DI, scoped)
```

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

2.2 Frontend Folder Layout

```
frontend/src/app/modules/monitoring/
  employee-workload/
    pages/workload.component.ts, workload.component.html     (WorkloadComponent)
    services/workload.service.ts                              (WorkloadService)
    models/workload.model.ts                                  (EmployeeWorkload,
WorkloadSummary)
  monitoring.routes.ts                                        (path 'workload' +
permissionGuard)
frontend/src/app/layouts/nav-items.ts                         (menu item "Employee Workload")
frontend/src/app/modules/management/project-management/services/project.service.ts (Project
filter options)
frontend/src/app/shared/auth/  auth.guard.ts (permissionGuard), permissions.ts, auth.service.ts
```

2.3 Layer Rules

Rule	Enforced by
Controller → Service → Repository only, through interfaces	`ArchitectureTests` (`TaskFlow.UnitTests/Architecture/ArchitectureTests.cs`)
Only `Persistence`, `Repositories` and startup touch `AppDbContext`; repositories never return `IQueryable`	`ArchitectureTests`
Controllers take/return no entities (the controller returns `EmployeeWorkloadDto`)	`ArchitectureTests`
Namespaces match folders; one interface per file beside its class	`ArchitectureTests`
Frontend module layout (`pages`, `services`, `models`)	`npm run check:structure` (`scripts/check-frontend-structure.mjs`, first step of `npm test`)

3. Cross-Cutting Design

Shared design (pipeline, JWT and `SessionValidation`, `MfaSetupGateMiddleware`, ProblemDetails, logging) is described once in the overall LLD (`../../00-Overall/LLD-TaskFlow-Overall.md`). Only what applies to this sub-module is listed.

Concern	Design
Validation	No request body. `projectId` is bound from the query as `int?`; a non-integer value fails model binding (400 by `[ApiController]`). No FluentValidation validator exists for this endpoint
Error handling	`GlobalExceptionHandler` – any unexpected fault becomes a generic 500 "Something went wrong. Please try again."
Transactions	None – read-only; no `IUnitOfWork` call
Authorization	Class-level `[RequirePermission(PermissionKeys.WorkloadView)]` = policy `perm:workload.view`, satisfied by the `permission` claim that `SessionValidation` refreshes from the database on every request

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Concern	Design
Logging	`RequestLoggingMiddleware` (shared); refused authorizations recorded by `DeniedActionAuditHandler`
Time & time zone	"Overdue" is an instant comparison `Deadline < IAppClock.UtcNow` (UTC). The application time zone (`Application:Timezone`) is not used by this sub-module

3.1 Exception → HTTP Status

Exception / outcome	Status	When
Policy `perm:workload.view` fails	403	Caller's role lacks `workload.view` (empty body)
No / invalid token	401	Not signed in, token expired or session revoked
Model-binding failure	400	`projectId` is not an integer
Unhandled exception	500	Database or other fault (`GlobalExceptionHandler.GenericErrorDetail`)

`BusinessRuleException`, `NotFoundException` and `ConflictException` are not raised by this sub-module; an unknown `projectId` simply returns an empty array.

---

4. Module Designs

4.1 Module: TaskFlow Monitoring

4.1.1 Child module: Employee Workload (`WORK`)


Class / file inventory

Layer	Type	File	Responsibility
Controller	`WorkloadController`	`Controllers/Monitoring/WorkloadController.cs`	`[Route("api/v1/workload")]`, class-level `[RequirePermission(PermissionKeys.WorkloadView)]`; action `Get(int? projectId)`
Service	`IWorkloadService` / `WorkloadService`	`Services/Monitoring/EmployeeWorkload/`	`GetWorkloadAsync(projectId)` – joins employees with counts, sums allocations
Repository	`IWorkloadRepository` / `WorkloadRepository` (: `BaseRepository<User>`)	`Repositories/Monitoring/EmployeeWorkload/`	`GetEmployeesAsync`, `GetTaskCountsAsync`
Repository records	`WorkloadEmployee(Id, FullName, Projects)`, `WorkloadCounts(UserId, Active, HighPriority, Overdue, Completed)`	`Repositories/Monitoring/EmployeeWorkload/WorkloadEmployee.cs`, `WorkloadCounts.cs`	Typed query results

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Type	File	Responsibility
DTOs	`EmployeeWorkloadDto`; `ProjectAllocationDto` (reused)	`Dtos/Monitoring/EmployeeWorkload/WorkloadDto.cs`; `Dtos/Management/EmployeeManagement/UserDto.cs`	Response contract
Validator	–	–	None (query parameter only)
Clock	`IAppClock` / `AppClock`	`Services/Settings/ApplicationSettings/Clock/`	`UtcNow` for the Overdue count
Frontend page	`WorkloadComponent` (`app-workload`)	`modules/monitoring/employee-workload/pages/workload.component.ts` / `.html`	Screen, summary, high-load rule, filters, bars, link
Frontend service	`WorkloadService`	`modules/monitoring/employee-workload/services/workload.service.ts`	`getWorkload(projectId)` → `GET /api/v1/workload`
Frontend models	`EmployeeWorkload`, `WorkloadSummary`	`modules/monitoring/employee-workload/models/workload.model.ts`	Row and summary shapes
Frontend service (other module)	`ProjectService.getAll()`	`modules/management/project-management/services/project.service.ts`	Project filter options (GET `/api/v1/projects`)
Route / guard	path `'workload'`, `permissionGuard`, `data.permissions = [Permissions.WorkloadView]`	`modules/monitoring/monitoring.routes.ts`	Screen access
Menu	"Employee Workload" (`/workload`, icon `gauge`)	`layouts/nav-items.ts`	Shown only with `workload.view`

Class diagram



API contracts

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

#	Method	Route	Permission / policy	Request	Response	Status codes
1	GET	`/api/v1/workload`	`workload.view` (policy `perm:workload.view`, class-level `[RequirePermission]`)	Query `projectId` (optional `int`)	`IReadOnlyCollection<EmployeeWorkloadDto>`	200, 400 (binding), 401, 403, 500

Consumed endpoint of another sub-module: GET `/api/v1/projects` (`projects.view`, Project Management) – options of the Project filter. If it fails the drop-down simply stays at "All projects" (the subscription has no error handler).

`EmployeeWorkloadDto` (`record`, camelCase JSON)

Property	Type	Source
`userId`	`int`	`User.Id`
`fullName`	`string`	`User.FullName`
`projects`	`IReadOnlyList<ProjectAllocationDto>`	Allocations ordered by project name
`allocatedPercent`	`int`	`Sum(projects.percent)`
`activeTasks`	`int`	`WorkloadCounts.Active` (0 when the user has no live task)
`highPriorityTasks`	`int`	`WorkloadCounts.HighPriority`
`overdueTasks`	`int`	`WorkloadCounts.Overdue`
`completedTasks`	`int`	`WorkloadCounts.Completed`

`ProjectAllocationDto` (`record ProjectAllocationDto(int ProjectId, string ProjectName, int PositionId, string PositionName, int Percent)`) → JSON `projectId`, `projectName`, `positionId`, `positionName`, `percent` (matches the frontend `EmployeeWorkload.projects` type).

Request / response example

The endpoint is read-only (no write endpoint in this sub-module). Example: `GET /api/v1/workload` with query `projectId=3` → 200 OK

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

```
[
  {
    "userId": 12,
    "fullName": "Asha Nair",
    "projects": [
      { "projectId": 3, "projectName": "Website Revamp", "positionId": 4, "positionName":
"Developer", "percent": 60 }
    ],
    "allocatedPercent": 60,
    "activeTasks": 4,
    "highPriorityTasks": 1,
    "overdueTasks": 1,
    "completedTasks": 9
  }
]
```

Service logic – `WorkloadService.GetWorkloadAsync(int? projectId, CancellationToken)`

1. Authorization has already run (policy `perm:workload.view`); the service takes no user id – the result is organization-wide for every caller (FR-WORK-19).
2. Call `IWorkloadRepository.GetEmployeesAsync(PermissionKeys.TasksViewAll, projectId)` – active, non-deleted users whose role has **no stored grant** of `tasks.view.all`, optionally only those allocated to `projectId`, ordered by `FullName` then `Id`, each with its allocations (FR-WORK-01, FR-WORK-02, FR-WORK-08, FR-WORK-13).
3. If the list is empty, return `Array.Empty<EmployeeWorkloadDto>()` without a second query (FR-WORK-21).
4. Call `GetTaskCountsAsync(userIds, IAppClock.UtcNow)` – one grouped query over live tasks of those users (FR-WORK-03…06).
5. Build `byUser = counts.ToDictionary(UserId)`; for each employee (keeping the repository order) create an `EmployeeWorkloadDto` with the counts or **0** when the user has no live task (FR-WORK-07), and `AllocatedPercent = Projects.Sum(Percent)` (FR-WORK-08).
6. Return the list. Nothing is written (FR-WORK-20).

> Note: the Project filter narrows **who** is listed, not **which tasks** are counted – the four counts always cover all of the person's live tasks across every project (see §10).

Frontend logic – `WorkloadComponent`


Member	Logic	FR
`ngOnInit()`	`projectService.getAll()` → `projects`; then `load()`	FR-WORK-13
`load()`	`loading = true`, `error = null`; `workloadService.getWorkload(projectId())`; on error (`catchError → of(null)`) `error = "Could not load the workload. Check your connection and try again."`, else `rows.set(rows)`	FR-WORK-21, NFR-WORK-01
`setProject(value)`	`projectId = Number(value)` or `null`; `employeeId = null`; `load()` (server reload)	FR-WORK-13
`setEmployee(value)`	`employeeId = Number(value)` or `null` – no reload	FR-WORK-14

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Member	Logic	FR
`reset()`	Clears `projectId` and `employeeId`, `load()`; the **Reset** button is disabled while both are `null`	FR-WORK-14
`filteredRows` (computed)	`rows` or only the row whose `userId === employeeId`	FR-WORK-14
`summary` (computed)	`headcount = filteredRows.length`; `totalActive = Σ activeTasks`; `averageActive = headcount ? totalActive / headcount : 0`; `highLoadThreshold = 2 × averageActive`	FR-WORK-09
`isHighLoad(row)`	`threshold > 0 && row.activeTasks >= threshold` → badge "High load" and class `workload-row--high`	FR-WORK-10
`averageLabel()`	`averageActive.toFixed(1)` – used in the header and in the legend "Highlighted rows carry at least twice the average active load (X active tasks)."	FR-WORK-09, FR-WORK-11
`maxActive` / `barWidth(row)`	`max(1, …activeTasks)`; width `round(activeTasks / maxActive × 100)` %	FR-WORK-12
Overdue cell	class `workload-cell--overdue` when `overdueTasks > 0`	FR-WORK-05
`canFilter` (computed)	`auth.hasPermission(Permissions.WorkloadFilters)` – shows the filter toolbar	FR-WORK-16
`canOpenTasks` (computed)	`auth.hasPermission(Permissions.WorkloadTasksOpen)` – shows the **Tasks** → column; link `routerLink ['/tasks']` with `queryParams { assignedToUserId: row.userId }`	FR-WORK-15, FR-WORK-17
Empty state	`!loading && rows.length === 0` → "No employees to show" / "There are no active employees in this project."	FR-WORK-21
Header text	"Loading workload…" while loading with no rows; otherwise "N employee(s) · average X active tasks"	FR-WORK-09

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Sequence diagram



Repository methods

Method	Query / purpose	Notes
`GetEmployeesAsync(string viewAllPermissionKey, int? projectId)`	`Users` (`Set`) where `IsActive` and `!Role.Permissions.Any(grant => grant.Permission.Key == viewAllPermissionKey)`; if `projectId` given, `ProjectAllocations.Any(a => a.ProjectId == projectId)`; `OrderBy(FullName).ThenBy(Id)`; projected to `WorkloadEmployee` with `ProjectAllocations.OrderBy(a => a.Project.Name)` → `new ProjectAllocationDto(a.ProjectId, a.Project.Name, a.PositionId, a.Position.Name, a.AllocationPercent)`	Projection (untracked). Global query filters apply: `User` `!IsDeleted`; `UserProjectAllocation` `!User.IsDeleted && !Project.IsDeleted`. Checks the **stored** grant only (no `EffectivePermissions.Expand`). Uses PK of `RolePermissions` and `IX_Permissions_Key`, `IX_UserProjectAllocations_ProjectId`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Method	Query / purpose	Notes
`GetTaskCountsAsync(IReadOnlyCollection<int> userIds, DateTime now)`	`Db.Tasks` where `!IsDeleted && userIds.Contains(AssignedToUserId)`; `GroupBy(AssignedToUserId)` → `WorkloadCounts(Key, Active, HighPriority, Overdue, Completed)`	Active = `Status != Completed && Status != Cancelled`; HighPriority = Active and `Priority is High or Critical`; Overdue = Active and `Deadline < now`; Completed = `Status == Completed`. Users without live tasks are absent from the result. Uses `IX_Tasks_AssignedToUserId`

Validation rules

Field	Rule	Message
`projectId` (query)	Optional; must bind to `int`	Framework model-binding 400 (ProblemDetails `errors`)
`projectId` value	Not checked for existence	– (an unknown or deleted project yields `[]`)

Error cases

Case	Exception / result	Status
Caller lacks `workload.view`	Policy failure	403
Not signed in / session invalid	JWT bearer challenge	401
No matching employees	Empty array (screen: "No employees to show")	200
Database fault	Unhandled → `GlobalExceptionHandler`	500
Client receives any error	`WorkloadComponent.load` shows "Could not load the workload. Check your connection and try again." with **Retry**	–

State machine (if any)

Not applicable for this sub-module. The screen changes no state; task statuses are only read.


---

5. Database Design

The sub-module **owns no tables and writes nothing**. It reads the tables below; their full design (all columns, migrations) is in the owning LLDs (Task Management for `Tasks`; Employee / Project Management for `Users`, `UserProjectAllocations`, `Projects`, `Positions`; Role Configuration for `Roles`, `Permissions`, `RolePermissions`). Only the columns used here are listed.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

5.1 ER Diagram



5.2 Tables

`Users` (`User`) – read

Column	Type	Null	Key / index	Default	Description
Id	INTEGER	No	PK	identity	`userId`
FullName	TEXT(200)	No	–	–	`fullName`; sort key
RoleId	INTEGER	No	FK → `Roles.Id` (Restrict), `IX_Users_RoleId`	–	Joins to the role's grants
IsActive	INTEGER (bool)	No	–	–	Only active users are listed
IsDeleted	INTEGER (bool)	No	Global query filter `!IsDeleted`	–	Deleted users never listed

`RolePermissions` (`RolePermission`) and `Permissions` (`Permission`) – read

Column	Type	Null	Key / index	Default	Description
RolePermissions.RoleId	INTEGER	No	PK (`RoleId`, `PermissionId`), FK → `Roles.Id` (Cascade)	–	Role holding a grant
RolePermissions.PermissionId	INTEGER	No	PK, FK → `Permissions.Id` (Restrict), `IX_RolePermissions_PermissionId`	–	Granted permission
Permissions.Key	TEXT(100)	No	Unique `IX_Permissions_Key`	–	Compared with `tasks.view.all`

`UserProjectAllocations` (`UserProjectAllocation`) – read

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Column	Type	Null	Key / index	Default	Description
UserId	INTEGER	No	PK (`UserId`, `ProjectId`), FK → `Users.Id` (Cascade)	–	Employee
ProjectId	INTEGER	No	PK, FK → `Projects.Id` (Cascade), `IX_UserProjectAllocations_ProjectId`	–	Project filter, Projects column
PositionId	INTEGER	No	FK → `Positions.Id` (Restrict), `IX_UserProjectAllocations_PositionId`	–	`positionId` / `positionName`
AllocationPercent	INTEGER	No	Check `CK_UserProjectAllocations_AllocationPercent` (1–100)	–	`percent`, summed into `allocatedPercent`
IsProjectManager	INTEGER (bool)	No	–	–	Not used by this sub-module

`Projects` (`Project`) and `Positions` (`Position`) – read

Column	Type	Null	Key / index	Default	Description
Projects.Name	TEXT(200)	No	Unique `IX_Projects_Name` (filter `IsDeleted = 0`)	–	`projectName`; allocation order
Projects.IsDeleted	INTEGER (bool)	No	Global query filter	–	Deleted projects drop out of allocations
Positions.Name	TEXT(100) NOCASE	No	Unique `IX_Positions_Name`	–	`positionName`

`Tasks` (`Task`) – read

Column	Type	Null	Key / index	Default	Description
AssignedToUserId	INTEGER	No	FK → `Users.Id` (Restrict), `IX_Tasks_AssignedToUserId`	–	Group key
Status	INTEGER (`TaskStatus`)	No	–	–	Active / Completed
Priority	INTEGER (`TaskPriority`)	No	–	–	High priority count
Deadline	TEXT (UTC `DateTime`)	No	`IX_Tasks_Deadline`	–	Overdue count
IsDeleted	INTEGER (bool)	No	**No global filter** – explicit `!IsDeleted` in the query	–	Deleted tasks never counted

5.3 Indexes, Constraints & Triggers

Object	Definition	Purpose
`IX_Tasks_AssignedToUserId`	`Tasks (AssignedToUserId)`	Grouped count per assignee

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Object	Definition	Purpose
`IX_UserProjectAllocations_ProjectId`	`UserProjectAllocations (ProjectId)`	Project filter
`IX_Permissions_Key`	Unique `Permissions (Key)`	`tasks.view.all` lookup
`CK_UserProjectAllocations_AllocationPercent`	`"AllocationPercent" BETWEEN 1 AND 100`	Valid percentages
Global query filters	`User: !IsDeleted`; `UserProjectAllocation: !User.IsDeleted && !Project.IsDeleted`; `Project: !IsDeleted`	Soft-deleted rows excluded
Triggers	–	None used by this sub-module

5.4 Enumerations

Enum	Values	Stored as
`TaskStatus`	`ToDo`, `InProgress`, `Blocked`, `Completed`, `Cancelled`, `InQA` (appended last)	INTEGER (no conversion on `Tasks`); JSON as names
`TaskPriority`	`Low`, `Medium`, `High`, `Critical`	INTEGER; JSON as names

Count mapping: Active = not `Completed` / `Cancelled` (so `ToDo`, `InProgress`, `Blocked`, `InQA`); High priority = Active and `High` / `Critical`.

5.5 Migrations

Migration	Change relevant to this sub-module
`20261012124843_AddTasks`	Creates `Tasks`
`20261013104629_AddTaskReminderSettings`	Creates `IX_Tasks_AssignedToUserId`, `IX_Tasks_Deadline`
`20261019133820_AddRolesAndPermissions`	Creates `Roles`, `Permissions`, `RolePermissions`, `Users.RoleId`
`20261023160825_UserProjectAllocationsAndDepartments`	Creates `Positions`, `UserProjectAllocations` (check constraint, indexes)
`20261023173211_AddProjectManagerFlag`	Adds `UserProjectAllocations.IsProjectManager`

The workload keys `workload.view`, `workload.filters.use`, `workload.tasks.open` are seeded from `PermissionCatalog` (granted to the Manager system role on first seeding; `AccessControlSeeder` grants the Administrator every permission on every start).

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

6. Algorithms & Background Jobs

Job / algorithm	Trigger / schedule	Steps	Idempotency
Workload aggregation (`WorkloadService.GetWorkloadAsync`)	Each `GET /api/v1/workload`	Candidate users → grouped counts → left-join with zero default → sum allocations	Pure read; same input and clock give the same result
High-load rule (`WorkloadComponent.isHighLoad`)	Whenever `filteredRows` changes	`avg = Σ active / rows`; badge when `active ≥ 2 × avg` and `avg > 0`	Client-only, recomputed by Angular signals
Bar scaling (`barWidth`)	Same	`round(active / max(1, max active) × 100)` %	Client-only

No background job belongs to this sub-module.

7. Security Design (detailed)

Item	Implementation
Endpoint permission	`[RequirePermission(PermissionKeys.WorkloadView)]` on the class → policy `perm:workload.view` (`RequireClaim(AuthClaims.Permission, "workload.view")`)
Claim freshness	`SessionValidation` replaces role and permission claims from the database on every request, so a role change applies to the next call
Data scope	Organization for every caller holding `workload.view`; the service takes no caller id (FR-WORK-19)
Who is listed	Users whose role has **no stored** `tasks.view.all` grant (`PermissionKeys.TasksViewAll`)
`workload.filters.use`	**Frontend only** (`canFilter`); the API accepts `projectId` without it
`workload.tasks.open`	**Frontend only** (`canOpenTasks`); the Task List it opens applies the caller's own task scope (`TaskService.VisibilityForCallerAsync`)
Screen access	`permissionGuard` with `Permissions.WorkloadView`; otherwise redirect to `dashboardRouteFor(role, permissions)`
Menu	`nav-items.ts` adds "Employee Workload" only when `workload.view` is held (under **TaskFlow Monitoring** with `tasks.view.all`, otherwise under **Task Management**)
Audit	Refused authorizations recorded by `DeniedActionAuditHandler` (identifiers only)
Secrets	None handled

8. Configuration

Not applicable for this sub-module. Workload has no configuration keys of its own. Inherited keys that affect it:

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Key	Default	Purpose
`Mfa:Required`	`true`	`MfaSetupGateMiddleware` blocks the call until the user has set up MFA
`Jwt:Issuer`	`TaskFlow`	Token validation for the bearer token
`ConnectionStrings:Default`	`<secret>`	SQLite database

9. Testing Design

Paths are relative to `backend/tests`. Only the file names are available; coverage is inferred from them.

Area	Test class / file	Type	Covers
Workload endpoint	`TaskFlow.IntegrationTests/Monitoring/EmployeeWorkload/WorkloadEndpointsTests.cs`	Integration	`GET /api/v1/workload` – 200 / 403, project filter, response shape
Workload service	`TaskFlow.UnitTests/Monitoring/EmployeeWorkload/WorkloadServiceTests.cs`	Unit	Counts (active, high priority, overdue, completed), zero rows, ordering
Custom roles	`TaskFlow.UnitTests/Monitoring/EmployeeWorkload/CustomRoleWorkloadTests.cs`	Unit	Who is listed when a custom role holds or lacks `tasks.view.all`
Harness	`TaskFlow.UnitTests/TestSupport/WorkloadReportHarness.cs`	Support	Shared fixture for workload and report tests
Architecture	`TaskFlow.UnitTests/Architecture/ArchitectureTests.cs`	Unit	Layer, folder and naming rules
Frontend	–	–	No spec file for `WorkloadComponent` (facts: 0 frontend spec files); client rules checked manually

> ⚠️ To be confirmed: the exact cases inside each test file (only file names are available).

10. Known Limitations & Open Issues

- `workload.filters.use` and `workload.tasks.open` are enforced only in the frontend (R-WORK-01).
- Workload is organization-wide, not narrowed to a Manager's team (FR-WORK-19, R-WORK-02).
- The Project filter limits the listed people but **not the counted tasks**: counts include the person's tasks in every project.
- The "listed employee" test reads the stored grant only. `EffectivePermissions.LegacyChildren` currently maps no legacy key to `tasks.view.all`, so the case described in R-WORK-03 cannot occur with today's catalog; it would if such a mapping were added.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

- "High load" is relative to the rows shown, so selecting a single Employee never shows the badge.
- No Department column or filter, unlike original BRD Screen 16 (R-WORK-04).
- The Project filter options come from GET `/api/v1/projects`, which needs `projects.view`; without it the drop-down only offers "All projects".
- No paging: every listed employee is returned in one response.

---

11. Traceability (FRD → code)

FRD requirement	Endpoint / class	Test
FR-WORK-01	`GET /api/v1/workload` · `WorkloadRepository.GetEmployeesAsync` (role without stored `tasks.view.all`, ordered by name)	`WorkloadServiceTests.cs`, `CustomRoleWorkloadTests.cs`
FR-WORK-02	`WorkloadRepository.GetEmployeesAsync` (`IsActive`, `User` query filter)	`WorkloadServiceTests.cs`
FR-WORK-03	`WorkloadRepository.GetTaskCountsAsync` (Active) · `EmployeeWorkloadDto.ActiveTasks`	`WorkloadServiceTests.cs`
FR-WORK-04	`GetTaskCountsAsync` (HighPriority)	`WorkloadServiceTests.cs`
FR-WORK-05	`GetTaskCountsAsync` (Overdue, `IAppClock.UtcNow`) · `workload-cell--overdue`	`WorkloadServiceTests.cs`
FR-WORK-06	`GetTaskCountsAsync` (Completed)	`WorkloadServiceTests.cs`
FR-WORK-07	`WorkloadService.GetWorkloadAsync` (zero default)	`WorkloadServiceTests.cs`
FR-WORK-08	`GetEmployeesAsync` (`ProjectAllocationDto`) · `AllocatedPercent` sum	`WorkloadEndpointsTests.cs`
FR-WORK-09	`WorkloadComponent.summary`, `averageLabel()`	Manual UI
FR-WORK-10	`WorkloadComponent.isHighLoad`	Manual UI
FR-WORK-11	`workload.component.html` legend	Manual UI
FR-WORK-12	`WorkloadComponent.maxActive`, `barWidth`	Manual UI
FR-WORK-13	`GET /api/v1/workload` (`projectId`) · `WorkloadComponent.setProject`	`WorkloadEndpointsTests.cs`
FR-WORK-14	`WorkloadComponent.setEmployee`, `filteredRows`, `reset`	Manual UI
FR-WORK-15	**Tasks →** `routerLink ['/tasks']` + `assignedToUserId` · `GET /api/v1/tasks` scope in `TaskService`	`TasksEndpointsTests.cs`
FR-WORK-16	`WorkloadComponent.canFilter` (`workload.filters.use`)	Manual UI
FR-WORK-17	`WorkloadComponent.canOpenTasks` (`workload.tasks.open`)	Manual UI
FR-WORK-18	`[RequirePermission(PermissionKeys.WorkloadView)]` · `permissionGuard` · `nav-items.ts`	`WorkloadEndpointsTests.cs`
FR-WORK-19	`WorkloadService.GetWorkloadAsync` (no caller scope)	`WorkloadServiceTests.cs`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

FRD requirement	Endpoint / class	Test
FR-WORK-20	Only `GET`; no `IUnitOfWork` in `WorkloadService`	Code inspection (no write path)
FR-WORK-21	Empty array · `WorkloadComponent.load` error text and empty state	Manual UI
FR-WORK-22	Same rules as `TaskBucketRules` / `ToCard` (`Deadline < now`, not Completed/Cancelled, not deleted)	`WorkloadServiceTests.cs`

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.