Low-Level Design – Reports

TaskFlow – Intelligent Task Allocation & Tracking System

> **Document:** Low-Level Design (sub-module 10 – RPT) · **Version:** 1.0 · **Status:** Draft
> **Project type:** Personal Project (Skill Development) · **Date:** 31-Oct-2026
> **Author:** Jojo George (jojogeorge3344@gmail.com)
> **Based on:** HLD – Reports v1.0, FRD – Reports v1.0 (FR-RPT-01 – FR-RPT-42), TaskFlow code as built
> © 2026 Jojo George. All rights reserved.

Document Control

Version	Date	Author	Summary of changes
1.0	31-Oct-2026	Jojo George	Initial version: Task Reports summary and CSV export (controller, service, CSV writer, repository, validator, Angular page), derived from the code and verified against the code fact sheet

Related documents: BRD – Reports (`../../../BRD/05-Reports/05.1-Reports/BRD-Reports.md`) · FRD – Reports (`../../../FRD/05-Reports/05.1-Reports/FRD-Reports.md`) · HLD – Reports (`../../../HLD/05-Reports/05.1-Reports/HLD-Reports.md`) · LLD – Overall (`../../00-Overall/LLD-TaskFlow-Overall.md`) · LLD – Dashboard (`../../01-Dashboard/01.1-Dashboard/LLD-Dashboard.md`) · TDD (`TF - Documents/TF - TDD/TDD-TaskFlow.md` v2.0)

1. Introduction

1.1 Purpose

Detailed design of the Reports sub-module (Task Reports screen, original BRD Screen 17): the two controller actions, the classes and files behind them, the filter DTO and its validator, the summary and export logic, the CSV format with formula protection, the repository queries, the tables read, the tests, and the traceability from FR-RPT-nn to endpoint, class and test.

1.2 Scope & Conventions

- One child module: **Task Reports** (summary totals, filters, CSV export).
- **Endpoints in this sub-module: 2** (facts.md §3: `ReportController` – `GET /api/v1/reports`, `GET /api/v1/reports/export`). Both are read only.
- Naming: `ReportController`, `IReportService` / `ReportService`, `IReportRepository` / `ReportRepository`, static writer `ReportCsv`, query DTO `ReportFilter`, records `ReportCriteria`, `ReportTaskRow`, DTOs `ReportSummaryDto`, `ReportRowDto`.

- API base path: `/api/v1/reports`; JSON camelCase, enums as names (`JsonStringEnumConverter`); errors as `ProblemDetails` / `ValidationProblemDetails`.
- Paths are relative to `backend/src/TaskFlow.Api/` (backend) and `frontend/src/app/` (frontend).

---

2. Code Structure

2.1 Backend Folder Layout

```
TaskFlow.Api/
  Controllers/Reports/          ReportController.cs
  Services/Reports/             IReportService.cs, ReportService.cs, ReportCsv.cs (static CSV
writer)
  Repositories/Reports/         IReportRepository.cs, ReportRepository.cs, ReportCriteria.cs,
ReportTaskRow.cs
  Dtos/Reports/                 ReportDto.cs (ReportFilter, ReportSummaryDto, ReportRowDto)
  Dtos/Reports/Validators/      ReportFilterValidator.cs
  Services/Assistant/Knowledge/ reports-and-workload.md (help article, not code)
  Config/                       ServiceRegistration.cs, RepositoryRegistration.cs (scoped
registrations)
```

2.2 Frontend Folder Layout

```
src/app/modules/reports/
  reports.routes.ts              REPORTS_ROUTES: path 'reports', permissionGuard, reports.view
  pages/report.component.ts/.html ReportComponent (selector app-report, standalone)
  services/report.service.ts     ReportService: getSummary, exportCsv, toParams
  models/report.model.ts         ReportFilter, ReportSummary
src/app/shared/utils/            local-day.ts (startOfLocalDay, endOfLocalDay), save-blob.ts
(saveBlob)
src/app/shared/services/         toast.service.ts (ToastService)
src/app/layouts/nav-items.ts     "Reports" item when reports.view is held
```

2.3 Layer Rules

Rule	Enforced by
Controller → Service → Repository; the controller only encodes the CSV bytes	Code structure; shared architecture rules in the overall LLD
Input validated before the action runs	`ValidationFilter` with `ReportFilterValidator`
Read only: no `SaveChanges`, no notification, mail or activity entry	`AsNoTracking` queries; no `IUnitOfWork` dependency
CSV formatting in one static class	`ReportCsv`
The page calls only `ReportService`; option lists come from the owning modules' services	`ProjectService.getAll`, `TaskService.getAssignees`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

3. Cross-Cutting Design

Shared cross-cutting design (JWT, `perm:` policies, `ValidationFilter`, `GlobalExceptionHandler`, `DeniedActionAuditHandler`, logging, DI) is described once in the overall LLD (`../../00-Overall/LLD-TaskFlow-Overall.md`). Reports-specific points:

Concern	Design
Validation	`ReportFilterValidator` (FluentValidation) run by the global `ValidationFilter` for the bound `ReportFilter`; MVC model binding refuses unparseable dates and enum names. The date pickers set `min` / `max`.
Error handling	Validation → 400 `ValidationProblemDetails`; policy → 403; anything else → 500 via `GlobalExceptionHandler`. The page shows MSG-RPT-01 (load) or the toast MSG-RPT-03 (export) whatever the server says. No `AppException` is thrown by this sub-module.
Transactions	None – read only.
Authorization	Class-level `RequirePermission(reports.view)`; the export action adds `perm:reports.export`, so export needs both keys. Data scope is the whole organisation (design note D3 in `ReportService`).
Logging	Refused policy checks are logged by `DeniedActionAuditHandler` (user id, method, path, policy).
Time & time zone	The browser turns the chosen local days into UTC instants (`startOfLocalDay`, `endOfLocalDay`); `ReportService.AsUtc` normalises them; "overdue" uses `IAppClock.UtcNow`. The application timezone is not used.

3.1 Exception → HTTP Status

Exception / outcome	Status	When
`ValidationFilter` failure	400	`DeadlineTo` before `DeadlineFrom`; `Status` / `Priority` not a defined enum value
Model-binding failure (`[ApiController]`)	400	Unparseable date, unknown enum name, non-numeric id
Authentication failure	401	No or expired access token
Policy failure	403	Missing `reports.view` (both actions) or `reports.export` (export)
Any other exception	500	"Something went wrong. Please try again."

4. Module Designs

4.1 Module: Reports (RPT)

4.1.1 Child module: Task Reports

Class / file inventory


© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Type	File	Responsibility
Controller	`ReportController`	`Controllers/Reports/ReportController.cs`	`Get` (summary), `Export` (CSV file)
Service	`IReportService` / `ReportService`	`Services/Reports/`	`GetSummaryAsync`, `GetRowsAsync`; `Criteria`, `AsUtc`; `MaxExportRows = 50_000`
CSV writer	`ReportCsv` (static)	`Services/Reports/ReportCsv.cs`	`Write(rows)`, `Escape`, `FormatDate`; `ContentType = "text/csv"`, `FileName = "taskflow-report.csv"`
Repository	`IReportRepository` / `ReportRepository` (extends `BaseRepository` of `Task`)	`Repositories/Reports/`	`GetSummaryAsync`, `GetRowsAsync`, `GetProjectNamesByUserAsync`, private `Covered`
Records	`ReportCriteria`, `ReportTaskRow`	`Repositories/Reports/`	UTC criteria; row before the Project column is filled
DTOs	`ReportFilter`, `ReportSummaryDto`, `ReportRowDto`	`Dtos/Reports/ReportDto.cs`	Query input, totals, export row
Validator	`ReportFilterValidator`	`Dtos/Reports/Validators/ReportFilterValidator.cs`	Range order, enum values
Dependency	`IAppClock`	`Services/Settings/ApplicationSettings/Clock/`	`UtcNow` for "overdue"
Frontend route	`REPORTS_ROUTES`	`modules/reports/reports.routes.ts`	`/reports`, `permissionGuard` with `reports.view` (under the shell `authGuard`, `mfaSetupGuard`)
Frontend page	`ReportComponent` (`app-report`)	`modules/reports/pages/report.component.ts/.html`	Filters, count cards, completion bar, error panel, Export CSV
Frontend service	`ReportService`	`modules/reports/services/report.service.ts`	`getSummary(filter)`, `exportCsv(filter)` (blob), `toParams` drops empty values
Frontend models	`ReportFilter`, `ReportSummary`	`modules/reports/models/report.model.ts`	TypeScript contracts
Frontend utils	`startOfLocalDay`, `endOfLocalDay`, `saveBlob`, `ToastService`	`shared/utils/local-day.ts`, `shared/utils/save-blob.ts`, `shared/services/toast.service.ts`	Local day → UTC, download, error toast

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Type	File	Responsibility
Cross-module	`ProjectService.getAll`, `TaskService.getAssignees`	`modules/management/project-management/services/project.service.ts`, `modules/monitoring/task-management/services/task.service.ts`	Project and Employee options

Class diagram



API contracts (route prefix `[Route("api/v1/reports")]`, class attribute `[RequirePermission(PermissionKeys.ReportsView)]`)

#	Method	Route	Permission / policy	Request	Response	Status codes
1	GET	`/api/v1/reports`	`reports.view` (class)	`ReportFilter` (query)	`ReportSummaryDto`	200, 400, 401, 403
2	GET	`/api/v1/reports/export`	`reports.view` (class) **and** `[Authorize(Policy = PermissionPolicy.Prefix + PermissionKeys.ReportsExport)]`	`ReportFilter` (query)	`text/csv` file `taskflow-report.csv`	200, 400, 401, 403

`ReportFilter` query parameters (all optional): `deadlineFrom`, `deadlineTo` (`DateTime`, ISO instants), `assignedToUserId` (int), `projectId` (int), `status` (`TaskStatus` name), `priority` (`TaskPriority` name).

Dependency endpoints called by the page (owned by other sub-modules): `/api/v1/projects` (`projects.view`, Project list) and `/api/v1/tasks/assignees` (`[Authorize]`, scoped to the caller's task access, Employee list).

Request / response example

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

```
{
  "request": "GET /api/v1/reports?deadlineFrom=2026-09-30T18:30:00.000Z&deadlineTo=2026-10-
31T18:29:59.999Z&assignedToUserId=7&priority=High",
  "response": { "totalTasks": 6, "pendingTasks": 4, "completedTasks": 2, "overdueTasks": 1 }
}
```

```
{
  "type": "https://tools.ietf.org/html/rfc9110#section-15.5.1",
  "title": "One or more validation errors occurred.",
  "status": 400,
  "errors": { "DeadlineTo": ["The report 'to' deadline must be on or after the 'from'
deadline."] }
}
```

```
GET /api/v1/reports/export?priority=High  ->  200, Content-Type: text/csv, attachment;
filename=taskflow-report.csv
TaskCode,Title,Assignee,Project,Priority,Status,StartDate,Deadline,EstimatedHours,CompletedAt
TF-0012,'=SUM(A1),Arun Kumar,"Portal, Website",High,InProgress,2026-10-01,2026-10-20,6.5,
```

Values are illustrative (the task-code format belongs to Task Management); lines end with CRLF.

Service logic – `ReportService.GetSummaryAsync(filter)` (FR-RPT-07 – FR-RPT-30)

1. `ValidationFilter` has already run `ReportFilterValidator`.
2. `Criteria(filter)` → `ReportCriteria(AsUtc(DeadlineFrom), AsUtc(DeadlineTo), AssignedToUserId, ProjectId, Status, Priority)`. `AsUtc`: `Local` kind → `ToUniversalTime()`; `Unspecified` → `SpecifyKind(Utc)`; `Utc` unchanged.
3. `_reports.GetSummaryAsync(criteria, _clock.UtcNow)` – "overdue" is measured at the application clock's current UTC time.
4. Return `ReportSummaryDto`; `(0, 0, 0, 0)` when nothing matches.

Service logic – `ReportService.GetRowsAsync(filter)` (FR-RPT-33 – FR-RPT-38)

1. Same `Criteria(filter)`.
2. `_reports.GetRowsAsync(criteria, MaxExportRows)` – ordered by `Deadline`, then `Id`, at most 50,000 rows.
3. Distinct `AssignedToUserId` values → `_reports.GetProjectNamesByUserAsync(userIds)` (report filters not applied, so a deleted person's work keeps its projects).
4. Map each `ReportTaskRow` to `ReportRowDto`; `Project` = `string.Join(", ", names)` of the assignee's allocations sorted by project name, or empty.

CSV logic – `ReportCsv.Write(rows)` (FR-RPT-36 – FR-RPT-39)

1. Header `TaskCode,Title,Assignee,Project,Priority,Status,StartDate,Deadline,EstimatedHours,CompletedAt` + `\r\n`.
2. Per row, every cell through `Escape`: `null` → empty; a value starting with `=`, `+`, `-` or `@` gets a leading `'` (formula-injection guard, D8); a value containing `,`, `"`, CR or LF is quoted with inner quotes doubled.
3. Dates `yyyy-MM-dd` (invariant culture); `EstimatedHours` invariant culture; `CompletedAt` empty when null; `Priority` and `Status` as enum names.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com


4. Controller: `File(Encoding.UTF8.GetBytes(csv), ReportCsv.ContentType, ReportCsv.FileName)` (no BOM added explicitly).

Frontend logic – `ReportComponent`

1. `ngOnInit`: `projectService.getAll()` → `projects`; `taskService.getAssignees()` → `assignees` (no error handler – the list stays empty on failure); `load()`.
2. `load()`: `loading = true`, `error = null`; `reportService.getSummary(currentFilter())` with `catchError(() => of(null))`; `null` → `error` = "Could not load the report. Check your connection and try again." (panel "Something went wrong" + **Retry** → `load()`); else `summary`.
3. Each `setDeadlineFrom`, `setDeadlineTo`, `setAssignee`, `setProject`, `setStatus`, `setPriority` updates its signal and calls `load()` (no Apply button); `resetFilters()` clears all and calls `load()`.
4. `currentFilter()`: `deadlineFrom` = `startOfLocalDay(day)`, `deadlineTo` = `endOfLocalDay(day)` (last millisecond of the local day), ids and enum names only when set.
5. `completionRate` = 0 when total is 0, else `Math.round(completed / total × 100)`; text "X of Y completed · Z%".
6. `canExport()` = `authService.hasPermission(Permissions.ReportsExport)`; `exportCsv()`: `exporting = true` (label "Exporting…", button disabled) → `exportCsv(currentFilter())` blob → `saveBlob(blob, REPORT_FILE_NAME)`; error → toast "Could not export the report. Please try again."; `exporting = false` in both cases.


© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Sequence diagram – summary



© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Sequence diagram – export



Repository methods – `ReportRepository`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Method	Query / purpose	Notes
`Covered(criteria)` (private)	Base query: `Set.AsNoTracking().IgnoreQueryFilters().Where(!IsDeleted)`; optional `Deadline >= DeadlineFromUtc`, `Deadline <= DeadlineToUtc` (both inclusive), `AssignedToUserId == x`, `AssignedTo.ProjectAllocations.Any(ProjectId == x)` (the **assignee's** allocation, not `Tasks.ProjectId`), `Status == x`, `Priority == x`	`IgnoreQueryFilters` keeps tasks of soft-deleted users; uses `IX_Tasks_Deadline`, `IX_Tasks_AssignedToUserId`
`GetSummaryAsync(criteria, now)`	Each task → 0/1 flags (Total, Pending, Completed, Overdue); `GroupBy(_ => 1)`; `Sum` per flag; `SingleOrDefaultAsync`	Pending = not Completed and not Cancelled; Completed = Completed; Overdue = pending and `Deadline < now`; zeros when no rows
`GetRowsAsync(criteria, take)`	`OrderBy(Deadline).ThenBy(Id).Take(take)` → `ReportTaskRow`	`Assignee` = `AssignedTo.FullName` or empty
`GetProjectNamesByUserAsync(userIds)`	`Db.UserProjectAllocations.IgnoreQueryFilters().Where(userIds.Contains(UserId)).OrderBy(Project.Name)`; grouped in memory	Returns `IReadOnlyDictionary` of user id → project names

Validation rules (`ReportFilterValidator`)

Field	Rule	Message
`DeadlineTo`	`>= DeadlineFrom` when both are given	"The report 'to' deadline must be on or after the 'from' deadline."
`Status`	`IsInEnum()` when given	FluentValidation default enum message
`Priority`	`IsInEnum()` when given	FluentValidation default enum message
`DeadlineFrom` / `DeadlineTo` / ids / enum names	Must bind (model binding)	Default model-state problem
Deadline to (client)	Picker `min` = Deadline from, Deadline from picker `max` = Deadline to	– (earlier date not selectable)

Error cases

Case	Exception / outcome	Status
"To" before "from"	`ValidationFilter` result	400
Unknown status / priority value	`ValidationFilter` or model binding	400
Missing `reports.view`	Policy (audited)	403
Export without `reports.export`	Policy (audited)	403
Unexpected fault	`GlobalExceptionHandler`	500


State machine: *Not applicable for this sub-module* – Reports reads task status; transitions belong to Task Management.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

5. Database Design

Reports owns **no table** and runs **no migration**. It reads the tables below (full definitions in the Task Management, Employee Management and Project Management LLDs). Only the columns read are listed.

5.1 ER Diagram



5.2 Tables

`Tasks` (Task)

Column	Type	Null	Key / index	Default	Description
Id	int	No	PK	identity	Export tie-break sort
TaskCode	string(32)	No	Unique `IX_Tasks_TaskCode`	–	CSV TaskCode
Title	string(200)	No	–	–	CSV Title
AssignedToUserId	int	No	FK → `Users.Id` (Restrict), `IX_Tasks_AssignedToUserId`	–	Employee filter, Assignee, project lookup
Priority	`TaskPriority` (int)	No	–	–	Priority filter, CSV Priority
Status	`TaskStatus` (int)	No	–	–	Status filter, Pending / Completed / Overdue
StartDate	DateTime	No	–	–	CSV StartDate
Deadline	DateTime (UTC)	No	`IX_Tasks_Deadline`	–	Range filter, overdue, export order
EstimatedHours	decimal	No	–	–	CSV EstimatedHours
CompletedAt	DateTime	Yes	–	null	CSV CompletedAt

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Column	Type	Null	Key / index	Default	Description
IsDeleted	bool	No	–	false	Deleted tasks excluded
ProjectId	int	Yes	FK → `Projects.Id` (Restrict), `IX_Tasks_ProjectId`	null	**Not read** by Reports

`Users` (User)

Column	Type	Null	Key / index	Default	Description
Id	int	No	PK	identity	Assignee
FullName	string(200)	No	–	–	CSV Assignee
IsDeleted	bool	No	Query filter `!IsDeleted` (bypassed with `IgnoreQueryFilters`)	false	Deleted people's tasks and names are kept

`UserProjectAllocations` (UserProjectAllocation)

Column	Type	Null	Key / index	Default	Description
UserId	int	No	Composite PK; FK → `Users.Id` (Cascade)	–	Allocated person
ProjectId	int	No	Composite PK; FK → `Projects.Id` (Cascade), `IX_UserProjectAllocations_ProjectId`	–	Project filter and CSV Project
(query filter)	–	–	User and project not deleted (bypassed with `IgnoreQueryFilters`)	–	–

`Projects` (Project)

Column	Type	Null	Key / index	Default	Description
Id	int	No	PK	identity	–
Name	string(200)	No	Unique among live rows (`IX_Projects_Name`, filter `"IsDeleted" = 0`)	–	CSV Project names, sorted
IsDeleted	bool	No	Query filter	false	Soft delete

5.3 Indexes, Constraints & Triggers

Object	Definition	Purpose
`IX_Tasks_Deadline`	(Deadline)	Deadline range filter, export ordering
`IX_Tasks_AssignedToUserId`	(AssignedToUserId)	Employee filter, assignee join
`IX_UserProjectAllocations_ProjectId`	(ProjectId)	Project filter (`ProjectAllocations.Any`)
Composite PK `UserProjectAllocations`	(UserId, ProjectId)	Project names per user

No triggers are used.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

5.4 Enumerations

Enum	Values	Stored as
`TaskStatus`	ToDo (0), InProgress (1), Blocked (2), Completed (3), Cancelled (4), InQA (5)	int; JSON / query / CSV as name
`TaskPriority`	Low (0), Medium (1), High (2), Critical (3)	int; JSON / query / CSV as name

5.5 Migrations

Not applicable for this sub-module – no migration; the tables read come from `20261012124843_AddTasks`, `20261020173455_RenameDepartmentsToProjectsAndAddDepartments` and `20261023160825_UserProjectAllocationsAndDepartments` (described in the owning LLDs).

6. Algorithms & Background Jobs

Job / algorithm	Trigger / schedule	Steps	Idempotency
Summary aggregation	`GET /api/v1/reports`	Covered tasks → 0/1 flags → one grouped `SUM` row	Pure read
Export	`GET /api/v1/reports/export`	Covered tasks by deadline (cap 50,000) → project names per assignee → `ReportCsv.Write` → UTF-8 bytes	Pure read
Formula protection	Every CSV cell	Prefix `'` for leading `=`, `+`, `-`, `@`; then RFC 4180 quoting	Deterministic
Background jobs	–	None in this sub-module	–

7. Security Design (detailed)

Shared items (password hashing, tokens, cookies, secrets) are in the overall LLD.

Item	Implementation
Permission checks	`[RequirePermission(PermissionKeys.ReportsView)]` on `ReportController`; `Export` adds `[Authorize(Policy = PermissionPolicy.Prefix + PermissionKeys.ReportsExport)]`
Catalogue defaults (`PermissionCatalog`)	`reports.view` "View reports" (`GrantedToManager`); `reports.export` "Export reports" (`GrantedToManager`, `GrantFrom` and `Requires` `reports.view`); Administrator re-granted all keys on start (`AccessControlSeeder`); Employee has neither
Data scope	Organisation for every holder of `reports.view`; no Own / Team selector (D3)
Hidden dependency	Project list needs `projects.view` (not declared in the catalogue `Requires`); Employee list follows the caller's task access
CSV safety	Formula-injection guard in `ReportCsv.Escape` (D8)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Item	Implementation
Frontend	`permissionGuard` on `/reports` redirects to `dashboardRouteFor(...)`; menu item shown with `has(Permissions.ReportsView)`; Export button only when `canExport()`
Audit	`DeniedActionAuditHandler` logs every refused policy check

8. Configuration

Key	Default	Purpose
`ConnectionStrings:Default`	`<secret>`	SQLite database
`Jwt:AccessTokenMinutes` / `Jwt:RefreshTokenDays`	`<secret>`	Session lifetime for report calls
`Application:Timezone`	`Asia/Kolkata`	Not used by the report calculations (deadline bounds come from the browser)

Code constants: `ReportService.MaxExportRows` = 50000; `ReportCsv.FileName` = `taskflow-report.csv`, `ReportCsv.ContentType` = `text/csv`; Angular `REPORT_FILE_NAME` = `taskflow-report.csv`.

9. Testing Design

Paths relative to `backend/tests`. Only file names are available; "Covers" is inferred from the names.

Area	Test class / file	Type	Covers
Service	`TaskFlow.UnitTests/Reports/ReportServiceTests.cs`	Unit	Totals, filters, deleted tasks / people, project semantics, row cap and order
CSV	`TaskFlow.UnitTests/Reports/ReportCsvTests.cs`	Unit	Header, column order, quoting, formula guard, date format
Endpoints	`TaskFlow.IntegrationTests/Reports/ReportEndpointsTests.cs`	Integration	Both endpoints, validation, `reports.view` / `reports.export`
Permissions	`TaskFlow.UnitTests/Settings/RoleConfiguration/PermissionCatalogTests.cs`	Unit	Catalogue entries incl. report keys
Permissions	`TaskFlow.IntegrationTests/Common/PermissionAuthorizationTests.cs`, `ModuleBasedPermissionEndpointsTests.cs`	Integration	Policy enforcement across modules
Support	`TaskFlow.UnitTests/TestSupport/WorkloadReportHarness.cs`	Support	> ⚠️ To be confirmed: whether the report tests use it
Frontend	–	–	No spec file for `ReportComponent` in the snapshot

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

10. Known Limitations & Open Issues

- Organisation-wide data for every `reports.view` holder; the original BRD asked for records the user may access.

  > ⚠️ To be confirmed (R-RPT-01).

- Export capped at 50,000 rows without a warning; built fully in memory, not streamed. > ⚠️ To be confirmed (R-RPT-02).
- Deadline-day bounds use the browser's time zone, not `Application:Timezone` (BR-17). > ⚠️ To be confirmed (R-RPT-03).
- Project and Employee option loads have no error handler; a missing `projects.view` leaves the list empty silently.

  > ⚠️ To be confirmed (R-RPT-04, R-RPT-05).

- Project filter and CSV Project use the assignee's allocations, not `Tasks.ProjectId`; allocations to soft-deleted projects may appear because of `IgnoreQueryFilters`. > ⚠️ To be confirmed (R-RPT-06).
- Counting differs from the Dashboard: Reports counts Cancelled in Total and all open tasks as Pending (BR-RPT-10).
- The server message MSG-RPT-02 is not shown; the page shows MSG-RPT-01.
- `report.component.ts` declares `styleUrl: './report.component.css'`, but the file is not in the source snapshot.

  > ⚠️ To be confirmed.

- The TDD names reports/tasks and reports/tasks/export routes and `ReportsComponent`; the code uses the two routes in §4 and `ReportComponent`.
- The help article `reports-and-workload.md` mentions summaries "by status, priority and employee"; the code returns four totals only.

11. Traceability (FRD → code)

FRD requirement	Endpoint / class	Test
FR-RPT-01	`nav-items.ts` (`has(Permissions.ReportsView)`)	Manual UI check (AC-RPT-01)
FR-RPT-02	`REPORTS_ROUTES` + `permissionGuard` → `dashboardRouteFor`	Manual UI check (AC-RPT-01)
FR-RPT-03	`[RequirePermission(PermissionKeys.ReportsView)]` on `ReportController`; `DeniedActionAuditHandler`	`ReportEndpointsTests`, `PermissionAuthorizationTests`
FR-RPT-04	`ReportComponent.ngOnInit` → `GET /api/v1/reports`, `/api/v1/projects`, `/api/v1/tasks/assignees`	`ReportEndpointsTests`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

FRD requirement	Endpoint / class	Test
FR-RPT-05, FR-RPT-06	`loading` / `error` signals, `load()` retry in `ReportComponent`	Manual UI check
FR-RPT-07	`report.component.html` count cards	Manual UI check
FR-RPT-08, FR-RPT-09, FR-RPT-10, FR-RPT-11, FR-RPT-12	`ReportRepository.GetSummaryAsync` (flags), `ReportService.GetSummaryAsync` (`IAppClock.UtcNow`)	`ReportServiceTests`
FR-RPT-13	`ReportComponent.completionRate`	Manual UI check
FR-RPT-14	`GetSummaryAsync` fallback `ReportSummaryDto(0, 0, 0, 0)`	`ReportServiceTests`
FR-RPT-15, FR-RPT-16	`startOfLocalDay` / `endOfLocalDay`; `ReportService.AsUtc`; `Covered` inclusive bounds	`ReportServiceTests`
FR-RPT-17	Date inputs `[min]` / `[max]` in `report.component.html`	Manual UI check
FR-RPT-18	`ReportFilterValidator` (`DeadlineTo` rule) via `ValidationFilter`	`ReportEndpointsTests`
FR-RPT-19	`Covered` – `AssignedToUserId == x`	`ReportServiceTests`
FR-RPT-20	`TaskService.getAssignees()` → `/api/v1/tasks/assignees`	Manual UI check
FR-RPT-21	`Covered` – `AssignedTo.ProjectAllocations.Any(ProjectId == x)`	`ReportServiceTests`
FR-RPT-22	`ProjectService.getAll()` → `/api/v1/projects` (`projects.view`)	Manual UI check
FR-RPT-23, FR-RPT-24	`Covered` – `Status`, `Priority`; `ReportFilterValidator.IsInEnum`	`ReportEndpointsTests`
FR-RPT-25	`ReportFilter` optional fields; `toParams` drops empty values; `Covered` adds only given filters	`ReportServiceTests`
FR-RPT-26, FR-RPT-27	`set*()` methods and `resetFilters()` call `load()`	Manual UI check
FR-RPT-28, FR-RPT-29	`Covered` – `IgnoreQueryFilters().Where(!IsDeleted)`; `GetProjectNamesByUserAsync` `IgnoreQueryFilters`	`ReportServiceTests`
FR-RPT-30	`ReportService` (no scope selector, D3)	`ReportEndpointsTests`
FR-RPT-31	`ReportComponent.canExport()`	Manual UI check
FR-RPT-32	`GET /api/v1/reports/export` – class `reports.view` + `perm:reports.export`	`ReportEndpointsTests`, `PermissionCatalogTests`
FR-RPT-33, FR-RPT-34	`ReportService.GetRowsAsync` (`MaxExportRows`), `ReportRepository.GetRowsAsync` (`OrderBy(Deadline).ThenBy(Id).Take`)	`ReportServiceTests`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

FRD requirement	Endpoint / class	Test
FR-RPT-35	`ReportController.Export` → `File(…, ReportCsv.ContentType, ReportCsv.FileName)`; `saveBlob(blob, REPORT_FILE_NAME)`	`ReportEndpointsTests`
FR-RPT-36, FR-RPT-38	`ReportCsv.Headers`, `ReportCsv.Write`, `FormatDate`	`ReportCsvTests`
FR-RPT-37	`ReportService.GetRowsAsync` (`string.Join(", ", names)`), `GetProjectNamesByUserAsync` (`OrderBy(Project.Name)`)	`ReportServiceTests`, `ReportCsvTests`
FR-RPT-39	`ReportCsv.Escape` (leading `=`, `+`, `-`, `@`)	`ReportCsvTests`
FR-RPT-40, FR-RPT-41	`ReportComponent.exporting`, `exportCsv()` error → `ToastService.error`	Manual UI check
FR-RPT-42	Read-only queries (`AsNoTracking`); no notification, mail or activity dependency	Manual check – no data change

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.