Low-Level Design – Role Configuration

TaskFlow – Intelligent Task Allocation & Tracking System

> **Document:** Low-Level Design · **Version:** 1.0 · **Status:** Draft
> **Project type:** Personal Project (Skill Development) · **Date:** 31-Oct-2026
> **Author:** Jojo George (jojogeorge3344@gmail.com)
> **Based on:** HLD-Role-Configuration v1.0, FRD-Role-Configuration v1.0
> **Module:** Settings · **Sub-module:** 06.4 Role Configuration · **Code:** ROLE
> © 2026 Jojo George. All rights reserved.

Document Control

Version	Date	Author	Summary of changes
1.0	31-Oct-2026	Jojo George	Initial version

Related documents: BRD · FRD · HLD · TDD · Specs

Document	Location
BRD – Role Configuration	`../../../BRD/06-Settings/06.4-Role-Configuration/BRD-Role-Configuration.md`
FRD – Role Configuration (FR-ROLE-01…26, UC-ROLE-01…04)	`../../../FRD/06-Settings/06.4-Role-Configuration/FRD-Role-Configuration.md`
HLD – Role Configuration	`../../../HLD/06-Settings/06.4-Role-Configuration/HLD-Role-Configuration.md`
Overall LLD (authentication, sessions, permission policies)	`../../00-Overall/LLD-TaskFlow-Overall.md`
LLD – Employee Management (role assignment, `GET /api/v1/users/roles`)	`../../03-TaskFlow-Management/03.1-Employee-Management/LLD-Employee-Management.md`
TDD v2.0	`TDD-TaskFlow.md` §6.6 (authorization model), §7.2.1 (`Role`, `Permission`, `RolePermission`), §7.4 (triggers)

1. Introduction

1.1 Purpose

Detailed design of Role Configuration (Permissions Management): the controller actions for roles and the fixed permission catalogue, `RoleService` rules, the code catalogue `PermissionCatalog` and `EffectivePermissions`, the `Roles`, `Permissions` and `RolePermissions` tables with their triggers, start-

up seeding, session revocation on a permission change, the Angular tree/matrix screen, tests and FR-ROLE-nn traceability. Everything is taken from the code.

1.2 Scope & Conventions

- Covered: `RolesController` (9 HTTP actions), `RoleService`, `RoleRepository`, `PermissionRepository`, `PermissionCatalog`, `EffectivePermissions`, `SystemRoles`, `RoleException`, `AccessControlSeeder`, and `PermissionsManagementComponent` with `permission-tree.ts`.
- Referenced only: `SessionValidation` / `SessionService` (claims refresh), `EmployeesController` (role assignment and `roles.administrator.assign` check), `IEmployeeRepository`, `IRefreshTokenRepository`.
- Naming: `*Controller`, `I*Service` / `*Service`, `I*Repository` / `*Repository`, DTOs `*Dto` / `*Request`.
- API base path `/api/v1`; JSON camelCase; errors as ProblemDetails. There is no FluentValidation validator for this sub-module: rules live in `RoleService` and raise `RoleException`.

---

2. Code Structure

2.1 Backend Folder Layout

```
TaskFlow.Api/
  Controllers/Settings/RolesController.cs
  Services/Settings/RoleConfiguration/IRoleService.cs, RoleService.cs
  Repositories/Settings/RoleConfiguration/Roles/IRoleRepository.cs, RoleRepository.cs,
RoleSummary.cs
  Repositories/Settings/RoleConfiguration/Permissions/IPermissionRepository.cs,
PermissionRepository.cs
  Dtos/Settings/RoleConfiguration/RoleDtos.cs
  Models/Entities/Role.cs, Permission.cs, RolePermission.cs
  Common/Security/PermissionKeys.cs, PermissionCatalog.cs, EffectivePermissions.cs,
SystemRoles.cs, PermissionPolicy.cs
  Common/Exceptions/RoleException.cs
  Authorization/Policies/RequirePermissionAttribute.cs
  Persistence/Seeders/AccessControlSeeder.cs
  Persistence/Migrations/20261019133820_AddRolesAndPermissions.cs   (tables, system roles,
triggers)
```

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

2.2 Frontend Folder Layout

```
src/app/modules/settings/
  settings.routes.ts                                          (route
settings/permissions)
  role-configuration/pages/permissions-management.component.{ts,html,css}
  role-configuration/pages/permissions-management.model.ts        (Selection, EnabledFilter,
PermissionView, ModuleView, ScreenView, FeatureView)
  role-configuration/models/role.model.ts                         (AccessRole, PermissionInfo,
SaveRoleRequest, SYSTEM_ROLE_IDS)
  role-configuration/services/role.service.ts                     (RoleService, Angular)
  role-configuration/utils/permission-tree.ts                     (buildTree, toggleKey,
setMany, setScope, restrictForCaller, ...)
src/app/shared/auth/permissions.ts, auth.guard.ts; src/app/layouts/nav-items.ts
```

2.3 Layer Rules

Rule	Enforced by
Controller → Service → Repository only, through interfaces	`ArchitectureTests`
Services commit through `IUnitOfWork`; repositories never return `IQueryable`	`ArchitectureTests`
Catalogue integrity (unique keys, valid `Requires`, scope groups)	`PermissionCatalogTests`
Utilities in `utils/`, API service in `services/` of the module	`npm run check:structure`

---

3. Cross-Cutting Design

Shared mechanisms are in the overall LLD. Applied here:

Concern	Design
Validation	No validator; `RoleService.ValidateName` and `ResolvePermissionsAsync` throw `RoleException(RoleFailure, message)`
Error handling	`GlobalExceptionHandler` maps `RoleException.StatusCode` (3.1); `Forbid()` in the controller gives an empty 403
Transactions	One `SaveChangesAsync` per create/update/delete; grant changes, security-stamp rotation and token revocation commit together
Authorization	Class-level `[RequirePermission(PermissionKeys.RolesManage)]`; in-action claim checks for `roles.view.all` and `roles.modify.access`
Session effect	`SessionValidation` rebuilds role and permission claims per request from the database (`SessionService` → `EffectivePermissions.Expand`)
Database guard	SQLite triggers refuse changes to system roles, their grants and the catalogue

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

3.1 Exception → HTTP Status

Exception	Status	When
`RoleException` `RoleFailure.Invalid`	400	Name blank or over 100; unknown key; missing prerequisite; Administrator-only key
`RoleException` `RoleFailure.ReadOnly`	403	Update or delete of a system role
`RoleException` `RoleFailure.NotFound`	404	Role id does not exist
`RoleException` `RoleFailure.Duplicate`	409	Name already used (check or unique index)
`RoleException` `RoleFailure.InUse`	409	Delete while users hold the role
`Forbid()`	403 (empty body)	Create/update/delete without `roles.modify.access`
`Problem(...)` in `CatalogIsFixed`	403	Any POST/PUT/DELETE on `/api/v1/permissions`
Policy failure	403	Caller lacks `roles.manage`
`DbUpdateException` from a trigger (`RAISE(ABORT, ...)`)	500	Only if the service checks are bypassed

4. Module Designs

4.1 Module: Settings

4.1.1 Child module: Role Configuration (ROLE)

Class / file inventory

Layer	Type	File	Responsibility
Controller	`RolesController`	`Controllers/Settings/RolesController.cs`	9 HTTP actions under `/api/v1`; claim checks; `CatalogIsFixed`
Service	`IRoleService` / `RoleService`	`Services/Settings/RoleConfiguration/`	List, get, create, update, delete roles; catalogue view; rules
Repository	`IRoleRepository` / `RoleRepository`, `RoleSummary`	`Repositories/Settings/RoleConfiguration/Roles/`	Role summaries, tracked role, name check, keys by role name
Repository	`IPermissionRepository` / `PermissionRepository`	`Repositories/Settings/RoleConfiguration/Permissions/`	Key → id map, tracked rows by keys


© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Type	File	Responsibility
Other repositories	`IEmployeeRepository`, `IRefreshTokenRepository`	`Repositories/Management/...`, `Repositories/Auth/RefreshTokens/`	Holders of a role; their active refresh tokens
DTOs	`RoleDto`, `PermissionDto`, `RoleOptionDto`, `SaveRoleRequest`	`Dtos/Settings/RoleConfiguration/RoleDtos.cs`	Contracts
Entities	`Role`, `Permission`, `RolePermission`	`Models/Entities/`	Tables
Catalogue	`PermissionDefinition`, `PermissionCatalog`	`Common/Security/PermissionCatalog.cs`	64 entries: module/screen/section/action, defaults, `IsAssignable`, `AlwaysGranted`, `Requires`, scope
Keys	`PermissionKeys`	`Common/Security/PermissionKeys.cs`	Key constants (incl. legacy keys)
Effective rights	`EffectivePermissions`	`Common/Security/EffectivePermissions.cs`	`LegacyChildren`, `Expand`, `Visible`, `IsLegacy`
System roles	`SystemRoles`	`Common/Security/SystemRoles.cs`	Names and ids 1, 2, 3
Exception	`RoleException`, `RoleFailure`	`Common/Exceptions/RoleException.cs`	Failure → status
Seeder	`AccessControlSeeder`	`Persistence/Seeders/AccessControlSeeder.cs`	System roles, catalogue rows, default grants
Frontend page	`PermissionsManagementComponent`	`role-configuration/pages/permissions-management.component.ts`	Role list, tree and matrix views, draft, save bar
Frontend service	`RoleService` (Angular)	`role-configuration/services/role.service.ts`	`list()`, `permissions()`, `create()`, `update()`, `delete()`, `assignable()`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Type	File	Responsibility
Frontend utils	`buildTree`, `effectiveKeys`, `toggleKey`, `setMany`, `setScope`, `restrictForCaller`, `RESTRICTED_KEYS`, `isSelectable`, `changeCount`, `matches`	`role-configuration/utils/permission-tree.ts`	Tree building and tick logic

Class diagram



API contracts

Controller `RolesController`, `[Route("api/v1")]`, class-level `[RequirePermission(PermissionKeys.RolesManage)]`. HTTP actions of this sub-module (facts.md §3, `RolesController`): **9** (8 C# methods; `CatalogIsFixed` serves three routes).

#	Method	Route	Permission / policy	Request	Response	Status codes
1	GET	`/api/v1/roles`	`roles.manage`; without claim `roles.view.all` only the caller's own role	–	`IReadOnlyList<RoleDto>`	200, 401, 403
2	GET	`/api/v1/roles/{id}`	`roles.manage`	route `id` (int)	`RoleDto`	200, 401, 403, 404
3	POST	`/api/v1/roles`	`roles.manage` + claim `roles.modify.access`	`SaveRoleRequest`	`RoleDto` (`CreatedAtAction(GetRole)`)	201, 400, 401, 403, 409
4	PUT	`/api/v1/roles/{id}`	`roles.manage` + claim `roles.modify.access`	`SaveRoleRequest`	`RoleDto`	200, 400, 401, 403, 404, 409
5	DELETE	`/api/v1/roles/{id}`	`roles.manage` + claim `roles.modify.access`	–	–	204, 401, 403, 404, 409
6	GET	`/api/v1/permissions`	`roles.manage`	–	`IReadOnlyList<PermissionDto>` (catalogue order)	200, 401, 403
7	POST	`/api/v1/permissions`	`roles.manage`	–	ProblemDetails "The permission list is fixed and cannot be changed."	403

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

#	Method	Route	Permission / policy	Request	Response	Status codes
8	PUT	`/api/v1/permissions/{id}`	`roles.manage`	–	ProblemDetails (same)	403
9	DELETE	`/api/v1/permissions/{id}`	`roles.manage`	–	ProblemDetails (same)	403

Related, owned by Employee Management: GET `/api/v1/users/roles` returns `RoleOptionDto` (no permissions) for the employee form, used by Angular `RoleService.assignable()`.

DTOs

DTO	Fields
`RoleDto`	`Id`, `Name`, `IsSystem`, `UserCount` (every account holding it, deleted ones included), `PermissionKeys` (`EffectivePermissions.Visible(Expand(stored))`, sorted)
`PermissionDto`	`Id` (0 for always-on entries), `Key`, `Name`, `Description`, `Group`, `IsAssignable`, `Module`, `Screen`, `Section`, `Action`, `Requires`, `ScopeGroup`, `ScopeRank`, `AlwaysGranted`
`SaveRoleRequest`	`Name` (`string?`), `PermissionKeys` (`IReadOnlyList<string>?`)
`RoleOptionDto`	`Id`, `Name`, `IsSystem` (Employee Management)

Request / response example

```
// POST /api/v1/roles
{ "name": "Team Lead", "permissionKeys": ["tasks.view.all", "tasks.create", "workload.view",
"workload.filters.use"] }
```

```
// 201 Created (Location: /api/v1/roles/4; id illustrative)
{ "id": 4, "name": "Team Lead", "isSystem": false, "userCount": 0,
  "permissionKeys": ["tasks.create", "tasks.view.all", "workload.filters.use", "workload.view"]
}
```

```
// 400 Bad Request (prerequisite missing)
{ "status": 400, "detail": "\"Use workload filters\" also needs \"View workload\"." }
```

```
// 409 Conflict (role in use)
{ "status": 409, "detail": "2 users still hold this role. Move them to another role first." }
```

Service logic – `GetRolesAsync` / `GetRoleAsync` / `GetPermissionsAsync`

1. `GetRolesAsync`: `RoleRepository.GetSummariesAsync()` → `RoleDto` with keys `EffectivePermissions.Visible(EffectivePermissions.Expand(stored))` (legacy keys expanded and hidden, lower scope levels added, unknown keys dropped).

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

2. Controller filter: without the `roles.view.all` claim, only the role whose name equals the caller's role claim (case-insensitive); empty list when there is no role claim (FR-ROLE-02).
3. `GetRoleAsync(id)`: from the full list; missing → `RoleException(NotFound, "That role does not exist.")`.
4. `GetPermissionsAsync`: `PermissionCatalog.All` in code order mapped to `PermissionDto`, `Id` from `PermissionRepository.GetIdsByKeyAsync()` (0 when not stored, i.e. always-on).

Service logic – `CreateAsync(request)`

1. `ValidateName`: trim; empty → "Enter a name for the role."; over 100 → "The role name can be at most 100 characters."
2. `ResolvePermissionsAsync(keys)`:
    1. trim, drop blanks, distinct;
    2. replace legacy keys by `EffectivePermissions.LegacyChildren`; drop `AlwaysGranted` keys (never stored, FR-ROLE-14);
    3. `GetByKeysAsync(wanted)`; any key not found → "Unknown permission: `keys`." (FR-ROLE-12);
    4. for each found key whose catalogue `Requires` is not in `Expand(wanted)` → "`name`" also needs "`needed`"." (FR-ROLE-11);
    5. any key with catalogue `IsAssignable = false` (`roles.administrator.assign`, and the always-on ones) → "`names` can only be held by the Administrator role and cannot be given to another role." (FR-ROLE-13).
3. `EnsureNameFreeAsync(name, null)`: `NameTakenAsync` (column collation `NOCASE`) → `RoleFailure.Duplicate` "A role named "`name`" already exists." (FR-ROLE-10).
4. New `Role { IsSystem = false, CreatedAt = now }` with one `RolePermission` per permission; `Add`.
5. `SaveAsync`: `UniqueConstraintException` → "A role with that name already exists." (409). Return `GetRoleAsync(id)`.

Service logic – `UpdateAsync(id, request)`

1. `LoadCustomRoleAsync(id)`: tracked role with grants; missing → 404; `IsSystem` → `RoleFailure.ReadOnly` "`name` is a system role and is read-only: it cannot be changed or deleted." (FR-ROLE-06).
2. `ValidateName`, `ResolvePermissionsAsync`, `EnsureNameFreeAsync(name, id)` as for create.
3. Set `Name`; remove grants not wanted; add missing grants; `permissionsChanged` when either happened.
4. If `permissionsChanged`: `EndSessionsOfRoleHoldersAsync(id)` – every holder (`GetHoldingRoleForUpdateAsync`, deleted accounts included) gets `SecurityStamp = Guid.NewGuid().ToString("N")`; their active refresh tokens (`GetActiveForUsersForUpdateAsync`) get `RevokedAt = now` (FR-ROLE-18). A rename alone signs nobody out.
5. `SaveAsync`; return `GetRoleAsync(id)`.


Service logic – `DeleteAsync(id)`

1. `LoadCustomRoleAsync(id)` (404 / 403 as above).
2. `IEmployeeRepository.CountHoldingRoleAsync(id)` (ignores the soft-delete filter) > 0 → `RoleFailure.InUse` "1 user still holds this role. Move them to another role first." / "`n` users still hold this role. Move them to another role first." (FR-ROLE-20).

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com


3. `Remove(role)`; `RolePermissions` rows deleted by cascade; `SaveAsync` (FR-ROLE-19).

Sequence diagram – update a custom role



© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Sequence diagram – effect on the next request of a holder



Repository methods

Method	Query / purpose	Notes
`RoleRepository.GetSummariesAsync()`	Roles with `UserCount` and stored keys	`AsNoTracking`, `OrderByDescending(IsSystem).ThenBy(Id)`; count via `Db.Users.IgnoreQueryFilters()`
`RoleRepository.GetWithPermissionsForUpdateAsync(id)`	Tracked role + grants	`Include(Permissions)`
`RoleRepository.NameTakenAsync(name, exceptRoleId)`	Name collision	`AnyAsync`; `NOCASE` collation on `Name`; `IX_Roles_Name`
`RoleRepository.GetPermissionKeysByRoleNameAsync(roleName)`	Stored keys of a role name	Used by `TaskService` (Task Management)
`PermissionRepository.GetIdsByKeyAsync()`	Key → Id	`AsNoTracking`, `ToDictionaryAsync`
`PermissionRepository.GetByKeysAsync(keys)`	Tracked rows to grant	`Where(keys.Contains(Key))`; `IX_Permissions_Key`
`EmployeeRepository.CountHoldingRoleAsync(roleId)` / `GetHoldingRoleForUpdateAsync(roleId)`	Holders	`IgnoreQueryFilters()`
`RefreshTokenRepository.GetActiveForUsersForUpdateAsync(userIds)`	Active tokens	`RevokedAt == null`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Validation rules (in `RoleService`)

Field	Rule	Message
`Name`	Required after trim	"Enter a name for the role."
`Name`	At most 100 characters after trim (`MaxNameLength`)	"The role name can be at most 100 characters."
`Name`	Unique, case-insensitive	"A role named "`name`" already exists." / "A role with that name already exists."
`PermissionKeys`	Every key in the stored catalogue (after legacy expansion; always-on keys ignored)	"Unknown permission: `keys`."
`PermissionKeys`	`Requires` held (scope expansion counts)	""`name`" also needs "`needed`"."
`PermissionKeys`	No `IsAssignable = false` key	"`names` can only be held by the Administrator role and cannot be given to another role."

Client mirror: `nameError` "Enter a name for the role." when the trimmed draft name is empty; `toggleKey` ticks the `requires` chain when a key is ticked and clears dependants when it is unticked; `restrictForCaller` marks `roles.administrator.assign` as not assignable for callers who do not hold it; `isSelectable` excludes always-on and non-assignable entries.

Error cases

Case	Exception / result	Status
No `roles.manage`	Policy refusal (logged)	403
No `roles.modify.access` on POST/PUT/DELETE	`Forbid()` (empty body; screen shows "Could not save the role." / "Could not delete the role.")	403
System role update/delete	`RoleException(ReadOnly)`	403
Unknown role	`RoleException(NotFound)`	404
Invalid name or keys	`RoleException(Invalid)`	400
Duplicate name	`RoleException(Duplicate)`	409
Role in use	`RoleException(InUse)`	409
Catalogue mutation	`CatalogIsFixed`	403


Frontend design – `PermissionsManagementComponent`

Member	Behaviour
`load()`	`forkJoin(list(), permissions())`; catalogue passed through `restrictForCaller(catalog, hasPermission(RolesAdministratorAssign))`; error "Could not load roles and permissions."
`filteredRoles`	Own role only without `canViewAllRoles`; filtered by **Find a role** text (FR-ROLE-01, FR-ROLE-02)
`view` (`'tree'` / `'matrix'`)	Tree by module → screen → section → feature, or role-by-permission matrix (**Compare roles**, FR-ROLE-04)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Member	Behaviour
`search`, `filter` (`'all'` / `'enabled'` / `'disabled'`)	Permission search and filter (FR-ROLE-05)
`editable`	`canModifyAccess` and (new draft or non-system role); otherwise read-only (FR-ROLE-23)
`toggle`, `chooseScope`, `toggleScreen`, `toggleModule`, `setAll`	`toggleKey` / `setScope` / `setMany` on `draftKeys` (FR-ROLE-03, FR-ROLE-11, FR-ROLE-15)
`startNew`, `duplicate`, `copyFrom`	New draft; "`name` copy" draft from a role; copies only selectable keys (FR-ROLE-07...09)
`dirty`, `changes`, `discard`, `confirmDiscard`	Change count via `changeCount`; "Discard unsaved changes?" dialog; `beforeunload` warning (FR-ROLE-17)
`heldCount`, `totalCount`, `heldPercent`	"N of M permissions", "x% enabled" (FR-ROLE-24)
`save()`	`create` or `update`; toast "`name` created" / "`name` saved"; error kept in the form (`formError`)
`remove()`	Confirm "Delete `name`?" ("The role and its permissions are removed. This cannot be undone."); toast "`name` deleted"; error "Could not delete the role."

State machine – custom role (as handled by the service)




System roles (`IsSystem = true`, ids 1–3) have no transitions: every update or delete is refused by the service and the triggers.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

5. Database Design

5.1 ER Diagram



5.2 Tables

`Roles` (Role)

Column	Type	Null	Key / index	Default	Description
Id	int (INTEGER)	No	PK	identity; system ids 1, 2, 3	1 Administrator, 2 Manager, 3 Employee

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Column	Type	Null	Key / index	Default	Description
Name	string(100) (TEXT, collation `NOCASE`)	No	Unique `IX_Roles_Name`	–	Case-insensitive unique
IsSystem	bool (INTEGER)	No	–	false	System roles read-only
CreatedAt	DateTime (TEXT)	No	–	–	UTC

`Permissions` (Permission) – read-only catalogue

Column	Type	Null	Key / index	Default	Description
Id	int (INTEGER)	No	PK	identity	Referenced by grants
Key	string(100) (TEXT)	No	Unique `IX_Permissions_Key`	–	e.g. `roles.modify.access`
Name	string(200) (TEXT)	No	–	–	Display name
Description	string(500) (TEXT)	No	–	–	Description
Group	string(100) (TEXT)	No	–	–	Catalogue module
IsAssignable	bool (INTEGER)	No	–	true	False = Administrator only (informational; the code catalogue decides)

`RolePermissions` (RolePermission)

Column	Type	Null	Key / index	Default	Description
RoleId	int (INTEGER)	No	PK (`RoleId`, `PermissionId`), FK → `Roles.Id` Cascade	–	Role
PermissionId	int (INTEGER)	No	PK, FK → `Permissions.Id` Restrict, `IX_RolePermissions_PermissionId`	–	Permission

Also used, owned elsewhere: `Users.RoleId` (FK Restrict, `IX_Users_RoleId`) and `Users.SecurityStamp` (Employee Management / Auth), `RefreshTokens.RevokedAt` (Auth).

5.3 Indexes, Constraints & Triggers

Object	Definition	Purpose
`IX_Roles_Name`	Unique (`Name`), collation `NOCASE`	"team lead" collides with "Team Lead"
`IX_Permissions_Key`	Unique (`Key`)	One row per key
`IX_RolePermissions_PermissionId`	(`PermissionId`)	FK lookup
`IX_Users_RoleId`	(`RoleId`)	Holder count

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Object	Definition	Purpose
`TR_Roles_SystemNoUpdate`	BEFORE UPDATE ON `Roles` WHEN `OLD.IsSystem = 1` → "System roles are read-only."	Protect system roles
`TR_Roles_SystemNoDelete`	BEFORE DELETE ON `Roles` WHEN `OLD.IsSystem = 1` → "System roles cannot be deleted."	Protect system roles
`TR_Permissions_NoUpdate` / `TR_Permissions_NoDelete`	BEFORE UPDATE / DELETE ON `Permissions` → "The permission catalog is read-only."	Fixed catalogue
`TR_RolePermissions_SystemNoUpdate` / `TR_RolePermissions_SystemNoDelete`	BEFORE UPDATE / DELETE ON `RolePermissions` when the role is a system role → "System roles are read-only."	Inserts stay allowed so the seeder can add grants

5.4 Enumerations

Enum	Values	Stored as
`RoleFailure`	`NotFound`, `Invalid`, `ReadOnly`, `Duplicate`, `InUse`	Not stored; selects the HTTP status

Permission keys handled by this sub-module: `roles.manage`, `roles.view.all`, `roles.modify.access`, `roles.administrator.assign` (catalogue `IsAssignable: false`). Always-on keys (never stored as grants): `dashboard.view.own`, `tasks.view.own`, `profile.view`, `profile.edit`, `profile.password.change`, `profile.mfa.manage`. Legacy keys expanded by `EffectivePermissions.LegacyChildren`: `dashboard.admin`, `dashboard.manager`, `projects.manage`, `departments.manage`, `employees.manage`, `settings.ai.manage`.

5.5 Migrations

Migration	Change
`20261019133820_AddRolesAndPermissions`	Creates `Roles`, `Permissions`, `RolePermissions`, indexes; inserts the three system roles; moves `Users.Role` to `Users.RoleId`; rotates security stamps; creates the six triggers
`20261021070943_FixDepartmentFollowUps`	Inserts `projects.view` / `projects.manage` rows and copies grants from the department keys

6. Algorithms & Background Jobs

Job / algorithm	Trigger / schedule	Steps	Idempotency
`AccessControlSeeder.SeedAsync`	Every start-up, after `SettingsInitializer`	1. `EnsureSystemRolesAsync` (ids 1–3). 2. Insert each missing `PermissionCatalog.Stored` row. 3. Grant every permission to Administrator (FR-ROLE-22). 4. For newly created permissions only: grant to Manager/Employee per `GrantedToManager` / `GrantedToEmployee`, to all existing roles when `GrantToAllExistingRoles`, to holders of `GrantFrom`	Inserts only; later edits are never overwritten

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Job / algorithm	Trigger / schedule	Steps	Idempotency
`EffectivePermissions.Expand`	Each session check, each role read	Add legacy children; add lower scope levels of the same `ScopeGroup`	Pure
`EndSessionsOfRoleHoldersAsync`	Role update with grant changes	New security stamp per holder; revoke active refresh tokens	Saved with the grant change
Tree logic (`toggleKey` , `setScope` , `setMany`)	User ticks on the screen	Prerequisite chain on tick; dependants cleared on untick	Pure

7. Security Design (detailed)

Item	Implementation
Permission checks	`perm:roles.manage` on the controller; `User.HasClaim("permission", roles.view.all)` and `roles.modify.access` inside actions
Privilege raise	`roles.administrator.assign` is `IsAssignable: false` ; refused by `ResolvePermissionsAsync` ; checked by `EmployeesController.CanAssignAdministrator()` when an Administrator role is assigned
Defaults	`roles.manage` , `roles.view.all` , `roles.modify.access` granted to Administrator only on first seed; custom roles configurable
Session revocation	Grant change → security stamp rotation (access tokens fail in `SessionValidation`) and refresh-token revocation
Claims freshness	Permission claims are rebuilt from the database on every request; in addition, any grant change signs the holders out (FR-ROLE-18)
Database defence	Six triggers protect system roles and the catalogue
Frontend	`permissionGuard` with `Permissions.RolesManage` on `settings/permissions` ; menu "Role Configuration"; `canViewAllRoles` , `canModifyAccess` , `editable` (FR-ROLE-25)
Audit	Denied requests logged by `DeniedActionAuditHandler` ; no activity row for role changes

8. Configuration

Not applicable for this sub-module. The catalogue is code (`PermissionCatalog.cs`); no `appsettings.json` key is read. Session behaviour depends on the Auth configuration (`Jwt:AccessTokenMinutes` , `Jwt:RefreshTokenDays` , values `<secret>`), described in the overall LLD.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

9. Testing Design

Test file names from `tests-filelist.json`; contents were not available, coverage inferred from names.

Area	Test class / file	Type	Covers
Catalogue	`TaskFlow.UnitTests/Settings/RoleConfiguration/PermissionCatalogTests.cs`	Unit	Catalogue integrity
Migration	`TaskFlow.UnitTests/Persistence/RolesMigrationTests.cs`	Unit	Tables, system roles, triggers
Endpoints	`TaskFlow.IntegrationTests/Settings/RoleConfiguration/RolesEndpointsTests.cs`	Integration	Roles and permissions endpoints
Safeguards	`TaskFlow.IntegrationTests/Settings/RoleConfiguration/RoleAssignmentSafeguardTests.cs`	Integration	Administrator-role safeguards
Custom roles elsewhere	`TaskFlow.UnitTests/Monitoring/TaskManagement/Tasks/CustomRolePermissionTests.cs`, `TaskFlow.UnitTests/Monitoring/EmployeeWorkload/CustomRoleWorkloadTests.cs`	Unit	Custom role grants applied in other modules
Policies	`TaskFlow.IntegrationTests/Common/PermissionAuthorizationTests.cs`, `ModuleBasedPermissionEndpointsTests.cs`	Integration	Policy per key
Sessions	`TaskFlow.UnitTests/Auth/Login/AuthServiceRefreshAndLogoutTests.cs`, `TaskFlow.IntegrationTests/Common/AuthenticationWiringTests.cs`	Unit / Integration	Refresh refusal and session validation (by name)
Structure	`TaskFlow.UnitTests/Architecture/ArchitectureTests.cs`	Unit	Layer rules

Frontend spec files: 0.

10. Known Limitations & Open Issues

- `roles.manage` is assignable to custom roles; a custom role holding `roles.manage` and `roles.modify.access` can create a role with `employees.role.assign`.
- `GET /api/v1/roles/{id}` ignores `roles.view.all`; a caller limited to their own role in the list can still read any role by id.
- `Forbid()` returns an empty 403 body, so the screen shows only the fallback message.
- **Duplicate as custom role** is shown without `roles.modify.access`; the draft cannot be saved.
- Holder counts (list and delete check) include soft-deleted accounts (`IgnoreQueryFilters`), so such accounts block a delete.
- A rename alone does not sign holders out; only grant changes do.
- No activity or history row for role changes.
- Stale comments: Angular `RoleService` and `PermissionsManagementComponent` say "Administrator only".

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

- ⚠️ To be confirmed (FRD open issues): whether `roles.manage` should be Administrator-only, whether a direct read of another role should be refused, whether **Duplicate as custom role** should be hidden, whether a specific message is wanted for a missing `roles.modify.access`, and whether soft-deleted accounts should block role deletion.

---

11. Traceability (FRD → code)

FRD requirement	Endpoint / class	Test
FR-ROLE-01	`GET /api/v1/roles` · `GetSummariesAsync` (order, `UserCount`) · `filteredRoles`	`RolesEndpointsTests`
FR-ROLE-02	`RolesController.GetRoles` claim check `roles.view.all` · `filteredRoles`	`RolesEndpointsTests`
FR-ROLE-03	`GET /api/v1/permissions` · `buildTree` · `toggleModule` / `toggleScreen` / `setAll`	`RolesEndpointsTests`
FR-ROLE-04	`view = 'matrix'` (Compare roles)	– (no frontend specs)
FR-ROLE-05	`search`, `filter`, `matches`	– (no frontend specs)
FR-ROLE-06	`LoadCustomRoleAsync` (`ReadOnly`) · triggers `TR_Roles_*`, `TR_RolePermissions_*`	`RolesEndpointsTests`, `RolesMigrationTests`
FR-ROLE-07	`POST /api/v1/roles` · `CreateAsync` · `startNew`	`RolesEndpointsTests`
FR-ROLE-08	`duplicate()` → `copyFrom`	– (no frontend specs)
FR-ROLE-09	`copyFrom(roleId)`	– (no frontend specs)
FR-ROLE-10	`ValidateName` · `EnsureNameFreeAsync` · `IX_Roles_Name` (`NOCASE`)	`RolesEndpointsTests`
FR-ROLE-11	`ResolvePermissionsAsync` (`Requires`) · `toggleKey`	`RolesEndpointsTests`, `PermissionCatalogTests`
FR-ROLE-12	`ResolvePermissionsAsync` ("Unknown permission")	`RolesEndpointsTests`
FR-ROLE-13	`IsAssignable: false` · `ResolvePermissionsAsync` · `restrictForCaller`	`RoleAssignmentSafeguardTests`
FR-ROLE-14	`AlwaysGranted` entries dropped · `PermissionCatalog.Stored` · `PermissionDto.Id = 0`	`PermissionCatalogTests`
FR-ROLE-15	`ScopeGroup` / `ScopeRank` · `EffectivePermissions.Expand` · `setScope`	`PermissionCatalogTests`
FR-ROLE-16	`PUT /api/v1/roles/{id}` · `UpdateAsync`	`RolesEndpointsTests`
FR-ROLE-17	`dirty`, `changes`, `discard`, `confirmDiscard`, `beforeunload`	– (no frontend specs)
FR-ROLE-18	`EndSessionsOfRoleHoldersAsync` · `SessionValidation`	`RolesEndpointsTests`, `AuthServiceRefreshAndLogoutTests`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

FRD requirement	Endpoint / class	Test
FR-ROLE-19	`DELETE /api/v1/roles/{id}` · `DeleteAsync` · cascade · `remove()` confirm	`RolesEndpointsTests`
FR-ROLE-20	`CountHoldingRoleAsync` · `RoleFailure.InUse`	`RolesEndpointsTests`
FR-ROLE-21	`POST /api/v1/permissions`, `PUT /api/v1/permissions/{id}`, `DELETE /api/v1/permissions/{id}` · `CatalogIsFixed` · `TR_Permissions_*`	`RolesEndpointsTests`, `RolesMigrationTests`
FR-ROLE-22	`AccessControlSeeder` (Administrator grants on every start)	`PermissionCatalogTests`
FR-ROLE-23	Claim check `roles.modify.access` (`Forbid()`) · `editable`	`RolesEndpointsTests`
FR-ROLE-24	`heldCount`, `totalCount`, `heldPercent`	– (no frontend specs)
FR-ROLE-25	`[RequirePermission(PermissionKeys.RolesManage)]` · `permissionGuard` (`settings/permissions`) · `buildNavigation()`	`RolesEndpointsTests`, `PermissionAuthorizationTests`
FR-ROLE-26	Toasts and `formError` / `loadError` texts · `RoleFailure.NotFound`	`RolesEndpointsTests`

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.