
Login – Technical Documentation

Project: TaskFlow – Intelligent Task Allocation & Tracking System
Parent Module: Authentication · **Child Module:** 01.1 Login
Version: 1.0 · **Last Updated:** 31-Oct-2026
Backend: ASP.NET Core Web API (.NET 10) · **Frontend:** Angular · **Database:** SQLite (EF Core)
Author: Jojo George (jojogeorge3344@gmail.com)
© 2026 Jojo George. All rights reserved.

1. Technical Overview

Login is the password sign-in and the second MFA step at sign-in. `AuthController` → `AuthService.LoginAsync` checks the password with ASP.NET Core Identity's `PasswordHasher<User>` (PBKDF2). When MFA is off it issues a JWT access token (body) and a refresh token (HttpOnly cookie `taskflow_refresh`, see 01.4 Sessions and Tokens). When MFA is on it returns a Data-Protection-signed **challenge token** bound to the user id and security stamp instead; `POST /auth/mfa/verify` exchanges the challenge and a TOTP or backup code for the session through `IMfaService.VerifyAsync`. `GET /auth/me` returns the current user, role, effective permissions and `mfaSetupRequired`. On the client, `LoginComponent` drives both steps and `dashboardRouteFor(role, permissions)` picks the landing page.

2. Architecture Flow



3. Backend File Structure

All paths are under `TaskFlow Proj/backend/src/TaskFlow.Api/`.

Layer	Path	Files
Controller	`Controllers/Auth/`	`AuthController.cs` (actions `Login`, `VerifyMfa`, `Me`; `Refresh` / `Logout` are in 01.4)
Service	`Services/Auth/Login/`	`IAuthService.cs`, `AuthService.cs` (`LoginAsync`, `VerifyMfaAsync`, `GetCurrentAsync`, `IssueTokens`, `ToDtoAsync`)
Service (used)	`Services/Auth/Mfa/`	`IMfaService.cs`, `MfaService.cs` (`VerifyAsync`, see 01.3)
Repository	`Repositories/Auth/Accounts/`	`IAccountRepository.cs`, `AccountRepository.cs`
Repository (used)	`Repositories/Auth/RefreshTokens/`	`IRefreshTokenRepository.cs`, `RefreshTokenRepository.cs` (`Add`)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Path	Files
DTOs	`Dtos/Auth/`	`LoginRequest.cs`, `AuthResponse.cs` (`AuthResponse`, `AuthenticatedUserResponse`), `AuthResult.cs` (`AuthResult`, `MfaSignInResult`), `AuthTokens.cs`, `UserDto.cs`
DTOs	`Dtos/Auth/Mfa/`	`MfaRequests.cs` (`MfaVerifyRequest`, `MfaChallengeResponse`), `MfaResults.cs` (`MfaVerifyOutcome`: Success, Invalid, LockedOut)
Validators	`Dtos/Auth/Validators/`	`LoginRequestValidator.cs`
Validators	`Dtos/Auth/Mfa/Validators/`	`MfaRequestValidators.cs` (`MfaVerifyRequestValidator`)
Integrations	`Integrations/Security/MfaSecrets/`	`IMfaSecretProtector.cs`, `MfaSecretProtector.cs` (`CreateChallenge`, `ReadChallenge`)
Integrations	`Integrations/Security/Tokens/`	`ITokenService.cs`, `JwtTokenService.cs` (`CreateAccessToken`, see 01.4)
Entities	`Models/Entities/`	`User.cs`, `Role.cs`, `RefreshToken.cs`
Common / Security	`Common/Security/`	`RefreshTokenCookie.cs` (`CreateOptions`), `EffectivePermissions.cs` (`Expand`)
Config	`Config/`	`MfaOptions.cs` (`ChallengeMinutes`, `Required`)

4. Frontend File Structure

All paths are under `TaskFlow Proj/frontend/src/app/`.

Type	Path	Purpose
Routes	`modules/auth/auth.routes.ts`	`login` route (outside the shell)
Page component	`modules/auth/login/pages/login.component.ts` / `.html`	Password step and MFA code step (`challenge` signal)
Child component	`modules/auth/login/components/login-background.component.ts` / `.html`	Decorative background
Utility	`modules/auth/login/utils/remembered-identifier.ts`	`localStorage` key `taskflow.lastIdentifier`
API service	`shared/auth/auth.service.ts`	`login`, `verifyMfa`
Models	`shared/auth/auth.models.ts`	`AuthUser`, `LoginRequest`, `AuthResponse`, `MfaChallenge`, `isMfaChallenge()`
Routing helper	`shared/auth/role-routes.ts`	`dashboardRouteFor(role, permissions)`
Messages	`shared/auth/login-reasons.ts`	`reason` query values and login notices

> ⚠️ To be confirmed: `login.component.ts` references `styleUrl: './login.component.css'`, but the

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

> CSS file is not present in the snapshot.

5. API & Logic

5.1 API Endpoints

#	Method	Endpoint	Description	Permission (Policy)	Request DTO	Response DTO
1	POST	`/api/v1/auth/login`	Password sign-in. Returns a session, or an MFA challenge when MFA is on	`[AllowAnonymous]`	`LoginRequest`	`AuthResponse` + `Set-Cookie: taskflow_refresh` / `MfaChallengeResponse` / `401`
2	POST	`/api/v1/auth/mfa/verify`	Second sign-in step with the challenge and an authenticator or backup code	`[AllowAnonymous]`	`MfaVerifyRequest`	`AuthResponse` + cookie / `400` / `429` (ProblemDetails)
3	GET	`/api/v1/auth/me`	Current user, role, effective permissions, `mfaSetupRequired`	`[Authorize]`	–	`AuthenticatedUserResponse`

5.2 Request / Response Samples

```
// POST /api/v1/auth/login
{ "emailOrUsername": "jane.doe@taskflow.com", "password": "S3cret!" }
```

```
// 200 OK – MFA is on (no cookie, no session yet)
{ "mfaRequired": true, "challengeToken": "CfDJ8...protected..." }
```

```
// 200 OK – session issued (also Set-Cookie: taskflow_refresh=...; HttpOnly; Secure;
SameSite=Strict; Path=/api/v1/auth)
{
  "accessToken": "eyJhbGciOiJIUzI1NiIs...",
  "expiresAt": "2026-10-31T10:30:00Z",
  "user": {
    "id": 7, "fullName": "Jane Doe", "username": "jane", "email": "jane.doe@taskflow.com",
    "role": "Employee", "employeeCode": "EMP007",
    "permissions": ["dashboard.analytics.view", "tasks.status.change"],
    "mfaSetupRequired": false
  }
}
```

```
// POST /api/v1/auth/mfa/verify
{ "challengeToken": "CfDJ8...protected...", "code": "123456" }
```

```
// 400 Bad Request (ProblemDetails)
{ "status": 400, "detail": "The code is incorrect, or the sign-in has expired. Try again or
sign in again." }
```

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

5.3 Service Layer Logic

Method: `AuthService.LoginAsync(LoginRequest request, CancellationToken)`

1. `IAccountRepository.FindByLoginForUpdateAsync(request.EmailOrUsername.Trim())` – matches `Username == identifier || Email == identifier`, includes `Role`; deleted users are excluded by the global query filter.
2. Returns `AuthResult.Failure()` (→ `401`) if the user is null or `!IsActive`.
3. `IPasswordHasher<User>.VerifyHashedPassword`; `Failed` → failure. `SuccessRehashNeeded` → re-hashes and stores the new hash.
4. If `MfaEnabledAt` is set: saves a rehash if needed and returns `AuthResult.RequiresMfa(IMfaSecretProtector.CreateChallenge(user.Id, user.SecurityStamp, Mfa:ChallengeMinutes))`. No token and no `LastLoginAt` update.
5. Otherwise sets `LastLoginAt` and `UpdatedAt`, calls `IssueTokens` (creates the JWT via `ITokenService.CreateAccessToken`, creates a refresh token, adds a `RefreshToken` row with its SHA-256 hash), `SaveChangesAsync`.
6. Maps to `UserDto` via `ToDtoAsync`: permissions = `EffectivePermissions.Expand(GetPermissionKeysAsync(roleId))` ordered ordinally; `MfaSetupRequired = Mfa:Required && MfaEnabledAt == null`.
7. Controller writes the refresh cookie (`RefreshTokenCookie.CreateOptions(expiresAt)`) and returns `AuthResponse`.

Method: `AuthService.VerifyMfaAsync(string? challengeToken, string? code, CancellationToken)`

1. `IMfaSecretProtector.ReadChallenge` – null when forged, tampered, malformed or expired → `Invalid`.
2. `FindWithRoleForUpdateAsync(userId)`; invalid if null, inactive, MFA off, or `SecurityStamp` differs from the stamp inside the challenge.
3. `IMfaService.VerifyAsync(user, code, allowBackupCode: true)` – returns `Success`, `Invalid` or `LockedOut` (core logic in 01.3 MFA Security Setup, `VerifyCoreAsync`).
4. On success: `LastLoginAt` / `UpdatedAt`, `IssueTokens`, save; returns `MfaSignInResult(Success)`.
5. Controller: `Success` → cookie + `AuthResponse`; `LockedOut` → `429` with `MfaService.LockedMessage`; anything else → `400`.

Method: `AuthService.GetCurrentAsync(int userId)` – loads the user with role and maps with `ToDtoAsync`; the controller returns `401` when the subject claim is not an int or the user is not found.

Frontend: after a successful sign-in `LoginComponent` navigates to the `returnUrl` (only when it is a path inside TaskFlow) or to `dashboardRouteFor(role, permissions)`; when `mfaSetupRequired` is true the shell guard sends the user to `/security-setup`.

5.4 Repository Layer


Method	Description	Query Notes
`AccountRepository.FindByLoginForUpdateAsync(identifier)`	User by username or email, with role	Tracked; `Include(Role)`; exact string comparison; soft-deleted excluded by `HasQueryFilter(!IsDeleted)`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Method	Description	Query Notes
`AccountRepository.FindWithRoleForUpdateAsync(userId)`	User by id, with role	Tracked
`AccountRepository.GetPermissionKeysAsync(roleId)`	Stored permission keys of the role	`AsNoTracking`, `RolePermissions` → `Permission.Key` (not expanded)
`RefreshTokenRepository.Add(RefreshToken)`	New refresh-token row	From `BaseRepository`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

5.5 Sequence Diagram



6. Database Design

Full `Users` column list and relationships: parent document section 6. Columns this child reads or writes:

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Table	Column	Type	Constraints	Description
`Users`	`Id`	INTEGER	PK, autoincrement	User id (JWT subject, challenge user id)
`Users`	`Username`	TEXT(100)	Not Null, Unique (`IX_Users_Username`)	Sign-in name (matched exactly)
`Users`	`Email`	TEXT(256)	Not Null, Unique (`IX_Users_Email`)	Sign-in email (stored lower-case, matched exactly)
`Users`	`PasswordHash`	TEXT	Not Null	Verified; re-hashed when `SuccessRehashNeeded`
`Users`	`SecurityStamp`	TEXT(64)	Not Null	Copied into the challenge and the JWT `sstamp` claim
`Users`	`MfaEnabledAt`	TEXT (DateTime)	Nullable	Decides whether a challenge is returned
`Users`	`MfaLastUsedStep`, `MfaFailedAttempts`, `MfaLockedUntil`	INTEGER / INTEGER / TEXT	Concurrency tokens (first two)	Updated by `MfaService.VerifyAsync` at the code step
`Users`	`IsActive`, `IsDeleted`	INTEGER (bool)	Not Null; global query filter `!IsDeleted`	Inactive or deleted users cannot sign in
`Users`	`LastLoginAt`, `UpdatedAt`	TEXT (DateTime)	Nullable / Not Null	Set on successful sign-in
`Users`	`FullName`, `EmployeeCode`, `RoleId`	TEXT(200) / TEXT(32) / INTEGER	`RoleId` FK → `Roles.Id`	Mapped into `UserDto`
`RefreshTokens`	all columns	–	See 01.4	One row inserted per successful sign-in
`MfaBackupCodes`	`UsedAt`	TEXT (DateTime)	Concurrency token	Set when a backup code is accepted at `/auth/mfa/verify` (see 01.3)
`RolePermissions`, `Permissions`	`RoleId`, `Key`	–	Settings module	Read to build the permission list

7. Security & Authorization

- Both sign-in endpoints are `[AllowAnonymous]`; `GET /auth/me` needs a valid bearer token (`[Authorize]`).
- **Anti-enumeration:** login returns a bare `401` for any failure (unknown account, inactive, deleted, wrong password).
- **Challenge:** protected with Data Protection purpose `TaskFlow.MfaChallenge`, 5-minute lifetime (`Mfa:ChallengeMinutes`), bound to the user id and security stamp, so a password change or reset invalidates it.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

- **Codes:** TOTP SHA1 / 6 digits / 30 s, ±1 step, single use per step; an unused backup code is also accepted here; lockout after 5 wrong codes for 5 minutes (shared counter, see 01.3).
- **Frontend:** the `returnUrl` is used only when it is an internal path.

Permission Key	Endpoint(s)	UI Element Controlled
(none – `[AllowAnonymous]`)	`POST /api/v1/auth/login`, `POST /api/v1/auth/mfa/verify`	Login screen (password step and code step)
(none – `[Authorize]`)	`GET /api/v1/auth/me`	Current user, role and permission sync (also the session check, 01.4)

8. Validations & Error Handling

Rule	Layer	HTTP Code	Error Message
`EmailOrUsername` required, max 256; `Password` required, max 128	`LoginRequestValidator`	400	FluentValidation default messages (validation ProblemDetails `errors` map)
Wrong credentials, inactive or deleted account	`AuthService` / `AuthController`	401	(empty body); UI shows "Invalid email or password."
`ChallengeToken` required, max 2048; `Code` required, max 32	`MfaVerifyRequestValidator`	400	FluentValidation defaults
Wrong code or expired challenge	`AuthController.VerifyMfa`	400	The code is incorrect, or the sign-in has expired. Try again or sign in again.
MFA locked	`AuthController.VerifyMfa`	429	Too many wrong codes. Try again in a few minutes.
Subject claim not an int or user not found	`AuthController.Me`	401	(empty body)

9. Integrations / Side Effects

- **Session:** a successful sign-in inserts a `RefreshTokens` row and sets the `taskflow_refresh` cookie (lifecycle in 01.4).
- **Audit fields:** `Users.LastLoginAt` and `UpdatedAt` are set; an outdated password hash is upgraded.
- **Notifications / Email / Activity Log / AI Assistant:** none for this child.

10. Configuration

Key (`appsettings.json`)	Purpose	Default
`Mfa:ChallengeMinutes`	Sign-in challenge lifetime (code default)	`5`

Token lifetimes and signing (`Jwt:*`) are in 01.4 Sessions and Tokens; `Mfa:Required`, `Mfa:MaxFailedAttempts` and `Mfa:LockoutMinutes` are in the parent document.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

11. Testing

Paths are relative to `backend/tests`.

Test Type	File / Location	Covers
Unit	`TaskFlow.UnitTests/Auth/Login/AuthServiceLoginTests.cs`	`AuthService.LoginAsync`
Unit	`TaskFlow.UnitTests/Auth/Mfa/AuthServiceMfaTests.cs`	`VerifyMfaAsync` / challenge
Integration	`TaskFlow.IntegrationTests/Auth/Mfa/MfaSignInEndpointsTests.cs`	Two-step sign-in

Shared: `AuthServiceHarness.cs` and `AuthEndpointsTests.cs` (login, refresh, logout, me endpoints) are listed in the parent document. No frontend spec files were found under `modules/auth/login`.

12. Known Limitations / Gaps found

- Password sign-in (`POST /auth/login`) has no attempt limit or lockout; only MFA codes, recovery and password re-entry are throttled.
- **BRD vs UI – username sign-in:** BRD Screen 1 requires "email address or username" and the API accepts both, but `login.component.ts` applies `Validators.email` and labels the field "Email", so a plain username cannot be submitted from the screen.
- **Backup codes at sign-in:** the API accepts an unused backup code at `/auth/mfa/verify`, but the login code input has `maxlength="6"`, so the 11-character `XXXXX-XXXXX` codes cannot be typed there.
- **Hard-coded role routing:** `role-routes.ts` sends Administrator/Manager by role name ahead of permissions (also in permission-gaps.md section E).
- **Case-sensitive identifier:** `FindByLoginForUpdateAsync` compares `Email`/`Username` with `==` without lower-casing the input, while emails are stored lower-case and the columns have no NOCASE collation. > ⚠️ To be confirmed: whether signing in with a mixed-case email fails at runtime on SQLite.
- **Missing style file:** `login.component.css` is referenced but absent from the snapshot.

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.