
Two-Step Verification – Technical Documentation

Project: TaskFlow – Intelligent Task Allocation & Tracking System
Parent Module: Profile · **Child Module:** 07.3 Two-Step Verification (self-service MFA endpoints)
Version: 1.0 · **Last Updated:** 31-Oct-2026
Backend: ASP.NET Core Web API (.NET 10) · **Frontend:** Angular · **Database:** SQLite (EF Core)
Author: Jojo George (jojogeorge3344@gmail.com)
© 2026 Jojo George. All rights reserved.

1. Technical Overview

These four self-service authenticator-MFA endpoints are hosted in `ProfileController` under `api/v1/users/me/mfa`. Their logic is in the Auth module's `MfaService` (see 01-Auth, MFA / Security Setup); `ProfileService` adds the current-password attempt budget through `IAttemptLimiter`. The Auth module's `SecuritySetupComponent` is the only UI caller. `MfaSetupGateMiddleware` allows `/api/v1/users/me` (exact path) and `/api/v1/users/me/mfa/*` while the token carries the `MfaSetupRequired` claim. Every other API path returns 403 with `code = "mfa_setup_required"`. The controller has only `[Authorize]`; the catalog key `profile.mfa.manage` is always on and not enforced.

2. Architecture Flow



3. Backend File Structure

Layer	Path	Files
Controller	`TaskFlow.Api/Controllers/Profile/`	`ProfileController.cs` (`SetupMfa`, `EnableMfa`, `CheckMfa`, `RegenerateBackupCodes`)
Service	`TaskFlow.Api/Services/Profile/`	`IProfileService.cs`, `ProfileService.cs` (`BeginMfaSetupAsync`, `EnableMfaAsync`, `CheckMfaCodeAsync`, `RegenerateBackupCodesAsync`)
Service (reused)	`TaskFlow.Api/Services/Auth/Mfa/`	`IMfaService.cs`, `MfaService.cs`
Service (reused)	`TaskFlow.Api/Services/Auth/AttemptLimits/`	`IAttemptLimiter.cs`, `AttemptLimiter.cs`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Path	Files
Integrations (reused)	`TaskFlow.Api/Integrations/Security/`	`MfaSecrets/IMfaSecretProtector.cs`, `MfaSecrets/MfaSecretProtector.cs`, `OneTimeCodes/Totp.cs`
Repository (reused)	`TaskFlow.Api/Repositories/Auth/Accounts/`	`IAccountRepository.cs`, `AccountRepository.cs`
Repository (reused)	`TaskFlow.Api/Repositories/Auth/Mfa/`	`IMfaBackupCodeRepository.cs`, `MfaBackupCodeRepository.cs`
DTOs (reused)	`TaskFlow.Api/Dtos/Auth/Mfa/`	`MfaRequests.cs` (`MfaSetupRequest`, `MfaSetupResponse`, `MfaEnableRequest`, `MfaPasswordCodeRequest`, `MfaBackupCodesResponse`), `MfaResults.cs` (`MfaVerifyOutcome`, `MfaSetupResult`)
Validators (reused)	`TaskFlow.Api/Dtos/Auth/Mfa/Validators/`	`MfaRequestValidators.cs`
Entities	`TaskFlow.Api/Models/Entities/`	`User.cs`, `MfaBackupCode.cs`
Security	`TaskFlow.Api/Common/Security/`	`PermissionKeys.cs`, `PermissionCatalog.cs` (`profile.mfa.manage`)
Middleware	`TaskFlow.Api/Middleware/`	`MfaSetupGateMiddleware.cs`, `GlobalExceptionHandler.cs`
Config / DI	`TaskFlow.Api/Config/`	`MfaOptions.cs`, `ServiceRegistration.cs` (`IMfaService` → `MfaService`, scoped; `MfaOptions` bound from the `Mfa` section)
Migration	`TaskFlow.Api/Persistence/Migrations/`	`20261023101938_AddMfaAndAccountRecovery.cs`

4. Frontend File Structure

Type	Path	Purpose
API service	`src/app/modules/profile/services/profile.service.ts`	`startMfaSetup`, `enableMfa`, `checkMfaCode` (unused)
Consumer page	`src/app/modules/auth/security-setup/pages/security-setup.component.ts`	Step 2: current password → `startMfaSetup`, QR code and key, first code → `enableMfa`; shows backup codes once with copy and download (`taskflow-backup-codes.txt`)
Models	`src/app/modules/auth/security-setup/pages/security-setup.model.ts`	Security Setup form models
Status display	`src/app/modules/profile/pages/profile.component.html`	"Two-step on/off" chip (see 07.1)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

5. API & Logic

5.1 API Endpoints

#	Method	Endpoint	Description	Permission (Policy)	Request DTO	Response DTO
1	POST	`/api/v1/users/me/mfa/setup`	Check the current password, issue a new TOTP key (MFA stays off)	`[Authorize]`. Catalog key `profile.mfa.manage` (always on, not enforced).	`MfaSetupRequest`	`MfaSetupResponse` (200), 400, 404, 429
2	POST	`/api/v1/users/me/mfa/enable`	Confirm with the first code, turn MFA on, return backup codes once	`[Authorize]`, `profile.mfa.manage` (not enforced)	`MfaEnableRequest`	`MfaBackupCodesResponse` (200), 400, 404
3	POST	`/api/v1/users/me/mfa/check`	Check a TOTP code without using it up (backup codes not accepted)	`[Authorize]`, `profile.mfa.manage` (not enforced)	`MfaEnableRequest`	`204`, 400 (`InvalidCodeMessage`), 429 (`LockedMessage`)
4	POST	`/api/v1/users/me/mfa/backup-codes`	Replace backup codes after the password and a valid code	`[Authorize]`, `profile.mfa.manage` (not enforced)	`MfaPasswordCodeRequest`	`MfaBackupCodesResponse` (200), 400, 404, 429

5.2 Request / Response Samples

```
// POST /api/v1/users/me/mfa/setup
{ "currentPassword": "my-current-password" }
```

```
// 200 OK
{ "key": "JBSWY3DPEHPK3PXP", "provisioningUri":
"otpauth://totp/TaskFlow:anita.v%40taskflow.com?secret=JBSWY3DPEHPK3PXP&issuer=TaskFlow" }
```

```
// POST /api/v1/users/me/mfa/enable  ->  200 OK
{ "codes": [ "ABCDE-FGHIJ", "KLMNO-PQRST" ] }
```

> ⚠️ To be confirmed: the exact `provisioningUri` format comes from `Totp.ProvisioningUri(issuer, email, secret)`, which was not inspected. The sample is illustrative.

5.3 Service Layer Logic

Method: `BeginMfaSetupAsync(userId, currentPassword)`

1. `AcquirePasswordAttempt`: `IAttemptLimiter.TryAcquire("pwd:" + userId, remoteAddress: null)`. If the budget is spent (5 attempts in a 5-minute sliding window, in memory), it throws `RateLimitedException("Too many attempts. Try again in a few minutes.")` → 429.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

2. `MfaService.BeginSetupAsync`: checks the password (`"Current password is incorrect."`) and refuses if MFA is already on. Otherwise it creates a new secret, stores it encrypted in `MfaSecretProtected`, and resets the step, failed attempts and lockout.
3. On success, `_limiter.Reset(passwordKey)`. A wrong password throws before the reset, so the attempt stays counted.

Method: `EnableMfaAsync(userId, code)` → `MfaService.EnableAsync`. It refuses if MFA is already on or no key exists. It verifies the TOTP (no backup codes), sets `MfaEnabledAt`, deletes and recreates `BackupCodeCount` (10) codes in the form `XXXXX-XXXXX`, and stores SHA-256 hashes.

Method: `CheckMfaCodeAsync(userId, code)` → `MfaService.CheckCodeAsync`. `VerifyCoreAsync` runs with `consumeCode: false` and `countFailure: true`. It returns `Invalid` when MFA is off. The controller maps `LockedOut` to 429 and other failures to 400.

Method: `RegenerateBackupCodesAsync(userId, currentPassword, code)` uses the same password budget as setup. `MfaService.RegenerateBackupCodesAsync` checks the password, requires MFA on, verifies the code (backup codes allowed) and replaces every backup code.


Shared lockout: `MfaOptions.MaxFailedAttempts` (5) wrong codes in a row set `MfaLockedUntil = now + LockoutMinutes` (5). `MfaLastUsedStep`, `MfaFailedAttempts` and `MfaBackupCode.UsedAt` are EF concurrency tokens. If a parallel save loses, the code is treated as `Invalid`.

5.4 Repository Layer

Method	Description	Query Notes
`IAccountRepository.FindLiveForUpdateAsync(id)`	Tracked live user	Auth module
`IMfaBackupCodeRepository.GetForUserForUpdateAsync(userId)`	All backup codes, for replacement	Tracked
`IMfaBackupCodeRepository.FindUnusedForUpdateAsync(userId, hash)`	One unused code	Index `(UserId, CodeHash)`
`IMfaBackupCodeRepository.Add / Remove`	Insert or delete codes	Saved through `IUnitOfWork`

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

5.5 Sequence Diagram



6. Database Design

Table	Column	Type	Constraints	Description
`Users`	`Id`	int	PK	User id (taken from the JWT)
`Users`	`PasswordHash`	text	Not Null	Read to check the current password (setup, backup codes)
`Users`	`MfaSecretProtected`	text	Max 512, nullable	Encrypted TOTP key
`Users`	`MfaEnabledAt`	datetime	nullable	MFA on when not null
`Users`	`MfaLastUsedStep`	bigint	Concurrency token	Replay protection

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Table	Column	Type	Constraints	Description
`Users`	`MfaFailedAttempts`	int	Concurrency token	Shared lockout counter
`Users`	`MfaLockedUntil`	datetime	nullable	Lockout end
`MfaBackupCodes`	`Id`, `UserId`, `CodeHash`, `CreatedAt`, `UsedAt`	int / text / datetime	PK; `CodeHash` Not Null, Max 64; index `(UserId, CodeHash)`; `UsedAt` concurrency token	SHA-256 hex of backup codes

Relationships

- `MfaBackupCodes.UserId → Users.Id` (FK, Cascade)

7. Security & Authorization

- `[Authorize]` only; the id comes from `ClaimTypes.NameIdentifier` (unparseable → 401). Own account only.
- `profile.mfa.manage` has `AlwaysGranted: true, IsAssignable: false` in `PermissionCatalog.cs` and is never checked.
- **MFA gate:** `/api/v1/users/me/mfa/*` is on the `MfaSetupGateMiddleware` allow-list (with `Mfa:Required = true`), so these endpoints work while setup is pending.
- **Brute-force limits:** the current-password budget is 5 per 5 minutes per account (`AttemptLimiter`, in memory). The TOTP lockout is 5 wrong codes → 5 minutes (`MfaOptions`), shared with sign-in and 07.2.
- **Secret storage:** the TOTP key is stored encrypted (`IMfaSecretProtector`); backup codes are stored as SHA-256 hashes and shown once.

Permission Key	Endpoint(s)	UI Element Controlled
`profile.mfa.manage`	`POST /api/v1/users/me/mfa/setup`, `/enable`, `/check`, `/backup-codes`	Security Setup screen (Auth module), "Two-step on/off" chip

8. Validations & Error Handling

Rule	Layer	HTTP Code	Error Message
Wrong current password (setup, backup codes)	`MfaService`	400	Current password is incorrect.
Password attempt budget spent	`ProfileService`	429 (`Too many requests`)	Too many attempts. Try again in a few minutes.
MFA already on (setup)	`MfaService`	400	Authenticator MFA is already on. Turn it off first to set it up again.
MFA already on (enable)	`MfaService`	400	Authenticator MFA is already on.
Enable without setup	`MfaService`	400	Start the setup first to get a key.
Backup codes with MFA off	`MfaService`	400	Authenticator MFA is not on.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Rule	Layer	HTTP Code	Error Message
Code wrong or expired	`MfaService` / Controller (`mfa/check`)	400	The code is incorrect or has expired.
Code lockout (enable, backup codes)	`MfaService`	400	Too many wrong codes. Try again in a few minutes.
Code lockout (`mfa/check`)	Controller	429	Too many wrong codes. Try again in a few minutes.
User not found or deleted	Controller	404	– (empty `NotFound()`)

Request DTO validation is done by `MfaRequestValidators.cs` (Auth module). Shared error handling is described in the parent document.

9. Integrations / Side Effects

- **Notifications / Email / Activity Log:** none raised by these endpoints. (The admin MFA reset in the Auth module notifies the user and points them to Profile.)
- **Auth module:** `SecuritySetupComponent` drives setup and enable; once `MfaEnabledAt` is set, the setup gate no longer applies and sign-in asks for a code.

10. Configuration

Key (`appsettings.json`)	Purpose	Default
`Mfa:Issuer`	Name shown in the authenticator app (provisioning URI)	`TaskFlow`
`Mfa:Required`	Enforce MFA setup before any other API use	`true`
`Mfa:MaxFailedAttempts`	Wrong codes before lockout (code default, not in the JSON)	`5`
`Mfa:LockoutMinutes`	Lockout length (code default)	`5`
`Mfa:BackupCodeCount`	Backup codes issued on enable or regenerate (code default)	`10`
`AttemptLimiter.AttemptsPerAccount` / `Window`	Current-password budget (constants, not configurable)	`5` per `5` minutes

11. Testing

Test Type	File / Location	Covers
Integration	`tests/TaskFlow.IntegrationTests/Auth/Mfa/MfaEnrolmentEndpointsTests.cs`	`mfa/setup` and `mfa/enable`
Integration	`tests/TaskFlow.IntegrationTests/Auth/Mfa/MfaSetupGateEndpointsTests.cs`	Setup gate allow-list (`/users/me`, `/users/me/mfa/*`)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Test Type	File / Location	Covers
Unit	`tests/TaskFlow.UnitTests/Auth/Mfa/MfaServiceTests.cs`	`MfaService` code verification, lockout, backup codes
Unit	`tests/TaskFlow.UnitTests/Auth/AttemptLimits/AttemptLimiterTests.cs`	Current-password attempt budget
Unit	`tests/TaskFlow.UnitTests/Integrations/Security/OneTimeCodes/TotpTests.cs`	TOTP generation and validation
Support	`tests/TaskFlow.IntegrationTests/TestSupport/MfaTestSupport.cs`, `tests/TaskFlow.UnitTests/TestSupport/AcceptingMfaService.cs`	MFA test helpers

> ⚠️ To be confirmed: only test file names were available. What each file covers is inferred from its name and folder. No test file name refers to `mfa/check` or `mfa/backup-codes`.

12. Known Limitations / Gaps found

- `AttemptLimiter` is in memory, so a restart resets the password budget, and the budget is not shared across instances.
- Possible enhancement: a Profile security card to view remaining backup codes and regenerate them.
- **Endpoints without UI:** `POST /users/me/mfa/backup-codes` has no frontend caller (also noted in `permission-inventory.csv`). `ProfileService.checkMfaCode()` in Angular is defined but never used. The catalog description of `profile.mfa.manage` mentions "regenerate backup codes", which users cannot do from any screen.
- Lockout returns 429 from `mfa/check` but 400 from enable and backup-codes (see parent).

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.