Settings Module – Technical Documentation

Project: TaskFlow – Intelligent Task Allocation & Tracking System
Module: Settings · **Child Modules:** Application Settings, Reminder Settings, Role Configuration, TFA Settings
Version: 1.0 · **Last Updated:** 31-Oct-2026
Backend: ASP.NET Core Web API (.NET 10) · **Frontend:** Angular · **Database:** SQLite (EF Core)
Author: Jojo George (jojogeorge3344@gmail.com)
© 2026 Jojo George. All rights reserved.

✅ Target framework confirmed: `net10.0` (.NET 10), from `backend/src/TaskFlow.Api/TaskFlow.Api.csproj`.


1. Technical Overview

The Settings module is four REST controllers under `Controllers/Settings/`. Each one has a service and a repository behind it:

- **Application Settings** and **Reminder Settings** read and write typed views over one key/value table, `ApplicationSettings`. The keys are defined in `Common/Constants/SettingKeys.cs`. `SettingsInitializer` inserts any missing row at startup. `AppClock` resolves the single application timezone for all deadline-day calculations.
- **Role Configuration** manages custom `Roles` and their `RolePermissions` grants against the fixed permission catalogue in `Common/Security/PermissionCatalog.cs`. System roles and the `Permissions` table are protected by SQLite triggers. A permission change on a role signs out its holders: their security stamp is rotated and their refresh tokens are revoked.
- **TFA Settings** stores one `AiProviderConfigs` row per AI provider (Ollama, Gemini, OpenAI) and the list of selectable `AiModels`. API keys are encrypted with ASP.NET Core Data Protection (`AiKeyProtector`). The connection test goes through the Assistant's `IChatModelGateway` to the provider clients in `Integrations/Ai/Providers/`.

Every write endpoint needs a permission policy (`[RequirePermission]`). Validation uses FluentValidation through the global `ValidationFilter`. Errors are mapped to ProblemDetails by `GlobalExceptionHandler`.

2. Architecture Flow



3. Backend File Structure

Module-level summary. Each child document lists its own files in full.

Layer	Path	Files / Owner
Controllers	`TaskFlow.Api/Controllers/Settings/`	`ApplicationSettingsController.cs` (08.1), `ReminderSettingsController.cs` (08.2), `RolesController.cs` (08.3), `AiProvidersController.cs` (08.4)
Services	`TaskFlow.Api/Services/Settings/`	`ApplicationSettings/General/`, `ApplicationSettings/Clock/` (08.1), `ReminderSettings/` (08.2), `RoleConfiguration/` (08.3), `TfaSettings/ProviderConfig/`, `TfaSettings/ConnectionTest/` (08.4)

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Layer	Path	Files / Owner
Repositories	`TaskFlow.Api/Repositories/Settings/`	`ApplicationSettings/` (shared by 08.1 and 08.2), `RoleConfiguration/Roles/`, `RoleConfiguration/Permissions/` (08.3), `TfaSettings/ProviderConfig/`, `TfaSettings/AiModels/` (08.4)
DTOs + Validators	`TaskFlow.Api/Dtos/Settings/<Child>/` and `<Child>/Validators/`	One DTO file and (except Role Configuration) one validator file per child
Shared entity	`TaskFlow.Api/Models/Entities/`	`ApplicationSetting.cs` (08.1 and 08.2)
Shared constants	`TaskFlow.Api/Common/Constants/`	`SettingKeys.cs` (08.1 and 08.2)
Shared security	`TaskFlow.Api/Common/Security/`	`PermissionKeys.cs`, `PermissionPolicy.cs` (all children)
Authorization	`TaskFlow.Api/Authorization/Policies/`	`RequirePermissionAttribute.cs`, `AuthPolicies.cs` (all children)
Shared exceptions	`TaskFlow.Api/Common/Exceptions/`	`AppException.cs`, `PersistenceExceptions.cs`
Shared seeder	`TaskFlow.Api/Persistence/Seeders/`	`SettingsInitializer.cs` (08.1 and 08.2)
Shared config	`TaskFlow.Api/Config/`	`ApplicationOptions.cs` (08.1 and 08.2)
Cross-cutting	`TaskFlow.Api/Filters/`, `TaskFlow.Api/Middleware/`	`ValidationFilter.cs`, `GlobalExceptionHandler.cs`, `SessionValidation.cs`
Migration (shared table)	`TaskFlow.Api/Persistence/Migrations/`	`20261017062735_AddReminderEngine.cs` creates the `ApplicationSettings` table

4. Frontend File Structure

Module-level summary. Each child document lists its own page, service and model files.

Type	Path	Purpose
Routes	`src/app/modules/settings/settings.routes.ts`	`SETTINGS_ROUTES`: `settings/reminders`, `settings/application`, `settings/tfa`, `settings/permissions`, each with `permissionGuard`
Shell route	`src/app/routes/app.routes.ts`	Lazy-loads `SETTINGS_ROUTES` under the authenticated shell
Menu	`src/app/layouts/nav-items.ts`	`buildNavigation()` adds the Settings group with Reminder Settings / Application Settings / TFA Settings / Role Configuration by permission

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Type	Path	Purpose
Permission constants	`src/app/shared/auth/permissions.ts`	`SettingsReminders`, `SettingsApplication`, `SettingsAiView`, `SettingsAiEdit`, `SettingsAiTest`, `SettingsAiRemoveModel`, `RolesManage`, `RolesViewAll`, `RolesModifyAccess`, `RolesAdministratorAssign`
Guard	`src/app/shared/auth/auth.guard.ts`	`permissionGuard`: redirects to the user's dashboard when none of `data.permissions` is held
Shared model	`src/app/modules/settings/models/settings.model.ts`	`ApplicationSettings`, `ReminderSettings` interfaces (08.1 and 08.2)
Error helper	`src/app/shared/utils/api-error.ts`	`apiErrorMessage()` reads ProblemDetails `detail` / `errors`
Child folders	`src/app/modules/settings/application-settings/`, `reminder-settings/`, `role-configuration/`, `tfa-settings/`	One folder per child module


5. Child Modules

#	Child Module	Main endpoints (count)	Key permissions	Document
08.1	Application Settings	`GET`, `PUT` `/api/v1/settings/application` (2)	`settings.application.manage` (GET: signed in only)	`08.1-Application-Settings.md`
08.2	Reminder Settings	`GET`, `PUT` `/api/v1/settings/reminders` (2)	`settings.reminders.manage`	`08.2-Reminder-Settings.md`
08.3	Role Configuration	`/api/v1/roles` (5) and `/api/v1/permissions` (4) (9)	`roles.manage`, `roles.view.all`, `roles.modify.access`, `roles.administrator.assign`	`08.3-Role-Configuration.md`
08.4	TFA Settings	`/api/v1/assistant/providers/config` (2), `/{kind}/models` (1), `/{kind}/test` (1) (4)	`settings.ai.view`, `settings.ai.edit`, `settings.ai.test`, `settings.ai.model.remove`	`08.4-TFA-Settings.md`

The child documents are in the `08-Settings/` folder next to this file. Total: 17 endpoints.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

6. Database Design



ApplicationSettings	
int	Id
string	Key
string	Value
string	Category

Table	Owner child	Shared with	Notes
`ApplicationSettings`	08.1 Application Settings (`Application.*`, `Notification.InAppEnabled`)	08.2 Reminder Settings (`Reminder.*`, `Notification.MailEnabled`)	Key/value table. No FK. Full column list below
`Roles`	08.3 Role Configuration	Management (`Users.RoleId`)	System roles protected by triggers
`Permissions`	08.3 Role Configuration	–	Fixed catalogue, protected by triggers
`RolePermissions`	08.3 Role Configuration	–	Composite PK
`AiProviderConfigs`	08.4 TFA Settings	Assistant (runtime)	One row per provider
`AiModels`	08.4 TFA Settings	–	Unique (`Kind`, `Name`)

`ApplicationSettings` columns (shared by 08.1 and 08.2)

Table	Column	Type	Constraints	Description
`ApplicationSettings`	`Id`	int	PK, Identity	Row id
`ApplicationSettings`	`Key`	string(128)	Not Null, Unique	e.g. `Application.Timezone`, `Reminder.Enabled`
`ApplicationSettings`	`Value`	string(1024)	Not Null	Invariant-culture string value
`ApplicationSettings`	`Category`	string(64)	Not Null	`Application`, `Reminder` or `Notification`
`ApplicationSettings`	`UpdatedByUserId`	int?	– (no FK)	Last editor

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Table	Column	Type	Constraints	Description
`ApplicationSettings`	`UpdatedAt`	DateTime	Not Null	UTC

Seed data (shared): `SettingsInitializer` inserts missing setting rows at every start and never overwrites existing ones. The role and AI seeders are described in 08.3 and 08.4.

Columns of the other tables, relationships and triggers are in the owning child document.

7. Security & Authorization

- **Authentication:** JWT bearer token + refresh token cookie.
- **Authorization:** `[RequirePermission(key)]` maps to the policy `perm:{key}` (`PermissionPolicy`). Permission claims are refreshed from the database on each request by `SessionValidation`, so role changes apply to the next call. Refused policies are logged by `DeniedActionAuditHandler`.
- **Data scope:** None. Every setting is organization-wide. Role listing is narrowed to the caller's own role without `roles.view.all` (see 08.3).
- **Frontend:** `permissionGuard` on each route and `buildNavigation()` for the menu. In-component checks are described in each child document.

Permission Key(s)	Child	Endpoint group
(signed in), `settings.application.manage`	08.1	`/api/v1/settings/application`
`settings.reminders.manage`	08.2	`/api/v1/settings/reminders`
`roles.manage`, `roles.view.all`, `roles.modify.access`, `roles.administrator.assign`	08.3	`/api/v1/roles*`, `/api/v1/permissions*`
`settings.ai.view`, `settings.ai.edit`, `settings.ai.test`, `settings.ai.model.remove`, `settings.ai.manage` (legacy)	08.4	`/api/v1/assistant/providers/*`

8. Validations & Error Handling

Shared rules that apply to every child. Child-specific rules are in each child document.

Rule	Layer	HTTP Code	Error Message
No permission	Policy	403	Forbidden
User id claim missing on PUT	Controllers	401	–
Concurrent update	`GlobalExceptionHandler`	409	Someone else changed this record while you were saving. Reload it and try again.
Unhandled	`GlobalExceptionHandler`	500	Something went wrong. Please try again.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

Errors are returned by `GlobalExceptionHandler` as `application/problem+json`. `AppException` subclasses (`RoleException`, `RequestValidationException`, `NotFoundException`, `ConflictException`) keep their status and message. `RequestValidationException` becomes a `ValidationProblemDetails` with an `errors` map. The Angular screens show `apiErrorMessage()`, and the Application and Reminder screens map `errors` keys onto form controls.

9. Integrations / Side Effects

- **Activity Log:** No activity or audit row is written for settings or role changes. Only `UpdatedByUserId` and `UpdatedAt` are stored on each setting and provider row. Denied requests are logged by `DeniedActionAuditHandler`.
- **Notifications / Reminders / Mail:** see 08.1 (in-app switch) and 08.2 (reminder engine, Mail copies).
- **Sessions:** see 08.3 (role permission change signs holders out).
- **AI Assistant:** see 08.4 (provider runtime, model selector); the brand name comes from 08.1.
- **Assistant knowledge pages:** `Services/Assistant/Knowledge/application-settings.md` (08.1), `reminder-settings.md` (08.2), `change-role.md` (08.3), `tfa-settings.md` (08.4).

10. Configuration

Key (`appsettings.json`)	Purpose	Default
`Storage:Root`	Root folder for the database, key ring and attachments	`""`
`ConnectionStrings:Default`	SQLite database	`<secret>`

Child-specific keys: `Application:Timezone` (08.1, also the 08.2 fallback), `Reminders:SchedulerEnabled` / `Reminders:TickSeconds` (08.2), `AiProviders:KeyRingPath` / `AiProviders:TimeoutSeconds` (08.4). The runtime-editable keys of the `ApplicationSettings` table are listed in 08.1 and 08.2.

11. Testing

Shared tests. Child-specific tests are listed in each child document.

Test Type	File / Location	Covers
Unit	`tests/TaskFlow.UnitTests/Persistence/SettingsInitializerTests.cs`	Missing setting rows inserted (08.1 and 08.2)
Unit (support)	`tests/TaskFlow.UnitTests/TestSupport/SettingsTestDatabase.cs`	Test database helper (by name)
Integration	`tests/TaskFlow.IntegrationTests/Common/PermissionAuthorizationTests.cs`, `ModuleBasedPermissionEndpointsTests.cs`	Policies per key

> Test paths are taken from `tests-filelist.json` (stored with backslashes, shown here with `/`). Test contents were not read.

© 2026 Jojo George. All rights reserved. · jojogeorge3344@gmail.com

12. Known Limitations / Future Enhancements

- Settings and role changes are not written to an audit or activity log. Only the last editor and time are kept per setting row.
- There is no "Reset to defaults" action for Application or Reminder Settings. Defaults only apply when a row is missing.

Gaps found (module-wide)

- **BRD Screen 20 FR-6 "Record significant configuration changes"** is not implemented beyond `UpdatedByUserId` / `UpdatedAt`. No history table or activity entry exists.
- **Stale file names:** the permission inventory still refers to the old file names `SettingsController.cs`, `AssistantController.cs` and `features/settings/*`.
- **.NET version:** confirmed as `net10.0` in `TaskFlow.Api.csproj`.

Child-specific gaps are listed in each child document.

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.