
Change Password – Technical Documentation

> **Project:** TaskFlow – Intelligent Task Allocation & Tracking System **Parent Module:** Profile · **Child Module:** 07.2 Change Password **Version:** 1.0 · **Last Updated:** 31-Oct-2026 **Backend:** ASP.NET Core Web API (.NET 10) · **Frontend:** Angular · **Database:** SQLite (EF Core) **Author:** Jojo George (jojogeorge3344@gmail.com) © 2026 Jojo George. All rights reserved.

1. Technical Overview

Change Password is a single endpoint, `POST /api/v1/users/me/password` on `ProfileController`, plus the Angular `ChangePasswordComponent`. The caller's identity is proved by an MFA step-up (authenticator or backup code) through the Auth module's `IMfaService`, not by the current password. On success the password hash is replaced, `Users.SecurityStamp` is rotated and every active refresh token is revoked, so the user is signed out everywhere. The controller has only `[Authorize]`; the catalog key `profile.password.change` is always on and not enforced. The TFA tool `ExplainPasswordChangeTool` gives fixed guidance only.

2. Architecture Flow



3. Backend File Structure

Layer	Path	Files
Controller	`TaskFlow.Api/Controllers/Profile/`	`ProfileController.cs` (`ChangePassword`)
Service	`TaskFlow.Api/Services/Profile/`	`IProfileService.cs`, `ProfileService.cs` (`ChangePasswordAsync`)
Service (reused)	`TaskFlow.Api/Services/Auth/Mfa/`	`IMfaService.cs`, `MfaService.cs` (`RequireCodeAsync`, `VerifyAsync`)
Repository (reused)	`TaskFlow.Api/Repositories/Management/EmployeeManagement/Employees/`	`IEmployeeRepository.cs`, `EmployeeRepository.cs`
Repository (reused)	`TaskFlow.Api/Repositories/Auth/RefreshTokens/`	`IRefreshTokenRepository.cs`, `RefreshTokenRepository.cs`
Repository (reused, via `MfaService`)	`TaskFlow.Api/Repositories/Auth/Accounts/`, `TaskFlow.Api/Repositories/Auth/Mfa/`	`IAccountRepository.cs`, `AccountRepository.cs`, `IMfaBackupCodeRepository.cs`, `MfaBackupCodeRepository.cs`
DTOs	`TaskFlow.Api/Dtos/Profile/`	`ProfileRequests.cs` (`ChangePasswordRequest`)
Validators	`TaskFlow.Api/Dtos/Profile/Validators/`	`UpdateOwnProfileRequestValidator.cs` (holds `ChangePasswordRequestValidator`)
Entities	`TaskFlow.Api/Models/Entities/`	`User.cs`, `RefreshToken.cs`, `MfaBackupCode.cs`

Layer	Path	Files
Security	`TaskFlow.Api/Common/Security/`	`PermissionKeys.cs`, `PermissionCatalog.cs` (`profile.password.change`)
Middleware / Filters	`TaskFlow.Api/Middleware/`, `TaskFlow.Api/Filters/`	`MfaSetupGateMiddleware.cs`, `SessionValidation.cs`, `GlobalExceptionHandler.cs`, `ValidationFilter.cs`
Config	`TaskFlow.Api/Config/`	`MfaOptions.cs`
Assistant (TFA)	`TaskFlow.Api/Services/Assistant/Tools/`, `Services/Assistant/Chat/`	`AssistantReadTools.cs` (`ExplainPasswordChangeTool`), `AssistantTexts.cs` (`PasswordGuidance`)

4. Frontend File Structure

Type	Path	Purpose
Routes	`src/app/modules/profile/profile.routes.ts`	`profile/change-password` → `ChangePasswordComponent` (lazy `loadComponent`)
Page component	`src/app/modules/profile/pages/change-password.component.ts` / `.html`	New and confirm password, strength meter (`passwordStrength()`), `<dialog>` that asks for the code
Models	`src/app/modules/profile/pages/change-password.model.ts`	`PasswordField`
Models (shared)	`src/app/modules/management/employee-management/models/user.model.ts`	`ChangePassword`
API service	`src/app/modules/profile/services/profile.service.ts`	`changePassword`
Route / Guard	`src/app/routes/app.routes.ts`	Child of the shell route guarded by `authGuard` and `mfaSetupGuard`. No `permissionGuard`.
Shared utils	`src/app/shared/utils/api-error.ts`; `shared/auth/login-reasons.ts`; `shared/auth/auth.service.ts` (`clearSession`)	Error text extraction, the `credentials-changed` login message, session clearing
Entry point	`src/app/modules/profile/pages/profile.component.html`	Password card → **Change password** link (see 07.1)

> ⚠️ To be confirmed: `change-password.component.ts` references `profile-shared.css` and `change-password.component.css` in `styleUrls`, but these files are not in the source snapshot.

5. API & Logic

5.1 API Endpoints

#	Method	Endpoint	Description	Permission (Policy)	Request DTO	Response DTO
1	POST	`/api/v1/users/me/password`	Change the caller's own password after an MFA step-up, then revoke all sessions	`[Authorize]` only. Catalog key `profile.password.change` (always on, not enforced). Blocked by `MfaSetupGateMiddleware` while MFA setup is pending.	`ChangePasswordRequest`	`204 No Content`, 400, 401, 404

5.2 Request / Response Samples

```
// POST /api/v1/users/me/password
{ "newPassword": "N3w-Secret!", "mfaCode": "123456" }
```

```
// 204 No Content (empty body). Every refresh token is revoked and the security stamp changes.
```

```
// 400 Bad Request (BusinessRuleException)
{ "type": "https://tools.ietf.org/html/rfc9110#section-15.5.1", "title": "Bad Request",
"status": 400,
  "detail": "The code is incorrect or has expired." }
```

5.3 Service Layer Logic

Method: `ChangePasswordAsync(int userId, ChangePasswordRequest request, CancellationToken)`


1. `ChangePasswordRequestValidator` (through `ValidationFilter`): `NewPassword` must not be empty and must be 6–128 characters (`MinPasswordLength`, `MaxPasswordLength`). `MfaCode` may be at most 32 characters.
2. `GetAsync(userId)`. A null result returns `null` (→ 404).
3. If `!current.MfaEnabled`, it throws `BusinessRuleException(MfaRequiredForPasswordMessage)` = *"Set up two-step verification before changing your password."* This is a defence in depth in case the setup gate fails.
4. `IMfaService.RequireCodeAsync(userId, request.MfaCode)`. A blank code throws `"Enter the code from your authenticator app."` The code is then checked with `VerifyAsync(allowBackupCode: true)`, which uses up the code: it advances `MfaLastUsedStep` or sets `MfaBackupCode.UsedAt`. `Invalid` throws `"The code is incorrect or has expired."` and `LockedOut` throws `"Too many wrong codes. Try again in a few minutes."` (both `BusinessRuleException` → 400).
5. Reloads the tracked user, sets `PasswordHash = IPasswordHasher<User>.HashPassword(user, NewPassword)` and `UpdatedAt = now`.
6. Sets `SecurityStamp = Guid.NewGuid().ToString("N")`. Access tokens with the old stamp now fail `SessionValidation`.
7. `IRefreshTokenRepository.GetActiveForUsersForUpdateAsync([userId])` → sets `RevokedAt = now` on each token.
8. `SaveChangesAsync`. Returns the DTO. The controller answers `204`.
9. Client: `authService.clearSession()`, then navigates to `/login?reason=credentials-changed`.

Shared lockout: `MfaOptions.MaxFailedAttempts` (5) wrong codes in a row set `MfaLockedUntil = now + LockoutMinutes` (5). The counter is shared with sign-in and the 07.3 endpoints.

5.4 Repository Layer

Method	Description	Query Notes
`IEmployeeRepository.GetDtoAsync(id)`	Reads `MfaEnabled` before the step-up	No tracking
`IEmployeeRepository.GetActiveWithRoleForUpdateAsync(id)`	Tracked user to update the hash and stamp	`Include(Role)`
`IRefreshTokenRepository.GetActiveForUsersForUpdateAsync(userIds)`	Active refresh tokens to revoke	Tracked. Query filter excludes tokens of deleted users.
`IAccountRepository.FindLiveForUpdateAsync(id)` (inside `MfaService`)	Tracked user for code verification	Defined in the Auth module
`IMfaBackupCodeRepository.FindUnusedForUpdateAsync(userId, hash)` (inside `MfaService`)	Backup code lookup	`UsedAt` is a concurrency token

5.5 Sequence Diagram



6. Database Design

Table	Column	Type	Constraints	Description
`Users`	`Id`	int	PK	User id (taken from the JWT)
`Users`	`PasswordHash`	text	Not Null	Set by password change (`IPasswordHasher<User>`)
`Users`	`SecurityStamp`	text	Not Null, Max 64	Rotated on password change, ending access tokens
`Users`	`MfaEnabledAt`	datetime	nullable	Must be set (MFA on) before a change is allowed

Table	Column	Type	Constraints	Description
`Users`	`MfaLastUsedStep`	bigint	Concurrency token	Replay protection; advanced when the TOTP code is spent
`Users`	`MfaFailedAttempts`	int	Concurrency token	Shared lockout counter
`Users`	`MfaLockedUntil`	datetime	nullable	Lockout end
`Users`	`UpdatedAt`	datetime	–	Set on save
`RefreshTokens`	`Id`, `UserId`, `TokenHash`, `ExpiresAt`, `CreatedAt`, `RevokedAt`	int / text / datetime	PK `Id`; index `TokenHash`; FK `UserId`	`RevokedAt` set for every active token on password change
`MfaBackupCodes`	`UsedAt`	datetime	Concurrency token	Set when a backup code is used as the step-up code

Relationships

- `RefreshTokens.UserId → Users.Id` (FK, Cascade)
- `MfaBackupCodes.UserId → Users.Id` (FK, Cascade)

7. Security & Authorization

- `[Authorize]` only; the id comes from `ClaimTypes.NameIdentifier` (unparseable → 401). Only the caller's own password can be changed.
- `profile.password.change` has `AlwaysGranted: true, IsAssignable: false` in `PermissionCatalog.cs` and is never checked.
- **Step-up:** an authenticator or unused backup code is required; the current password is not.
- **MFA gate:** `POST /users/me/password` is not on the `MfaSetupGateMiddleware` allow-list, so it returns 403 `mfa_setup_required` while setup is pending. The service also refuses when MFA is off.
- **Session revocation:** `SecurityStamp` rotation invalidates access tokens in `SessionValidation`; refresh tokens are revoked.
- **Code lockout:** 5 wrong codes → 5 minutes (`MfaOptions`), shared with sign-in.

Permission Key	Endpoint(s)	UI Element Controlled
`profile.password.change`	`POST /api/v1/users/me/password`	Password card, Change password screen

8. Validations & Error Handling

Rule	Layer	HTTP Code	Error Message
`NewPassword` empty, shorter than 6 or longer than 128	`ChangePasswordRequestValidator`	400	FluentValidation default
`MfaCode` longer than 32	Validator	400	FluentValidation default
MFA off on password change	Service	400	Set up two-step verification before changing your password.
Code missing	`MfaService.RequireCodeAsync`	400	Enter the code from your authenticator app.
Code wrong or expired	`MfaService`	400	The code is incorrect or has expired.

Rule	Layer	HTTP Code	Error Message
Code lockout	`MfaService`	400	Too many wrong codes. Try again in a few minutes.
MFA setup pending	`MfaSetupGateMiddleware`	403 (`code: mfa_setup_required`)	Set up two-step verification to continue.
User not found or deleted	Controller	404	– (empty `NotFound()`)

Client-side messages: `Required.`, `Password must be at least 6 characters.`, `Password must be at most 128 characters.`, `Passwords do not match.`, `Enter the code from your authenticator app.`, `That code did not work. Try the new code from your app.`, `Could not change your password.`. Login reason `credentials-changed`: `Your username or password was changed. Sign in again with your new details.` `ChangePasswordComponent` maps 400 `errors` keys onto its form controls. Shared error handling is described in the parent document.

9. Integrations / Side Effects

- **Notifications / Email / Activity Log:** none.
- **Sessions:** a password change rotates `Users.SecurityStamp` and revokes all `RefreshTokens` rows for the user. The client clears its session.
- **AI Assistant (TFA):** `ExplainPasswordChangeTool` (`explain_password_change`) returns the fixed `AssistantTexts.PasswordGuidance` with a link to `/profile`. It never handles passwords.

10. Configuration

Key (`appsettings.json`)	Purpose	Default
`Mfa:Required`	Enforce MFA setup before any other API use. This makes the password change possible.	`true`
`Mfa:MaxFailedAttempts`	Wrong codes before lockout (code default, not in the JSON)	`5`
`Mfa:LockoutMinutes`	Lockout length (code default)	`5`
`Jwt:AccessTokenMinutes` / `Jwt:RefreshTokenDays`	Lifetimes of the sessions a password change ends	`30` / `7`

11. Testing

Test Type	File / Location	Covers
Integration	`tests/TaskFlow.IntegrationTests/Auth/Mfa/MfaStepUpEndpointsTests.cs`	Step-up code (e.g. password change)
Integration	`tests/TaskFlow.IntegrationTests/Auth/Mfa/MfaSetupGateEndpointsTests.cs`	Setup gate blocks `/users/me/password` while setup is pending
Unit	`tests/TaskFlow.UnitTests/Auth/Mfa/MfaServiceTests.cs`	`MfaService` code verification and lockout

Test Type	File / Location	Covers
Support	`tests/TaskFlow.IntegrationTests/TestSupport/MfaTestSupport.cs`, `tests/TaskFlow.UnitTests/TestSupport/AcceptingMfaService.cs`	MFA test helpers

> ⚠️ To be confirmed: only test file names were available. What each file covers is inferred from its name and folder. No Angular spec files for `modules/profile` appear in the snapshot.

12. Known Limitations / Gaps found

- No audit or activity entry is written for password changes.
- The password policy is length-only (6–128). The strength meter is a client-side hint.
- Possible enhancement: notifying the user (in-app or by email) after a password change.
- **BRD vs code – current password:** BRD 19 FR5 says "Require the current password when appropriate". The code deliberately does not ask for it. `ChangePasswordRequest` has no current-password field, and the authenticator code is the proof. The route is `POST /api/v1/users/me/password`.
- **Assistant text vs code:** `AssistantTexts.PasswordGuidance` tells users the Change password form asks for the "current password, new password, confirm". The form has no current-password field and asks for an authenticator code instead.
- **BRD vs UI layout:** the BRD lists a "Change password form" on the profile screen. The code puts it on a separate route, `/profile/change-password`.
- **No bypass through employee edit:** `UpdateUserRequest.Password` is ignored and `EmployeeService.UpdateAsync` never sets a password, so the authenticator-gated Profile flow is the only self-service way to change a password.
- **Strength meter bug:** `passwordStrength()` tests `/d/` (the letter "d") instead of `/\d/` (a digit), so the digit-plus-symbol point is awarded wrongly.
- Lockout returns 400 here but 429 from `mfa/check` (see parent).

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.