Low-Level Design – Reminder Settings

TaskFlow – Intelligent Task Allocation & Tracking System

> **Document:** Low-Level Design · **Version:** 1.0 · **Status:** Draft **Project type:** Personal Project (Skill Development) · **Date:** 31-Oct-2026 **Author:** Jojo George (jojogeorge3344@gmail.com) **Based on:** HLD-Reminder-Settings v1.0, FRD-Reminder-Settings v1.0 **Module:** Settings · **Sub-module:** 06.1 Reminder Settings · **Code:** REM © 2026 Jojo George. All rights reserved.

Document Control

Version	Date	Author	Summary of changes
1.0	31-Oct-2026	Jojo George	Initial version

Related documents: BRD · FRD · HLD · TDD · Specs

Document	Location
BRD – Reminder Settings	`../../../BRD/06-Settings/06.1-Reminder-Settings/BRD-Reminder-Settings.md`
FRD – Reminder Settings (FR-REM-01…23, UC-REM-01…03)	`../../../FRD/06-Settings/06.1-Reminder-Settings/FRD-Reminder-Settings.md`
HLD – Reminder Settings	`../../../HLD/06-Settings/06.1-Reminder-Settings/HLD-Reminder-Settings.md`
Overall LLD (stack, cross-cutting design, Auth)	`../../00-Overall/LLD-TaskFlow-Overall.md`
LLD – Application Settings (shares the `ApplicationSettings` table and repository)	`../06.2-Application-Settings/LLD-Application-Settings.md`
LLD – Notification (reminder engine that consumes these values)	`../../04-Communication/04.2-Notification/LLD-Notification.md`
LLD – Task Management (Create Task, which uses the defaults)	`../../02-TaskFlow-Monitoring/02.1-Task-Management/LLD-Task-Management.md`
TDD v2.0	`TDD-TaskFlow.md` §7.2.6 (`ApplicationSetting`), §7.5 (timezone)

1. Introduction

1.1 Purpose

Detailed design of the Reminder Settings sub-module (original BRD Screen 13 "Deadline Reminder Settings"): the controller actions, service logic, DTOs, validator, repository methods, the rows of the `ApplicationSettings` table it owns, the Angular screen, the tests and the traceability from FR-REM-nn to code. Everything below is taken from the code as built.

1.2 Scope & Conventions

- Covered: `ReminderSettingsController` (2 actions), `ReminderSettingsService`, `UpdateReminderSettingsRequestValidator`, the shared `ApplicationSettingsRepository`, the six reminder/notification setting rows, and the Angular `ReminderSettingsComponent` with its API service.
- Not covered here (only referenced): the reminder engine `ReminderService` / `ReminderSchedulerService` (Notification LLD), Create Task (Task Management LLD), the timezone and in-app switch (Application Settings LLD).
- Naming: `*Controller`, `I*Service` / `*Service`, `I*Repository` / `*Repository`, DTOs `*Dto` / `*Request`, validators `*RequestValidator`.
- API base path `/api/v1`; JSON camelCase; enums serialised as strings (`JsonStringEnumConverter`); errors as ProblemDetails (`application/problem+json`).

---

2. Code Structure

2.1 Backend Folder Layout

```
TaskFlow.Api/
  Controllers/Settings/ReminderSettingsController.cs
  Services/Settings/ReminderSettings/IReminderSettingsService.cs, ReminderSettingsService.cs
  Repositories/Settings/ApplicationSettings/IApplicationSettingsRepository.cs,
ApplicationSettingsRepository.cs  (shared with APP)
  Dtos/Settings/ReminderSettings/ReminderSettingsDtos.cs
  Dtos/Settings/ReminderSettings/Validators/UpdateReminderSettingsRequestValidator.cs
  Models/Entities/ApplicationSetting.cs, Models/Enums/ReminderFrequency.cs
  Common/Constants/SettingKeys.cs, Common/Utils/SettingValues.cs
  Config/ApplicationOptions.cs
  Persistence/Seeders/SettingsInitializer.cs
```

2.2 Frontend Folder Layout

```
src/app/modules/settings/
  settings.routes.ts                                (route settings/reminders)
  models/settings.model.ts                          (ReminderSettings,
UpdateReminderSettings)
  reminder-settings/pages/reminder-settings.component.{ts,html,css}
  reminder-settings/pages/reminder-settings.model.ts   (SettingsField)
  reminder-settings/services/reminder-settings.service.ts
src/app/shared/utils/reminder-options.ts            (shared with Create Task)
src/app/layouts/nav-items.ts, src/app/shared/auth/auth.guard.ts
```

2.3 Layer Rules

Rule	Enforced by
Controller → Service → Repository only, through interfaces	`ArchitectureTests`
Repositories never save; the service commits through `IUnitOfWork`	`ArchitectureTests`

Rule	Enforced by
Controllers do not validate; FluentValidation runs in `ValidationFilter`	`ArchitectureTests`, global filter
Page component in `pages/`, API service in the module whose endpoint it calls	`npm run check:structure`

---

3. Cross-Cutting Design

Shared mechanisms are described once in the overall LLD (`../../00-Overall/LLD-TaskFlow-Overall.md`). What applies here:

Concern	Design
Validation	`UpdateReminderSettingsRequestValidator` runs in the global `ValidationFilter` before the action; failure → 400 `ValidationProblemDetails` with an `errors` map keyed by property name
Error handling	`GlobalExceptionHandler` (see 3.1)
Transactions	One `IUnitOfWork.SaveChangesAsync` per save; all six rows are written in one SaveChanges (one SQLite transaction)
Authorization	Class-level `[RequirePermission(PermissionKeys.SettingsReminders)]` → policy `perm:settings.reminders.manage`; permission claims refreshed per request by `SessionValidation`; refusals logged by `DeniedActionAuditHandler`
Logging	No sub-module-specific logging; unhandled faults logged by `GlobalExceptionHandler`
Time & time zone	`UpdatedAt` stored in UTC from `TimeProvider`; the application timezone is read-only here (owned by APP)

3.1 Exception → HTTP Status

Exception	Status	When
Validation failure (`ValidationFilter`)	400	A field missing, out of range, or second reminder not less than first
Policy failure	403	Caller lacks `settings.reminders.manage`
– (`Unauthorized()` in the action)	401	PUT without a numeric `NameIdentifier` claim
`ConcurrencyConflictException` / `DbUpdateConcurrencyException`	409	Concurrent save race reported by EF Core
`UniqueConstraintException`	409	Two first-time inserts of the same key race (index `IX_ApplicationSettings_Key`)
`ArgumentException` ("Every reminder setting must be provided.")	500	Only reachable if the validator is bypassed; not an `AppException`, so it becomes the generic 500

---

4. Module Designs

4.1 Module: Settings


4.1.1 Child module: Reminder Settings (REM)

Class / file inventory

Layer	Type	File	Responsibility
Controller	`ReminderSettingsController`	`Controllers/Settings/ReminderSettingsController.cs`	Routes `GET` / `PUT` `/api/v1/settings/reminders`; class-level permission; resolves `userId`
Service	`IReminderSettingsService` / `ReminderSettingsService`	`Services/Settings/ReminderSettings/`	Typed view over the six setting rows; defaults; upsert
Repository	`IApplicationSettingsRepository` / `ApplicationSettingsRepository`	`Repositories/Settings/ApplicationSettings/`	Key/value reads and tracked rows (shared with APP)
Base	`BaseRepository<ApplicationSetting>`, `IUnitOfWork` / `UnitOfWork`	`Repositories/Base/`	`Add`, save and conflict mapping
DTOs	`ReminderSettingsDto`, `UpdateReminderSettingsRequest`	`Dtos/Settings/ReminderSettings/ReminderSettingsDtos.cs`	Contracts
Validator	`UpdateReminderSettingsRequestValidator`	`Dtos/Settings/ReminderSettings/Validators/`	Input rules (`MaxIntervalDays = 30`)
Entity	`ApplicationSetting`	`Models/Entities/ApplicationSetting.cs`	Key/value row
Enum	`ReminderFrequency`	`Models/Enums/ReminderFrequency.cs`	`Daily`, `Weekly`
Constants	`SettingKeys`, `SettingValues`	`Common/Constants/SettingKeys.cs`, `Common/Utils/SettingValues.cs`	Key names, categories, defaults; invariant formatting (`"true"` / `"false"`, ints)
Options	`ApplicationOptions`	`Config/ApplicationOptions.cs`	Timezone fallback (`Application:Timezone`, code default `UTC`)
Seeder	`SettingsInitializer`	`Persistence/Seeders/SettingsInitializer.cs`	Inserts missing rows at start-up
Frontend page	`ReminderSettingsComponent`	`modules/settings/reminder-settings/pages/reminder-settings.component.ts`	Screen, reactive form, `firstBeforeSecond` group validator
Frontend service	`ReminderSettingsService` (Angular)	`modules/settings/reminder-settings/services/reminder-settings.service.ts`	`get()`, `save()`

Layer	Type	File	Responsibility
Frontend models	`ReminderSettings`, `UpdateReminderSettings`, `SettingsField`	`modules/settings/models/settings.model.ts`, `reminder-settings/pages/reminder-settings.model.ts`	Types
Frontend utils	`FIRST_REMINDER_OPTIONS`, `SECOND_REMINDER_OPTIONS`, `OVERDUE_FREQUENCY_OPTIONS`, `withReminderDay()`	`shared/utils/reminder-options.ts`	Fixed choices (shared with Create Task)
Route / guard / menu	`SETTINGS_ROUTES`, `permissionGuard`, `buildNavigation()`	`settings.routes.ts`, `shared/auth/auth.guard.ts`, `layouts/nav-items.ts`	Access to `/settings/reminders`

Class diagram



API contracts

Controller `ReminderSettingsController`, `[Route("api/v1/settings")]`, class-level `[RequirePermission(PermissionKeys.SettingsReminders)]`. Endpoints of this sub-module (facts.md §3): **2**.

#	Method	Route	Permission / policy	Request	Response	Status codes
1	GET	`/api/v1/settings/reminders`	`settings.reminders.manage` (class)	–	`ReminderSettingsDto`	200, 401, 403
2	PUT	`/api/v1/settings/reminders`	`settings.reminders.manage` (class)	`UpdateReminderSettingsRequest`	`ReminderSettingsDto`	200, 400, 401, 403, 409

`GET /api/v1/settings/reminders` is also called by Create Task (`task-create.component.ts`, `loadReminderDefaults()`) to pre-fill the reminder fields; for a caller without `settings.reminders.manage` it returns 403, the form shows a hint and sends the fields as `null`, and `TaskService` applies the stored defaults on the server (FR-REM-16).

DTOs

DTO	Field	Type	Notes
`ReminderSettingsDto`	`Enabled`	`bool`	`Reminder.Enabled`
	`DeadlineDayEnabled`	`bool`	`Reminder.DeadlineDayEnabled`

DTO	Field	Type	Notes
	`DefaultFirstDays`	`int`	`Reminder.DefaultFirstDays`
	`DefaultSecondDays`	`int`	`Reminder.DefaultSecondDays` (0 = deadline day)
	`DefaultOverdueFrequency`	`ReminderFrequency`	`Reminder.DefaultOverdueFrequency`
	`MailEnabled`	`bool`	`Notification.MailEnabled`
	`Timezone`	`string`	`Application.Timezone`, read-only here
`UpdateReminderSettingsRequest`	`Enabled`, `DeadlineDayEnabled`, `MailEnabled`	`bool?`	Nullable only so that an omitted field is a validation error
	`DefaultFirstDays`, `DefaultSecondDays`	`int?`	
	`DefaultOverdueFrequency`	`ReminderFrequency?`	
	(no timezone field)	–	The timezone can never be changed here (FR-REM-11)

Request / response example

```
// PUT /api/v1/settings/reminders
{ "enabled": true, "deadlineDayEnabled": true, "defaultFirstDays": 3, "defaultSecondDays": 1,
"defaultOverdueFrequency": "Weekly", "mailEnabled": true }
```

```
// 200 OK
{ "enabled": true, "deadlineDayEnabled": true, "defaultFirstDays": 3, "defaultSecondDays": 1,
"defaultOverdueFrequency": "Weekly", "mailEnabled": true, "timezone": "Asia/Kolkata" }
```

```
// 400 Bad Request (first not earlier than second)
{ "title": "One or more validation errors occurred.", "status": 400, "errors": {
"DefaultSecondDays": ["The first reminder must come earlier than the second reminder."] } }
```


Service logic – `ReminderSettingsService.GetAsync`

1. `GetValuesAsync(ReminderKeys)` reads the seven keys `Application.Timezone`, `Reminder.Enabled`, `Reminder.DeadlineDayEnabled`, `Reminder.DefaultFirstDays`, `Reminder.DefaultSecondDays`, `Reminder.DefaultOverdueFrequency`, `Notification.MailEnabled` (no tracking).
2. Each value is parsed; a missing or unparsable value falls back to its `SettingKeys` default: `ReadBool` → `DefaultReminderEnabled` (true), `DefaultDeadlineDayEnabled` (true), `DefaultMailEnabled` (true); `ReadInt` (invariant culture) → `DefaultFirstDays` (2), `DefaultSecondDays` (1); `ReadFrequency` (`Enum.TryParse`, ignore case, `Enum.IsDefined`) → `DefaultOverdueFrequency` ("Daily").
3. Timezone: the stored value when not blank, otherwise `ApplicationOptions.Timezone`.
4. Returns `ReminderSettingsDto`.


Service logic – `ReminderSettingsService.UpdateAsync(userId, request)`

1. The validator has already run in `ValidationFilter` (400 on failure).
2. Defensive check: any null field → `ArgumentException("Every reminder setting must be provided.")` (FR-REM-14).
3. `GetForUpdateAsync(ReminderKeys)` loads the tracked rows; `now = TimeProvider.GetUtcNow().UtcDateTime`.
4. Local `Set(key, value, category)`: creates a missing row (`new ApplicationSetting { Key, Category }` + `Add`), then sets `Value`, `UpdatedByUserId = userId`, `UpdatedAt = now` (FR-REM-19).
5. Writes five keys in category `Reminder` (`SettingValues.Format` for bool/int, `ToString()` for the enum) and `Notification.MailEnabled` in category `Notification`. `Application.Timezone` is never written.
6. `IUnitOfWork.SaveChangesAsync` (one transaction), then returns `GetAsync()`.

Sequence diagram – save



Sequence diagram – consumers (read path)



Repository methods (`ApplicationSettingsRepository : BaseRepository<ApplicationSetting>`)

Method	Query / purpose	Notes
`GetValuesAsync(keys)`	`Set.AsNoTracking().Where(keys.Contains(Key)).ToDictionaryAsync(Key, Value)`	Keys without a row are absent; uses `IX_ApplicationSettings_Key`
`GetValueAsync(key)`	One value or null, projection	Used by `AppClock` / `NotificationPublisher` (APP), not by this service
`GetForUpdateAsync(keys)`	Tracked rows, `ToDictionaryAsync(Key)`	For the upsert

Method	Query / purpose	Notes
`Add(entity)` (base)	Stages a new row	From `BaseRepository`

Validation rules (`UpdateReminderSettingsRequestValidator`)

Field	Rule	Message
`Enabled`	`NotNull()`	FluentValidation default (`'Enabled' must not be empty.`)
`DeadlineDayEnabled`	`NotNull()`	FluentValidation default
`MailEnabled`	`NotNull()`	FluentValidation default
`DefaultFirstDays`	`NotNull()` , `InclusiveBetween(1, 30)`	FluentValidation default
`DefaultSecondDays`	`NotNull()` , `InclusiveBetween(0, 30)`	FluentValidation default
`DefaultSecondDays`	`LessThan(DefaultFirstDays)` when first is 1–30 and second is not null	"The first reminder must come earlier than the second reminder."
`DefaultOverdueFrequency`	`NotNull()` , `IsInEnum()`	FluentValidation default

Client mirror: `firstBeforeSecond` group validator (`Number(first) > Number(second)`) shows the same text under **Second reminder**; server `errors` keys (PascalCase) are mapped onto the camelCase controls by `applyServerErrors()` .

> ⚠️ To be confirmed: the exact wording of the FluentValidation default messages as returned at run time (not overridden in code).

Error cases

Case	Exception / result	Status
Caller lacks `settings.reminders.manage`	Policy refusal (logged by `DeniedActionAuditHandler`)	403
No numeric user id claim on PUT	`Unauthorized()`	401
Field missing / out of range / ordering	`ValidationFilter`	400
Validator bypassed with a null field	`ArgumentException`	500
Concurrent first insert of a key	`UniqueConstraintException`	409
Concurrency race	`ConcurrencyConflictException`	409

Frontend design – `ReminderSettingsComponent`

Member	Behaviour
`form`	`FormGroup` with `enabled` , `deadlineDayEnabled` , `defaultFirstDays` (2), `defaultSecondDays` (1), `defaultOverdueFrequency` ('Daily'), `mailEnabled` ; group validator `firstBeforeSecond`
`load()`	`loading` → `ReminderSettingsService.get()` ; on error `loadError` = `apiErrorMessage(err, 'Could not load the reminder settings.')` (error card with **Retry**)
`apply(settings)`	Sets `firstReminderOptions` / `secondReminderOptions` through `withReminderDay()` (adds a stored value outside the fixed list, FR-REM-23), sets `timezone` , `form.reset(...)`


Member	Behaviour
`fieldError(name)`	Server message first, else the client ordering message for `defaultSecondDays`
`save()`	Refuses when invalid or saving; sends the six values; on success `apply`, `savedAt`, toast "Reminder settings saved"; on error `applyServerErrors` and `saveError` = "Could not save the reminder settings."
constructor	`valueChanges` clears `savedAt` (the **Saved** tick goes stale on edit)

State machine: *Not applicable for this sub-module.* (Settings rows have no lifecycle states.)

---

5. Database Design

5.1 ER Diagram



5.2 Tables

`ApplicationSettings` (ApplicationSetting) – shared with Application Settings

Column	Type	Null	Key / index	Default	Description
Id	int (INTEGER)	No	PK	identity	Row id
Key	string(128) (TEXT)	No	Unique `IX_ApplicationSettings_Key`	–	Setting key (`SettingKeys`)
Value	string(1024) (TEXT)	No	–	–	Invariant-culture string (`"true"` / `"false"` , integer, enum name)

Column	Type	Null	Key / index	Default	Description
Category	string(64) (TEXT)	No	–	–	`Reminder` or `Notification` for this sub-module
UpdatedByUserId	int? (INTEGER)	Yes	– (no FK)	null	Last editor
UpdatedAt	DateTime (TEXT)	No	–	–	UTC time of the last write

Rows owned by this sub-module:

Key	Category	Seed default	Read by
`Reminder.Enabled`	Reminder	`true`	`ReminderService` (skip run when false)
`Reminder.DeadlineDayEnabled`	Reminder	`true`	`ReminderService` → `ReminderCalculator.DueReminders`
`Reminder.DefaultFirstDays`	Reminder	`2`	`TaskService` (create), Create Task screen
`Reminder.DefaultSecondDays`	Reminder	`1`	`TaskService` (create), Create Task screen
`Reminder.DefaultOverdueFrequency`	Reminder	`Daily`	`TaskService` (create), Create Task screen
`Notification.MailEnabled`	Notification	`true`	`ReminderService` (Mail copy of each reminder)
`Application.Timezone` (read only)	Application	owned by APP	Shown read-only

The per-task columns `Tasks.FirstReminderDays`, `SecondReminderDays`, `OverdueReminderFrequency` belong to Task Management (migration `20261013104629_AddTaskReminderSettings`); this sub-module only supplies their defaults.

5.3 Indexes, Constraints & Triggers

Object	Definition	Purpose
`IX_ApplicationSettings_Key`	Unique (`Key`)	One row per key; key lookups
PK `Id`	Identity	Row id
–	No FK on `UpdatedByUserId`, no triggers, no concurrency token	Last writer wins

5.4 Enumerations

Enum	Values	Stored as
`ReminderFrequency`	`Daily`, `Weekly`	Enum name in `ApplicationSettings.Value`; JSON string

5.5 Migrations

Migration	Change
`20261013104629_AddTaskReminderSettings`	Per-task reminder columns on `Tasks` (Task Management)
`20261017062735_AddReminderEngine`	Creates the `ApplicationSettings` table and `IX_ApplicationSettings_Key`
`20261017090431_AddInternalMail`	Deletes the old `Email.%` keys and `Notification.EmailEnabled` (SMTP superseded by internal Mail)

---

6. Algorithms & Background Jobs

Job / algorithm	Trigger / schedule	Steps	Idempotency
`SettingsInitializer.InitializeAsync`	Every start-up, after `MigrateAsync` (`Program.cs`)	Reads existing keys; inserts each missing default row (`UpdatedAt = now`, `UpdatedByUserId` null)	Never overwrites an existing row (FR-REM-15)
Default fallback (`ReadBool` / `ReadInt` / `ReadFrequency`)	Every `GetAsync`	Missing or unparsable value → `SettingKeys` default	Pure function
Consumer: `ReminderSchedulerService` → `ReminderService.GenerateDueAsync`	Every `Reminders:TickSeconds` (60 s) when `Reminders:SchedulerEnabled`	Reads `GetAsync()` each run, so a save applies from the next run without restart (FR-REM-18); detailed in the Notification LLD	De-duplication in the Notification sub-module

---

7. Security Design (detailed)

Item	Implementation
Permission checks	Class-level `[RequirePermission(PermissionKeys.SettingsReminders)]`, policy `perm:settings.reminders.manage` = `RequireClaim("permission", key)`; both GET and PUT need it (FR-REM-22)
Claims freshness	`SessionValidation` replaces permission claims from the database on every request
Frontend	`permissionGuard` with `Permissions.SettingsReminders` on `settings/reminders` (redirect to the user's dashboard); menu item only when held (FR-REM-21)
Defaults	`settings.reminders.manage`: Administrator granted (re-granted on every start), Manager granted on first seed, Employee denied, custom roles configurable
Secrets	None; all values are non-secret
Audit	Denied requests logged; saves keep only `UpdatedByUserId` / `UpdatedAt`

---

8. Configuration

Key	Default	Purpose
`Application:Timezone`	`Asia/Kolkata` (code default `UTC`)	Fallback for the read-only timezone while `Application.Timezone` is missing
`Reminders:SchedulerEnabled`	`true`	Reminder engine that consumes these settings (Notification)
`Reminders:TickSeconds`	`60`	Interval of the reminder run
`ConnectionStrings:Default`	`Data Source=taskflow.db`	SQLite database

Runtime-editable keys: see 5.2.

9. Testing Design

"Covers" was checked against the test sources. Backend paths are relative to `backend/tests`; frontend paths to `frontend/src/app/modules/settings/reminder-settings`.

Area	Test class / file	Type	Covers
Service	`TaskFlow.UnitTests/Settings/ReminderSettings/ReminderSettingsServiceTests.cs`	Unit	Fresh-database defaults, missing / unreadable rows fall back to defaults and configured timezone, save round trip, who / when recorded, timezone unchanged
Validator	`TaskFlow.UnitTests/Settings/ReminderSettings/ReminderSettingsValidatorTests.cs`	Unit	Defaults valid, second interval 0 valid, first / second out of range, second not before first, unknown overdue frequency, missing fields and intervals invalid
Endpoints	`TaskFlow.IntegrationTests/Settings/ReminderSettings/SettingsEndpointsTests.cs`	Integration	GET for Manager and Administrator, PUT saves and ignores the timezone, invalid values and missing fields 400 with nothing changed, Employee 403, 401
Seeder	`TaskFlow.UnitTests/Persistence/SettingsInitializerTests.cs`	Unit	Every default key inserted once, only missing keys added, existing values never overwritten, timezone seeded from configuration
Policies	`TaskFlow.IntegrationTests/Common/PermissionAuthorizationTests.cs`, `ModuleBasedPermissionEndpointsTests.cs`	Integration	Policy per key
Consumers	`TaskFlow.UnitTests/Communication/Notification/Reminders/ReminderServiceTests.cs`, `ReminderCalculatorTests.cs`, `TaskFlow.UnitTests/Monitoring/TaskManagement/Tasks/TaskServiceTests.cs`	Unit	Reminder switches (disabled, mail on / off, deadline-day toggle), schedule from the intervals and overdue frequency, configured defaults applied on task create
Support	`TaskFlow.UnitTests/TestSupport/SettingsTestDatabase.cs`, `FakeTimeProvider.cs`	Support	Test database, clock

Area	Test class / file	Type	Covers
Structure	`TaskFlow.UnitTests/Architecture/ArchitectureTests.cs`	Unit	Layer rules

| Frontend page | `pages/reminder-settings.component.spec.ts` | Frontend unit | Loads values with read-only timezone, shows a stored non-preset interval, saves without the timezone, hides Saved after an edit, field error linked to its select, blocks a second interval not shorter than the first, server 400 field errors, retryable load error, Mail delivery option |
| Frontend service | `services/reminder-settings.service.spec.ts` | Frontend unit | GET read; PUT of the editable fields |

---

10. Known Limitations & Open Issues

- The screen offers fixed choices (3/2/1 and 1/0 days) while the API accepts 1–30 and 0–30; other values are only displayed (`withReminderDay`).
- The settings rule is strict (`second < first`), while the per-task rule `ReminderIntervals.AreOrdered` allows equal values ("The second reminder cannot come before the first reminder."); the two rules differ.
- Create Task reads the defaults through an endpoint that needs `settings.reminders.manage`; users without it get a hint and the server applies the defaults.
- No history of earlier values and no "reset to defaults"; no concurrency token (last writer wins).
- `ReminderService` adds reminder bell notifications through `INotificationRepository` directly, not through `NotificationPublisher`, so the Application Settings switch `Notification.InAppEnabled` does not stop reminder bell notifications (consistent with FR-REM-10, but see the Application Settings LLD §10 for FR-APP-13).
- `ArgumentException` in `UpdateAsync` would surface as a generic 500 (only if the validator is bypassed).
- > ⚠️ To be confirmed: whether an outbound SMTP channel should be tied to **Also deliver reminders to Mail**; today it controls internal Mail copies only (original Screen 13 "Email notification setting").

---

11. Traceability (FRD → code)

FRD requirement	Endpoint / class	Test
FR-REM-01	`GET /api/v1/settings/reminders` · `ReminderSettingsService.GetAsync` · `ReminderSettingsComponent.load`	`SettingsEndpointsTests`, `ReminderSettingsServiceTests`
FR-REM-02	`ReminderSettingsComponent.load` (`loading`, `loadError`, Retry)	`reminder-settings.component.spec.ts`
FR-REM-03	`PUT /api/v1/settings/reminders` · `UpdateAsync` (`Reminder.Enabled`)	`ReminderSettingsServiceTests`
FR-REM-04	`ReminderService.GenerateDueAsync` (returns 0 when `Enabled` false)	`ReminderServiceTests`
FR-REM-05	`UpdateAsync` (`Reminder.DeadlineDayEnabled`) · `ReminderCalculator.DueReminders`	`ReminderCalculatorTests`

FRD requirement	Endpoint / class	Test
FR-REM-06	`FIRST_REMINDER_OPTIONS` · `UpdateAsync` (`Reminder.DefaultFirstDays`)	`ReminderSettingsServiceTests`
FR-REM-07	`SECOND_REMINDER_OPTIONS` · `UpdateAsync` (`Reminder.DefaultSecondDays`)	`ReminderSettingsServiceTests`
FR-REM-08	`OVERDUE_FREQUENCY_OPTIONS` · `ReminderFrequency` · `Reminder.DefaultOverdueFrequency`	`ReminderSettingsServiceTests`
FR-REM-09	`UpdateAsync` (`Notification.MailEnabled`) · `ReminderService` `BuildMail` when `MailEnabled`	`ReminderServiceTests`
FR-REM-10	`ReminderService.TryDeliverAsync` (adds the `Notification` row for every recipient; Mail copy only when `mail` is set)	`ReminderServiceTests`
FR-REM-11	`ReminderSettingsDto.Timezone`; no timezone in `UpdateReminderSettingsRequest`	`ReminderSettingsServiceTests`
FR-REM-12	`firstBeforeSecond` · `fieldError` · validator `LessThan` rule	`ReminderSettingsValidatorTests`
FR-REM-13	`UpdateReminderSettingsRequestValidator` (ranges, enum)	`ReminderSettingsValidatorTests`, `SettingsEndpointsTests`
FR-REM-14	Validator `NotNull` rules · `ArgumentException` guard	`ReminderSettingsValidatorTests`
FR-REM-15	`SettingsInitializer` · `ReadBool` / `ReadInt` / `ReadFrequency` defaults	`SettingsInitializerTests`, `ReminderSettingsServiceTests`
FR-REM-16	`TaskService` create (defaults when null) · `task-create.component.ts` `loadReminderDefaults`	`TaskServiceTests`
FR-REM-17	Defaults copied once into `Tasks` columns; never rewritten	`TaskServiceTests`
FR-REM-18	`ReminderService` reads `GetAsync()` on every run	`ReminderServiceTests`
FR-REM-19	`Set()` writes `UpdatedByUserId`, `UpdatedAt`	`ReminderSettingsServiceTests`
FR-REM-20	`ReminderSettingsComponent.save` (toast, `savedAt`, `saveError`)	`reminder-settings.component.spec.ts`
FR-REM-21	`permissionGuard` (`settings/reminders`) · `buildNavigation()`	`app.routes.spec.ts`, `nav-items.spec.ts`
FR-REM-22	`[RequirePermission(PermissionKeys.SettingsReminders)]` on the controller	`SettingsEndpointsTests`, `PermissionAuthorizationTests`
FR-REM-23	`withReminderDay()` in `ReminderSettingsComponent.apply`	`reminder-settings.component.spec.ts`

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.