
User Profile – Technical Documentation

> **Project:** TaskFlow – Intelligent Task Allocation & Tracking System **Parent Module:** Profile · **Child Module:** 07.1 User Profile **Version:** 1.0 · **Last Updated:** 31-Oct-2026 **Backend:** ASP.NET Core Web API (.NET 10) · **Frontend:** Angular · **Database:** SQLite (EF Core) **Author:** Jojo George (jojogeorge3344@gmail.com) © 2026 Jojo George. All rights reserved.

1. Technical Overview

User Profile is the read and update API for the caller's own account, plus the Angular **My Profile** page. `ProfileController` (`api/v1/users/me`) exposes `GET` and `PUT`. The user id is always taken from the JWT `ClaimTypes.NameIdentifier` claim. The controller has only `[Authorize]`; the catalog keys `profile.view` and `profile.edit` are always on and not enforced. `ProfileService` reuses `IEmployeeRepository` (Management) and `IUnitOfWork`, and applies `EmailPolicy` and `MobileNumberPolicy`. The same `PUT` is also called by step 1 of the Auth module's Security Setup screen and, after confirmation, by the TaskFlow Assistant (TFA).

2. Architecture Flow



3. Backend File Structure

Layer	Path	Files
Controller	`TaskFlow.Api/Controllers/Profile/`	`ProfileController.cs` (`Get`, `Update`)
Service	`TaskFlow.Api/Services/Profile/`	`IProfileService.cs`, `ProfileService.cs` (`GetAsync`, `UpdateAsync`)
Repository (reused)	`TaskFlow.Api/Repositories/Management/EmployeeManagement/Employees/`	`IEmployeeRepository.cs`, `EmployeeRepository.cs`
DTOs	`TaskFlow.Api/Dtos/Profile/`	`ProfileRequests.cs` (`UpdateOwnProfileRequest`)
DTOs (reused)	`TaskFlow.Api/Dtos/Management/EmployeeManagement/`	`UserDto.cs` (`UserDto`, `ProjectAllocationDto`, `UserDepartmentDto`, `UserManagerDto`)
Validators	`TaskFlow.Api/Dtos/Profile/Validators/`	`UpdateOwnProfileRequestValidator.cs`
Rules	`TaskFlow.Api/Common/Rules/`	`EmailPolicy.cs`, `MobileNumberPolicy.cs`
Entities	`TaskFlow.Api/Models/Entities/`	`User.cs`
Security	`TaskFlow.Api/Common/Security/`	`PermissionKeys.cs`, `PermissionCatalog.cs` (`profile.view`, `profile.edit`)

Layer	Path	Files
Middleware / Filters	`TaskFlow.Api/Middleware/`, `TaskFlow.Api/Filters/`	`SessionValidation.cs`, `MfaSetupGateMiddleware.cs`, `GlobalExceptionHandler.cs`, `ValidationFilter.cs`
Assistant (TFA)	`TaskFlow.Api/Services/Assistant/Tools/`	`AssistantActionTools.cs` (`ProposeProfileUpdateTool`)
Assistant (TFA)	`TaskFlow.Api/Services/Assistant/Actions/`	`AssistantActionService.cs` (applies the confirmed card)
Assistant (TFA)	`TaskFlow.Api/Repositories/Assistant/People/`	`IAssistantDirectoryRepository.cs`, `AssistantDirectoryRepository.cs` (`EmailUsedByOtherAsync`)
Assistant knowledge	`TaskFlow.Api/Services/Assistant/Knowledge/`	`edit-profile.md`
DI	`TaskFlow.Api/Config/`	`ServiceRegistration.cs` (`IProfileService` → `ProfileService`, scoped; `ProposeProfileUpdateTool` as `IAssistantTool`)

4. Frontend File Structure

Type	Path	Purpose
Routes	`src/app/modules/profile/profile.routes.ts`	`PROFILE_ROUTES`: `profile` → `ProfileComponent` (lazy `loadComponent`)
Page component	`src/app/modules/profile/pages/profile.component.ts` / `.html`	My Profile: header and chips, read-only Account details, Personal information form, Password card
Models	`src/app/modules/profile/pages/profile.model.ts`	`ProfileField`, `ReadonlyField`
Models (shared)	`src/app/modules/management/employee-management/models/user.model.ts`	`User`, `UpdateOwnProfile`
API service	`src/app/modules/profile/services/profile.service.ts`	`get`, `update`
Route / Guard	`src/app/routes/app.routes.ts`	Child of the shell route guarded by `authGuard` and `mfaSetupGuard`. There is no `permissionGuard`.
Menu	`src/app/layouts/nav-items.ts`	`{ label: 'My Profile', icon: 'user', route: '/profile' }` is always added, with no permission check. Also `layouts/shell.component.html` account link → `/profile`.
Shared utils	`src/app/shared/utils/email-domain.ts`, `mobile-number.ts`, `api-error.ts`; `shared/auth/auth.service.ts` (`applyProfile`)	Client-side copies of the server rules, error text extraction, session re-sync

Type	Path	Purpose
Consumer	`src/app/modules/auth/security-setup/pages/security-setup.component.ts`	Step 1 ("details") calls `ProfileService.get` and `update` with full name, email and mobile number

---

5. API & Logic

5.1 API Endpoints

#	Method	Endpoint	Description	Permission (Policy)	Request DTO	Response DTO
1	GET	`/api/v1/users/me`	Read the caller's own profile	`[Authorize]` only. Catalog key `profile.view` (always on, not enforced).	–	`UserDto` (200), 401, 404
2	PUT	`/api/v1/users/me`	Update the caller's own full name, email and mobile number	`[Authorize]` only. Catalog key `profile.edit` (always on, not enforced).	`UpdateOwnProfileRequest`	`UserDto` (200), 400, 401, 404

Both endpoints stay open while MFA setup is pending (`MfaSetupGateMiddleware` allows the exact path `/api/v1/users/me`).

5.2 Request / Response Samples

```
// PUT /api/v1/users/me
{ "fullName": "Anita Varghese", "email": "anita.v@taskflow.com", "mobileNumber":
"+919876543210" }
```

```
// 200 OK  (UserDto, abridged)
{
  "id": 12, "employeeCode": "EMP012", "fullName": "Anita Varghese", "username": "anita",
  "email": "anita.v@taskflow.com", "roleId": 3, "role": "Employee", "isActive": true,
  "createdAt": "2026-10-11T09:00:00Z", "updatedAt": "2026-10-31T10:00:00Z", "lastLoginAt":
"2026-10-31T08:55:00Z",
  "projectAllocations": [ { "projectId": 2, "projectName": "Apollo", "positionId": 4,
"positionName": "Developer", "percent": 60 } ],
  "departments": [ { "id": 1, "name": "Engineering" } ],
  "managers": [ { "id": 5, "fullName": "Rahul Menon" } ],
  "managerProjects": [], "reports": [],
  "mfaEnabled": true, "backupCodesRemaining": 9, "mobileNumber": "+919876543210",
  "totalAllocatedPercent": 60, "remainingPercent": 40
}
```

`mobileNumber` semantics: omitted or `null` keeps the current number. An empty or blank string clears it. The Angular form always sends a string, so an empty field clears the number.

5.3 Service Layer Logic

Method: `GetAsync(int userId, CancellationToken)`

1. Returns `IEmployeeRepository.GetDtoAsync(userId)`: a no-tracking projection of the non-deleted user, with allocations, departments, managers (from department managers and project leads), and for managers their managed projects and reports, MFA status and remaining backup codes.

Method: `UpdateAsync(int userId, UpdateOwnProfileRequest request, CancellationToken)`


1. `ValidationFilter` has already run `UpdateOwnProfileRequestValidator`. Failures return a 400 `ValidationProblemDetails`.
2. Loads a tracked user with `GetActiveWithRoleForUpdateAsync(userId)`. Returns `null` (→ 404) if there is no such user.
3. `EmailPolicy.Normalize` trims and lower-cases the email. If `!EmailPolicy.IsValid`, it throws `BusinessRuleException(EmailPolicy.InvalidMessage)`.
4. Mobile number: if `request.MobileNumber` is `null`, the current value is kept. Otherwise `MobileNumberPolicy.Normalize` strips whitespace, `-`, `.`, `(` and `)`, and blank input becomes `null`. A non-null value that fails `IsValid` throws `BusinessRuleException(MobileNumberPolicy.InvalidMessage)`.
5. If the mobile number is not null and `EmailAndMobileTakenAsync(email, mobile, userId)` returns true, it throws `"A user with this email and mobile number already exists."`
6. If `EmailPrefixTakenAsync(LocalPart(email) + "@", userId)` returns true, it throws `"Email already exists."` This check ignores query filters, so deleted users still reserve their address.
7. Sets `FullName` (trimmed), `Email`, `MobileNumber` and `UpdatedAt = DateTime.UtcNow`. Role, project, username, employee code and status are not touched.
8. `IUnitOfWork.SaveChangesAsync`, then returns a fresh `GetAsync`.
9. No notification, mail or activity log is written.

Client: on success `ProfileComponent` calls `authService.applyProfile(...)` and shows the toast *Profile updated*. `profile.component.ts` shows the "Managed projects" and "Team" rows only when `user.role === 'Manager'`.


5.4 Repository Layer

Method	Description	Query Notes
`IEmployeeRepository.GetDtoAsync(id)`	Projects one user to `UserDto`	`AsNoTracking`, `!IsDeleted`. Extra queries for the `Managers` and `Reports` lists (department managers and project leads with `IsProjectManager`).
`IEmployeeRepository.GetActiveWithRoleForUpdateAsync(id)`	Tracked user with `Role`	`Include(u => u.Role)`, `!IsDeleted`. Does **not** filter on `IsActive`. Inactive users are already stopped by `SessionValidation`.
`IEmployeeRepository.EmailPrefixTakenAsync(prefix, exceptUserId)`	Is another user's email starting with `localpart@`?	`IgnoreQueryFilters()` (includes deleted users), `Email.ToLower().StartsWith(prefix)`
`IEmployeeRepository.EmailAndMobileTakenAsync(email, mobile, exceptUserId)`	Exact email and mobile pair on another user	Query filter on (deleted users excluded)
`IAssistantDirectoryRepository.EmailUsedByOtherAsync`	Assistant pre-check before the action card	Used only by `ProposeProfileUpdateTool`

5.5 Sequence Diagram



Assistant (TFA) path



---

6. Database Design

Table	Column	Type	Constraints	Description
`Users`	`Id`	int	PK	User id (taken from the JWT)
`Users`	`EmployeeCode`	text	Max 32, nullable	Read-only on Profile
`Users`	`FullName`	text	Not Null, Max 200	Editable
`Users`	`Username`	text	Not Null, Max 100, Unique index	Read-only on Profile

Table	Column	Type	Constraints	Description
`Users`	`Email`	text	Not Null, Max 256, Unique index	Editable. Lower-case, `@taskflow.com`.
`Users`	`MobileNumber`	text	Max 20, nullable, **not unique**	Editable, E.164
`Users`	`RoleId`	int	FK → `Roles.Id`, Restrict	Read-only on Profile
`Users`	`IsActive`	bool	–	Read-only on Profile
`Users`	`MfaEnabledAt`	datetime	nullable	Read only here: drives `mfaEnabled` and the "Two-step on/off" chip
`Users`	`CreatedAt`, `UpdatedAt`, `LastLoginAt`	datetime	–	`UpdatedAt` set on every save
`Users`	`IsDeleted`	bool	Global query filter `!IsDeleted`	Soft delete

Read-only joins used by `UserDto`: `UserProjectAllocations` (with `Projects` and `Positions`), `UserDepartments` (with `Departments`), `DepartmentManagers`, `ManagerProjects`. `backupCodesRemaining` is read from `MfaBackupCodes` (see 07.3).

Relationships

- `Users.RoleId → Roles.Id` (FK, Restrict)

7. Security & Authorization

- `[Authorize]` only; the id comes from `ClaimTypes.NameIdentifier` (unparseable → 401). Data scope is Own, fixed by the token.
- `profile.view` and `profile.edit` have `AlwaysGranted: true, IsAssignable: false` in `PermissionCatalog.cs` and are never checked.
- Both endpoints are on the `MfaSetupGateMiddleware` allow-list, so a user with setup pending can still read and save their profile.
- The TFA tool `ProposeProfileUpdateTool` has `Policy => null` (no extra permission check).

Permission Key	Endpoint(s)	UI Element Controlled
`profile.view`	`GET /api/v1/users/me`	My Profile menu item and page (always shown)
`profile.edit`	`PUT /api/v1/users/me`	Personal information form and Save changes

8. Validations & Error Handling

Rule	Layer	HTTP Code	Error Message
`FullName` empty or longer than 200	`UpdateOwnProfileRequestValidator`	400 (validation `errors` map)	FluentValidation default (e.g. `'Full Name' must not be empty.`)
`Email` empty or longer than 256	Validator	400	FluentValidation default

Rule	Layer	HTTP Code	Error Message
`Email` not a valid `@taskflow.com` address	Validator and Service	400	Email must be a name using letters, digits, dot, underscore or hyphen followed by @taskflow.com.
`MobileNumber` not E.164	Validator and Service	400	Mobile number must be in international format, for example +919876543210.
Email and mobile pair already used	Service	400	A user with this email and mobile number already exists.
Email local part already used (including deleted users)	Service	400	Email already exists.
User not found or deleted	Controller	404	– (empty `NotFound()`)
Concurrent edit of the same row	`GlobalExceptionHandler`	409	Someone else changed this record while you were saving. Reload it and try again.

Client-side messages: `Full name is required.`, `Email is required.`, `Use letters, digits, dot, underscore or hyphen before @taskflow.com.`, `This field is too long.`, `Use international format, for example +919876543210.`, `Could not load your profile.`, `Could not update your profile.`. Toast: `Profile updated.` `ProfileComponent` maps 400 `errors` keys onto its form controls. Shared error handling (401, 500, problem details) is described in the parent document.

9. Integrations / Side Effects

- **Notifications / Email / Activity Log:** none.
- **Shell:** after a profile save, `AuthService.applyProfile()` re-syncs the cached user (name, email) and keeps the permissions it already has.
- **AI Assistant (TFA):** `ProposeProfileUpdateTool` (`propose_profile_update`, `AssistantActionKind.UpdateOwnProfile`, `Policy => null`) checks a name or email change with `IValidator<UpdateOwnProfileRequest>` and checks `IAssistantDirectoryRepository.EmailUsedByOtherAsync`. It then creates a pending action card. On confirmation, `AssistantActionService` calls `IProfileService.UpdateAsync(caller.UserId, new UpdateOwnProfileRequest(FullName, Email))`. The mobile number is passed as `null` and therefore kept. The reply is "Done. Your profile was updated."
- **Help knowledge:** `Services/Assistant/Knowledge/edit-profile.md`.
- **Auth (Security Setup):** step 1 of onboarding saves details through `PUT /api/v1/users/me`.

10. Configuration

Not applicable – this child has no configuration of its own. Module-wide keys (`ConnectionStrings:Default`, `Mfa:Required`) are in the parent document.

11. Testing

Test Type	File / Location	Covers
Unit	`tests/TaskFlow.UnitTests/Profile/UpdateOwnProfileRequestValidatorTests.cs`	Profile update validation rules
Integration	`tests/TaskFlow.IntegrationTests/Profile/UserProfileEndpointsTests.cs`	`/api/v1/users/me` endpoints

> Frontend specs: `profile.component.spec.ts`, `profile.component.layout.spec.ts`, `profile.service.spec.ts`. Backend coverage in the table is inferred from file names.

12. Known Limitations / Gaps found

- No audit or activity entry is written for profile edits.
- **Help knowledge vs UI:** `Knowledge/edit-profile.md` says to edit name and email "Under **Account details**". In the UI, editing is in the **Personal information** card, and Account details is read-only. The article also leaves out the mobile number.
- **Hardcoded role check:** `profile.component.ts` shows "Managed projects" and "Team" when `user.role === 'Manager'`. This is a role-name check, not a permission check, so a custom manager-like role does not see these rows.
- **Email uniqueness check differs:** the Assistant's pre-check uses `EmailUsedByOtherAsync`, while `ProfileService` uses the local-part prefix rule, which includes deleted users. A proposal can pass the Assistant check and still fail with "Email already exists." on confirmation.
- **Method naming:** `GetActiveWithRoleForUpdateAsync` does not filter on `IsActive` (shared with 07.2, see parent).

© 2026 Jojo George. All rights reserved. Unauthorized copying or distribution of this document is prohibited.