

Script-Controlled ACL Lab – Phase 3

Milestone 3: Data Creation & Access Control List (ACL) Configuration

Step 1: Create Test Records

1. Navigate to the newly created table or search `u_institution_details.list` in the filter navigator.
2. Click **New** to create multiple test sample records.
3. Ensure you create diverse entries with varying values for the **Branch** choice field: **ECE**, **EEE**, and **CSE**.

Step 2: Elevate Privileges to `security_admin`

1. In the ServiceNow banner, click your user profile icon (top right).
2. Select **Elevate Roles**.
3. Check the box for **security_admin** and click **Update**.

Step 3: Create the Read Access Control List (ACL)

1. In the Application Navigator, search for **System Security** → **Access Control (ACL)**.
2. Click **New** to instantiate a fresh access rule rule.
3. Fill in the primary details as follows:

Field Name	Configuration Value
Type	record
Operation	read
Name	Institution Details [u_institution_details]
Active	True (Checked)
Advanced	True (Checked)

4. Scroll down to the **Requires role** related list and add the custom role: **bb1**.
5. Under the **Condition** section, add a data condition: **Branch is EEE**.
6. In the **Script** field, replace any default scaffolding with the following JavaScript logic:

```
(function () {  
    // Allow admin users full access  
    &nbsp; if; (gs.hasRole('admin')) {
```

```
        return true;
    }
    // Allow only EEE branch users to see EEE records
    &nbsp;if; (gs.hasRole('bb1')){
        return true;
    }
    // Deny access for all others
    &nbsp;return; false;
}());
```

7. Click **Submit** or **Save** to commit the security rules.