

Script-Controlled ACL Lab – Phase 6

1. Post-Creation Verification Framework

Verify the expected behavior after applying the Read and Create ACL restrictions:

- **User with bb1 & bb2 roles:** Can view only EEE branch records, and can see/click the **New** button on the list view.
- **User without the roles:** Restricted entirely from accessing or initializing data parameters.
- **Admin user:** Maintains full, override-enabled structural visibility to view all records regardless of branch values.

2. Creation of Access Control Lists (Write ACL)

To restrict record amendment capabilities to qualified personnel, deploy a dedicated table-level Write operation:

Form Field	Target Configuration Value
Type	record
Operation	write
Name	u_institution_details
Active	True (Checked)
Requires Role	bb3 (custom role)
Condition Builder	<i>No data condition required</i>

1. Navigate to **System Security** → **Access Control (ACL)** via your Application Navigator workspace.
2. Ensure your session context is currently elevated to **security_admin** privileges.
3. Click the **New** button situated inside the top actions ribbon element to initialize a blank security definition form.
4. Configure the structural parameters on the rule block exactly as detailed in the matrix above.
5. Scroll to the **Requires role** related list block down at the bottom section area layout, double-click the empty row slot, and explicitly map the custom **bb3** permission flag.
6. Click **Submit** or right-click the top header bar panel and select **Save** to store your structural access parameters safely.