

ServiceNow Access Control Lab

Phase 7: Delete Operation Security & Verification Matrix

1. Comprehensive Validation & Verification Matrix

Before configuring administrative table boundaries for data destruction, you must verify the existing cascade of cumulative read and write rules. Test the active multi-role setup using the **Impersonation Tool**.

Target Profile Context	Assigned Security Roles	Expected Behavior Matrix
EEE Test User Profile	bb1, bb2, bb3	Can safely View and Edit explicit EEE Branch records. The global New Button renders fully inside the UI header context.
Standard Unassigned User	None	Completely restricted. No visibility into table records and no execution rights over CRUD UI operations.
System Administrator	admin	Retains full system-wide permissions across all records globally, bypassing branch conditions.

Verification Action Items:

- Navigate to the top-right user profile banner widget and select **Impersonate User**.
- Search for **EEE User** to load the session context safely inside the platform interface.
- Execute the global view command by typing u_institution_details.list inside the unified **All Menu** filter field.
- Ensure that fields are fully interactive for editing and the **New** creation action element remains functional.

2. Creation of Access Control Lists (Delete ACL)

To round out full table lifecycle operations, establish systemic boundaries for record removal. This step locks data destruction permissions down tightly to the designated security tier.

Configuration Steps:

1. Switch context back to the master administrative account by terminating user impersonation.
2. Ensure your user context maintains active elevation status for the **security_admin** infrastructure role.
3. In the global navigation application matrix, locate and click on **System Security → Access Control (ACL)**.
4. Click the primary **New** action button to open the workspace record canvas.

Field Specification Matrix:

Form Element Label	Target Specification Value
Type	record
Operation	delete
Name	Institution Details [u_institution_details] * (All Fields/Records)
Active	True (Checked)
Advanced Condition	False (Unchecked — No data logic evaluation required)

5. Role Requirements Mapping:

- Locate the **Requires role** embedded related list matrix situated at the baseline of the main configuration card.
- Double-click the inline insertion bar or click the edit reference lock icon.
- Query, map, and cleanly insert the custom infrastructure role: **bb4**.
- Leave the data condition builder completely empty.
- Right-click the header workspace title banner and click **Save** or execute a primary **Submit** action to finalize rule persistence.