COSTELL		CHECKE	CHECKFORMIN'								
	(七)	CUSTOMER	OUSTOMER						ORDER		
www.costelli	i.com	TYPESYSTI	TYPESYSTEM						REGN°		
		TE	STRESULTATION					RESU	г	COMMENT	
CONFORMITY CHECK WHITTHE CRIGINAL LIST											
SZECHECKORBULDING DISPOSITION FROMDRAW											
SEALS	STANDAR		☐ VITON								
PLMP	VARIABLE	[	EXTERNAL GEARS	[	PISTONS						
			VANEPUMP								
Displacement l/min  PRESSUPEREDUCING											
VALLE REFEATABLYTY											
OPERATIONTEST PRESSURE PERIOD											
Overpressure:  Pressure:  Pressur											
VALVE											
SEDUENCE   REDUCKSPRESSURE   ROWRESLATOR   COMPRISATED FLOWRESLATOR											
G-ECKVALVE RILDIEDG-ECKVALVE											
ACCESSORIES											
ACCUMULATORUT. FO BAR STANDARD  FILTERS Asp. Man. M. Rit. H. R											
HEAT BYCHANGE AIR-OIL WATER-OIL											
INSTRUMENTS	RRESSU	TEGALCE METER	PRESS.SWITCH THERMOSTAT		LEVEL.SV						
SEALCHECK CAP PORTHOLE TANK  MANIFOLD VALVE HTTINGS											
FLUD MNERALOIL □								2000			
CENERAL ARRANDEMENTERNAT											
STANDARD RAL											
ATH-EBNOFTH-ES/STBMTESTO-BOX  QEANINGINTH-ETANK											
VOLTAGEBLETTROVALVECOIL V											
ELECTRICALMOTOR KW 2POLI											
220/380 - 50 Hz CV 4POL											
ATTACH-DOBRINGATES BECTRICALMOTOR											
			ACCUMULATOR								
Α			В	NOSESUR	VEYEXTRACT FROM	/UN 7712-7 dBCHEC			O A DIA CITTO A CO		
					A	В	С		OUNDMETERMOD IOTE:		
				Pmin Ba	r			1 180			
				Pmax Ba	r			4			
С			D H1 mt	BACKGROUN NOISE				12			
EUDEI VVILDEI EVOL					***********			TESTERSIGNT	I DE		
FOR PLANT RELEASED WITH NON-CONFORMING OUTCOME, ANNEX MOTIVATION  BULDED BY TESTER				SIGNATUR					NSABLE DATA		
				Guido Costelli							