

Causal graph quantum dynamic simulation

auteurs...

1 Introduction

2 Results

3 Tests

We did some tests to validate the simulations, including (but not limited to) the classical and quantum injectivity tests.

3.1 classical injectivity test

To check if our graph dynamics is reversible, we can apply on a huge number of random graphs a single step, and a reversed step and check that we get back the same graph with started with.

This was tested on around 10k graphs, for which the particles position were randomized, but the graph name was kept, making it more complex as each step on random particles positions caused splits and merges.

3.2 quantum injectivity test

To check that our graph dynamic is unitary, we can check that computing an arbitrary amount of steps on an arbitrary initial state (increasing drastically the number of graphs), and then apply the same number of reversed step, and we check that we get back the state we started with.

Even including floating points errors, we can easily do this test with around 5 steps, obtain around 200k graphs after the 5 forward iteration, and come back to the same step within 0.001% error in the magnitude.

4 Implementation

The code shown below is a simplification of the actual code ¹ (classes are shown without member function or decorators, and code inside loops is represented by functions).

The following classes are used in the implementation:

node names corresponding to the name ² of a single node.

graph names i.e. ordered set of node.

graphs with particles graph name and positions of particles.

superposition of graphs

¹<https://github.com/jolatechno/Quantum-graph-simulation.git>

²arithmetique de nom

4.1 node names

Nodes can either be "left" or "right" containers (pointing to another node), "elemnts" (a simple integer name) or pairs (a merge of two other nodes, pointing to two other nodes).

We mark each node with a "has_most_left_zero_" (which is inherited through merges) variable to keep track of the node that contains the first nodes.

4.1.1 class

```
1 struct node {
2     int left_idx_or_element_;
3     int right_idx_or_type_;
4     size_t hash_ = 0;
5     bool has_most_left_zero_ = false;
6     //...
```

4.1.2 constructors

The following constructor helps construct an "element-type" node (which are just a single integer, and are used to initialize graphs):

```
1 //...
2 node(int n) :
3     left_idx_or_element_(n), right_idx_or_type_(element_idx) {
4
5     hash_ = n;
6     boost::hash_combine(hash_, element_idx);
7
8     has_most_left_zero_ = n == 0;
9 }
10 //...
```

We also need a constructor for "left/right-type" node (noted "u.l" or "u.r"):

```
1 //...
2 node(int const idx, node_t const &other, int const type) :
3     left_idx_or_element_(idx), right_idx_or_type_(type) {
4
5     boost::hash_combine(hash_, other.hash_);
6     boost::hash_combine(hash_, type);
7
8     // check for most left zero
9     if (is_left())
10         has_most_left_zero_ = other.has_most_left_zero_;
11 }
12 //...
```

And finally, we need a constructor to construct "pair-type" nodes (noted "u \wedge v"):

```
1 //...
2 node(int const left_idx, node_t const &left,
3     int const right_idx, node_t const &right) :
4     left_idx_or_element_(left_idx),
5     right_idx_or_type_(right_idx){
6
7     boost::hash_combine(hash_, left.hash_);
8     boost::hash_combine(hash_, right.hash_);
9     has_most_left_zero_ = left.has_most_left_zero_ || right.has_most_left_zero_;
10 }
11 //...
12 }
```

4.1.3 hash

the hash of a node is stored in the "hash_" varibale, and is simply calculated by the constructor (since it never changes).

To compute the hash of a node, we simply combine the hash of all children nodes or of the integer representing the element, and/or the type of the node.

4.2 graph names

To store the list of nodes, we use a main nodes list, which we keep in a lexicographical order (the first node should always be the node with the "most left zero").

Other nodes which are pointed to are stored into a buffer vector, for which we use grabage collection.

4.2.1 class

```
1 class graph_name {
2 private:
3     // node list
4     std::vector<node_t> nodes_;
5     std::vector<node_t> node_buff_;
6     std::vector<int> trash_collection_;
7
8     // hash
9     size_t mutable hash_ = 0;
10    bool mutable hashed_ = false;
11
12    // ...
```

4.2.2 usefull functions

Since we use trash collection to manage memory, we need to implement a collection to insert a node into the "buffer vector":

```
1 // ...
2 int push_to_buffer(node_t &n) {
3     if (trash_collection_.empty()) {
4         node_buff_.push_back(n);
5         return node_buff_.size() - 1;
6     }
7
8     int buff_idx = trash_collection_.back();
9     trash_collection_.pop_back();
10    node_buff_[buff_idx] = n;
11    return buff_idx;
12 }
13 // ...
```

4.2.3 split

```
1 // ...
2 bool inline split(unsigned int idx) {
3     hashed_ = false;
4
5     node_t node = nodes_[idx];
6     if (node.is_pair()) {
7         // read indexes
8         int const left_idx = node.left_idx();
9         int const right_idx = node.right_idx();
```

```

10
11 // add left node
12 nodes_[idx] = node_buff_[left_idx];
13 trash_collection_.push_back(left_idx);
14
15 // add right node
16 nodes_.insert(nodes_.begin() + idx + 1, node_buff_[right_idx]);
17 trash_collection_.push_back(right_idx);
18
19 // check if we should rotate
20 if (idx == 0 && nodes_[1].has_most_left_zero()) {
21     std::rotate(nodes_.begin(), nodes_.begin() + 1, nodes_.end());
22     return true;
23 }
24
25 return false;
26 }
27
28 // add current node to buffer
29 int buff_idx = push_to_buffer(node);
30
31 // add left node
32 nodes_[idx] = node_t(buff_idx, node, point_l_idx);
33
34 // add right node
35 nodes_.insert(nodes_.begin() + idx + 1,
36     node_t(buff_idx, node, point_r_idx));
37
38 return false;
39 }
40 //...

```

The boolean return argument of this function is used to check if the merge requires a rotation of nodes.

4.2.4 merges

```

1 //...
2 void inline merge(unsigned int idx) {
3     hashed_ = false;
4
5     // destination idx
6     unsigned int right_idx = (idx + 1) % size();
7     auto left = nodes_[idx];
8     auto right = nodes_[right_idx];
9
10    if (left.is_left() && right.is_right()) {
11        int const left_left = left.left_idx();
12        int const right_left = right.left_idx();
13
14        if (node_buff_[left_left].hash() == node_buff_[right_left].hash()) {
15            // trash collect
16            trash_collection_.push_back(left_left);
17            if (left_left != right_left)
18                trash_collection_.push_back(right_left);
19
20            //add node
21            nodes_[right_idx] = node_buff_[left_left];
22            nodes_.erase(nodes_.begin() + idx);
23            return;
24        }
25    }
26
27    //add node
28    int const left_idx = push_to_buffer(left);
29    int const right_idx_ = push_to_buffer(right);

```

```

30
31     nodes_[right_idx] = node_t(left_idx, left, right_idx_, right);
32     nodes_.erase(nodes_.begin() + idx);
33 }
34 // ...

```

4.2.5 hash()

To hash a graph name, we simply combine the hash of all the nodes.

```

1  // ...
2  size_t inline hash() const {
3      if (hashed_)
4          return hash_;
5
6      hash_ = 0;
7
8      /* combine all nodes hash */
9      for (auto &n : nodes_)
10         boost::hash_combine(hash_, n.hash());
11
12     hashed_ = true;
13     return hash_;
14 }
15 // ...
16 }

```

4.3 graphs with particles

A graph is represented by a graph name, and an ordered list of the node's index of particles going both ways.

4.3.1 class

```

1  class graph {
2      // variables
3      graph_name_t* name_;
4      std::vector<unsigned int> left_;
5      std::vector<unsigned int> right_;
6
7      // hash
8      size_t mutable hash_ = 0;
9      bool mutable hashed_ = false;
10
11     // ...

```

4.3.2 step and reversed_step()

The function to step all particles uses the functions "rotate_once_left" and "rotate_once_right" which rotate particles if they overflow:

```

1  // ...
2  void inline step() {
3      hashed_ = false;
4
5      rotate_once_right(right_);
6      rotate_once_left(left_);
7  }
8  // ...

```

To implement the reverse step we simply exchange the roles of "left" and "right" in the "step" function:

```

1 //...
2 void inline reversed_step() {
3     hashed_ = false;
4
5     rotate_once_right(left_);
6     rotate_once_left(right_);
7 }
8 //...

```

4.3.3 split_merge()

```

1 //...
2 void split_merge(std::vector<split_merge_t>& split_merge) {
3     /* first check if there are any split or merges */
4
5     hashed_ = false;
6
7     // check for last merge
8     /* ... */
9     if (last_merge()) {
10         name_>merge(last_idx);
11         overflow_right(left_);
12         split_merge.pop_back();
13         /* ... */
14     }
15
16     // check for first element split
17     bool first_split = false;
18
19     // split and merge names
20     // and calculating max displacement
21     int total_displacement = 0;
22     for (auto split_merge_it = split_merge.rbegin(); split_merge_it != split_merge.rend(); ++split_merge_it)
23         if ((*split_merge_it).second == split_t) {
24             first_split |= name_>split((*split_merge_it).first) && (*split_merge_it).first == 0;
25
26             ++total_displacement;
27         } else {
28             name_>merge((*split_merge_it).first);
29             --total_displacement;
30         }
31
32     // move particules
33     int displacement = total_displacement;
34     auto split_merge_it = last_split_merge;
35     for (auto left_it = left_.rbegin(); left_it != left_.rend(); ++left_it) {
36         // check if there are any nodes left
37         while (split_merge_it >= split_merge.begin()) {
38             // check if the node is split or merged
39             if ((*split_merge_it).first >= *left_it) {
40                 if ((*split_merge_it).second == split_t) {
41                     --displacement; // decrement the displacement
42                 } else
43                     ++displacement; // decrement the displacement
44                 --split_merge_it;
45             } else
46                 break;
47         }
48
49         if (split_merge_it == split_merge.begin() && displacement == 0)
50             break;
51     }
52 }

```

```

53     *left_it += displacement;
54 }
55
56 /* we than do the exact same thing with particule going to the right, rplacing ">=" at line
57 48 by a ">" */
58
59 // finish first split
60 if (first_split) {
61     rotate_once_left(left_);
62     rotate_once_left(right_);
63 }
64 }
65 //...

```

4.3.4 hash()

To hash graphs we simply combine all the positions of particules going in one directions, a separator, the paricules going the other, a separator way and finally the hash of the graph's name.

```

1 //...
2 size_t hash() const {
3     if (hashed_)
4         return hash_;
5
6     hash_ = 0;
7     boost::hash<unsigned int> hasher;
8
9     // left hash
10    for (auto &l : left_)
11        boost::hash_combine(hash_, l);
12
13    // separator
14    boost::hash_combine(hash_, separator);
15
16    // right hash
17    for (auto &r : right_)
18        boost::hash_combine(hash_, r);
19
20    // separator
21    boost::hash_combine(hash_, separator);
22
23    // name hash
24    boost::hash_combine(hash_, name->hash());
25
26
27    hashed_ = true;
28    return hash_;
29 }
30 //...
31 }

```

4.3.5 get_split_merges()

To get the list of all indeces of splits and merges, we iterate through both the "left" and "right" positions, iterating the one that is the smallest so that it always converges towards positions that match (or are one apart for merges):

```

1 /* function to get all split and merges */
2 std::vector<graph::split_merge_t> inline get_split_merge(graph_t* graph) {
3     std::vector<graph::split_merge_t> split_merge;
4
5     /* first check if there are any particules to check */
6
7     /* definition of left_it , right_it , last_left , last_right ... */
8

```

```

9  bool first_or_last_split = *left_it == *right_it && *left_it == 0;
10  while (true) {
11      /* check if there are any particules left after iterating */
12      if (right_it > last_right ||
13          left_it > last_left)
14          break;
15
16      if (*left_it == *right_it) {
17          /* check for split */
18          split_merge.push_back({(*left_it), graph->split_t});
19
20          /* check for last split */
21          if (*right_it == last_idx)
22              first_or_last_split = true;
23
24          ++right_it;
25          ++left_it;
26      } else if (*left_it < *right_it) {
27          /* check for merges */
28          if (*left_it == *right_it - 1)
29              if (left_it == last_left) {
30                  split_merge.push_back({(*left_it), graph->merge_t});
31              } else if (*(left_it + 1) != *right_it)
32                  split_merge.push_back({(*left_it), graph->merge_t});
33
34          ++left_it;
35      } else
36          ++right_it;
37  }
38
39  if (!first_or_last_split)
40      if (*last_left == last_idx &&
41          graph->right()[0] == 0)
42          split_merge.push_back({last_idx, graph->merge_t});
43
44  return split_merge;
45 }

```

4.4 superposition of graphs

4.4.1 class

To allow parallel insertions of graphs into the lists of all graphs, we use tbb concurrent hashmap.

We make the approximation that graphs with the same hash are equals and should therefor interact.

```

1  class state {
2      // hasher
3      struct graph_hasher { /* */ }
4
5      // comparator
6      struct graph_comparator { /* */ }
7
8      // type definition
9      typedef tbb::concurrent_unordered_multimap<graph_t*, std::complex<long double>, graph_hasher,
10         graph_comparator> graph_map_t;
11
12      // main list
13      graph_map_t graphs_;
14
15      // parameters
16      std::complex<long double> non_merge_ = -1;
17      std::complex<long double> merge_ = 0;
18
19      // ..

```


4.4.2 subset of splist and merges

We first need to know the number of possible graphs from the lists of splits and merges:

```
1 template<class T>
2 int num_subset(std::vector<T> const &vect) {
3     return pow(2, vect.size());
4 }
```

We can then associate a number between 0 and "num_subset" to a certain compositions of all the splits and merges (by seeing the nth binary digit of this number as enabling the nth split or merge) :

```
1 std::pair<std::vector<graph::split_merge_t>, std::complex<long double>> subset(std::vector<graph
   ::split_merge_t>& split_merge, int subset_numb,
2     std::complex<long double>& non_merge, std::complex<long double>& merge) {
3
4     std::vector<graph::split_merge_t> res;
5     std::complex<long double> proba = 1;
6
7     for (int i = 0; i < split_merge.size(); ++i) {
8         long double sign = 1 - 2*split_merge[i].second;
9
10        /* i-th bit of subset_numb */
11        if (subset_numb%2) {
12            /* add operation to res */
13            res.push_back(split_merge[i]);
14
15            /* get proba */
16            proba *= std::complex<long double>(merge.real(), sign*merge.imag());
17        } else
18            proba *= sign*non_merge;
19
20        subset_numb /= 2;
21    }
22
23    return {res, proba};
24 }
25 }
```

4.4.3 reduce_all()

```
1 //...
2 void reduce_all() {
3     for(auto it = graphs_.begin(); it != graphs_.end(); ) {
4         // range of similar graphs to delete
5         auto range = graphs_.equal_range(it->first);
6         auto start = range.first;
7
8         for(auto jt = std::next(it); jt != range.second; ++jt)
9             it->second += jt->second;
10
11        // if the first graphs has a zero probability, erase the whole range
12        if (!check_zero(it->second))
13            ++start;
14
15        it = graphs_.unsafe_erase(start, range.second);
16    }
17    //...
```

4.4.4 step_split_merge_all() and reversed_split_merge_step_all()

```
1 //...
2 void step_split_merge_all() {
3     graph_map_t buff;
```

```

4     buff.swap(graphs_);
5
6     #pragma omp parallel
7     #pragma omp single
8     for (auto & [graph, mag] : buff)
9     #pragma omp task
10    {
11
12        graph->step(); //graph->reversed_step(); for reversed_split_merge_step_all()
13
14        auto split_merge = get_split_merge(graph);
15
16        #pragma omp task
17        {
18            // update the probability of the graph without split or merge
19            auto [-, mag_no_split_merge] = subset(split_merge, 0, non_merge_, merge_);
20            graphs_.insert({graph, mag * mag_no_split_merge});
21        }
22
23        // add all graphs that actually have some split ot merge
24        const int n_max = num_subset(split_merge);
25        #pragma omp taskloop
26        for (int j = 1; j < n_max; ++j) {
27            graph_t* g_ = graph->copy();
28
29            auto [split_merge_list, mag_split_merge] = subset(split_merge, j, non_merge_, merge_);
30            g_->split_merge(split_merge_list);
31
32            //add graph
33            graphs_.insert({g_, mag * mag_split_merge});
34        }
35    }
36 }
37 // ...

```

4.4.5 source of errors