

Naive Utility Calculus

Joseph Low

August 2025

Table of Contents

- 1 Introduction
- 2 Related Work
- 3 NUC Computational Framework
- 4 Experiments
- 5 Discussion

Table of Contents

- 1 Introduction
- 2 Related Work
- 3 NUC Computational Framework
- 4 Experiments
- 5 Discussion

How do we make sense of other people's
behavior?

How do we make sense of other people's behavior?

- Why did you sleep late last night?

How do we make sense of other people's behavior?


- Why did you sleep late last night?
- Why did you sign up for this course?

How do we make sense of other people's behavior?

- Why did you sleep late last night?
- Why did you sign up for this course?
- Why did you choose to eat out instead of cooking?

$$\text{Utility} = \text{Rewards} - \text{Costs}$$

- There is empirical support that humans intuitively use utility-based reasoning to make sense of other people's behavior




$$U(p, o) = R(o) - C(p)$$

- $U(p, o)$: utility expected from acting according to plan p to reach outcome o
- $R(o)$: subjective reward the agent expects from outcome o
- $C(p)$: subjective cost of executing plan p

- **Descriptive, not normative:** This is not about how people *should* make decisions (economic utility theory)
- **How we actually operate:** This describes how we *intuitively* make sense of other people's behavior
- People don't explicitly compute utilities when they act - this is the cognitive framework we use to understand others

Utility and Efficiency



- More efficient paths are less costly and therefore produce higher utilities
- When agents act, they will fulfill their goals as efficiently as possible to maximize utility

Graded Preference Inference

added

Costs Vary Across Agents

added

Rewards Vary Across Agents

added

Table of Contents

- 1 Introduction
- 2 Related Work**
- 3 NUC Computational Framework
- 4 Experiments
- 5 Discussion

Inverse Decision-Making

added

Inverse Planning

- Inferring goals and preferences from observed actions
- Often modeled using Markov Decision Processes (MDPs)
- Agent state transitions and reward functions

added

Research Questions

added

Table of Contents


- 1 Introduction
- 2 Related Work
- 3 NUC Computational Framework**
- 4 Experiments
- 5 Discussion

Hierarchical Mind Model

Level	Component	Observable?
4	Desires (Reward functions)	No
3	Goals (World states)	No
2	Intentions (Goal sequences)	No
1	Actions (Behaviors)	Yes

↓ Inference Direction ↑

Generative Process




Goal: Reach Object A

$$V^*(s) = \max_a \sum_{s'} P(s'|s, a) [R(a, s) - C(a, s) + \gamma V^*(s')]$$

Policy: $p(a|s) \propto \exp(\sum_{s'} P(s'|s, a) V^*(s') / \alpha)$

Each goal \rightarrow Separate MDP \rightarrow Efficient path

The Inference Problem



$$p(C, R|A) \propto p(A|C, R) \cdot p(C, R)$$

Two Types of Rationality

Type	What	Formula
Rational Choice	Intention selection	$p(I C, R) \propto \exp(U(I)/\beta)$
Rational Action	Efficient execution	$p(A I)$ via MDP policy

Likelihood: $p(A|C, R) = \sum_I p(A|I) \cdot p(I|C, R)$

Table of Contents

- 1 Introduction
- 2 Related Work
- 3 NUC Computational Framework
- 4 Experiments**
- 5 Discussion

Experimental Setup

added

Experiment 1

added

Experiment 2

added

Experiment 5

added

Table of Contents

- 1 Introduction
- 2 Related Work
- 3 NUC Computational Framework
- 4 Experiments
- 5 Discussion**

- Summary of key points
- Main takeaways from this presentation
- Future directions and next steps
- Questions and discussion