

Convolutional Neural Networks (CNN)

By Prof. Seungchul Lee
iSystems Design Lab
<http://isystems.unist.ac.kr/>
UNIST

Table of Contents

- I. 1. Convolution on Image
- II. 2. Convolutional Neural Networks (CNN)
 - I. 2.1. Convolutional operator
 - II. 2.2. Nonlinear activation function
 - III. 2.3. Pooling
 - IV. 2.4. Inside Convolution Layer
- III. 3. CNN with TensorFlow
 - I. 3.1. Import Library
 - II. 3.2. Load MNIST Data
 - III. 3.3. Build Model
 - IV. 3.4. Define a CNN Shape
 - V. 3.5. Define Weights, Biases and Network
 - VI. 3.6. Define Loss, Initializer and Optimizer
 - VII. 3.7. Summary of Model
 - VIII. 3.8. Define Configuration
 - IX. 3.9. Optimization
 - X. 3.10. Test
- IV. 4. Deep Learning of Things

1. Convolution on Image

Filter (or Kernel)

- Modify or enhance an image by filtering
- Filter image to emphasize certain features or remove other features
- Filtering include smoothing, sharpening and edge enhancement


Convolution in 2D

1	1	1	0	0
0	1	1	1	0
0	0	1	1	1
0	0	1	1	0
0	1	1	0	0


Image

4		


Convolved
Feature



Image



Kernel



Output

In [1]:

```
# Import libraries
import numpy as np
import matplotlib.pyplot as plt
from scipy.misc import imread, imresize
from scipy.signal import convolve2d
from six.moves import cPickle

%matplotlib inline
```

In [2]:

```
# Import image
input_image = cPickle.load(open('./image_files/lena.pkl', 'rb'))

# Edge filter
image_filter = np.array([[ -1, 0, 1]
                        ,[-1, 0, 1]
                        ,[-1, 0, 1]])

# Compute feature
feature = convolve2d(input_image, image_filter, boundary='symm', mode='same')
```

In [3]:

```
# Plot
fig = plt.figure(figsize=(10, 6))
ax1 = fig.add_subplot(1, 3, 1)
ax1.imshow(input_image, 'gray')
ax1.set_title('Input image (512 x 512)', fontsize=15)
ax1.set_xticks([])
ax1.set_yticks([])


ax2 = fig.add_subplot(1, 3, 2)
ax2.imshow(image_filter, 'gray')
ax2.set_title('Image filter (3 x 3)', fontsize=15)
ax2.set_xticks([])
ax2.set_yticks([])

ax3 = fig.add_subplot(1, 3, 3)
ax3.imshow(feature, 'gray')
ax3.set_title('Feature', fontsize=15)
ax3.set_xticks([])
ax3.set_yticks([])
plt.show()
```


Input image (512 x 512)



Image filter (3 x 3)



Feature



In [4]:

```
# Import image
input_image = cPickle.load(open('./image_files/lena.pkl', 'rb'))

# Gaussian filter
image_filter = 1/273*np.array([[1, 4, 7, 4, 1]
                               ,[4, 16, 26, 16, 4]
                               ,[7, 26, 41, 26, 7]
                               ,[4, 16, 26, 16, 4]
                               ,[1, 4, 7, 4, 1]])
image_filter = imresize(image_filter, [15, 15])

# Compute feature
feature = convolve2d(input_image, image_filter, boundary='symm', mode='same')
```

In [5]:

```
# Plot
fig = plt.figure(figsize=(10, 6))
ax1 = fig.add_subplot(1, 3, 1)
ax1.imshow(input_image, 'gray')
ax1.set_title('Input image (512 x 512)', fontsize=15)
ax1.set_xticks([])
ax1.set_yticks([])


ax2 = fig.add_subplot(1, 3, 2)
ax2.imshow(image_filter, 'gray')
ax2.set_title('Image filter (15 x 15)', fontsize=15)
ax2.set_xticks([])
ax2.set_yticks([])

ax3 = fig.add_subplot(1, 3, 3)
ax3.imshow(feature, 'gray')
ax3.set_title('Feature', fontsize=15)
ax3.set_xticks([])
ax3.set_yticks([])
plt.show()
```


Input image (512 x 512)



Image filter (15 x 15)




Feature



2. Convolutional Neural Networks (CNN)

Convolutional Networks


- Simply neural networks that use convolution in place of general matrix multiplication in at least one of their layers
- Convolution can be interpreted as matrix multiplication



2.1. Convolutional operator


Matrix multiplication

- Every output unit interacts with every input unit




Convolution


- Local connectivity
- Weight sharing
- Typically have sparse interactions
- Accomplished by making the filter smaller than input (sparse interactions)



2.2. Nonlinear activation function




Rectified linear unit (ReLU)




2.3. Pooling

- Compute a maximum value in a sliding window (max pooling)
- Pooling size : 2×2




- Max pooling introduces invariances




2.4. Inside Convolution Layer

- First, the layer performs several convolutions to produce a set of linear activations
- Second, each linear activation is run through a nonlinear activation function
- Third, use pooling function to modify the output of the layer further



3. CNN with TensorFlow

- MNIST example
- Classifying hand written digits



In [6]:

```
%%html
<center><iframe src="https://www.youtube.com/embed/z6k_RMKExlQ?start=5150&end=6132"
width="560" height="315" frameborder="0" allowfullscreen></iframe></center>
```

ml4a @ itp nyu :: 03 convolutional neural networks



3.1. Import Library

In [7]:

```
# Import Library
import numpy as np
import matplotlib.pyplot as plt
import tensorflow as tf
```

3.2. Load MNIST Data

- Download MNIST data from tensorflow tutorial example

In [8]:


```
from tensorflow.examples.tutorials.mnist import input_data
mnist = input_data.read_data_sets("MNIST_data/", one_hot=True)
```

```
Extracting MNIST_data/train-images-idx3-ubyte.gz
Extracting MNIST_data/train-labels-idx1-ubyte.gz
Extracting MNIST_data/t10k-images-idx3-ubyte.gz
Extracting MNIST_data/t10k-labels-idx1-ubyte.gz
```

In [9]:

```
# Check data
train_x, train_y = mnist.train.next_batch(10)
img = train_x[9,:].reshape(28, 28)

plt.figure(figsize=(5, 3))
plt.imshow(img, 'gray')
plt.title("Label : {}".format(np.argmax(train_y[9])))
plt.xticks([])
plt.yticks([])
plt.show()
```




3.3. Build Model

Convolution layers

- First, the layer performs several convolutions to produce a set of linear activations
- Second, each linear activation is run through a nonlinear activation function
- Third, use pooling function to modify the output of the layer further

Fully connected layers

- Simple multi layer perceptrons



First, the layer performs several convolutions to produce a set of linear activations

1 <small>$\times 1$</small>	1 <small>$\times 0$</small>	1 <small>$\times 1$</small>	0	0
0 <small>$\times 0$</small>	1 <small>$\times 1$</small>	1 <small>$\times 0$</small>	1	0
0 <small>$\times 1$</small>	0 <small>$\times 0$</small>	1 <small>$\times 1$</small>	1	1
0	0	1	1	0
0	1	1	0	0

Image


4		

Convolved
Feature


- Filter size : 3×3
- Stride : The stride of the sliding window for each dimension of input
- Padding : Allow us to control the kernel width and the size of the output independently
 - 'SAME' : zero padding
 - 'VALID' : No padding

```
conv1 = tf.nn.conv2d(x, weights['conv1'], strides= [1,1,1,1], padding = 'SAME')
```

- The number of channels: 2




Second, each linear activation is run through a nonlinear activation function




```
conv1 = tf.nn.relu(tf.add(conv1, biases['conv1']))
```

Third, use a pooling function to modify the output of the layer further

- Compute a maximum value in a sliding window (max pooling)



- Pooling size : 2×2
- Max pooling introduces invariances



```
maxp1 = tf.nn.max_pool(conv1,
                        ksize = [1, p1_h, p1_w, 1],
                        strides = [1, p1_h, p1_w, 1],
                        padding = 'VALID')
```

Fully connected layer

- Input is typically flattened features



```
output = tf.add(tf.matmul(hidden1, weights['output']), biases['output'])
```

3.4. Define a CNN Shape

In [10]:

```
input_h = 28 # Input height
input_w = 28 # Input width
input_ch = 1 # Input channel : Gray scale
# (None, 28, 28, 1)

## First convolution layer
# Filter size
k1_h = 3
k1_w = 3
# the number of channels
k1_ch = 32
# Pooling size
p1_h = 2
p1_w = 2
# (None, 14, 14, 32)

## Second convolution layer
# Filter size
k2_h = 3
k2_w = 3
# the number of channels
k2_ch = 64
# Pooling size
p2_h = 2
p2_w = 2
# (None, 7, 7, 64)

## Fully connected
# Flatten the features
# -> (None, 7*7*64)
conv_result_size = int((28/(2*2)) * (28/(2*2)) * k2_ch)
n_hidden1 = 100
n_output = 10
```

3.5. Define Weights, Biases and Network

- Define parameters based on predefined layer size
- Initialize with normal distribution with $\mu = 0$ and $\sigma = 0.1$

In [11]:

```
weights = {
    'conv1' : tf.Variable(tf.random_normal([k1_h, k1_w, input_ch, k1_ch],stddev = 0.1)),
    'conv2' : tf.Variable(tf.random_normal([k2_h, k2_w, k1_ch, k2_ch],stddev = 0.1)),
    'hidden1' : tf.Variable(tf.random_normal([conv_result_size, n_hidden1], stddev = 0.1)),
    'output' : tf.Variable(tf.random_normal([n_hidden1, n_output], stddev = 0.1))
}

biases = {
    'conv1' : tf.Variable(tf.random_normal([k1_ch], stddev = 0.1)),
    'conv2' : tf.Variable(tf.random_normal([k2_ch], stddev = 0.1)),
    'hidden1' : tf.Variable(tf.random_normal([n_hidden1], stddev = 0.1)),
    'output' : tf.Variable(tf.random_normal([n_output], stddev = 0.1))
}

x = tf.placeholder(tf.float32, [None, input_h, input_w, input_ch])
y = tf.placeholder(tf.float32, [None, n_output])
```

In [12]:

```
# Define Network
def net(x, weights, biases):
    ## First convolution layer
    conv1 = tf.nn.conv2d(x, weights['conv1'],
                        strides= [1, 1, 1, 1],
                        padding = 'SAME')
    conv1 = tf.nn.relu(tf.add(conv1, biases['conv1']))
    maxp1 = tf.nn.max_pool(conv1,
                        ksize = [1, p1_h, p1_w, 1],
                        strides = [1, p1_h, p1_w, 1],
                        padding = 'VALID'
                        )

    ## Second convolution layer
    conv2 = tf.nn.conv2d(maxp1, weights['conv2'],
                        strides= [1, 1, 1, 1],
                        padding = 'SAME')
    conv2 = tf.nn.relu(tf.add(conv2, biases['conv2']))
    maxp2 = tf.nn.max_pool(conv2,
                        ksize = [1, p2_h, p2_w, 1],
                        strides = [1, p2_h, p2_w, 1],
                        padding = 'VALID')

    # shape = conv2.get_shape().as_list()
    # maxp2_re = tf.reshape(conv2, [-1, shape[1]*shape[2]*shape[3]])
    maxp2_re = tf.reshape(maxp2, [-1, conv_result_size])

    ### Fully connected
    hidden1 = tf.add(tf.matmul(maxp2_re, weights['hidden1']), biases['hidden1'])
    hidden1 = tf.nn.relu(hidden1)
    output = tf.add(tf.matmul(hidden1, weights['output']), biases['output'])
    return output
```


3.6. Define Loss, Initializer and Optimizer

Loss

- Classification: Cross entropy
 - Equivalent to apply logistic regression

$$-\frac{1}{N} \sum_{i=1}^N y^{(i)} \log(h_{\theta}(x^{(i)})) + (1 - y^{(i)}) \log(1 - h_{\theta}(x^{(i)}))$$

Initializer

- Initialize all the empty variables

Optimizer

- GradientDescentOptimizer
- AdamOptimizer: the most popular optimizer

In [13]:


```
LR = 0.0001

pred = net(x, weights, biases)
loss = tf.nn.softmax_cross_entropy_with_logits(labels=y, logits=pred)
loss = tf.reduce_mean(loss)

# optimizer = tf.train.GradientDescentOptimizer(learning_rate).minimize(cost)
optm = tf.train.AdamOptimizer(LR).minimize(loss)

init = tf.global_variables_initializer()
```

3.7. Summary of Model



3.8. Define Configuration

- Define parameters for training CNN
 - `n_batch` : batch size for stochastic gradient descent
 - `n_iter` : the number of training steps
 - `n_prt` : check loss for every `n_prt` iteration

In [14]:

```
n_batch = 50
n_iter = 2500
n_prt = 250
```

3.9. Optimization

In [15]:

```
# Run initialize
# config = tf.ConfigProto(allow_soft_placement=True) # GPU Allocating policy
# sess = tf.Session(config=config)
sess = tf.Session()
sess.run(init)

# Training cycle
for epoch in range(n_iter):
    train_x, train_y = mnist.train.next_batch(n_batch)
    train_x = np.reshape(train_x, [-1, input_h, input_w, input_ch])
    sess.run(optm, feed_dict={x: train_x, y: train_y})

    if epoch % n_prt == 0:
        c = sess.run(loss, feed_dict={x: train_x, y: train_y})
        print ("Iter : {}".format(epoch))
        print ("Cost : {}".format(c))
```

```
Iter : 0
Cost : 2.6954658031463623
Iter : 250
Cost : 0.5047059655189514
Iter : 500
Cost : 0.2169661968946457
Iter : 750
Cost : 0.2717432677745819
Iter : 1000
Cost : 0.1554456651210785
Iter : 1250
Cost : 0.20649540424346924
Iter : 1500
Cost : 0.18961450457572937
Iter : 1750
Cost : 0.09369628131389618
Iter : 2000
Cost : 0.13712839782238007
Iter : 2250
Cost : 0.018157735466957092
```

3.10. Test

In [16]:

```
test_x, test_y = mnist.test.next_batch(100)

my_pred = sess.run(pred, feed_dict={x : test_x.reshape(-1, 28, 28, 1)})
my_pred = np.argmax(my_pred, axis=1)

labels = np.argmax(test_y, axis=1)

accr = np.mean(np.equal(my_pred, labels))
print("Accuracy : {}".format(accr*100))
```


Accuracy : 96.0%

In [17]:

```
test_x, test_y = mnist.test.next_batch(1)
logits = sess.run(tf.nn.softmax(pred), feed_dict={x : test_x.reshape(-1, 28, 28, 1)})
predict = np.argmax(logits)

plt.imshow(test_x.reshape(28, 28), 'gray')
plt.xticks([])
plt.yticks([])
plt.show()

print('Prediction : {}'.format(predict))
np.set_printoptions(precision=2, suppress=True)
print('Probability : {}'.format(logits.ravel()))
```



Prediction : 1
Probability : [0. 1. 0. 0. 0. 0. 0. 0. 0. 0.]

4. Deep Learning of Things

- CNN implemented in an Embedded System

In [18]:

```
%%html
<center><iframe src="https://www.youtube.com/embed/baPLXhjslL8"
width="560" height="315" frameborder="0" allowfullscreen></iframe></center>
```

[iSystems] CNN in Raspberry Pi



In [19]:

```
%%javascript
$.getScript('https://kmahelona.github.io/ipython_notebook_goodies/ipython_notebook_toc.js')
```

