

Class Activation Map (CAM)

Prof. Seungchul Lee

CNN with Image

- A class of deep artificial neural networks
- Most commonly applied to classifying visual images
- LeNet-5
 - The original Convolutional Neural Network model goes back to 1989 (LeCun)





Fig. 2. Architecture of LeNet-5, a Convolutional Neural Network, here for digits recognition. Each plane is a feature map, i.e. a set of units whose weights are constrained to be identical.


CNN with Image

- A class of deep artificial neural networks
- Most commonly applied to classifying visual images
- AlexNet (Krizhevsky, Sutskever, Hinton 2012)
 - ImageNet 2012 15.4% error rate



CNN with Vibration Signals

- A class of deep artificial neural networks
- Most commonly applied to classifying visual images
- A spectrogram is a visual representation of the spectrum of frequencies of signal as they vary with time




Convolutional Neural Networks

Issues on CNN (or Deep Learning)

- Deep learning performs well comparing with any other existing algorithms
- But works as a black box
 - A classification result is simply returned without knowing how the classification results are derived → little interpretability
- When we visually identify images, we do not look at the whole image
- Instead, we intuitively focus on the most important parts of the image
- When CNN weights are optimized, the more important parts are given higher weights
- Class activation map (CAM)
 - We can determine which parts of the image the model is focusing on, based on the learned weights
 - Highlighting the importance of the image region to the prediction


Fully Connected Layer



Convolutional Neural Networks

Global Average Pooling

- Class Activation Map (or Attention)




Global Average Pooling Implementation

```
## global average pooling
SUM = tf.zeros([1,7,7,1])
for i in range(int(weights['w'].shape[0])):
    SUM = tf.add(weights['w'][i]*tf.reshape(maxp2[:, :, :, i], (-1,7,7,1)), SUM)

attention = tf.reduce_sum(SUM, axis = (3))
output = tf.reduce_sum(attention, axis = (1,2))
output = tf.nn.sigmoid(output)
output = tf.stack(((1-output), output),1)
```



$$S_c = \sum_k \omega_k^c \sum_{x,y} f_k(x,y) = \underbrace{\sum_{x,y} \sum_k \omega_k^c f_k(x,y)}_{\text{Heatmap}}$$




$$P_c = \frac{\exp(S_c)}{\sum_c \exp(S_c)}$$

A 'sigmoid' block is shown with two arrows pointing to 'OK' and 'NG' boxes.


Example: MNIST



Example: MNIST



Example: Frequency Sweep



Example: Real-time Human Detection

