

Autoencoder

By Prof. Seungchul Lee
iSystems Design Lab
<http://isystems.unist.ac.kr/>
UNIST

Table of Contents

- I. 1. Unsupervised Learning
- II. 2. Autoencoders
- III. 3. Autoencoder with TensorFlow
 - I. 3.1. Import Library
 - II. 3.2. Load MNIST Data
 - III. 3.3. Define an Autoencoder Shape
 - IV. 3.4. Define Weights and Biases
 - V. 3.5. Build a Model
 - VI. 3.6. Define Loss, Initializer and Optimizer
 - VII. 3.7. Summary of Model
 - VIII. 2.8. Define Configuration
 - IX. 2.9. Optimization
 - X. 2.10. Test
- IV. 3. Visualization



1. Unsupervised Learning

Definition

- Unsupervised learning refers to most attempts to extract information from a distribution that do not require human labor to annotate example
- Main task is to find the 'best' representation of the data

Dimension Reduction

- Attempt to compress as much information about x as possible in a smaller representation
- Preserve as much information about x as possible while obeying some constraint aimed at keeping the representation simpler





2. Autoencoders

- It is like 'deep learning version' of unsupervised learning

Definition

- An autoencoder is a neural network that is trained to attempt to copy its input to its output
- The network consists of two parts: an encoder function and a decoder that produces a reconstruction




Encoder and Decoder

- Encoder function : $h = f(x)$
- Decoder function : $r = g(h)$
- We learn to set $g(f(x)) = x$


Modern Autoencoders

- Beyond deterministic functions to stochastic mapping: $p_{\text{encoder}}(h | x)$ and $p_{\text{decoder}}(x | h)$
 - Variational autoencoder (VAE)
 - Generative adversarial network (GAN)
- Will not cover them in this tutorial



3. Autoencoder with TensorFlow

- MNIST example
- Use only (1, 5, 6) digits to visualize in 2-D



3.1. Import Library

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
import tensorflow as tf
```

3.2. Load MNIST Data

```
In [2]: def batch_maker(batch_size, img, label):
img_len = len(img)
random_idx = np.random.randint(img_len, size = batch_size)
return img[random_idx], label[random_idx]
```

```
In [3]: from six.moves import cPickle

mnist = cPickle.load(open('./data_files/mnist.pkl', 'rb'))
train_idx = ((np.argmax(mnist.train.labels, 1) == 1) | \
              (np.argmax(mnist.train.labels, 1) == 5) | \
              (np.argmax(mnist.train.labels, 1) == 6))
test_idx = ((np.argmax(mnist.test.labels, 1) == 1) | \
            (np.argmax(mnist.test.labels, 1) == 5) | \
            (np.argmax(mnist.test.labels, 1) == 6))

train_imgs = mnist.train.images[train_idx]
train_labels = mnist.train.labels[train_idx]
test_imgs = mnist.test.images[test_idx]
test_labels = mnist.test.labels[test_idx]
n_train = train_imgs.shape[0]
n_test = test_imgs.shape[0]

print ("Packages loaded")
print ("The number of trainimgs : {}, shape : {}".format(n_train, train_imgs.shape))
print ("The number of testimgs : {}, shape : {}".format(n_test, test_imgs.shape))

Packages loaded
The number of trainimgs : 16583, shape : (16583, 784)
The number of testimgs : 2985, shape : (2985, 784)
```

3.3. Define an Autoencoder Shape

- Input shape and latent variable shape
- Encoder shape
- Decoder shape

```
In [4]: # Shape of input and latent variable
n_input = 28*28

# Encoder shape
n_encoder1 = 500
n_encoder2 = 300

n_latent = 2

# Decoder shape
n_decoder1 = 300
n_decoder2 = 500
```

3.4. Define Weights and Biases

- Define weights and biases for encoder and decoder, separately
- Based on the predefined layer size
- Initialize with normal distribution with $\mu = 0$ and $\sigma = 0.01$

```
In [5]: weights = {
    'encoder1' : tf.Variable(tf.random_normal([n_input, n_encoder1], stddev=0.1)),
    'encoder2' : tf.Variable(tf.random_normal([n_encoder1, n_encoder2], stddev=0.1)),
    'latent' : tf.Variable(tf.random_normal([n_encoder2, n_latent], stddev=0.1)),
    'decoder1' : tf.Variable(tf.random_normal([n_latent, n_decoder1], stddev=0.1)),
    'decoder2' : tf.Variable(tf.random_normal([n_decoder1, n_decoder2], stddev=0.1)),
    'reconst' : tf.Variable(tf.random_normal([n_decoder2, n_input], stddev=0.1))
}

biases = {
    'encoder1' : tf.Variable(tf.random_normal([n_encoder1], stddev=0.1)),
    'encoder2' : tf.Variable(tf.random_normal([n_encoder2], stddev=0.1)),
    'latent' : tf.Variable(tf.random_normal([n_latent], stddev=0.1)),
    'decoder1' : tf.Variable(tf.random_normal([n_decoder1], stddev=0.1)),
    'decoder2' : tf.Variable(tf.random_normal([n_decoder2], stddev=0.1)),
    'reconst' : tf.Variable(tf.random_normal([n_input], stddev=0.1))
}

x = tf.placeholder(tf.float32, [None, n_input])
```


3.5. Build a Model

Encoder

- Simple ANN (MLP) model
- Use *tanh* for nonlinear activation function
- *latent* is not applied with nonlinear activation function

Decoder

- Simple ANN (MLP) model
- Use *tanh* for nonlinear activation function
- *reconst* is not applied with nonlinear activation function



```
In [6]: def encoder(x, weights, biases):
        encoder1 = tf.add(tf.matmul(x, weights['encoder1']), biases['encoder1'])
        encoder1 = tf.nn.tanh(encoder1)

        encoder2 = tf.add(tf.matmul(encoder1, weights['encoder2']), biases['encoder2'])
        encoder2 = tf.nn.tanh(encoder2)

        latent = tf.add(tf.matmul(encoder2, weights['latent']), biases['latent'])

        return latent
```

```
In [7]: def decoder(latent, weights, biases):
        decoder1 = tf.add(tf.matmul(latent, weights['decoder1']), biases['decoder1'])
        decoder1 = tf.nn.tanh(decoder1)

        decoder2 = tf.add(tf.matmul(decoder1, weights['decoder2']), biases['decoder2'])
        decoder2 = tf.nn.tanh(decoder2)

        reconst = tf.add(tf.matmul(decoder2, weights['reconst']), biases['reconst'])

        return reconst
```

3.6. Define Loss, Initializer and Optimizer

Loss

- Squared loss

$$\frac{1}{N} \sum_{i=1}^N (t_i - y_i)^2$$

Initializer

- Initialize all the empty variables

Optimizer

- AdamOptimizer: The most popular optimizer


```
In [8]: LR = 0.0001

latent = encoder(x, weights, biases)
reconst = decoder(latent, weights, biases)
loss = tf.square(tf.subtract(x, reconst))
loss = tf.reduce_mean(loss)

optm = tf.train.AdamOptimizer(LR).minimize(loss)

init = tf.global_variables_initializer()
```

3.7. Summary of Model



2.8. Define Configuration

- Define parameters for training autoencoder
 - `n_batch` : batch size for stochastic gradient descent
 - `n_iter` : the number of training steps
 - `n_prt` : check loss for every `n_prt` iteration

```
In [9]: n_batch = 50  
        n_iter = 2500  
        n_prt = 250
```

2.9. Optimization


```
In [10]: # Run initialize
# config = tf.ConfigProto(allow_soft_placement=True) # GPU Allocating policy
# sess = tf.Session(config=config)
sess = tf.Session()
sess.run(init)

# Training cycle
for epoch in range(n_iter):
    train_x, train_y = batch_maker(n_batch, train_imgs, train_labels)
    sess.run(optm, feed_dict={x : train_x})

    if epoch % n_prt == 0:
        c = sess.run(loss, feed_dict={x: train_x})
        print ("Iter : {}".format(epoch))
        print ("Cost : {}".format(c))
```

```
Iter : 0
Cost : 0.3852435350418091
Iter : 250
Cost : 0.04895886033773422
Iter : 500
Cost : 0.04394324868917465
Iter : 750
Cost : 0.04409022256731987
Iter : 1000
Cost : 0.044253118336200714
Iter : 1250
Cost : 0.046419769525527954
Iter : 1500
Cost : 0.040652427822351456
Iter : 1750
Cost : 0.03434646129608154
Iter : 2000
Cost : 0.03555593267083168
Iter : 2250
Cost : 0.03936949744820595
```

2.10. Test


Test Reconstruction Performance

- To check validity of autoencoder

```
In [11]: test_x, test_y = batch_maker(1, test_imgs, test_labels)
x_reconst = sess.run(reconst, feed_dict={x : test_x})

fig = plt.figure(figsize=(5, 3))
ax1 = fig.add_subplot(1, 2, 1)
ax1.imshow(test_x.reshape(28, 28), 'gray')
ax1.set_title('Input Image', fontsize=15)
ax1.set_xticks([])
ax1.set_yticks([])

ax2 = fig.add_subplot(1, 2, 2)
ax2.imshow(x_reconst.reshape(28, 28), 'gray')
ax2.set_title('Reconstructed Image', fontsize=15)
ax2.set_xticks([])
ax2.set_yticks([])
plt.show()
```



Test Distribution of Latent Variable


- We project 784-dimensional image to 2-dimensional space

```

In [12]: test_x, test_y = batch_maker(500, test_imgs, test_labels)
test_y = np.argmax(test_y, axis=1)
test_latent = sess.run(latent, feed_dict={x : test_x})

plt.figure(figsize=(10,6))
plt.scatter(test_latent[test_y == 1,0], test_latent[test_y == 1,1], label = 'label = 1')
plt.scatter(test_latent[test_y == 5,0], test_latent[test_y == 5,1], label = 'label = 5')
plt.scatter(test_latent[test_y == 6,0], test_latent[test_y == 6,1], label = 'label = 6')
plt.title('Latent space', fontsize=15)
plt.xlabel('Z1', fontsize=15)
plt.ylabel('Z2', fontsize=15)
plt.legend(fontsize = 15)
plt.show()

```



Data Generation

```



In [13]: generate_data = np.array([[ -3, 4]])

fig = plt.figure(figsize=(15,6))
ax = plt.subplot2grid((1,3), (0,0), colspan=2)
ax.scatter(test_latent[test_y == 1,0], test_latent[test_y == 1,1], label = 'label = 1')
ax.scatter(test_latent[test_y == 5,0], test_latent[test_y == 5,1], label = 'label = 5')
ax.scatter(test_latent[test_y == 6,0], test_latent[test_y == 6,1], label = 'label = 6')
ax.scatter(generate_data[:,0], generate_data[:,1], label = 'generate', s = 150, c = 'k', marker = 'o')
ax.set_title('Latent space', fontsize=15)
ax.set_xlabel('Z1', fontsize=15)
ax.set_ylabel('Z2', fontsize=15)
ax.legend(fontsize = 15)

latent_input = tf.placeholder(tf.float32, [None, n_latent])
reconst = decoder(latent_input, weights, biases)
generate_x = sess.run(reconst, feed_dict={latent_input : generate_data})

ax = plt.subplot2grid((1, 3), (0, 2), colspan=1)
ax.imshow(generate_x.reshape(28, 28), 'gray')
ax.set_title('Generate Image', fontsize=15)
ax.set_xticks([])
ax.set_yticks([])
plt.show()

```



3. Visualization

Image Generation

- Select an arbitrary latent variable z
- Generate images using the learned decoder

```

In [14]: # Initialize canvas
nx = ny = 20
x_values = np.linspace(-8, 4, nx)
y_values = np.linspace(-4, 6, ny)
canvas = np.empty((28*ny, 28*nx))

# Define placeholder
latent_input = tf.placeholder(tf.float32, [None, n_latent])
reconst = decoder(latent_input, weights, biases)

for i, yi in enumerate(y_values):
    for j, xi in enumerate(x_values):
        latent_ = np.array([[xi, yi]])
        reconst_ = sess.run(reconst, feed_dict={latent_input : latent_})
        canvas[(nx-i-1)*28:(nx-i)*28,j*28:(j+1)*28] = reconst_.reshape(28, 28)

plt.figure(figsize=(10, 10))
plt.imshow(canvas, clim=(0, 1), cmap=plt.cm.jet)
plt.title('Manifold', fontsize=15)
plt.xticks([])
plt.xlabel('Z1', fontsize=15)
plt.yticks([])
plt.ylabel('Z2', fontsize=15)
plt.show()

```

