




# Regression 1

**Industrial AI Lab.**  
**Prof. Seungchul Lee**

# Assumption: Linear Model

$$\hat{y}_i = f(x_i ; \theta) \text{ in general}$$




- In many cases, a linear model is used to predict  $y_i$

$$\hat{y}_i = \theta_1 x_i + \theta_2$$

# Assumption: Linear Model

$$\hat{y}_i = f(x_i ; \theta) \text{ in general}$$



- In many cases, a linear model is used to predict  $y_i$


$$\hat{y}_i = \theta_1 x_i + \theta_2$$

# Linear Regression

- $\hat{y}_i = f(x_i, \theta)$  in general
- In many cases, a linear model is assumed to predict  $y_i$

Given  $\begin{cases} x_i : \text{inputs} \\ y_i : \text{outputs} \end{cases}$ , Find  $\theta_0$  and  $\theta_1$

$$x = \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_m \end{bmatrix}, \quad y = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_m \end{bmatrix} \approx \hat{y}_i = \theta_0 + \theta_1 x_i$$




- $\hat{y}_i$  : predicted output
- $\theta = \begin{bmatrix} \theta_0 \\ \theta_1 \end{bmatrix}$  : model parameters

# Linear Regression as Optimization

$$x = \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_m \end{bmatrix}, \quad y = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_m \end{bmatrix} \approx \hat{y}_i = \theta_0 + \theta_1 x_i$$

- How to find model parameters  $\theta = \begin{bmatrix} \theta_0 \\ \theta_1 \end{bmatrix}$
- Optimization problem



$$\hat{y}_i = \theta_0 + \theta_1 x_i \quad \text{such that} \quad \min_{\theta_0, \theta_1} \sum_{i=1}^m (\hat{y}_i - y_i)^2$$

# Re-cast Problem as Least Squares

- For convenience, we define a function that maps inputs to feature vectors,  $\phi$

$$\hat{y}_i = \theta_0 + x_i\theta_1 = 1 \cdot \theta_0 + x_i\theta_1$$

$$= \begin{bmatrix} 1 & x_i \end{bmatrix} \begin{bmatrix} \theta_0 \\ \theta_1 \end{bmatrix}$$

$$= \begin{bmatrix} 1 \\ x_i \end{bmatrix}^T \begin{bmatrix} \theta_0 \\ \theta_1 \end{bmatrix}$$

$$= \phi^T(x_i)\theta$$


$$\text{feature vector } \phi(x_i) = \begin{bmatrix} 1 \\ x_i \end{bmatrix}$$

$$\Phi = \begin{bmatrix} 1 & x_1 \\ 1 & x_2 \\ \vdots & \\ 1 & x_m \end{bmatrix} = \begin{bmatrix} \phi^T(x_1) \\ \phi^T(x_2) \\ \vdots \\ \phi^T(x_m) \end{bmatrix} \implies \hat{\mathbf{y}} = \begin{bmatrix} \hat{y}_1 \\ \hat{y}_2 \\ \vdots \\ \hat{y}_m \end{bmatrix} = \Phi\theta$$

# Optimization

$$\min_{\theta_0, \theta_1} \sum_{i=1}^m (\hat{y}_i - y_i)^2 = \min_{\theta} \|\Phi\theta - y\|_2^2 \quad \left( \text{same as } \min_x \|Ax - b\|_2^2 \right)$$

$$\text{solution } \theta^* = (\Phi^T \Phi)^{-1} \Phi^T y$$




# Optimization: Note

$$\begin{array}{ccccc} \text{input} & & \text{feature} & & \text{predicted output} \\ x_i & \rightarrow & \begin{bmatrix} 1 \\ x_i \end{bmatrix} & \rightarrow & \hat{y}_i \end{array}$$

$$\begin{array}{ccccc} \begin{bmatrix} 1 & x_1 \\ 1 & x_2 \\ \vdots & \vdots \\ 1 & x_m \end{bmatrix} & \begin{bmatrix} \theta_0 \\ \theta_1 \end{bmatrix} & = & \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_m \end{bmatrix} & \text{over-determined or} \\ \uparrow & \uparrow & & \uparrow & \text{projection} \\ \vec{A}_1 & \vec{A}_2 & & \vec{x} & \vec{B} \end{array}$$

$$A(= \Phi) = [\vec{A}_1 \ \vec{A}_2]$$



the same principle in a higher dimension




# 1. Solve using Linear Algebra

- known as *least square*

$$\theta = (A^T A)^{-1} A^T y$$

```
# data points in column vector [input, output]
x = np.array([0.1, 0.4, 0.7, 1.2, 1.3, 1.7, 2.2, 2.8, 3.0, 4.0, 4.3, 4.4, 4.9]).reshape(-1, 1)
y = np.array([0.5, 0.9, 1.1, 1.5, 1.5, 2.0, 2.2, 2.8, 2.7, 3.0, 3.5, 3.7, 3.9]).reshape(-1, 1)
```



# 1. Solve using Linear Algebra

- known as *least square*

$$\theta = (A^T A)^{-1} A^T y$$

```
m = y.shape[0]
#A = np.hstack([np.ones([m, 1]), x])
A = np.hstack([x**0, x])
A = np.asmatrix(A)


theta = (A.T*A).I*A.T*y

print('theta:\n', theta)
```

```
theta:
[[0.65306531]
 [0.67129519]]
```

```
# to plot
plt.figure(figsize=(10, 8))
plt.title('Regression', fontsize=15)
plt.xlabel('X', fontsize=15)
plt.ylabel('Y', fontsize=15)
plt.plot(x, y, 'ko', label="data")

# to plot a straight line (fitted line)
xp = np.arange(0, 5, 0.01).reshape(-1, 1)
yp = theta[0,0] + theta[1,0]*xp
```



## 2. Solve using Gradient Descent

$$\begin{aligned} f &= (A\theta - y)^T(A\theta - y) = (\theta^T A^T - y^T)(A\theta - y) \\ &= \theta^T A^T A\theta - \theta^T A^T y - y^T A\theta + y^T y \end{aligned}$$

$$\min_{\theta} \|\hat{y} - y\|_2^2 = \min_{\theta} \|A\theta - y\|_2^2$$

$$\nabla f = A^T A\theta + A^T A\theta - A^T y - A^T y = 2(A^T A\theta - A^T y)$$


$$\theta \leftarrow \theta - \alpha \nabla f$$

```
theta = np.random.randn(2,1)
theta = np.asmatrix(theta)

alpha = 0.001

for _ in range(1000):
    df = 2*(A.T*A*theta - A.T*y)
    theta = theta - alpha*df

print (theta)
```



### 3. Solve using CVXPY Optimization

```
theta2 = cvx.Variable([2, 1])
obj = cvx.Minimize(cvx.norm(A*theta2-y, 2))
cvx.Problem(obj, []).solve()

print('theta:\n', theta2.value)
```

```
theta:
[[0.65306531]
 [0.67129519]]
```

$$\min_{\theta} \|\hat{y} - y\|_2 = \min_{\theta} \|A\theta - y\|_2$$

### 3. Solve using CVXPY Optimization

```
theta2 = cvx.Variable([2, 1])
obj = cvx.Minimize(cvx.norm(A*theta2-y, 2))
cvx.Problem(obj, []).solve()

print('theta:\n', theta2.value)
```

$$\min_{\theta} \|\hat{y} - y\|_2 = \min_{\theta} \|A\theta - y\|_2$$

• By the way, do we have to use only  $L_2$  norm? No.  
— let's use  $L_1$  norm

- By the way, do we have to use only  $L_2$  norm? No.
  - Let's use  $L_1$  norm

```
theta1 = cvx.Variable([2, 1])
obj = cvx.Minimize(cvx.norm(A*theta1-y, 1))
cvx.Problem(obj).solve()


print('theta:\n', theta1.value)
```

$$\min_{\theta} \|\hat{y} - y\|_1 = \min_{\theta} \|A\theta - y\|_1$$

```
theta:
[[0.628129 ]
 [0.68520147]]
```

## $L_2$ Norm vs. $L_1$ Norm

- $L_1$  norm also provides a decent linear approximation.




# Regression with Outliers

- $L_1$  norm also provides a decent linear approximation.
- **What if outliers exist?**
  - Fitting with the different norms
  - source:
    - Week 9 of Computational Methods for Data Analysis by Coursera of Univ. of Washington
    - Chapter 17, online book [available](#)

# Regression with Outliers

```
# add outliers
x = np.vstack([x, np.array([0.5, 3.8]).reshape(-1, 1)])
y = np.vstack([y, np.array([3.9, 0.3]).reshape(-1, 1)])

A = np.hstack([x**0, x])
A = np.asmatrix(A)
```






# $L_2$ Norm vs. $L_1$ Norm


$$\min_{\theta} \|A\theta - y\|_2$$

```
theta2 = cvx.Variable([2, 1])
obj2 = cvx.Minimize(cvx.norm(A*theta2-y, 2))
prob2 = cvx.Problem(obj2).solve()
```



$$\min_{\theta} \|A\theta - y\|_1$$

```
theta1 = cvx.Variable([2, 1])
obj1 = cvx.Minimize(cvx.norm(A*theta1-y, 1))
prob1 = cvx.Problem(obj1).solve()
```




# Think About What Makes Different

- It is important to understand what makes them different

$$\min_{\theta} \|A\theta - y\|_1$$

$$\min_{\theta} \|A\theta - y\|_2$$




# Scikit-Learn

- Machine Learning in Python
- Simple and efficient tools for data mining and data analysis
- Accessible to everybody, and reusable in various contexts
- Built on NumPy, SciPy, and matplotlib
- Open source, commercially usable - BSD license
- <https://scikit-learn.org/stable/index.html#>



# Scikit-Learn



# Scikit-Learn: Regression

```
from sklearn import linear_model
```

```
reg = linear_model.LinearRegression()  
reg.fit(x, y)
```

```
LinearRegression(copy_X=True, fit_intercept=True, n_jobs=None,  
                 normalize=False)
```

```
reg.coef_
```

```
array([[0.67129519]])
```


```
reg.intercept_
```

```
array([0.65306531])
```

# Scikit-Learn: Regression

```
# to plot
plt.figure(figsize=(10, 8))
plt.title('Regression', fontsize=15)
plt.xlabel('X', fontsize=15)
plt.ylabel('Y', fontsize=15)
plt.plot(x, y, 'ko', label="data")

→ # to plot a straight line (fitted line)
plt.plot(xp, reg.predict(xp), 'r', linewidth=2, label="regression")
plt.legend(fontsize=15)
plt.axis('equal')
plt.grid(alpha=0.3)
plt.xlim([0, 5])
plt.show()
```



# Multivariate Linear Regression

- Linear regression for multivariate data


$$\hat{y} = \theta_0 + \theta_1 x_1 + \theta_2 x_2$$

$$\phi(x^{(i)}) = \begin{bmatrix} 1 \\ x_1^{(i)} \\ x_2^{(i)} \end{bmatrix}$$

$$\Rightarrow \theta^* = (\Phi^T \Phi)^{-1} \Phi^T y$$


$$\Phi = \begin{bmatrix} 1 & x_1^{(1)} & x_2^{(1)} \\ 1 & x_1^{(2)} & x_2^{(2)} \\ \vdots & \vdots & \vdots \\ 1 & x_1^{(m)} & x_2^{(m)} \end{bmatrix} \Rightarrow \hat{y} = \begin{bmatrix} \hat{y}^{(1)} \\ \hat{y}^{(2)} \\ \vdots \\ \hat{y}^{(m)} \end{bmatrix} = \Phi \theta$$

- Same in matrix representation



# Multivariate Linear Regression

```
#  $y = \theta_0 + \theta_1 x_1 + \theta_2 x_2 + \text{noise}$   
  
n = 200  
x1 = np.random.randn(n, 1)  
x2 = np.random.randn(n, 1)  
noise = 0.5 * np.random.randn(n, 1);  
  
y = 2 + 1 * x1 + 3 * x2 + noise
```






# Multivariate Linear Regression

$$\Phi = \begin{bmatrix} 1 & x_1^{(1)} & x_2^{(1)} \\ 1 & x_1^{(2)} & x_2^{(2)} \\ \vdots & \vdots & \vdots \\ 1 & x_1^{(m)} & x_2^{(m)} \end{bmatrix} \implies \hat{y} = \begin{bmatrix} \hat{y}^{(1)} \\ \hat{y}^{(2)} \\ \vdots \\ \hat{y}^{(m)} \end{bmatrix} = \Phi\theta$$

$$\implies \theta^* = (\Phi^T \Phi)^{-1} \Phi^T y$$


```
A = np.hstack([np.ones((n, 1)), x1, x2])
A = np.asmatrix(A)
theta = (A.T*A).I*A.T*y

X1, X2 = np.meshgrid(np.arange(np.min(x1), np.max(x1), 0.5),
                     np.arange(np.min(x2), np.max(x2), 0.5))
YP = theta[0,0] + theta[1,0]*X1 + theta[2,0]*X2
```



# Nonlinear Regression

- Linear regression for non-linear data
- Same as linear regression, just with non-linear features
- Method 1: constructing explicit feature vectors
  - polynomial features
  - Radial basis function (RBF) features
- Method 2: implicit feature vectors, **kernel trick** (*optional*)



# Nonlinear Regression

- Polynomial (here, quad is used as an example)

$$y = \theta_0 + \theta_1 x + \theta_2 x^2 + \text{noise}$$


$$\phi(x_i) = \begin{bmatrix} 1 \\ x_i \\ x_i^2 \end{bmatrix}$$

$$\Phi = \begin{bmatrix} 1 & x_1 & x_1^2 \\ 1 & x_2 & x_2^2 \\ \vdots & & \\ 1 & x_m & x_m^2 \end{bmatrix} \implies \hat{y} = \begin{bmatrix} \hat{y}_1 \\ \hat{y}_2 \\ \vdots \\ \hat{y}_m \end{bmatrix} = \Phi \theta$$

$$\implies \theta^* = (\Phi^T \Phi)^{-1} \Phi^T y$$

# Polynomial Regression


```
# y = theta0 + theta1*x + theta2*x^2 + noise  
  
n = 100  
x = -5 + 15*np.random.rand(n, 1)  
noise = 10*np.random.randn(n, 1)  
  
y = 10 + 1*x + 2*x**2 + noise
```



# Polynomial Regression

$$\theta = (A^T A)^{-1} A^T y$$

```
A = np.hstack([x**0, x, x**2])  
A = np.asmatrix(A)  
  
theta = (A.T*A).I*A.T*y  
print('theta:\n', theta)
```



## Summary: Linear Regression

- Though linear regression may seem limited, it is very powerful, since the input features can themselves include non-linear features of data
- Linear regression on non-linear features of data
- For least-squares loss, optimal parameters still are

$$\theta^* = (\Phi^T \Phi)^{-1} \Phi^T y$$