


# Linear Classification

by Prof. Seungchul Lee  
iSystems Design Lab  
<http://isystems.unist.ac.kr/>  
UNIST

## Table of Contents

- I. 1. Supervised Learning
- II. 2. Classification
- III. 3. Perceptron
  - I. 3.1. Linear Classifier
  - II. 3.2. Perceptron Algorithm
  - III. 3.3. Iterations of Perceptron
  - IV. 3.4. Perceptron loss function
  - V. 3.5. The best hyperplane separator?
  - VI. 3.6. Python Example

# 1. Supervised Learning



## 2. Classification

- where  $y$  is a discrete value
  - develop the classification algorithm to determine which class a new input should fall into
- start with binary class problems
  - Later look at multiclass classification problem, although this is just an extension of binary classification
- We could use linear regression
  - Then, threshold the classifier output (i.e. anything over some value is yes, else no)
  - linear regression with thresholding seems to work
- We will learn
  - perceptron
  - support vector machine
  - logistic regression

### 3. Perceptron

- For input  $x = \begin{bmatrix} x_1 \\ \vdots \\ x_d \end{bmatrix}$  'attributes of a customer'

- weights  $\omega = \begin{bmatrix} \omega_1 \\ \vdots \\ \omega_d \end{bmatrix}$

Approve credit if  $\sum_{i=1}^d \omega_i x_i > \text{threshold},$

Deny credit if  $\sum_{i=1}^d \omega_i x_i < \text{threshold}.$


$$h(x) = \text{sign} \left( \left( \sum_{i=1}^d \omega_i x_i \right) - \text{threshold} \right) = \text{sign} \left( \left( \sum_{i=1}^d \omega_i x_i \right) + \omega_0 \right)$$

- Introduce an artificial coordinate  $x_0 = 1$ :


$$h(x) = \text{sign} \left( \sum_{i=0}^d \omega_i x_i \right)$$

- In vector form, the perceptron implements

$$h(x) = \text{sign} (\omega^T x)$$




- Hyperplane
  - Separates a D-dimensional space into two half-spaces
  - Defined by an outward pointing normal vector  $\omega$
  - $\omega$  is orthogonal to any vector lying on the hyperplane
  - assume the hyperplane passes through origin,  $\omega^T x = 0$  with  $x_0 = 1$



### 3.1. Linear Classifier

- represent the decision boundary by a hyperplane  $\omega$
- The linear classifier is a way of combining expert opinion.
- In this case, each opinion is made by a binary "expert"
- Goal: to learn the hyperplane  $\omega$  using the training data



### 3.2. Perceptron Algorithm

The perceptron implements

$$h(x) = \text{sign}(\omega^T x)$$

Given the training set


$$(x_1, y_1), (x_2, y_2), \dots, (x_N, y_N) \quad \text{where } y_i \in \{-1, 1\}$$

1) pick a misclassified point

$$\text{sign}(\omega^T x_n) \neq y_n$$

2) and update the weight vector

$$\omega \leftarrow \omega + y_n x_n$$



### Why perceptron updates work ?

- Let's look at a misclassified positive example ( $y_n = +1$ )
  - perceptron (wrongly) thinks  $\omega_{old}^T x_n < 0$

- updates would be

$$\omega_{new} = \omega_{old} + y_n x_n = \omega_{old} + x_n$$

$$\omega_{new}^T x_n = (\omega_{old} + x_n)^T x_n = \omega_{old}^T x_n + x_n^T x_n$$

- Thus  $\omega_{new}^T x_n$  is less negative than  $\omega_{old}^T x_n$

### 3.3. Iterations of Perceptron

1. Randomly assign  $\omega$

2. One iteration of the PLA (perceptron learning algorithm)

$$\omega \leftarrow \omega + yx$$


where  $(x, y)$  is a misclassified training point

3. At iteration  $t = 1, 2, 3, \dots$ , pick a misclassified point from

$$(x_1, y_1), (x_2, y_2), \dots, (x_N, y_N)$$

4. and run a PLA iteration on it

5. That's it!



### 3.4. Perceptron loss function

$$L(\omega) = \sum_{n=1}^m \max \{0, -y_n \cdot (\omega^T x_n)\}$$

- Loss = 0 on examples where perceptron is correct, i.e.,  $y_n \cdot (\omega^T x_n) > 0$
- Loss > 0 on examples where perceptron misclassified, i.e.,  $y_n \cdot (\omega^T x_n) < 0$

**note:**  $\text{sign}(\omega^T x_n) \neq y_n$  is equivalent to  $y_n \cdot (\omega^T x_n) < 0$

### 3.5. The best hyperplane separator?

- Perceptron finds one of the many possible hyperplanes separating the data if one exists
- Of the many possible choices, which one is the best?
- Utilize distance information as well
- Intuitively we want the hyperplane having the maximum margin
- Large margin leads to good generalization on the test data
  - we will see this formally when we cover Support Vector Machine

### 3.6. Python Example

$$\omega = \begin{bmatrix} \omega_1 \\ \omega_2 \\ \omega_3 \end{bmatrix}$$
$$x = \begin{bmatrix} (x^{(1)})^T \\ (x^{(2)})^T \\ (x^{(3)})^T \\ \vdots \\ (x^{(m)})^T \end{bmatrix} = \begin{bmatrix} 1 & x_1^{(1)} & x_2^{(1)} \\ 1 & x_1^{(2)} & x_2^{(2)} \\ 1 & x_1^{(3)} & x_2^{(3)} \\ \vdots & \vdots & \vdots \\ 1 & x_1^{(m)} & x_2^{(m)} \end{bmatrix}$$
$$y = \begin{bmatrix} y^{(1)} \\ y^{(2)} \\ y^{(3)} \\ \vdots \\ y^{(m)} \end{bmatrix}$$

In [1]:

```
import numpy as np
import matplotlib.pyplot as plt

% matplotlib inline
```

In [2]:

```
#training data gereration
m = 100
x1 = 8*np.random.rand(m, 1)
x2 = 7*np.random.rand(m, 1) - 4

g0 = 0.8*x1 + x2 - 3
g1 = g0 - 1
g2 = g0 + 1
```




```
C1 = np.where(g1 >= 0)
C2 = np.where(g2 < 0)
print(C1)
```

In [4]:

(24, )  
(45, )

```
plt.figure(figsize=(10, 6))
plt.plot(x1[C1], x2[C1], 'ro', label='C1')
plt.plot(x1[C2], x2[C2], 'bo', label='C2')
plt.title('Linearly seperable classes', fontsize=15)
plt.legend(loc='upper left', fontsize=15)
plt.xlabel(r'$x_1$', fontsize=20)
plt.ylabel(r'$x_2$', fontsize=20)
plt.show()
```



$$x = \begin{bmatrix} (x^{(1)})^T \\ (x^{(2)})^T \\ (x^{(3)})^T \\ \vdots \\ (x^{(m)})^T \end{bmatrix} = \begin{bmatrix} 1 & x_1^{(1)} & x_2^{(1)} \\ 1 & x_1^{(2)} & x_2^{(2)} \\ 1 & x_1^{(3)} & x_2^{(3)} \\ \vdots & \vdots & \vdots \\ 1 & x_1^{(m)} & x_2^{(m)} \end{bmatrix}$$

$$y = \begin{bmatrix} y^{(1)} \\ y^{(2)} \\ y^{(3)} \\ \vdots \\ y^{(m)} \end{bmatrix}$$

In [6]:

```
X1 = np.hstack([np.ones([C1.shape[0],1]), x1[C1], x2[C1]])
X2 = np.hstack([np.ones([C2.shape[0],1]), x1[C2], x2[C2]])
X = np.vstack([X1, X2])

y = np.vstack([np.ones([C1.shape[0],1]), -np.ones([C2.shape[0],1])])

X = np.asmatrix(X)
y = np.asmatrix(y)
```

$$\omega = \begin{bmatrix} \omega_1 \\ \omega_2 \\ \omega_3 \end{bmatrix}$$

$$\omega \leftarrow \omega + yx$$

where  $(x, y)$  is a misclassified training point

In [7]:

```
w = np.ones([3,1])
w = np.asmatrix(w)

n_iter = y.shape[0]
for k in range(n_iter):
    for i in range(n_iter):
        if y[i,0] != np.sign(X[i,:]*w)[0,0]:
            w += y[i,0]*X[i,:].T

print(w)
```


```
[[ -9.          ]
 [ 1.97353111]
 [ 3.8229637  ]]
```

$$g(x) = \omega^T x + \omega_0 = \omega_1 x_1 + \omega_2 x_2 + \omega_0 = 0$$

$$\implies x_2 = -\frac{\omega_1}{\omega_2} x_1 - \frac{\omega_0}{\omega_2}$$

```
x1p = np.linspace(0,8,100).reshape(-1,1)
x2p = - w[1,0]/w[2,0]*x1p - w[0,0]/w[2,0]

plt.figure(figsize=(10, 6))
plt.scatter(x1[C1], x2[C1], c='r', s=50, label='C1')
plt.scatter(x1[C2], x2[C2], c='b', s=50, label='C2')
plt.plot(x1p, x2p, c='k', label='perceptron')
plt.xlim([0,8])
plt.xlabel('$x_1$', fontsize = 20)
plt.ylabel('$x_2$', fontsize = 20)
plt.legend(loc = 4, fontsize = 15)
plt.show()
```



In [9]:

```
# animation

import matplotlib.animation as animation
% matplotlib qt5

fig = plt.figure(figsize=(10, 6))
ax = fig.add_subplot(1, 1, 1)
plot_C1, = ax.plot(x1[C1], x2[C1], 'go', label='C1')
plot_C2, = ax.plot(x1[C2], x2[C2], 'bo', label='C2')
plot_perceptron, = ax.plot([], [], 'k', label='perceptron')

ax.set_xlim(0, 8)
ax.set_ylim(-3.5, 4.5)
ax.set_xlabel(r'$x_1$', fontsize=20)
ax.set_ylabel(r'$x_2$', fontsize=20)
ax.legend(fontsize=15, loc='upper left')

n_iter = y.shape[0]

def init():
    plot_perceptron.set_data(x1p, x2p)
    return plot_perceptron,

def animate(i):
    global w
    idx = i%n_iter
    if y[idx,0] != np.sign(X[idx,:]*w)[0,0]:
        w += y[idx,0]*X[idx,:].T
        x2p = - w[1,0]/w[2,0]*x1p - w[0,0]/w[2,0]
        plot_perceptron.set_data(x1p, x2p)
    return plot_perceptron,

w = np.ones([3,1])
x1p = np.linspace(0,8,100).reshape(-1,1)
x2p = - w[1,0]/w[2,0]*x1p - w[0,0]/w[2,0]

ani = animation.FuncAnimation(fig, animate, np.arange(0, n_iter**2), init_func=init,
                              interval=0, repeat=False)
plt.show()
```

In [10]:

```
%%javascript
$.getScript('https://kmahelona.github.io/ipython_notebook_goodies/ipython_notebook_toc.
js')
```