

REMOTE HUMAN-IN-THE-LOOP CONTROL

Multi-Day Claude Code SDLC from MacBook + iPhone

Revised, corrected, expanded operations manual

MacBook Pro M4 / macOS Sequoia | iPhone 15 Pro / AT&T | Spectrum home WAN
Ghostty or terminal host | local repo + external SSD | 20-60 minute HITL cadence

Bottom line Use first-party Claude Code Remote Control as the decision plane; add a separate audible pager triggered by deterministic Claude Code hooks; keep a durable terminal session plus Tailscale/SSH or Mosh as the execution-plane recovery path. Do not rely on a single iOS push channel, an immortal transcript, or --dangerously-skip-permissions on an unisolated laptop.

AS OF 28 AUGUST 2026

Target file: manual_hitl-remote-claude-code-iphone_v1_sol56xhigh_20260828.pdf

Research basis: supplied Grok v1 manual + supplied long-session customization research brief + fresh primary-source verification on 28 Aug 2026.

1. Executive verdict

The original manual correctly recognized that this is not fundamentally an **SSH-uptime problem**. The high-cost failure is the agent reaching a **human decision checkpoint** while the operator is away from the Mac. The required system is therefore a **multi-plane operations stack**: a **decision plane** for the actual Claude conversation, an independent **attention/pager plane**, an **execution-plane** recovery shell, and **durable project state outside** the chat transcript.

Recommended production stack

Plane	Default	Why	Fallback
Decision	Claude Code Remote Control + Claude iOS Code tab	First-party, bidirectional, same local process and environment.	Happy or heypandax/CC Pocket for sessions intentionally started under those control planes.
Attention	Claude hooks -> Bark (free OSS) or Pushover (low-cost)	Deterministic events and audible iOS delivery independent of Claude mobile push.	Moshi agent inbox/push; ntfy for non-critical/general alerts.
Persistence	tmux baseline	Officially aligned, simple, mature; process survives phone/SSH disconnect.	Herd for agent-aware blocked/working/done/idle visibility.
Recovery	Tailscale + traditional SSH/Mosh; Moshi if desired	No router port-forwarding; gives a real terminal when Remote Control UI fails.	Local physical access.
State	Repo artifacts + issue tracker + CONTEXT/ADR/HANDOFF	Survives compaction, resume, client changes and session loss.	Exported transcript is evidence, not the sole system of record.

Ten operating rules

1. **Remote Control** is the **primary phone conversation surface**; it is not a remote shell.
2. Treat **Claude mobile push as best-effort** until you personally verify sound/vibration on the exact iPhone build; current issue history includes silent iOS pushes.
3. Page immediately on **PreToolUse:AskUserQuestion** and **PermissionRequest**; do not misuse **idle_prompt** as the primary "blocked" event.
4. Keep a **separate recovery path** because current open iOS issues include **MCP permission dialogs that can block invisibly and permission flows** that can trap the composer.
5. Run the **long-lived shell in tmux**; use **Herd** only if its agent-awareness materially helps **multi-pane** operations.
6. **Do not expose SSH on the public Spectrum router**. **Reach the Mac through Tailscale**; on ordinary macOS Tailscale clients use regular SSH over the tailnet.
7. Leave the **MacBook open and powered for** the least fragile unattended host configuration; **caffeinate alone** is not a contractual closed-lid guarantee.
8. Move **durable decisions into CONTEXT.md, ADRs, tracker tickets, wayfinder artifacts and end-of-day HANDOFF.md**; a five-day transcript is a lossy cache after repeated compaction.
9. Prefer **sandbox + auto/targeted permission rules on the local Mac**. Anthropic now explicitly says `bypassPermissions` is for isolated containers/VMs.
10. **Acceptance-test the whole path over AT&T cellular** with the **phone locked** before depending on it away from home.

Version-sensitive facts Claude Code is changing quickly. The commands and hook types below were verified against live docs on **28 Aug 2026**. **Re-run claude doctor and re-check** the linked docs after CLI upgrades, especially **Remote Control**, **hooks**, **mobile permissions**, and **notification behavior**.

2. Problem restatement, scope, and major corrections to v1

The supplied background research brief asks for implementation-ready methods for **long-running, hours-to-multi-day AI-SWE sessions with reliability, repeatability, context survival, token efficiency and safety gates**. This manual narrows that broader problem to remote HITL operation of an already-running local Claude Code SDLC, while retaining the same reliability and safety bar.

The supplied v1 manual assumes **a MacBook Pro M4 with 24 GB unified memory, iPhone 15 Pro on AT&T, Spectrum residential WAN, Ghostty, a local/external-volume checkout, a 5-day Claude Code chat, frequent compaction, mattpocock skills and 20-60 minute decision intervals**. Those operational constraints remain useful; several implementation claims required correction.

Corrections that materially change the design

v1 advice / implication	Verified correction as of 28 Aug 2026	Operational import
Remote Control effectively described as Max-only.	The live page currently says "available on all plans" near the top, while its Requirements section enumerates Pro, Max, Team and Enterprise; API keys remain unsupported.	Treat live account/CLI eligibility as operative and do not tie the architecture to a Max-only assumption.
"Local" wording could imply the session stays entirely on the Mac.	Execution/filesystem remain local, but while Remote Control is connected the session transcript is stored on Anthropic servers for sync/reconnect .	Make an explicit privacy/compliance decision before enabling RC.
Notification matcher included agent_notification .	Current types include agent_needs_input and agent_completed ; agent_notification is not in the current matcher list.	Use live schema , not older examples.
idle_prompt treated as a decision/block signal.	idle_prompt fires ~60 seconds after Claude finished responding and the user has not typed.	It is a noisy fallback , not the primary HITL doorbell.
Bark / ntfy grouped as equivalent Critical Alert choices.	Bark documents critical alerts now; ntfy iOS critical-alert support is listed for v1.8.0 UNRELEASED , while stable iOS is v1.7.0 .	Prefer Bark or Pushover for critical attention today.
Herdrr presented as required host multiplexer.	Official Anthropic guidance uses tmux/screen as persistence primitives; Herdrr is an optional agent-aware upgrade .	Start with fewer moving parts .
Tailscale SSH implied as normal on Mac.	Tailscale SSH server requires the open-source tailscale+tailscaled macOS variant ; standard sandboxed macOS builds should use regular SSH over Tailscale .	Use the supported simple path : Remote Login + SSH key + tailnet address .
caffeinate/"disable lid sleep" could read as sufficient for clamshell operation.	Closed-display behavior on Apple Silicon is a separate operational problem; Amphetamine exposes a specific Closed-Display Mode/Power Protect path.	Safest unattended baseline is lid open + power + no-sleep setting.
Happy implied it can simply attach to an arbitrary existing vanilla process.	Happy documents starting with happy claude / happy codex; treat it as a wrapper/control plane for sessions started under it unless tested otherwise.	Do not wrap the irreplaceable 5-day session mid-flight .
--dangerously-skip-permissions normalized as a laptop default.	Anthropic says bypassPermissions should only be used in isolated containers/VMs where damage is constrained.	Move routine AFK work to sandbox + auto/targeted permissions ; keep dangerous bypass for isolation only .

3. Target architecture: four independent planes

The robust design deliberately **avoids a single point of failure**. A phone notification is not the session. A session is not the durable project memory. A remote conversation UI is not an execution shell. **Each responsibility gets its own mechanism**.

Reference architecture

iPhone	Claude app / Code tab	Bark or Pushover + optional Moshi
	decision / steer	^ audible pager / ack
Internet	Anthropic Remote Control (TLS)	APNs / pager service + Tailscale WireGuard
	bidirectional sync	
Mac host	tmux -> Claude Code process	hook scripts + traditional SSH/Mosh
State	repo + tests + MCP + local tools	CONTEXT.md / ADRs / tracker / HANDOFF.md

Decision plane

Claude Code stays on the Mac. **Remote Control connects** the Claude app or claude.ai/code to that local process, and both **phone and terminal can write into the same conversation**. Filesystem, tools and MCP remain on the host; **transcript synchronization** is handled by Anthropic while Remote Control is connected. [A1]

Attention plane

The **native Claude push channel** is convenient but not sufficient as the only doorbell. Claude Code **hooks provide deterministic event edges**. The key design is to fire an **asynchronous pager** at the instant an **AskUserQuestion** tool call or **PermissionRequest** occurs, then use **Notification events for delayed/fallback** classes such as **MCP elicitation and sandbox network** prompts. [A2]

Execution plane

Tailscale plus ordinary SSH/Mosh gives a **real terminal path** that is **independent of the Remote Control** renderer. It is the recovery mechanism for mobile UI bugs, MCP dialogs, reauthentication, shell-only slash commands, failed hooks, or host diagnosis. **Moshi is the strongest inexpensive native mobile cockpit** if you want this path to be pleasant rather than merely available. [T1][M1]

State plane

A multi-day session must be **restartable from artifacts**. **Project-root CLAUDE.md**, auto-memory, plans and certain recent files **survive compaction** in defined ways, but the transcript is still summarized. **Decisions and stage status** therefore belong on **disk/tracker**, not only in conversational history. [A5][A6]

4. Ship-today setup: the 30-minute robust baseline

This chapter is the shortest path from the v1 environment to a demonstrably reliable remote loop. It does **not require Herdr, Happy, Moshi Pro, a public port, or a cloud VM.**

Step 1 - verify the host and Claude authentication

```
cd /path/to/project
claude --version
claude doctor
claude
# In Claude Code, confirm workspace trust and claude.ai login if prompted.
```

Remote Control requires a **claude.ai subscription login** and **direct use of api.anthropic.com**. **API-key-only sessions, Bedrock/Agent Platform/Foundry, enterprise Claude apps gateway, or a custom ANTHROPIC_BASE_URL do not support it.** Certain **telemetry/feature-flag disabling variables also prevent** eligibility checks. [A1]

Step 2 - put the live shell in tmux

```
brew install tmux jq
cd /path/to/project
tmux new-session -A -s project-sdlc
# Start Claude inside tmux for a new durable session:
claude --remote-control "Project SDLc"
```

For the already-running five-day chat, do not restart just to obtain tmux. First write a **handoff/snapshot**. If the current process is already in a **durable multiplexer**, leave it. If it is not, **add durability at the next clean session boundary** rather than risking the only live process.

Step 3 - attach Remote Control to an existing session

```
# Inside the existing Claude Code conversation:
/remote-control
# or
/rc

# Then open /config and enable:
# - Enable Remote Control for all sessions (optional user-level default)
# - Push when Claude decides
# - Push when actions required
```

The setting equivalent is **remoteControlAtStartup=true** in **~/.claude/settings.json**. Project/local files can force false but cannot force true for everyone who opens a repo. [A1]

Step 4 - install the independent pager

```
mkdir -p "$HOME/.claude/hooks" "$HOME/.config/claude-hitl"
chmod 700 "$HOME/.claude/hooks" "$HOME/.config/claude-hitl"
# Create pager.env and hitl-pager.sh using Chapter 5.
chmod 600 "$HOME/.config/claude-hitl/pager.env"
chmod 700 "$HOME/.claude/hooks/hitl-pager.sh"
```

Default recommendation: **Bark** if you want free/open-source custom iOS push; **Pushover** if a **\$4.99 one-time iOS license** is acceptable and repeated emergency notifications/acknowledgement are useful. [B1][P1]

Step 5 - configure the recovery path

- **Tailscale**: install the recommended macOS standalone app; **Personal** is **\$0 for up to 6 users** for personal use. [T2]
- **macOS**: **System Settings** -> General -> Sharing -> **Remote Login**; restrict allowed users; use an **SSH** key.
- **Network**: do not create router port-forwarding for SSH. Connect to the **Mac's Tailscale/MagicDNS address** from the phone.
- **Client**: **Moshi** is the most integrated agent-focused option; **another SSH/Mosh client** is sufficient for **break-glass access**.

Step 6 - perform the cellular acceptance test

11. Turn **iPhone Wi-Fi OFF** so the test uses AT&T.
12. **Lock the phone** and put it in a pocket.
13. Trigger a **controlled AskUserQuestion** in the **Claude** session.
14. Confirm the independent **pager makes an audible alert** within seconds.
15. **Open Claude -> Code** and answer the question; verify the turn appears in the Mac terminal.
16. Trigger a **permission request in a disposable/safe context** if **your permission mode uses prompts**.
17. **Temporarily disable Remote Control** or simulate a **UI failure**, then connect through **Tailscale/SSH** and **reattach to tmux**.
18. Record pass/fail and do not leave home **until every required path passes**.

5. Deterministic iPhone doorbell with Claude Code hooks

The most important technical correction is **event selection**. A remote HITL pager should fire on events that mean "the agent is asking for a human" rather than on **generic inactivity**.

Recommended event policy

Event / matcher	Timing	Pager priority	Use
PreToolUse / AskUserQuestion	Immediately before the question tool is processed	HIGH	Primary decision-page edge. AskUserQuestion is explicitly matchable.
PermissionRequest / *	Immediately when Claude is about to ask permission	HIGH	Primary permission-page edge when permission prompts are used.
Notification / permission_prompt	~6s after an unanswered permission prompt	HIGH fallback	Catches sandbox network prompts not covered by PermissionRequest.
Notification / elicitation_dialog elicitation_url_dialog	~6s after MCP elicitation waits	HIGH	MCP forms/URL requests.
Notification / agent_needs_input	When a background session is waiting, with current version constraints	HIGH	Useful for agent-view workflows.
Notification / quota_auto_resume_stale quota_auto_resume_disabled	On failed/disabled quota resume	MEDIUM	Prevents multi-hour silent stalls.
Notification / agent_completed	Completion event	LOW	Optional chirp; can be noisy.
Notification / idle_prompt	~60s after Claude finished responding and user did not type	OFF by default	Not a reliable blocked-state detector; enable only as a low-priority audit.

User-level hook configuration

~/.claude/settings.json

```
{
  "remoteControlAtStartup": true,
  "hooks": {
    "PreToolUse": [
      {
        "matcher": "AskUserQuestion",
        "hooks": [
          {
            "type": "command",
            "command": "$HOME/.claude/hooks/hitl-pager.sh",
            "async": true
          }
        ]
      }
    ],
    "PermissionRequest": [
      {
        "matcher": "*",
        "hooks": [
          {
            "type": "command",
            "command": "$HOME/.claude/hooks/hitl-pager.sh",
            "async": true
          }
        ]
      }
    ],
    "Notification": [
      {
        "matcher": "permission_prompt|elicitation_dialog|elicitation_url_dialog|agent_needs_input|
quota_auto_resume_stale|quota_auto_resume_disabled",
        "hooks": [
          {
            "type": "command",
            "command": "$HOME/.claude/hooks/hitl-pager.sh",
            "async": true
          }
        ]
      }
    ]
  }
}
```

Why `async`: command hooks block Claude by default; `async=true` turns the network call into a background side effect, which is exactly what a pager should be. An asynchronous hook cannot control the tool decision, which is desirable here. [A2]

Bark pager implementation (recommended free/OSS default)

```
# ~/.config/claude-hitl/pager.env
# Treat this URL/device key as a secret. Never commit this file.
BARK_URL='https://api.day.app/YOUR_DEVICE_KEY'
BARK_LEVEL='timeSensitive' # set to critical only after testing

~/claude/hooks/hitl-pager.sh
#!/usr/bin/env bash
set -euo pipefail

ENV_FILE="$HOME/.config/claude-hitl/pager.env"
[[ -r "$ENV_FILE" ]] || exit 0
# shellcheck disable=SC1090
source "$ENV_FILE"

payload="$(cat)"
event="$(jq -r '.hook_event_name // "Claude"' <<<"$payload")"
tool="$(jq -r '.tool_name // empty' <<<"$payload")"
kind="$(jq -r '.notification_type // empty' <<<"$payload")"
question="$(jq -r '.tool_input.questions[0].question // .message // empty' \
  <<<"$payload" | tr '\n' ' ' | cut -c1-180)"

title='Claude needs input'
body="{kind:-${tool:-$event}}}"
[[ -n "$question" ]] && body="$body - $question"

jq -nc --arg title "$title" --arg body "$body" --arg level "${BARK_LEVEL:-timeSensitive}" \
  '{title:$title,body:$body,sound:"alarm",level:$level,group:"claude-hitl"}' \
  | curl -fsS --retry 2 --max-time 5 \
    -H 'Content-Type: application/json' -d @- "$BARK_URL" >/dev/null || true

exit 0
```

Bark documents `timeSensitive` and `critical` levels; its `critical` level is intended to ignore silent/DND and play sound. iOS still controls app permissions, so enable the needed notification permissions and test. [B1]

Pushover alternative for acknowledged/repeating alerts

Pushover costs \$4.99 once per platform for individuals after a 30-day trial. Its emergency `priority=2` repeats until acknowledged and requires `retry` and `expire` values; high `priority=1` plays sound/vibrates subject to device configuration. [P1][P2]

```
# Example POST for a genuine emergency-style page. Use sparingly.
curl -fsS https://api.pushover.net/1/messages.json \
  -F token="$PUSHOVER_APP_TOKEN" \
  -F user="$PUSHOVER_USER_KEY" \
  -F title='Claude needs input' \
  -F message="$body" \
  -F priority=2 \
  -F retry=60 \
  -F expire=900 >/dev/null
```

Do not leak source code into push Pager payloads should contain only the event class, repo/session nickname and a short decision summary. Do not send diffs, secrets, credentials, private document text, or the full prompt to a third-party push service. Keep pager credentials in a `chmod 600` file outside the repository.

6. Claude Code Remote Control: exact operating model

Remote Control is the correct primary decision surface for this use case because it **binds phone/web clients to a local Claude Code process** rather than starting a **separate vendor VM**. The local process remains the executor and retains the filesystem, MCP servers and project configuration. [A1]

Ways to start / attach

Use case	Command	Notes
Dedicated server mode	<code>claude remote-control</code>	Serves Remote Control sessions; can spawn same-dir/worktree/session modes.
Normal interactive session + RC	<code>claude --remote-control "Name"</code>	Local terminal stays interactive; shorthand <code>--rc</code> .
Existing running conversation	<code>/remote-control</code> or <code>/rc</code>	Carries the existing conversation into Remote Control.
Resume server-started session	<code>claude remote-control --continue</code>	Current docs: works for about four hours after server stop; version requirements apply.
Resume by ID	<code>claude remote-control --session-id <id></code>	Current docs: v2.1.200+; also about four-hour server-stop window.
Parallel server sessions	<code>--spawn worktree --capacity N</code>	Prefer worktrees over same-dir when multiple sessions edit concurrently.

Security and privacy boundary

- **Good:** the Mac opens **no inbound port** for Remote Control; the local process makes **outbound HTTPS connections** through the **Anthropic API over TLS**.
- **Important:** while Remote Control is connected, the **session transcript - messages, responses and tool activity** - is stored on **Anthropic servers** for device sync and reconnect.
- **Still local:** **execution and filesystem access remain on the host**. Remote Control does not make the iPhone a filesystem mount or shell.
- **Compliance:** organizations with incompatible data-retention settings such as **Zero Data Retention** cannot enable Remote Control.
- **Auth:** **API keys are not supported**. A custom `ANTHROPIC_BASE_URL` or third-party gateway prevents Remote Control because the session is no longer talking directly to `api.anthropic.com`.

Push behavior

In `/config` enable both **Push** when **Claude decides** and **Push** when **actions required**. Native push has **no per-event policy** beyond those toggles, which is why the **independent hook pager remains necessary**. **iOS Focus and Notification Summary** can suppress/delay pushes. [A1]

Current failure modes that justify the break-glass shell

Issue	Status on 28 Aug 2026	Implication
#53709 - iOS RC pushes arrive without sound/vibration	Closed, but real historical device report (iPhone 15 Pro)	Never assume native push is an audible pager until your exact device passes a locked-phone cellular test.
#87751 - native MCP tool-permission dialogs do not render on iPhone RC; <code>AskUserQuestion</code> works	Open, Aug 18 2026	A session can look idle on phone while terminal shows a blocking MCP prompt. Keep terminal access.
#89182 - composer locked during mobile permission prompt ; denial can advance into another prompt	Open, Aug 24 2026	Avoid approval-heavy workflows from phone; reduce prompt count with safe permissions/sandbox and retain shell access.

Connection notes

- **Interactive RC:** during extended network loss the local session can keep working and Claude Code retries; server mode gives up after roughly 10 minutes offline.
- **Forwarded dialogs:** permission prompts and `AskUserQuestion` remain open until answered; other forwarded dialogs can expire after a default wait. Keep terminal access because some session commands are local-only.

7. iPhone 15 Pro configuration and alert acceptance tests

The **phone is a client**, not the process host. **iOS can suspend the app**; the **Mac/tmux session must remain authoritative**. Configure notifications and Focus to make the phone a reliable operator endpoint, then test real cellular delivery.

Claude app

19. Install/update Claude; sign in with the same account and organization as the terminal session.
20. Open Code and verify the named Remote Control session appears with online status.
21. iOS Settings -> Notifications -> Claude: Allow Notifications ON; enable Sounds, Lock Screen and Banners as desired.
22. Claude Code /config: enable Push when Claude decides and Push when actions required.
23. If /config says no mobile is registered, open the Claude app so it refreshes its push token, then reconnect Remote Control.

Pager app

- **Bark:** enable notifications; use timeSensitive for routine HITL, and only use critical after confirming the app/device permits it and the behavior is appropriate.
- **Pushover:** choose an alert sound and use priority 1 for high priority or priority 2 only when repeated acknowledgement-style paging is warranted.
- **Focus:** either allow the pager app through relevant Focus modes or use a tested interruption level. Notification Summary should not batch the pager.
- **AT&T path:** test with Wi-Fi disabled. A local-LAN test proves almost nothing about away-from-home reliability.

Acceptance test matrix

Test	Expected phone behavior	Expected Mac behavior	Pass criterion
AskUserQuestion	Pager sounds; Claude Code card visible	Terminal shows pending question	Phone answer resumes turn within seconds.
PermissionRequest	Pager sounds immediately; native RC may also push	Terminal shows permission prompt	Remote response or shell answer unblocks safely.
MCP elicitation	Pager after ~6s if unanswered	Terminal shows elicitation form/URL	Operator knows it is blocked even if mobile renderer fails.
Network switch	Phone moves Wi-Fi -> LTE	Claude process unaffected	RC reconnects or shell path remains available.
RC UI failure	Claude UI unavailable/stuck	tmux process continues	Tailscale/SSH attaches and resolves block.
Phone locked 20 min	No active app required	Host keeps working	Next hook still produces audible notification.

8. Treat the MacBook as a temporary server - without pretending it is one

The MacBook Pro M4 is capable, but a **laptop has failure modes** a Mac mini or server does not: **lid-close sleep, power transitions, Wi-Fi roaming, GUI memory pressure and external-drive disconnection**. The right response is operational discipline, not more remote-control software.

Power / sleep baseline

- **Least fragile:** power **adapter connected, lid open, macOS** setting to prevent automatic sleep while display is off, display allowed to sleep, and **caffeinate** as an additional assertion if desired.
- **Closed lid:** use Apple-supported **clamshell conditions** or a deliberately tested utility. **Amphetamine** exposes Closed-Display Mode and Drive Alive; on **Apple Silicon** its **Power Protect** feature exists because power-source changes can affect closed-display behavior. [MAC1]
- **Do not claim:** **caffeinate -dims** by itself guarantees that an Apple Silicon MacBook will remain an unattended server with the lid closed.

```
# Additional keep-awake assertion while the shell is running.
# Treat this as one layer, not a closed-lid guarantee.
caffeinate -dimsu
```

Process persistence

```
# Named durable session
tmux new-session -A -s project-sdlc

# Useful checks
tmux list-sessions
tmux attach -t project-sdlc
```

If you prefer richer agent visibility, **Herd** is a credible fast-moving upgrade: its **sidebar recognizes blocked/working/done/idle** states and supports **Claude Code and Codex**. It is not necessary for correctness and should **not displace tmux** unless its **additional state model** pays for the extra dependency. [H1]

24 GB memory budget

- **Cap concurrency:** do not equate "subagent" with a separate giant local model, but remember that browser tabs, IDEs, test servers, Docker, local databases, build caches and terminal panes can **drive swap pressure**.
- **Use worktrees:** for parallel editing, **use separate worktrees rather than several agents writing the same checkout**. Remote Control server mode now has **--spawn worktree**.
- **Observe:** keep **Activity Monitor** or **memory_pressure** available; close unused Electron/browser workloads before multi-hour unattended waves.
- **Fail safe:** if the host **starts thrashing**, reduce parallel work before adding another phone-control daemon.

External 4 TB SSD

- **Durability:** if the active repo is on the OWC volume, a cable/power/idle unmount is equivalent to losing the project mid-session.
- **Safer placement:** keep the **active git worktree and critical environment** on the **internal SSD** when practical; use external storage for **corpora, caches and large assets**.
- **If external is required:** use a stable cable/power path, disable unintended drive sleep where appropriate, and include "volume mounted" in the recovery checklist.

9. Break-glass terminal: Tailscale + regular SSH/Mosh

Do not port-forward the Mac's SSH service on a residential router. Tailscale gives the iPhone and Mac a private WireGuard overlay and works through NAT/CGNAT. For the normal macOS Tailscale app, use ordinary SSH over the tailnet rather than assuming the Mac is a Tailscale SSH server. [T1][T3]

Mac setup

24. Install the recommended Tailscale standalone macOS client and sign into the same tailnet as the iPhone.
25. System Settings -> General -> Sharing -> Remote Login: turn on. Limit SSH access to the intended account.
26. Generate/import an SSH key in the phone client and append only the public key to ~/.ssh/authorized_keys on the Mac.
27. From the iPhone, connect to the Mac's MagicDNS name or Tailscale IP with the ordinary SSH/Mosh client.
28. Reattach to tmux: tmux attach -t project-sdlc.

Tailscale SSH nuance Tailscale documents that its SSH server component on macOS is available only on the open-source tailscale+tailscaled CLI variant. The recommended standalone/App Store macOS apps are not Tailscale SSH servers. Regular SSH over the Tailscale network works and is the simpler choice here.

Moshi as the rich execution-plane client

Moshi is strong when you want more than emergency shell access: native chat support for Claude Code and Codex, agent-aware hooks/inbox, push notifications, diff/browser views, SSH/Mosh transport and direct transcript streaming from host to phone through an SSH-forwarded local gateway. Its current free tier includes SSH, agent monitoring and push; Pro is \$7.99/month, \$69.99/year, or \$199 lifetime (limited offer, verify before purchase). [M1][M2]

Use Moshi when one iOS app should also drive Codex/Grok/other CLI panes, when you want Dynamic-Island/agent-inbox style workflow, or when Remote Control mobile rendering is the recurrent failure. It is an execution cockpit, not a reason to remove first-party Remote Control if Remote Control is working well.

10. Market landscape: ranked alternatives and when to use them

There are **three distinct product classes**. Do not compare them as if they were interchangeable: **first-party conversation sync**, **third-party agent control planes**, and **remote terminals** solve different parts of the problem.

Option	Class / cost	Strength	Important caveat	Rank for this use
Claude Remote Control	First-party; included with eligible subscription	Same local Claude session; bidirectional phone/web/terminal control	Transcript stored on Anthropic while connected; mobile push/UI issues exist	1 - primary decision plane
Bark	Free OSS iOS pager	Simple custom APNs push; timeSensitive/critical documented	Device key is a secret; no agent chat	1A - default pager
Pushover	\$4.99 one-time iOS individual license	Mature high/emergency priority; emergency repeats until acknowledged	Third-party service; keep payload minimal	1B - strongest low-cost pager
Tailscale + SSH/tmux	\$0 Personal for non-commercial personal use	Vendor-neutral break-glass shell without public port	Requires host awake + SSH hardening	1 - recovery plane
Moshi	Free terminal; optional Pro	Agent inbox/chat + real terminal + Mosh/Tailscale; multi-CLI	Commercial; more moving parts than pure RC	2 - best rich recovery / multi-CLI cockpit
Happy	MIT; free OSS	Claude + Codex mobile/web with E2E encryption; mature adoption	Docs say start with happy claude/codex; treat as wrapper for sessions started under it	2 - best mature OSS alternative control plane
heypandax/CC Pocket	MIT; local-first OSS	Zero-knowledge relay, E2E, multi-agent control from mobile	Younger ecosystem; verify iOS distribution/setup path before relying on it	3 - promising local-first alternative
Herdr	OSS terminal multiplexer fork	Agent blocked/working/done/idle awareness; detach/reattach	Not needed for core durability; install method currently repo script	3 - optional host upgrade
cmux	Free/open source; iOS beta early access	Ghostty-based integrated agent terminal/workspace; mobile connect beta	iOS app is beta/TestFlight/early access; not reliability baseline yet	Watch - fast-rising
ntfy	Open source; self-hostable	Excellent general notifications; cross-platform	iOS critical-alert support is v1.8.0 UNRELEASED as of date	Fallback/general alerts, not sole critical pager

Happy

Happy is the **strongest mature free/OSS alternative** if you want **one mobile/web UI for Claude Code and Codex**. The project is MIT-licensed, advertises end-to-end encryption, and currently documents **npm install -g happy** followed by **happy claude** or **happy codex**. That startup model is the key operational caveat: trial it on a disposable session, then adopt it for future sessions if it meets your same-session requirements. Do not insert it blindly around the irreplaceable five-day process. [HP1]

CC Pocket

The **heypandax/cc-pocket** project describes itself as a **local-first control plane** with an end-to-end encrypted zero-knowledge relay and no content logging. It supports **Claude Code and Codex** and is MIT-licensed. The architecture is compelling for operators who distrust hosted transcript services, but its **install/distribution** path is more involved than first-party Remote Control; validate the exact iOS release and upgrade workflow before making it P0 infrastructure. [CC1]

cmux

cmux is a notable fast-rising **Ghostty-based open-source macOS agent terminal**. Its repository states that the iOS app is in beta on TestFlight and early access is tied to the Founders Edition. That makes it strategically interesting, especially for a Ghostty-centric operator, but not the most conservative production control path today. [C1]

ntfy

ntfy remains excellent for **open-source/self-hosted notifications**. However, its own release notes list stable iOS as v1.7.0 and critical alerts that bypass silent/DND under iOS v1.8.0 UNRELEASED. Therefore do not repeat the v1 manual's implication that current stable ntfy iOS is equivalent to Bark/Pushover for critical paging. [N1]

11. Multi-day continuity: compaction, resumes, handoffs and mattlepock skills

The broader research brief correctly treats **context survival** as an operational concern, not a prompt-writing trick. A remote-HITL system fails if the phone can answer but tomorrow's session no longer knows what was decided.

What survives compaction - and what that implies

Mechanism	After compaction	Action for this workflow
Project-root CLAUDE.md / unscoped rules	Re-injected from disk	Keep always-on instructions short and high-value.
Auto memory	Re-injected	Useful for preferences/learned facts , not a transaction log.
Plan-mode plan	Re-injected	Use for active plan state , but still externalize stage decisions.
Nested/path-scoped rules	Reload when matching files are read	Do not assume they are present immediately after compact.
Recently read/edited files	Up to five reread, most recently modified first	Make HANDOFF/CONTEXT current before compact so they are likely to be useful.
Invoked skill bodies	Re-injected with per-skill/total caps	Put critical instructions at top of long SKILL.md files.
Prior hook-added context	Summarized with conversation	Hooks are not durable memory unless they read durable files again.
SessionStart hook source=compact	Runs and can add output after compact	Optional place to rehydrate current ticket/handoff state.

Recommended rhythm

29. At **every stage boundary or architecture decision**, **update the tracker/wayfinder ticket** and **ADR/CONTEXT** before continuing.
30. Before a deliberate compact, write the current objective, branch/worktree, completed tests, decisions, one open HITL question and the next command to **HANDOFF.md**.
31. Run **/compact with a focus instruction at task boundaries** rather than waiting for crisis compaction.
32. Use **/clear** when moving to unrelated work; do not drag an **old epic** into a **new task** merely because the chat is "alive."
33. Use **/context periodically** to see actual context **composition and optimize** what is always loaded.
34. **After >~1 hour inactivity on Pro/Max and >100k tokens**, evaluate the **Resume-from-summary** dialog; choose summary when exact old detail is no longer operationally needed.
35. **Delegate large searches/reads to subagents** so their raw context does not pollute the main decision thread.
36. At end of day, run the **handoff skill or write HANDOFF.md** and ensure **tracker status is authoritative** before leaving the session unattended overnight.

mattlepock skills mapping

Skill / pattern	Remote HITL rule
grill-me / grilling	One decision at a time. Prefer AskUserQuestion for actual blocking choices so hooks can page deterministically ; current community issue history means you should not assume every skill version always uses it.
grill-with-docs	Use the CONTEXT.md/ADR artifacts as durable decision memory ; they are more valuable remotely than a long interview transcript.
wayfinder	Its purpose is work too large for one session ; keep HITL decision tickets separate from AFK implementation tickets and resolve human tickets through actual human exchange.
to-spec / to-tickets	Convert decisions into discrete work with explicit blockers before launching parallel AFK waves.
implement / TDD / code-review	AFK work can proceed through tests and review gates ; stop before irreversible deploy/push or a new product decision.
handoff	Mandatory at day boundaries, major compaction, or before migrating to another control plane such as Happy.
wizard	Good for steps that truly require a human/browser/credential action ; the phone pager should summon the operator rather than pretending the agent can do it.

12. Remote safety: replace approval fatigue without disabling the safety boundary

The original environment runs with `--dangerously-skip-permissions` because the operator does not want to tap Allow/Deny repeatedly. That goal is reasonable; the mechanism is too broad for an unisolated personal laptop. Anthropic now explicitly says `bypassPermissions` should be used only in isolated containers or VMs where Claude Code cannot cause damage. [A3]

Preferred local-Mac policy

37. Use Claude Code sandboxing for Bash where possible. In auto-allow sandbox mode, sandboxable commands can run without asking while filesystem/network boundaries are still enforced.
38. Use auto permission mode if available and appropriate, or use default/acceptEdits plus targeted allow rules for recurring safe commands.
39. Deny outbound/irreversible commands you do not want an unattended agent to perform. The official docs show a deny rule for `Bash(git push *)`.
40. Keep deployments, production mutations, secret changes and irreversible data operations behind explicit human gates.
41. Treat hooks as deterministic policy/telemetry, not as a substitute for OS-level isolation.

Example settings fragment

```
{
  "permissions": {
    "allow": [
      "Bash(npm run *)",
      "Bash(git commit *)"
    ],
    "deny": [
      "Bash(git push *)"
    ]
  }
}
```

This exact pattern is aligned with Anthropic's documented example: allow npm scripts and git commits, refuse git push. Adapt the allow list to the project rather than using broad `Bash(git *)` patterns. Deny rules take precedence over ask and allow. [A3]

AFK vs HITL execution policy

Ticket class	Agent may do unattended	Must stop/page before
AFK implementation	Edit code, run unit/integration tests, local builds, static analysis, local commits if policy permits	New architecture/product decision; remote push/deploy; credential changes; destructive data migration
HITL design / grill / wayfinder	Read, compare options, prototype in throwaway/local scope	Choosing option, changing acceptance criteria, altering architecture baseline
Review / hardening	Read, test, lint, analyze diffs, propose patches	Publishing security-sensitive output; destructive remediation; production change
Deploy / migration	Prepare plan, preflight, dry-run where safe	Real production mutation unless explicitly approved for that step

If you deliberately keep `bypassPermissions`

Higher-risk compatibility mode Do not pretend a phone pager makes `bypassPermissions` safe. Use an isolated worktree/container/VM, no production credentials, least-privilege tokens, deterministic destructive-command hooks where useful, frequent git snapshots, and a clear blast radius. Re-test permission/deny behavior after version changes.

13. Failure matrix and recovery runbook

Symptom	Likely layer	Immediate action	Long-term fix
Claude phone push visible but silent	Native attention plane	Use Bark/Pushover; answer in Claude app	Keep independent pager; retest after app/CLI updates
No pager on question	Hook config/script	From shell: inspect <code>~/claude/settings.json</code> ; run hook script with sample JSON; check <code>jq/curl/network</code>	Add logging with no secrets; keep hook user-local
Phone shows session idle; terminal is blocked on MCP prompt	RC mobile renderer / MCP permission	Tailscale/SSH -> tmux; answer terminal dialog	Keep break-glass terminal; minimize MCP permission churn
Composer locked in permission sequence	RC mobile permission UX	Use terminal to deny/steer; do not keep tapping through unknown chain	Use sandbox/allow rules so routine work does not generate approval marathon
Remote Control disconnects, local terminal still works	Decision plane network/auth	Read RC status reason; <code>/remote-control</code> or resume path as documented	Check <code>direct.api.anthropic.com</code> , feature-flag env vars, account eligibility
Server-mode RC exited after outage	RC server mode	Restart <code>claude remote-control</code> ; use <code>--continue/--session-id</code> if within supported window	Prefer interactive RC for a single critical long conversation if local terminal remains active
SSH unavailable but RC works	Execution plane	Continue through RC; do not reboot host remotely unless necessary	Check Tailscale, Remote Login, SSH key, firewall
Both RC and SSH unavailable	Host/network/power	Wait for network if likely; physical access if host asleep/crashed	Open-lid powered baseline; Ethernet if available; monitor external drive
External SSD vanished	Storage	Stop agent writes; reconnect/remount; verify repo and git status	Move active worktree internal or harden cable/power/Drive Alive
Context lost after compact	State plane	Read <code>HANDOFF/CONTEXT/tracker</code> ; <code>/context</code> ; restate current ticket	Make artifact update mandatory before compaction/day end
Host swapping/thrashing	Resource plane	Stop/reduce parallel agents/apps; preserve state	Cap concurrency; internalize active repo; close browser/Electron loads
Need Codex/Grok/Gemini from phone	Product boundary	Use Moshi/Happy/CC Pocket or ordinary shell, not Claude RC	Adopt multi-vendor cockpit intentionally

Five-minute recovery sequence

42. Check the Mac is awake/powered and the project volume is mounted.
43. From iPhone, try Claude Code Remote Control. If the prompt is visible, answer there.
44. If RC is ambiguous, open Tailscale and the SSH/Mosh client; attach to tmux.
45. Inspect the exact terminal dialog before choosing an action. Do not blindly approve a queue.
46. If context looks wrong, stop new work, read `HANDOFF.md/CONTEXT.md/tracker` and re-establish the current ticket.
47. Only after state is secure, repair the notification/RC layer. The work process is more valuable than the remote UI.

14. Acceptance criteria, day-1 checklist, day-7 hardening

The system is "done" only when its failure paths are tested. A QR code that pairs successfully is not an acceptance test.

P0 - before leaving the house

Check	Done when
Remote Control attached	Same phone response appears in the live Mac conversation within seconds.
Native push configured	Both /config push toggles enabled; visual notification arrives on iPhone.
Independent pager	AskUserQuestion triggers a sound while phone is locked and Wi-Fi is off.
Permission signal	Safe test PermissionRequest pages immediately if permissions are enabled.
MCP fallback	Operator knows how to reach terminal for an invisible MCP permission dialog.
Host persistence	Disconnect phone/SSH; Claude remains alive in tmux.
Recovery shell	Tailscale + SSH/Mosh reaches Mac over AT&T without router port-forward.
Power	Mac remains awake in the exact unattended lid/power configuration for at least an hour.
State	HANDOFF.md/CONTEXT/tracker show current stage, decisions, tests and next HITL question.

P1 - next day

- Run one full 20-60 minute AFK wave from phone-away state and measure time-to-page and time-to-resume.
- Add a short hook log (timestamps/event type only) to diagnose missed notifications without storing prompts.
- Choose tmux vs Herdr based on observed multi-pane need; do not install Herdr merely because the prior manual ranked it.
- Replace broad permission bypass with sandbox/targeted permission rules where practical.
- Test a deliberate /compact at a clean task boundary; verify open question and current ticket remain obvious.

P2 - by day 7

- Run a controlled Remote Control failure drill and recover entirely through Tailscale/SSH.
- Trial Happy on a throwaway repo if you want a free OSS parallel control plane for Claude + Codex.
- Trial Moshi free tier if a richer terminal/agent inbox would reduce recovery friction; buy Pro only if the free tier proves insufficient.
- Review pager payload privacy and rotate/revoke any push credentials that were accidentally logged or committed.
- Pin/record the Claude Code version used for the project and re-check hook matchers after major upgrades.
- Measure whether 50% auto-compaction is helping. The live docs support explicit /autocompact token thresholds; choose a threshold from actual /context behavior, not habit alone.
- If running concurrent remote sessions, migrate shared-directory parallel editing to worktrees.

15. Stale advice to ignore

48. "Remote Control is Max-only." The same live page currently says "available on all plans" but its Requirements section enumerates Pro, Max, Team and Enterprise. Treat this as a documentation inconsistency; verify live eligibility on the account/CLI.
49. "Remote Control means nothing leaves the Mac." Execution/filesystem stay local, but the connected session transcript is stored on Anthropic servers.
50. "idle_prompt means Claude is blocked." It means Claude finished responding about 60 seconds ago and you did not type.
51. "agent_notification is the current Notification matcher." Use the current matcher set; agent_needs_input/agent_completed are current names.
52. "ntfy stable iOS has Critical Alerts." ntfy documents that feature for iOS v1.8.0 UNRELEASED as of this report.
53. "Herdr is required for durability." tmux/screen are the simple baseline; Herdr is an agent-aware enhancement.
54. "Tailscale SSH works as the server on the standard Mac app." On macOS, Tailscale SSH server support is limited to the open-source tailscale+tailscaled variant; regular SSH over the tailnet is the baseline.
55. "caffeinate means you can close the lid and forget the MacBook." Treat closed-display operation as a separate tested host configuration.
56. "Happy can be dropped around any existing session with zero migration risk." Its documented happy claude/codex launch path means existing-process attachment should be proven, not assumed.
57. "--dangerously-skip-permissions is just a convenience mode for a personal Mac." Anthropic now says bypassPermissions is for isolated environments where damage is constrained.
58. "A mattpocock grilling skill will always surface its question as AskUserQuestion." Current issue history shows this should not be assumed; keep the standing CLAUDE.md rule and a lower-priority fallback pager.
59. "A five-day compacted transcript is the project record." The project record is the repo/tracker/decision artifacts; the transcript is an execution cache with useful evidence.

16. Copy-paste operator snippets

Standing project instruction

CLAUDE.md (project root; keep this section short)

```
# Remote HITL - operator is often on iPhone

- When a human decision, authorization, redirect, architecture choice, or stage gate is required:
  1. Use AskUserQuestion whenever the choice can be expressed cleanly with 2-4 options.
  2. Keep the question short enough to read on a phone.
  3. Include the blast radius / trade-off in <=5 concise lines.
  4. Wait for the human answer; do not infer or self-answer a HITL ticket.
- Do not hide an open question inside a long status report.
- After /compact, first restate the active ticket and the single open HITL question, if any.
- AFK tickets: implement, test, and review within the agreed blast radius; stop before a new
product/architecture decision.
- Never push/deploy/force-reset/clean destructive state unless the current ticket explicitly authorizes that
exact action and the permission policy allows it.
- Before a deliberate compact and at end of day, update HANDOFF.md plus the tracker/wayfinder ticket.
- HANDOFF.md must contain: objective, branch/worktree, done, in-progress, tests, decisions/ADRs, blockers, open
HITL question, next command.
```

HANDOFF.md template

```
# HANDOFF
Updated: YYYY-MM-DD HH:MM TZ

## Objective
<one sentence>

## Current ticket / stage
<tracker URL or issue ID>

## Branch / worktree / cwd
<branch>
<path>

## Done
- ...

## In progress
- ...

## Tests / checks
- PASS: ...
- FAIL / not run: ...

## Decisions / ADRs
- ...

## Open HITL question
<exactly one blocking question, or NONE>

## Next safe action
<single next command / ticket>
```

Sample hook self-test

```
printf '%s\n' '{
  "hook_event_name":"PreToolUse",
  "tool_name":"AskUserQuestion",
  "tool_input":{"questions":[{"question":"Use Postgres or SQLite for MVP?"}]}
}' | "$HOME/.claude/hooks/hitl-pager.sh"
```

Version / environment diagnostic

```
claude --version
claude doctor
tailscale status
tmux list-sessions
mount | grep -i '/Volumes/' || true
ps aux | grep -E '[c]laude|[t]mux'
# Optional resource snapshots:
memory_pressure
df -h
```

17. Sources and verification notes

Source policy: primary live vendor documentation first; official GitHub repositories/issues for current behavior/bugs; product documentation/pricing for third-party tools. The supplied Grok manual is treated as prior art to verify, not as authority. Prices and beta status can change after 28 Aug 2026.

Anthropic / Claude Code primary sources

- [A1] Remote Control: <https://code.claude.com/docs/en/remote-control>
- [A2] Hooks reference: <https://code.claude.com/docs/en/hooks>
- [A3] Permissions: <https://code.claude.com/docs/en/permissions>
- [A4] Sandboxing: <https://code.claude.com/docs/en/sandboxing>
- [A5] Context window / compaction: <https://code.claude.com/docs/en/context-window>
- [A6] Sessions / resume: <https://code.claude.com/docs/en/sessions>
- [A7] Memory / CLAUDE.md: <https://code.claude.com/docs/en/memory>
- [A8] Mobile: <https://code.claude.com/docs/en/mobile>

Current Claude Code issue evidence

- [G1] #53709 - RC push notifications have no sound/vibration on iOS: <https://github.com/anthropics/claude-code/issues/53709>
- [G2] #87751 - iPhone RC native MCP tool-permission dialogs never render: <https://github.com/anthropics/claude-code/issues/87751>
- [G3] #89182 - mobile permission prompt locks composer / denial advances: <https://github.com/anthropics/claude-code/issues/89182>

mattpocock skills

- [S1] mattpocock/skills README: <https://github.com/mattpocock/skills>
- [S2] wayfinder documentation: <https://github.com/mattpocock/skills/blob/main/docs/engineering/wayfinder.md>
- [S3] grill-with-docs skill: <https://github.com/mattpocock/skills/blob/main/skills/engineering/grill-with-docs/SKILL.md>
- [S4] Issue #850 - grilling / AskUserQuestion behavior: <https://github.com/mattpocock/skills/issues/850>

Remote-control / pager / terminal ecosystem

- [HP1] Happy - MIT Claude Code/Codex mobile and web client: <https://github.com/slopus/happy>
- [CC1] heypandax/CC Pocket - local-first control plane: <https://github.com/heypandax/cc-pocket>
- [H1] Herdr - agent-aware terminal multiplexer: <https://github.com/motionharvest/herdr>
- [C1] cmux - Ghostty-based open-source macOS agent terminal: <https://github.com/manaflores-ai/cmux>
- [B1] Bark - iOS custom push / time-sensitive / critical alerts: <https://github.com/Finb/Bark>
- [P1] Pushover pricing: <https://pushover.net/pricing>
- [P2] Pushover message API / priority behavior: <https://pushover.net/api>
- [N1] ntfy release notes: <https://docs.ntfy.sh/releases/>
- [N2] ntfy publish docs: <https://docs.ntfy.sh/publish/>
- [M1] Moshi Claude Code guide: <https://getmoshi.app/guides/claude-code>
- [M2] Moshi hooks / agent inbox: <https://getmoshi.app/docs/hooks>
- [M3] Moshi pricing: <https://getmoshi.app/pricing>

Network / host sources

- [T1] Tailscale SSH feature and macOS server limitation: <https://tailscale.com/docs/features/tailscale-ssh>
- [T2] Tailscale pricing: <https://tailscale.com/pricing>
- [T3] Tailscale macOS variants: <https://tailscale.com/docs/concepts/macOS-variants>
- [MAC1] Amphetamine App Store - Closed-Display Mode / Drive Alive / Power Protect: <https://apps.apple.com/us/app/amphetamine/id937984704?mt=12>

Research interpretation notes

- Open GitHub issues are evidence of reported behavior, not proof that every device/build is affected. The manual therefore converts them into acceptance-test requirements rather than universal claims.
- Commercial prices are point-in-time observations and are explicitly labeled for re-verification before purchase.
- OSS maturity judgments weigh install path, license, current documentation, breadth of CLI support, and evidence of active development; star counts are not treated as a reliability guarantee.
- The hook JSON uses current documented event names and inputs. Re-run /hooks or inspect the live hooks reference after CLI upgrades.

Appendix A. Decision matrix: choose the smallest stack that satisfies the requirement

Need	Use	Do not use as substitute
Answer/steer the exact local Claude conversation from iPhone	Claude Remote Control	Raw SSH terminal alone
Guaranteed independent audible attention signal	Claude hooks -> Bark or Pushover	Native RC push alone until verified
Recover from invisible/buggy mobile dialogs	Tailscale + SSH/Mosh -> tmux	A second push service without shell access
One mobile cockpit for Claude + Codex + other CLIs	Moshi; or Happy/CC Pocket depending desired architecture	Claude RC, which is Claude-specific
Durable multi-agent host visibility	Herdr after baseline tmux works	Installing multiple wrappers before persistence is proven
Privacy-sensitive alternative control plane	CC Pocket / self-hosted or evaluated Happy architecture	Assuming first-party RC transcript stays only local
Long-session continuity	Tracker + CONTEXT/ADR/HANDOFF + deliberate compaction	One immortal chat transcript
Reduce permission fatigue safely on local Mac	Sandbox + auto/targeted rules	bypassPermissions on the raw laptop
Parallel edits	Git worktrees / RC --spawn worktree	Several agents editing one working directory

Appendix B. Final recommended deployment for the supplied environment

For the supplied MacBook Pro M4 + iPhone 15 Pro + AT&T + Spectrum environment, the recommended deployment is intentionally conservative:

60. Keep the critical current Claude Code conversation local on the Mac and attach first-party Remote Control from inside the existing session.
61. Enable both Claude mobile push toggles, but treat native push as visual/best-effort until it passes the locked-phone AT&T test.
62. Install an independent Bark pager hook now; choose Pushover instead if repeated acknowledgement-style paging is worth \$4.99.
63. At the next safe boundary, run Claude inside tmux. Add Herdr only if you need its blocked/working/done/idle overview for several concurrent agent panes.
64. Install Tailscale on Mac and iPhone, enable macOS Remote Login, use SSH keys, and keep router port-forwarding off.
65. If a better iOS shell/agent inbox is desirable, install Moshi and start with the free tier. It is the best complement for multi-vendor CLI operation.
66. Do not migrate the irreplaceable session into Happy/CC Pocket mid-flight. Trial them on disposable repos; adopt one for future sessions only if its control-plane trade-offs outperform first-party RC for your workflow.
67. Replace --dangerously-skip-permissions on the raw Mac with sandbox + targeted permissions as soon as practical; preserve dangerous bypass only in genuinely isolated environments.
68. Make HANDOFF.md + issue/wayfinder state mandatory before compaction, end of day, or any control-plane migration.
69. Retest the end-to-end doorbell and recovery shell after every material Claude Code / iOS / hook upgrade.

Definition of success You can leave the Mac for an hour, receive an audible iPhone page at the first real HITL gate, answer the same live session from the phone, and - if the mobile UI fails - reach the exact tmux pane over Tailscale and recover without losing context or exposing public SSH.