

```

import numpy as np
import pdb

from .layers import *
from .layer_utils import *

"""
This code was originally written for CS 231n at Stanford University
(cs231n.stanford.edu). It has been modified in various areas for use in the
ECE 239AS class at UCLA. This includes the descriptions of what code to
implement as well as some slight potential changes in variable names to be
consistent with class nomenclature. We thank Justin Johnson & Serena Yeung
for
permission to use this code. To see the original version, please visit
cs231n.stanford.edu.
"""

class TwoLayerNet(object):
    """
    A two-layer fully-connected neural network with ReLU nonlinearity and
    softmax loss that uses a modular layer design. We assume an input
    dimension
    of D, a hidden dimension of H, and perform classification over C classes.

    The architecture should be affine - relu - affine - softmax.

    Note that this class does not implement gradient descent; instead, it
    will interact with a separate Solver object that is responsible for
    running
    optimization.

    The learnable parameters of the model are stored in the dictionary
    self.params that maps parameter names to numpy arrays.
    """

    def __init__(self, input_dim=3*32*32, hidden_dims=100, num_classes=10,
                  dropout=0, weight_scale=1e-3, reg=0.0):
        """
        Initialize a new network.

        Inputs:
        - input_dim: An integer giving the size of the input
        - hidden_dims: An integer giving the size of the hidden layer
        - num_classes: An integer giving the number of classes to classify
        - dropout: Scalar between 0 and 1 giving dropout strength.
        - weight_scale: Scalar giving the standard deviation for random
          initialization of the weights.
        - reg: Scalar giving L2 regularization strength.
        """
        self.params = {}
        self.reg = reg

        # ===== #
        # YOUR CODE HERE:
        # Initialize W1, W2, b1, and b2. Store these as self.params['W1'],

```

```

# self.params['W2'], self.params['b1'] and self.params['b2']. The
# biases are initialized to zero and the weights are initialized
# so that each parameter has mean 0 and standard deviation
weight_scale.
# The dimensions of W1 should be (input_dim, hidden_dim) and the
# dimensions of W2 should be (hidden_dims, num_classes)
# ===== #

self.params['W1'] = weight_scale *
    np.random.randn(input_dim,hidden_dims)
self.params['b1'] = np.zeros(hidden_dims)
self.params['W2'] = weight_scale *
    np.random.randn(hidden_dims,num_classes)
self.params['b2'] = np.zeros(num_classes)

# ===== #
# END YOUR CODE HERE
# ===== #

def loss(self, X, y=None):
    """
    Compute loss and gradient for a minibatch of data.

    Inputs:
    - X: Array of input data of shape (N, d_1, ..., d_k)
    - y: Array of labels, of shape (N,). y[i] gives the label for X[i].

    Returns:
    If y is None, then run a test-time forward pass of the model and return:
    - scores: Array of shape (N, C) giving classification scores, where
      scores[i, c] is the classification score for X[i] and class c.

    If y is not None, then run a training-time forward and backward pass and
    return a tuple of:
    - loss: Scalar value giving the loss
    - grads: Dictionary with the same keys as self.params, mapping parameter
      names to gradients of the loss with respect to those parameters.
    """
    scores = None

    # ===== #
    # YOUR CODE HERE:
    # Implement the forward pass of the two-layer neural network. Store
    # the class scores as the variable 'scores'. Be sure to use the
    # layers
    # you prior implemented.
    # ===== #

    a1 = affine_forward(X,self.params['W1'],self.params['b1'])
    h = relu_forward(a1[0])
    a2 = affine_forward(h[0],self.params['W2'],self.params['b2'])
    scores = a2[0]

    # ===== #
    # END YOUR CODE HERE

```

```

# ===== #

# If y is None then we are in test mode so just return scores
if y is None:
    return scores

loss, grads = 0, {}
# ===== #
# YOUR CODE HERE:
# Implement the backward pass of the two-layer neural net. Store
# the loss as the variable 'loss' and store the gradients in the
# 'grads' dictionary. For the grads dictionary, grads['W1'] holds
# the gradient for W1, grads['b1'] holds the gradient for b1, etc.
# i.e., grads[k] holds the gradient for self.params[k].
#
# Add L2 regularization, where there is an added cost  $0.5 * \text{self.reg} * W^2$ 
# for each W. Be sure to include the 0.5 multiplying factor to
# match our implementation.
#
# And be sure to use the layers you prior implemented.
# ===== #

loss, ds = softmax_loss(scores, y)
loss += 1/2 * self.reg * np.sum(self.params['W1']**2) + 1/2 * self.reg
    * np.sum(self.params['W2']**2)

dx, grads['W2'], grads['b2'] = affine_backward(ds, a2[1])
_, grads['W1'], grads['b1'] =
    affine_backward(relu_backward(dx, h[1]), a1[1])

grads['W1'] += self.reg * self.params['W1']
grads['W2'] += self.reg * self.params['W2']

# ===== #
# END YOUR CODE HERE
# ===== #

return loss, grads

```

```

class FullyConnectedNet(object):
    """

```

A fully-connected neural network with an arbitrary number of hidden layers, ReLU nonlinearities, and a softmax loss function. This will also implement dropout and batch normalization as options. For a network with L layers, the architecture will be

{affine - [batch norm] - relu - [dropout]} x (L - 1) - affine - softmax

where batch normalization and dropout are optional, and the {...} block is repeated L - 1 times.

Similar to the TwoLayerNet above, learnable parameters are stored in the self.params dictionary and will be learned using the Solver class.

```
"""
```

```
def __init__(self, hidden_dims, input_dim=3*32*32, num_classes=10,
              dropout=0, use_batchnorm=False, reg=0.0,
              weight_scale=1e-2, dtype=np.float32, seed=None):
```

```
"""
```

```
Initialize a new FullyConnectedNet.
```

```
Inputs:
```

- hidden\_dims: A list of integers giving the size of each hidden layer.
- input\_dim: An integer giving the size of the input.
- num\_classes: An integer giving the number of classes to classify.
- dropout: Scalar between 0 and 1 giving dropout strength. If dropout=0 then the network should not use dropout at all.
- use\_batchnorm: Whether or not the network should use batch normalization.
- reg: Scalar giving L2 regularization strength.
- weight\_scale: Scalar giving the standard deviation for random initialization of the weights.
- dtype: A numpy datatype object; all computations will be performed using this datatype. float32 is faster but less accurate, so you should use float64 for numeric gradient checking.
- seed: If not None, then pass this random seed to the dropout layers. This will make the dropout layers deterministic so we can gradient check the model.

```
"""
```

```
self.use_batchnorm = use_batchnorm
self.use_dropout = dropout > 0
self.reg = reg
self.num_layers = 1 + len(hidden_dims)
self.dtype = dtype
self.params = {}
```

```
# ===== #
```

```
# YOUR CODE HERE:
```

```
# Initialize all parameters of the network in the self.params dictionary.
```

```
# The weights and biases of layer 1 are W1 and b1; and in general the weights and biases of layer i are Wi and bi. The biases are initialized to zero and the weights are initialized so that each parameter has mean 0 and standard deviation weight_scale.
```

```
#
```

```
# BATCHNORM: Initialize the gammas of each layer to 1 and the beta parameters to zero. The gamma and beta parameters for layer 1 should
```

```
# be self.params['gamma1'] and self.params['beta1']. For layer 2, they
```

```
# should be gamma2 and beta2, etc. Only use batchnorm if self.use_batchnorm
```

```
# is true and DO NOT do batch normalize the output scores.
```

```

# ===== #

for i in range(self.num_layers):
    if i == 0: # first layer
        self.params['W'+str(i+1)] = weight_scale *
            np.random.randn(input_dim,hidden_dims[i])
        self.params['b'+str(i+1)] = np.zeros(hidden_dims[i])
        if self.use_batchnorm == True:
            self.params['gamma' + str(i+1)] = np.ones(hidden_dims[i])
            self.params['beta' + str(i+1)] = np.zeros(hidden_dims[i])
    elif i < self.num_layers - 1:
        self.params['W'+str(i+1)] = weight_scale *
            np.random.randn(hidden_dims[i-1],hidden_dims[i])
        self.params['b'+str(i+1)] = np.zeros(hidden_dims[i])
        if self.use_batchnorm == True:
            self.params['gamma' + str(i+1)] = np.ones(hidden_dims[i])
            self.params['beta' + str(i+1)] = np.zeros(hidden_dims[i])
    else: # end of network
        self.params['W'+str(i+1)] = weight_scale *
            np.random.randn(hidden_dims[i-1],num_classes)
        self.params['b'+str(i+1)] = np.zeros(num_classes)

# ===== #
# END YOUR CODE HERE
# ===== #

# When using dropout we need to pass a dropout_param dictionary to each
# dropout layer so that the layer knows the dropout probability and the
# mode
# (train / test). You can pass the same dropout_param to each dropout
# layer.
self.dropout_param = {}
if self.use_dropout:
    self.dropout_param = {'mode': 'train', 'p': dropout}
    if seed is not None:
        self.dropout_param['seed'] = seed

# With batch normalization we need to keep track of running means and
# variances, so we need to pass a special bn_param object to each batch
# normalization layer. You should pass self.bn_params[0] to the forward
# pass
# of the first batch normalization layer, self.bn_params[1] to the
# forward
# pass of the second batch normalization layer, etc.
self.bn_params = []
if self.use_batchnorm:
    self.bn_params = [{'mode': 'train'} for i in
        np.arange(self.num_layers - 1)]

# Cast all parameters to the correct datatype
for k, v in self.params.items():
    self.params[k] = v.astype(dtype)

def loss(self, X, y=None):

```

```

"""
Compute loss and gradient for the fully-connected net.

Input / output: Same as TwoLayerNet above.
"""
X = X.astype(self.dtype)
mode = 'test' if y is None else 'train'

# Set train/test mode for batchnorm params and dropout param since they
# behave differently during training and testing.
if self.dropout_param is not None:
    self.dropout_param['mode'] = mode
if self.use_batchnorm:
    for bn_param in self.bn_params:
        bn_param[mode] = mode

scores = None

# ===== #
# YOUR CODE HERE:
# Implement the forward pass of the FC net and store the output
# scores as the variable "scores".
#
# BATCHNORM: If self.use_batchnorm is true, insert a bathnorm layer
# between the affine_forward and relu_forward layers. You may
# also write an affine_batchnorm_relu() function in layer_utils.py.
#
# DROPOUT: If dropout is non-zero, insert a dropout layer after
# every ReLU layer.
# ===== #

caches = []
data_in = X
for i in range(self.num_layers):

    if i < self.num_layers - 1:
        if self.use_batchnorm:
            out, cache = affine_batchnorm_relu_forward(data_in,
                self.params['W'+str(i+1)], self.params['b'+str(i+1)],
                self.params['gamma' + str(i+1)], self.params['beta'+str(i+1)],
                self.bn_params[i])
        else:
            out, cache =
                affine_relu_forward(data_in, self.params['W'+str(i+1)],
                self.params['b'+str(i+1)])

        if self.use_dropout :
            out, cacheDrop = dropout_forward(out, self.dropout_param)
            cache = (cache, cacheDrop)
        data_in = out
        caches.append(cache)
    else:
        out2, cache2 = affine_forward(data_in , self.params['W'+str(i+1)],
            self.params['b'+str(i+1)])

```

```

scores = out2

# ===== #
# END YOUR CODE HERE
# ===== #

# If test mode return early
if mode == 'test':
    return scores

loss, grads = 0.0, {}
# ===== #
# YOUR CODE HERE:
# Implement the backwards pass of the FC net and store the gradients
# in the grads dict, so that grads[k] is the gradient of
# self.params[k]
# Be sure your L2 regularization includes a 0.5 factor.
#
# BATCHNORM: Incorporate the backward pass of the batchnorm.
#
# DROPOUT: Incorporate the backward pass of dropout.
# ===== #

loss, ds = softmax_loss(out2, y)
regularization = 0
for i in range(self.num_layers):
    loss += 0.5 * self.reg * np.sum(self.params['W'+str(i+1)] *
        self.params['W'+str(i+1)])

for i in reversed(range(self.num_layers)):
    if i == self.num_layers - 1:
        dx1, grads['W'+str(i+1)], grads['b'+str(i+1)] =
            affine_backward(ds, cache2)
    else:
        cache = caches[i]
        if self.use_dropout:
            cache, cacheDrop = cache
            dx1 = dropout_backward(dx1, cacheDrop)

        if self.use_batchnorm:
            dx, grads['W'+str(i+1)], grads['b'+str(i+1)], grads['gamma' +
                str(i+1)], grads['beta' + str(i+1)] =
                affine_batchnorm_relu_backward(dx1, cache)
        else:
            dx, grads['W'+str(i+1)], grads['b'+str(i+1)] =
                affine_relu_backward(dx1, cache)
            dx1 = dx

for i in reversed(range(self.num_layers)):
    grads['W'+str(i+1)] += self.reg * self.params['W'+str(i+1)]

# ===== #
# END YOUR CODE HERE
# ===== #

```

return loss, grads