




NOTES:

1. FOR LINE PRESSURES, TEMPERATURES, INSULATION TYPE AND THICKNESS, ETC. REFER TO LATEST REVISION OF LDT.
2. FOR STANDARD PIPE SUPPORT DETAILS SEE PROJECT STANDARD.
3. FIELD SHIM TO SUIT UNLESS OTHERWISE NOTED.
4. FOR PWHT REQUIREMENTS REFER TO LINE CLASS SPECIFICATION.
5. ALL THREADED PIPE LINE SYSTEMS, FIELD SHALL VERIFY DIMENSION PRIOR TO ERECTION.
6. FFW DESIGNATION AT WELDS INDICATES FIELD FIT WELD, WHERE PIPE FABRICATOR IS TO ADD 9 INCH OF PIPE TO THE ISOMETRIC DIMENSION TO ENABLE THE FIELD TO CUT TO FIT AT SITE.
7. REFER TO 202998C-000-W1-1300-0001 FOR FRP AND DUAL-LAM FABRICATION.



Filler Material Requisition

Date: 12-4-24

Line Class: NOHD-NI03

WPS: 4130

Electrode: ERNi-1

Signature: *Glenn Sumrall Jr*

PIECE MARKS

6820-R2-67022-06-1 6820-R2-67022-06-2 6820-R2-67022-06-3
6820-R2-67022-06-4

SERVICE: R2	VAPOR/LIQUID: L	INSUL TYPE: Per LDT	INSUL THK: Per LDT	SHOP: Y	FIELD: Y	PAINT CODE: Per LDT	MODULE: -
				PID: 202998C-001-PID-0021-0322			
				UNIT#: 6800	EWP AREA: 6820	SPEC: NOHD-NI03	STRESS CALC #: CN-0388/0392
				LINE No. 8"-R2-67022-NOHD-NI03-H			
				DRAWING NUMBER 6820-R2-67022-06			
OxyChem Redstone Battleground PROJECT				REV. 1			